Designing of Fabric Reinforced Polymer in the Assessment of Sorption Capacity of Mussel Shell Powder for Divalent Ion: GIS Mapping and Statistical Studies

S. Charulatha

PSGR Krishnammal College for Women

K.S. Thangamani

Dr. N.G.P. Institute of Technology <https://orcid.org/0000-0003-3340-4813>

N. Muthulaksmi Andar (✉ thangs2012@gmail.com)

PSGR Krishnammal College for Women

Research Article

Keywords: Adsorption, Zinc ions, Parameters, Mussel shell powder, Isotherms, Column Studies, Effluent Treatment

Posted Date: November 17th, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-1070934/v1>

License: © ⓘ This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Designing of Fabric Reinforced Polymer in the Assessment of Sorption Capacity of Mussel Shell Powder for Divalent Ion: GIS Mapping and Statistical Studies

S.Charulatha^a , K.S. Thangamani^b, N.Muthulaksmi Andal^{a*}

^a Department of Chemistry, PSGR Krishnammal College for Women, Coimbatore-4

^b Department of Chemistry, Dr. N.G.P. Institute of Technology, Coimbatore -641048

Abstract

This paper discusses the efficiency of acid modified mollusc shell powder in adsorbing Zn(II) ions from synthetic wastewater and actual wastewater samples discharged from electroplating industries. The chemically treated adsorbent was characterized in terms of structure and surface properties. The parameters such as, size of the sorbent particles, dosage, initial Zn(II) concentration, temperature, contact time pH and temperature were varied for optimization using batch studies. The adsorbate-adsorbent system was studied by Langmuir, Freundlich, Tempkin and DKR isotherms. The adsorption experiments were conducted in a column packed with the acid modified mollusc shell powder. Further, real wastewater samples having Zn(II) concentration higher than the permissible levels were collected from the industrial belt in Coimbatore, to assess the potential of the bio adsorbent. A fiber reinforced polymer fabricated with the adsorbent material installed at the effluent discharge plants achieved 100% Zn(II) removal from electroplating wastewaters. Statistical analysis performed using SPSS software showed significant correlation among the input parameters and the analytical results post-adsorption.

Keywords: Adsorption, Zinc ions, Parameters, Mussel shell powder, Isotherms, Column Studies, Effluent Treatment

1. Introduction

Industrial effluents generated from various industries viz., mining, metallurgy, plating, paints, pigments etc., are the main sources of heavy metal pollution. Environmental Protection Agency (EPA) proposed that over exposure to Zn²⁺ ions leads to many undesirable physiological conditions such as hyperosmolarity, hyponatremia, stomach ache, vomiting sensation, light headedness and ataxia [1]. Thus, removal of zinc ions is essential to address the consequences of

pollution. Although there are a range of adsorption techniques, adsorption is one of the best and effective processes for the treatment of effluents because it minimizes the sludge formation, and is cost effective [2,3]. Many adsorbent materials of plant and animal origin proved effective for the removal of various metal ions [4-9]. These natural materials are readily available, cheap and easily modifiable to suit the needs. In this context, this work investigates the efficiency of chemically treated mussel shell powder in the adsorption of Zn(II) ions from aqueous solutions. Mussel shell belongs to the family bivalve molluscs found in saltwater and freshwater habitats. They are discarded as waste from shellfish processing.

2. Materials and Methods

2.1 Chemicals

Stock solution of 1000 mg/L zinc nitrate was prepared by dissolving appropriate quantity of the zinc salt in water. Aliquots of the adsorbate solutions of varying Zn(II) ion concentrations (100-1000 mg/L: 100 mg/L) were prepared by progressive dilutions from the stock solution, at natural pH conditions.

2.2 Preparation/Treatment of Adsorbent Materials

Mollusc shells were collected from shellfish processing units. The shells were cleansed using double distilled (DD) water repeatedly and converted into a coarse powder using a mortar and pestle. Then, the coarse mollusc shell powder (MSP) was kept in a flat bottom flask containing decinormal hydrochloric acid for 4 hours. Following this chemical treatment, MSP was washed with DD water again and dried under direct sunlight. This treated powder will be mentioned as TMSP hereafter. The TMSP was crushed well to a fine dust using a laboratory blender and segregated based on the particle size as 85 BSS, 72 BSS, 52 BSS, 36BSS and 22 BSS. These adsorbent samples were stocked in sealed holders. The images of the untreated mollusc shell powder and TMSP (0.18 mm: optimized particle size) are shown in Fig 1a& 1b

Treated mussel shell powder samples of different mesh sizes (15 samples) were microscoped under a CX21i Binocular Microscope to determine the particle size. The dimensions of each sample were measured and averaged. Finally, the particle size was calculated using multiplication factors. The calculated particle sizes for the mesh sizes 85BSS, 72BSS, 52BSS, 36BSS and 22BSS are 0.18 mm, 0.21 mm, 0.30 mm, 0.42 mm and 0.71 mm, respectively.

2.3 Surface Characterization

A JEOL JFM-6390 Scanning Electron Microscope with EDX was used to study the surface structure of the treated mollusc shell powder. Similarly, a Micromeritics (BEL, Japan Inc.) Surface Area Analyzer was employed to determine the surface area and pore volume by N₂ adsorption at 77 K following BET method.

Evaluation of the particle/ mesopore size distribution of sorbent material was carried out by BET (Fig.2a) and BJH (Fig.2b) methods. The adsorption performance is highly dependent on the internal pore structure. Pore sizes are classified in accordance with the classification adopted by the International Union of Pure and Applied Chemistry (IUPAC manual, 1982) i.e; micropores ($d < 20 \text{ \AA}$), mesopores ($20 \text{ \AA} < d < 500 \text{ \AA}$) and macropores ($d > 500 \text{ \AA}$). Because of the larger sizes of the liquid molecules, the adsorbents for liquid phase adsorbates should possess predominantly mesopores in the structure[10]. The mesopores are responsible for the better surface area of TMSP ($1.52 \text{ m}^2/\text{g}$), possible through the activation process. The mean pore diameter value as inferred from BET plot is found to be 24.04 nm. Particles under study are found to possess mesoporous nature predominantly, as their pore diameter lie in the range of $20 \text{ \AA} < d < 500 \text{ \AA}$

2.4 Batch Mode Adsorption Studies

In the batch adsorption studies, the Zn(II) samples were shaken well with TMSP in a KEMI agitator. To optimize the system for maximal adsorption, the particle size of TMSP (0.71 mm, 0.42 mm, 0.30 mm, 0.21 mm and 0.18 mm), dosage (200-500 mg 100 mg interval), pre-adsorption concentration of Zn(II) solution (100-1000 ppm; 100 ppm interval), contact time (30 min, 60 min, 120 min), pH (3, 5, 7, 9 and 11) and temperature (293K- 333 K: 10 K intervals) were varied.

The pre- and post-adsorption Zn(II) concentrations were determined using a Shimadzu (AA 6200) atomic absorption spectrophotometer.

2.4.1 Data Evaluation

The percentage of adsorption of Zn(II) ions from the test solutions was calculated by equation (1) [11]

$$\% \text{ removal} = \frac{C_0 - C}{C_0} \times 100 \quad \dots (1).$$

Similarly, application of equation (2) gives the quantity of Zn(II) ions removed by the adsorbent (q).

$$q = \frac{V(C_0 - C)}{W} \quad \dots (2)$$

where V, W, C_i and C_e are, respectively, volume of the solution in L, mass of the adsorbent in g, initial and equilibrium metal concentrations (mg/L).

2.5 Statistical Analysis

All statistical analyses were carried out with the help of IBM SPSS (Statistical Product and Service Solutions) package version 20 using ANOVA at 95% confidence level. Pearson Product-Moment Correlation Coefficient Method was used to establish the relationship between the amount of adsorbed Zn(II) ions and the variables.

3 Results and Discussion

3.1 SEM Analysis

Figures 3a and 3b show the surface structures TMSP before and after adsorption of Zn(II) ions. From Fig 3a, it is evident that the surface of the bare TMSP is porous and rough. But, the image after Zn(II) adsorption reveals a smooth surface (Fig 3a). From, these two figures, the adsorption of Zn(II) ions onto the active sites of the surface of TMSP can be confirmed.

3.2 EDAX Analysis

The chemical compositions of the adsorbent material before and after adsorption were determined by EDAX spectroscopy. Figures 4a and 4b, respectively, show the EDAX spectrum of free TMSP and Zn(II)-loaded TMSP. The EDAX spectrum of TMSP showed that oxygen, carbon, calcium and chlorine are the major elements [12]. In the spectrum of Zn(II)-loaded TMSP, a new peak observed at the energy range 8-10 KeV (fig 4b) confirms the adsorption of Zn(II) ions onto TMSP.

3.3 FTIR Spectral Studies

FTIR spectra of unloaded and Zn(II) loaded TMSP is shown in Fig.5 . The broad intense peak at 3722 cm^{-1} indicative of the stretching of O-H group [13]. The peak at 1465 cm^{-1} corresponds to carboxylate groups. The 856 cm^{-1} peak relates to the presence of aromatic heterocyclic molecules. Inclines and declines in the intensities of the peaks as perceived from the figure, indicate the appropriate shifts that had occurred in the FTIR spectra of Zn(II) laden material.

3.4 Effect of Particle sizes

The change in adsorption behavior of the Zn(II)-TMSP system with different particle size of the adsorbent (0.18 mm, 0.32 mm, 0.41 mm and 0.71 mm) was experimentally verified and illustrated in the bar diagram (Fig 6). The adsorption of Zn(II) onto TMSP was observed to increase from 19.32 mg/g to 83.76 mg/g, as the particle size decreased from 0.71 mm to 0.18 mm as expected based on the relationship between adsorption and surface area. Thus, 0.18 mm was fixed as the optimum particle size for further experiments. As per the statistical tool analysis (Table 1), the P-value (0.0297) at 95% confident level ($P < 0.05$) confirms that there is a significant correlation ($r = -0.7395$) between the particle size of the adsorbent and the amount of solute adsorbed.

3.5 Effect of Dosage

Bar chart (Fig 7) depicts the adsorption efficiency of TMSP with dosages. The maximum Zn(II) absorption at 1000 mg TMSP is due to the increased surface area. The P-value (0.0005) at 95% confident level ($P < 0.05$) shows positive correlation ($r = 0.9942$) between adsorbent dosage and the amount of Zn(II) adsorbed.

3.6 Effect of Initial Concentration and Agitation Time

The influence of contact time on Zn(II) removal is shown in the bar diagram (Fig. 8). The amount of Zn(II) ion adsorbed by TMSP for different values of initial Zn(II) concentrations (100-1000ppm: 100ppm intervals) at room temperature can be noted from it. It is evident that as the initial Zn(II) concentration increases, the corresponding amount of absorption also increases from 58.81 mg/g to 83.76 mg/g at the contact time of 60 minutes. A further increase in the

contact time has a negligible effect on the rate of adsorption. The reduction in the rate of adsorption at increased contact time may be due to the slow pore diffusion of the solute ion into the bulk of the adsorbent [14].

3.7 Effect of pH

The role of pH has also been ascertained experimentally and shown in Fig.9. The amounts of Zn(II) removed (particle size and dose: 0.18 mm & 1000 mg) at different pH environments imply that a moderate acidic pH of 5.5 facilitate maximum adsorption. Highly acidic and alkaline pH actually hinders the removal of Zn(II) because of the interferences of H^+ and OH^- ions with the surface prior to adsorption, which decreases the number of active sites[15]. The calculated P-value (0.0455) at 95% confidence level ($P < 0.05$), as evident from Table 2 proves the existence of significant correlation between pH and the amount of Zn(II) adsorption.

3.8 Effect of Temperature

Temperature has a pronounced effect on the adsorption capacity of the adsorbents. The effect of temperature (293-333 K: 10 K intervals) on Zn(II) are illustrated in table 1, where the adsorption percentage was observed to increase from 67.30 to 96.00 for rise in temperatures [16,17]. The enhancement of adsorption capacity with temperature may be attributed to the increase in the mobility of ions, which can cause small pores to widen and provide more surfaces for adsorption [18, 19].

3.9 Statistical Analysis

Statistically significant correlation between the experimental variables and the quantity of Zn(II) ions adsorbed onto the surface of TMSP was established by Pearson correlation analysis. These findings indicate that heavy metal pollution can be handled practicably once the factors affecting the adsorption of such ions are fixed. The Pearson correlation parameters are given in Table 3.

3.10 Adsorption Isotherm Models

Adsorption isotherms state the surface properties and affinity of the adsorbent towards the adsorbate [20]. Thus, different adsorption isotherms were applied to the Zn(II)-TMSP system under the influence of varying initial concentrations using the experimental data to understand

the process. Carrying out a linear regression and validation by correlation coefficients (R^2) can authenticate the best fit between the data and type of adsorption isotherm [21].

3.10.1 *Langmuir*

The Langmuir model assumes the occurrence of [22] sorption at precise homogeneous active sites that can attract only a single molecule. A second layer of adsorption is excluded in Langmuir isotherm and thus only a monolayer adsorption is possible, which is expressed by the following equation [23]

$$\frac{C_e}{q_e} = \frac{C_e}{q_m} + \frac{1}{bq_m} \quad \dots (2),$$

where

q_e = Sorption capacity of the sorbent (mg/g)

C_e = Equilibrium metal ion concentration in solution (mg/L),

q_m = Maximum monolayer adsorption capacity of the sorbent (mg/g)

b = Langmuir sorption constant (mg/L) related to the free energy of sorption.

The Langmuir constants q_m and b were determined from the slope and intercept values of the linear plot of C_e/q_e versus C_e (Fig 10). Higher the value of b , greater is the affinity of the adsorbent towards the metal ion [24]. The R^2 values ($R^2 = 0.9919$) suggests maximum linearity and best fit of the isotherm for Zn(II)-TMSP system.

3.10.2 *Freundlich*

In general, the adsorption characteristics of an aqueous can be studied by applying Freundlich isotherm. Batch isothermal data fitted to the linear form of the Freundlich isotherm equation,

$$\text{Log } q_e = \log k + 1/n \log C_e \quad \dots (4),$$

where

q_e = amount of metal ions sorbed per unit weight of the sorbent (mg/g)

C_e = equilibrium metal ion concentration (mg/L) of the metal ions in the solution

K_f and $1/n$ are Freundlich constants related to adsorption capacity and adsorption intensity, respectively [25]. From the slope and intercept of the plot $\log q_e$ vs $\log C_e$ (Fig. 11), values of K_f

and R^2 were determined (Table 4). The constants and the correlation coefficient values imply that the system does not comply well with Freundlich isotherm ($R^2=0.9765$) compared to its compliance with Langmuir isotherm ($R^2= 0.9919$).

3.10.3 Tempkin Isotherm Model

Tempkin isotherm was applied to the adsorption data under investigation, as per equation (17). Tempkin constants A_T and b_T which are related to the equilibrium binding constant and heat of adsorption are obtained from the linear plot of $\ln C_e$ vs q_e (Fig. 12). The constants and the correlation coefficient values reported in table 4, indicate that the isotherm is obeyed by the systems effectively. Similar results were documented by earlier researchers [26, 27].

3.10.4 Dubinin–Kaganer–Radushkevich Isotherm Model

The equilibrium data were applied to the DKR isotherm model to determine the nature of sorption processes as physical or chemical. Fig.13 represents the DKR plot for Zn(II) system. The value of correlation coefficient shown in table 4, indicate that the DKR isotherm fitted well with the experimental data. The results show that the sorption of the metal ion onto the sorbent material may be carried out via chemical ion exchange mechanism, as their value lie above 8 kJ/mol. Similar results were reported for various other adsorbents [28, 29].

3.11 Adsorption Dynamics

The thermodynamic parameters such as change in free energy (ΔG^0), enthalpy (ΔH^0) and entropy (ΔS^0) were calculated. The ΔH^0 , ΔS^0 calculated from the slope and intercept of Vant Hoff plot (Fig. 14) are shown in table 5. The positive values of ΔH^0 indicate the presence of an energy barrier in the adsorption process which is endothermic in nature²¹⁵. The negative values of ΔG^0 indicate the feasibility and spontaneous nature of adsorption of metal ions by the adsorbent [30]. The magnitude of ΔG^0 increased with temperature indicating that the sorption was more favourable at higher temperature [31]. The positive values of ΔS^0 suggest that the increased randomness at the solid-solution interface during the

adsorption of metal ions in aqueous solutions onto adsorbents [32]. The low value of ΔS^0 may imply that no remarkable change in entropy occurred during the sorption of metals on the adsorbent [33]. Similar trend was observed for adsorbents such as rice bran [34], tree fern [35], and rubber wood sawdust [36].

3.12 Column Method

The results obtained from the batch mode suggest the suitability and efficiency of TMSP in removing Zn(II) ions. Motivated by the batch mode results, the process was validated for quantification by continuous column runs. The inlet Zn(II) solutions of 1000 mg/L concentration was passed through the column packed with 300 g of 0.18 mm particle size of TMSP and the outlet solution was collected at the rate of 100 mL/2min. The maximum sorption capacity after quantification led to the extension of treating real run-off samples from electroplating industries containing excess Zn(II) concentration.

3.12.1 Column Packing

A glass column (inner diameter = 2.5 cm; height = 30 cm), shown in Fig.15 was first packed with glass wool (thickness = 3 cm) followed by glass beads (thickness = 2 cm). After making these two layers were made firm, about 50 g of the adsorbent (height = 6 cm) was carefully placed over the glass bead layer. Finally, the adsorbent was covered with another layer of glass wool (thickness = 1 cm).

About 500 mL of 1000 mg/L Zn(II) solution was introduced from the top of the column and the outlet sample was collected at a rate of 100 mL/20 s. After the collection of 1 litre of residual Zn(II) solution, 100% Zn(II) removal was ensured. A gradual decline in percentage removal was observed upto 90% at the end of passing 15 litres of inlet Zn(II) solution. Further reduction was continued upto 20 litres of inlet solution, following that TMSP packed column exhausted. Pictorial representation of the packed column with the experimental solution is shown in Fig 15.

3.13 Desorption/Regeneration Studies

Double distilled water was run through the exhausted column followed by the addition of 0.01 M H_2SO_4 as eluent at a collection of 100 mL/15 min. A complete Zn(II) desorption was

ensured through periodic analysis of the eluted samples through exhausted medium. After desorption, the packed material was again run with DD water. The regeneration capacity was registered as 90% recovery of TMSP against the freshly packed TMSP.

3.14 Mapping of Industrial Area-Choice of Study

Many electroplating industries were developed in Coimbatore. The electroplating units located at Kurumbapalayam area (highlighted in Table 6) were selected for the present study as numerous residential colonies nearby were subjected to heavy metal pollution due to improper and non-operative effluent treatment plants. Geographic Information System Mapping (GIS) of Sarcar Sama Kulam (study area) mapped using QGIS 3.8 software is shown in Fig 16, wherein, the green shade indicates the CODEA Industrial Park (10.5 acre) near Saravanampatti which comprises of 22 units of electroplating industries.

3.15 Collection of Effluents

Wastewaters containing excess Zn(II) than the permissible levels were collected from various electroplating industries in Kurumbapalayam region. About 10 L of these effluent samples were collected in precleaned PET bottles of 1 L capacity from each industrial unit. Analysis of Zn(II) ion (AAS) after a series of dilutions from table 7 revealed their concentrations to exceed the permissible limits (5.0 mg/L). The recorded pH and conductivity values imply that the samples are acidic.

3.15.1 Analysis of Industrial Effluents- Batch/Column Methods

Although, all the samples had excess Zn(II) concentration, batch/column experiment setup was limited to the sample collected from electroplating unit VII. The sample was diluted to 50 % and experimentally verified under optimized conditions. About 70% and 90% removal were achieved in batch and column studies, respectively.

3.16 Designing and Installation- Fiber Reinforced Polymer Column

Fiber Reinforced Polymer (FRP) Column was fabricated and installed at Kurumbapalayam, Coimbatore, Tamil Nadu with the assistance of a Design Engineer, Zion Enviro Systems Pvt. Ltd., Chennai. The dimensional and TMSP packing are shown below

The pictures representing the FRP Column, packing of material, installation and operation at field level is shown in Fig.17

The performance of the installed FRP Column was assessed by the passage of effluent sample [Zn(II)] through column inlet at a flow rate of 100 mL/5 min. About 15 L of the effluent sample was collected through the outlet and their residual concentrations were analyzed. The efficiency of the column was outstanding (0.5 mg/L of residual Zn(II) against 40 mg/L initial concentration).

4. Conclusion

Mollusc shell powder treated with HCl (TMSP) was found to be a cheap and efficient adsorbent of Zn(II) ions from aqueous solutions. The unloaded and Zn(II)-loaded TMSP samples were characterized structurally and morphologically by various characterization techniques. The surface analysis of Zn(II)-TMSP showed notable changes in the surface properties. The parameters such as, particle size of the adsorbent, dosage, initial concentration of Zn(II) ions, contact time, pH and temperature were optimized for maximal Zn(II) removal by batch studies. The experimental data when studied with Langmuir, Freundlich, Tempkin and DKR isotherm models to understand the type of adsorption, showed the best fit for Langmuir isotherm. The adsorption capacity of TMSP was also confirmed with column studies. Then, effluent wastewaters with higher Zn(II) concentration than the permissible levels were collected from Kurumbapalayam area and subjected to batch/column experiments. As close as 100% of Zn(II) removal from effluent wastewaters recorded in column studies against the batch studies (70%) under similar conditions. The exhausted TMSP material of the column could be desorbed using 0.01M H₂SO₄. Based on the column results and optimized conditions observed both at the laboratory and field levels for effluent analysis, a Fibre Reinforced Polymer (FRP) column was fabricated and installed at Kurumbapalayam. Statistical studies showed a significant correlation between the experimental variables and the quantity of Zn(II) ions adsorbed.

Financial Support

The authors have submitted their due acknowledgment to Defence Research & Development Organisation (DRDO), New Delhi for the timely Financial Support in execution of the research work.

References

- [1] H. M. Zwain, Comprehensive Study on Wastewater Treatment Using Low Cost Adsorbent, LAP Lambert Academic Publishing, Saarbrücken, Germany, 2012
- [2] D. Balkose and H. Baltacioglu, “Adsorption of heavy metal cations from aqueous solutions by wool fibers,” *Journal of Chemical Technology and Biotechnology*, vol. 54, no. 4, pp. 393–397, 1992.
- [3] Jaafari, J., Yaghmaeian, K., 2019. Optimization of heavy metal biosorption onto freshwater algae (*Chlorella coloniales*) using response surface methodology (RSM). *Chemosphere* 217, 447-455
- [4] Çelebi, H. & Gök, O. Evaluation of lead adsorption kinetics and isotherms from aqueous solution using natural walnut shell. *Int. J. Environ. Res.* 11, 83–90 (2017).
- [5] Benavente, V., Fullana, A. & Berge, N. D. Life cycle analysis of hydrothermal carbonization of olive mill waste: comparison with current management approaches. *J. Clean. Prod.* 142, 2637–2648 (2017).
- [6] Siddiqui, S. H. & Ahmad, R. Pistachio Shell carbon (PSC) e an agricultural adsorbent for the removal of Pb(II) from aqueous solution. *Groundw. Sustain. Dev.* 4, 42–48 (2017).
- [7] Ghorbani, F., Kamari, S., Zamani, S., Akbari, S. & Salehi, M. Optimization and modeling of aqueous Cr(VI) adsorption onto activated carbon prepared from sugar beet bagasse agricultural waste by application of response surface methodology. *Surf. Interfaces* 18, 100444 (2020)
- [8] Feizi, M. & Jalali, M. Removal of heavy metals from aqueous solutions using sunflower, potato, canola and walnut shell residues. *J. Taiwan Inst. Chem. Eng.* 54, 125–136 (2015)
- [9] Achanai Buasri, Nattawut Chaiyut, Kessarin Tapang, Supparoeck Jaroensin, and Sutheera Panphrom, Removal of Cu²⁺ from Aqueous Solution by Biosorption on Rice Straw - an Agricultural Waste Biomass, *International Journal of Environmental Science and Development*, Vol. 3, No. 1, February 2012
- [10] Efficient adsorption of Cr (VI) from aqueous solution on low cost adsorbent developed from *Limonia acidissima* (Wood apple) shell. *Ads. Sci.& Tech.*, 2010, 28 (6), 547-560..
- [11] HakanDemiral, IlknurDemiral, FatmaTumsek, BelginKarabacakoglu, (2008), Adsorption of Chromium(VI) from aqueous solution by activated carbon derived from olive bagasse and applicability of different adsorption models, *Chem. Eng. J.*, 144, 188-196.

- [12] M. Makeswari and Dr.T.Santhi, Use of *Ricinus communis* leaves as a low-cost adsorbent for removal of Cu(II) ions from aqueous solution, E-Journal of Chemistry 2009, 6(4), 1260-1266
- [13] D Harikishore Kumar Reddy, K Sessaiah, AVR Reddy, M Madhava Rao, MC Wang, Biosorption of Pb²⁺ from aqueous solutions by *Moringa oleifera* bark: Equilibrium and kinetic studies, J. Hazard. Mater. 174 (2010) 831-838
- [14] W Shaban Al Ramalli, A Abdella Dahmani, M Mohamed Abuein, A Amar Gleza, Biosorption of mercury from aqueous solutions by powdered leaves of castor tree (*Ricinus communis* L.), J. Hazard. Mater. 152 (2008) 955-959.
- [15] Wasewar, K. L., Atif, M., Prasad, B. & Mishra, I. M. Batch adsorption of zinc on tea factory waste. Desalination 244, 66–71 (2009).
- [16] Hui Gao, Yunguo Liu, Guangming Zeng, Weihua Xu, Ting Li, Wenbin Xia, Characterization of Cr(VI) removal from aqueous solutions by a surplus agricultural waste-Rice straw, J. Hazard. Mater. 150 (2008) 446-452.
- [17] Suresh Gupta, BV Babu, Utilization of waste product (tamarind seeds) for the removal of Cr(VI) from aqueous solutions: Equilibrium, kinetics, and regeneration studies, J. Environ. Manage. 90 (2009) 3013-3022.
- [18] Silke Schiewer, Ankit Balaria, Biosorption of Pb²⁺ by original and protonated citrus peels: Equilibrium, kinetics and mechanisms, Chem. Eng. J. 146 (2009) 211-219.
- [19] B Stephen Inbaraj, N Sulochana, Mercury adsorption on a carbon sorbent derived from fruit shell of *Terminalia catappa*, J. Hazard. Mater. 133 (2006) 283-290
- [20] Han JS, Rowell JS. Chemical composition of agro-based fibers, paper and composites from agro-based resources. Boca Raton: CRC Press,1996; pp. 83–134
- [21] Nemr A.E., J. Haz. Mat.,161,(2009), 132- 141.
- [22] Muhammad Riaz, RaziyaNadeem, Muhammad AsifHanif, Tariq Mehmood Ansari, Khalil-ur-Rehman, J. Haz. Mat., 161 (2008), 88-94.
- [23] Mehmet EminArgun, SukruDursun, CelalettinOzdemir, Mustafa Karatas, J. Haz. Mat., 141, (2007), 77-85
- [24] Nameni. M., AlaviMoghadam. M. R., Arami. M., Inter.J. Env. Sci.& Tech., 5,(2008), 161-168
- [25] Hanim Awab; Thanalechumi Paramalinggam, J. of Fund. Sci., 2012, 7(2), 113-119.

- [26] Kaustubha Mohanty, Mousam Jha, BC Meikap, MN Biswas, Removal of chromium (VI) from dilute aqueous solutions by activated carbon developed from Terminalia arjuna nuts activated with zinc chloride, Chem. Eng. Sci. 60 (2005) 3049-3059.
- [27] C. Namasivayam, M.V. Sureshkumar, Removal of chromium(VI) from water and wastewater using surfactant modified coconut coir pith as a biosorbent, Bio resource. Technol. 99 (2008) 2218-2222.
- [28] D. Nityanandi, C.V. Subbhuraam, Kinetics and thermodynamic of adsorption of chromium(VI) from aqueous solution using puresorbe. J. Hazard. Mater. 170 (2009) 876-882.
- [29] Runping Han, Jinghua Zhang, Weihua Zou, Jie Shi, Hongmin Liu, Equilibrium biosorption isotherm for lead ion on chaff, J. Hazard. Mater. 125 (2005) 266-271.
- [30] HP Boehm, Some aspects of the surface chemistry of carbon blacks and other carbons, Carbon. 32 (1994) 759-769.
- [31] Yuh-Shan Ho, Review of second-order models for adsorption systems, J. Hazard. Mater. 136 (2006) 681-689.
- [32] Efficient adsorption of Cr (VI) from aqueous solution on low cost adsorbent developed from Limonia acidissima (Wood apple) shell. Ads. Sci.& Tech., 2010, 28 (6), 547-560.
- [33] KP Shubha, C Raji, TS Anirudhan, Immobilization of heavy metals from aqueous solutions using polyacrylamide grafted hydrous Tin(IV) oxide gel having carboxylate functional groups, Water Res. 35 (2001) 300-310.
- [34] Yuh-Shan Ho, Chung-Chi Wang, Sorption equilibrium of mercury onto ground-up tree fern, J. Hazard. Mater. 156 (2008) 398-404
- [35] Alka Shukla, Yu-Hui Zhang, P Dubey, JL Margrave, S Shyam Shukla, The role of sawdust in the removal of unwanted materials from water, J. Hazard. Mater. 95 (2002) 137-152.
- [36] Suresh Gupta, BV Babu, Utilization of waste product (tamarind seeds) for the removal of Cr(VI) from aqueous solutions: Equilibrium, kinetics, and regeneration studies, J. Environ. Manage. 90 (2009) 3013-3022

Figures

Figure 1

a Untreated mollusc shell b TMSP

Figure 2

a BET plot for TMSP b BJH plot for TMSP

Figure 3

a: Unloaded TMSP- SEM b: Zn(II) loaded TMSP- SEM

Figure 4

a Unloaded TMSP- EDAX spectra b Zn(II) loaded TMSP- EDAX spectra

Figure 5

IR spectra of Unloaded and Zn(II) loaded TMSP

Figure 6

Particle Size-TMSP

Figure 7

Dosages-TMSP

Figure 8

Initial Concentrations

Figure 9

Effect of pH

Figure 10

Langmuir Isotherm

Figure 11

Freundlich Isotherm

Figure 12

Tempkin Isotherm Model

Figure 13

Dubinin-Kaganer-Radushkevich Isotherm Model

Figure 14

Vant Hoff's plot

Figure 15

Zn(II)- TMSP

Figure 16

GIS Mapping of Kurumbapalayam Area

Figure 17

FRP Column

Supplementary Files

This is a list of supplementary files associated with this preprint. Click to download.

- [Tables.pdf](#)
- [Graphicalabstract.pdf](#)