A Robust Embedded Load Cell Sensor for Tool Life Prognosis and Smart Sawing of Medium Carbon Steel

Yean-Ren Jeng (✉ imeyrj@gs.ncku.edu.tw)

National Cheng Kung University <https://orcid.org/0000-0001-6787-1538>

Ping-Chi Tsai

Chien-Wei Tseng

Research Article

Keywords: Tool life prognosis, Band saw, Tool wear, Surface roughness

Posted Date: February 11th, 2022

DOI: <https://doi.org/10.21203/rs.3.rs-1338130/v1>

License: This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Abstract

An embedded load cell sensor is proposed for the tool life prognosis and thrust force control of a band saw machine. The sensor enables the tool life and surface quality of the machined workpiece to be effectively improved through the use of a single sensing device strategically located in the cutting machine. The feasibility of the proposed sensor is demonstrated experimentally using a double-column horizontal sawing machine with medium carbon steel bars as the workpiece material. An investigation is performed into the effects of the cutting force, feed rate, and machining time on the tool wear and surface roughness of the machined workpiece. It is shown that the thrust force, tool wear and surface roughness of the machined workpiece are strongly correlated and increase over time. Based on the experimental results, a feedback control system is proposed for maintaining a constant thrust force on the band saw during cutting under even the most challenging conditions. Overall, the results confirm that the embedded load cell sensor and force monitoring and control methodology proposed in the present study provide an effective approach for maintaining the optimal cutting conditions in the sawing of medium carbon steel and improving the tool life and machined part quality.

1. Introduction

Sawing is an important manufacturing operation used in many industries to cut raw materials to a specific length prior to secondary precision manufacturing processes. There are three basic types of sawing process, namely band sawing, circular sawing, and hack sawing, where the choice between them depends primarily on the particular needs of the sawing task. Compared to circular sawing and hack sawing, band sawing achieves a lower kerf width, a higher metal removal rate, and an improved surface finish. As a result, it is frequently the method of choice for high-productivity sawing operations. However, such benefits are dependent on achieving a trouble-free operation of the sawing machine and its components. As for any machine tool, maintaining the cutting performance of band saw machines relies on a proper estimation of the tool life and working conditions [1]. Thus, monitoring the tool wear and surface quality of the sawed components, and adjusting the working conditions accordingly, is an important concern.

The literature contains many studies on tool condition monitoring (TCM) and life prediction methods. For example, Jemielniak [2] compared the signals obtained from laboratory and industrial cutting force sensors and concluded that cross-talk between the channels had a significant effect on the accuracy of the cutting force measurements in both cases. Choudhury and Rath [3] proposed a method for estimating the tool wear in the milling process based on the relationship between the flank wear and average cutting force coefficients produced under different cutting speeds, depths of cut, and feed rates. Gao et al. [4] introduced a data-driven model framework for TCM based on a statistical analysis of the cutting force. The validity of the proposed method was demonstrated experimentally through the lathe turning of Inconel 718 workpieces. Freyer et al. [5] compared the effectiveness of two TCM strategies based on orthogonal and unidirectional cutting force measurements, respectively, and found that the probability of a difference of less than 5 percentage points between the flank wear estimation errors of the two

methods was more than 95%. Kaya et al. [6] proposed an online TCM system for milling machines based on an analysis of the measured cutting force and torque by an artificial neural network (ANN). The proposed system was shown to achieve a high correlation rate and low error ratio between the actual and predicted values of the flank wear in the machining of Inconel 718. Garshelis et al. [7] developed a method for monitoring the cutting tool condition and operating parameters in a general machining process through an inspection of the magnetoelastic rate of change of a torque sensor signal. Ahmad et al. [8] used a three-component piezoelectric transducer to examine the effects of the machining parameters (i.e., the cutting speed and feed rate) and workpiece shape on the cutting performance of a band sawing machine with a variable pitch combination blade. Andersson et al. [9] detected the variation in the cutting force between the individual teeth of a band saw using a multi-sensor technique, and proposed a method for quantifying these variations using a cutting force model based on positional errors of the cutting edge, changes in the tool dynamics during machining, and edge wear of the cutting tool. Thaler et al. [10] presented a method for characterizing the band sawing process based on an analysis of the cutting force signals. It was shown that the force signals provided useful insights into not only the blade geometry, but also the homogeneity of the cut workpiece.

It is well-known that the surface texture plays an important role in determining how a real workpiece will interact with its cutting condition using in-process monitoring. The surface texture of a finished geometrically-defined component essentially represents the fingerprint of all the previous processing stages, and is generally quantified by the surface roughness [11-12]. For machining processes, the surface roughness not only provides an important indication of the part quality, but also yields valuable insights into the state of the manufacturing process and cutting tool. Consequently, monitoring and quantifying the surface roughness provides an effective approach for controlling the manufacturing process in such a way as to achieve the required degree of accuracy of the workpiece surface [13-15]. One of the most important factors affecting the surface roughness and machinability of the workpiece is the tool wear. In practice, the tool wear determines not only the surface roughness of the final part, but also the cutting force and tool life. Hence, by monitoring the cutting force, it is possible to both evaluate the evolution of the tool wear throughout the manufacturing process and to estimate the effect of this wear on the surface finish.

Various techniques based on multiple sensors have been proposed for monitoring the process variables during machining in order to estimate the tool wear. Bhogal et al. [16] showed that the cutting speed was one of the most important factors affecting tool vibration, and therefore had a critical effect on the surface finish. Amin et al. [17] investigated the effect of the chatter amplitude on the surface roughness under various cutting conditions, and found that the correlation between the chatter amplitude and the surface roughness increased with an increasing cutting speed. Arizmendi et al. [18] proposed a method for predicting the topography, surface roughness and form errors produced in the peripheral milling process based on an analysis of the tool vibration. David et al. [19] showed that, in the end-milling process, a higher cutting depth and feed rate lead to an increased cutting force and vibrational amplitude, which resulted in turn in a higher surface roughness. Zahoor [20] evaluated the effects of the feed rate, axial depth of cut and spindle vibration on the surface roughness and tool wear in the vertical milling of

AISI P20 steel workpieces using a solid carbide cutter. The results showed that the surface roughness depended mainly on the vibration amplitude and depth of cut, respectively, while the tool wear was governed principally by the vibration amplitude and feed rate.

In general, the accuracy of the prognostic estimation for the tool life of machine tools and surface quality of machined components is significantly dependent on the method used to collect and process the measurement data. However, while the tool condition can be accurately assessed through the deployment of multiple sensors on the machine tool system, such an approach is costly and applicable only to laboratory settings. Accordingly, taking the case of a band saw machine for illustration purposes, the present study proposes the use of the embedded load cell sensor, strategically located within the machine tool, to predict the wear of the band saw blade and estimate the surface quality of the machined component based on the measured value of the thrust force acting on the blade. Experimental trials are performed to investigate the effects of the cutting force, feed rate and machining time on the tool wear and surface roughness of the machined workpiece. It is shown that the thrust force, tool wear and surface quality of the machined workpiece are strongly correlated. As a result, the thrust force measurements provide a viable approach for evaluating the tool condition and predicting the tool life. Based on the experimental results, a feedback control system is developed for maintaining a stable thrust force on the band saw during cutting. The feasibility of the proposed approach is demonstrated experimentally through the machining of medium- and high-carbon steel workpieces with various cross-sections.

2. Experimental Setup

The experiments were performed on a fully automatic double-column horizontal band saw machine (E-530, Everising Machine Co., Taiwan), and involved sawing off small sections of carbon steel bars using a bi-metal band saw blade (HSS M42 cutting edge) spring steel backing material with a conventional raker tooth setting. Figs. 1 and 2 present a series of photographs showing the machining setup and observation apparatus, respectively. The sensor proposed in the present study had the form of a small metal cylindrical bar with two embedded piezoelectric films (see Fig. 2(a)). The geometry and dimensions of the sensor, and the installation positions of the two films, were carefully designed by finite element method (FEM) simulations to achieve the optimal tradeoff between the rigidity of the sensor structure and the sensitivity of the force measurement results [21]. As shown in the upper-left schematic in Fig. 2 (b), the sensor was installed within the machine tool itself by replacing one of the guide pins immediately above the band saw. During the sawing process, the thrust force exerted on the saw was transmitted mechanically to the force sensor through the structure of the machine tool, and the resulting piezoelectric signal was collected and analyzed by a multi-channel data logger (GL220, Graphtec Corporation, Japan). An industry-grade packaging technique was employed to protect the sensor from the harsh environment generated during the sawing process. A similar technique has also been utilized to produce the multidirectional force sensor for artificial or robotic finger applications by Cha et al. [22].

Having installed the sensor, experimental trials were performed to investigate the effects of the cutting force, feed rate, and machining time on the wear of the band saw and surface roughness of the machined bars. The machining process was real-time observed using a high-resolution image capture technology [23] from the machine tool (see Fig. 1). The tool wear and surface roughness of the machined parts were estimated at room temperature using a 3D confocal microscope attached to a 5 MP digital camera with a spatial resolution of 0.04 μm , a vertical resolution of less than 0.01 nm, and a 20x objective lens. A similar technique was also used by Jeng et al. [24] in the evaluation of surface roughness of cold-rolled aluminum sheets.

3. Results And Discussion

3.1 Tool life evaluation

The experiments commenced by measuring the thrust force acting on the band saw during the cutting of JIS S45C medium carbon steel workpieces with dimensions of $100 \times 100 \text{ mm}^2$. The experiments were performed under heavy cutting conditions with a cutting speed of 62 m/min and a cutting rate of 63 cm^2 / min . The cutting process was performed continuously over the full band saw life cycle, including the run-in stage, the steady-state cutting stage, the wear stage, and the failure stage. Fig. 3 shows the variation of the thrust force over time (in seconds) for the different number of sections cut during the sawing process. It is seen that the thrust force increases and becomes increasingly unstable as the number of repeated cuts increases. Fig. 4 shows the variation of the measured thrust force over the complete band saw life cycle. As shown, the force response increases over time, and can be divided into three main regions, namely (a) an initial break-in region with a rapidly increasing wear rate; (b) a steady-state wear region with a uniform wear rate; and (c) a failure region with a rapidly increasing wear rate. It is noted that the measurement results are similar to those reported for milling operations by Groover [25]. Figs. 5 and 6 show the face wear and flank wear, respectively, of the band saw blade in the run-in and failure stages of the band saw life cycle, where the tool wear level and wear area can be acquired and estimated based on machine vision by a high-resolution image capture technology [23, 26]. At the wear-in and final stages, the increased wear in both blade face and blade flank are more pronounced. As shown in Figs. 5 (a), 5(b), 6(a), and 6(b), the corresponding chip shapes and tooth tip shapes are shown below each figure for comparison purposes. It is noted that the higher wear levels for both blade face and blade flank at the initial sawing state (i.e. the cutting slices ranging from 50 to 150) may be induced due to their deburring process for removing sharp external edges. Moreover, the measured thrust force profile shown in Fig. 4 provides a feasible means of estimating the onset of break-in mechanism and wear behavior on the band saw during an overall cutting process.

Figure 7 shows the variation in the workpiece surface roughness (R_q) with the number of sections cut from the bar under the optimal sawing conditions. Note that to ensure the reliability of the measurement results, eight sampling lengths were performed on each workpiece, and the R_q values were computed as the average value of the corresponding measurements, in which about 95% confidence of the values (i.e.,

two standard deviations) has been employed to provide a purpose of obtaining the normal distribution in the present measures, and thus the experimental errors can be effectively avoided. As expected, the surface roughness increases with an increasing number of cuts. Moreover, a sudden increase in the blade displacement is observed as the number of sections removed increases beyond 350 (i.e., the estimated life of the tool, see Figs. 4, 5, and 6).

In general, the motor current signal is one of the widely accepted key indicators, albeit an experienced operator is often needed to filter out noise for an effective signal, which could show how tool machine cutting performance decrease over lifetime. Several similar observations were reported in the tool-wear monitoring for metal cutting machines by Snr et al. [27] and Pimenov et al. [28]. To better understand the relationship between motor current and thrust force in metal cutting operations, Fig. 8 shows the variation of the motor current and the thrust force with the number of sections cut from the bar under the optimized sawing conditions. Note that both bandsaw blades have been conducted with the same cutting conditions to study tool wear during the sawing process, where sample 1 and 2 are in Fig. 8. Both the thrust force and the corresponding current increase with an increasing number of cuts since, as the saw tooth gradually wears, the energy required to cut the workpiece material increases, and hence the required thrust force also increases, thereby increasing the associated current and the root-mean-square surface roughness of the workpiece.

3.2 Cutting parameter optimization

In practical sawing operations, it is desirable to set the cutting parameters (i.e., the cutting speed and cutting rate) in such a way as to achieve an acceptable tradeoff between the productivity of the machining process and the blade life. Accordingly, a further series of experiments was performed in which JIS S45C medium carbon steel bars with a diameter of 220 mm were sawed with gradually increasing cutting rates in the range of 85 to 135 cm²/min. To ensure the reliability of the experimental results, the cutting trials were performed three times for each cutting rate, with the corresponding thrust force and workpiece surface roughness measured each time.

Figure 9 shows the variation in the measured thrust force over time for the different cutting rates. As expected, the cutting force increases with an increasing cutting rate due to the corresponding increase in the friction mechanism required to cut the workpiece material. Fig. 10 shows the change in amplitude of the thrust force with the cutting rate. Once again, the amplitude of the thrust force increases with an increasing cutting rate. Finally, Fig. 11 shows the variation of the R_q with the cutting rate. The surface roughness increases only moderately as the cutting rate first increases from 85 cm²/min to 115 cm²/min. However, as the cutting rate is further increased to 135 cm²/min, a significant increase in the surface roughness occurs. Thus, the optimal cutting rate for the S45C material was determined to be 115 cm²/min.

3.3 Thrust force feedback control methodology

In the process of sawing a bar with a constant and solid cross-section, the contact area first increases toward a maximum value as the blade penetrates into the workpiece, and then decreases to zero as the blade leaves the workpiece. The change in contact area prompts a variation in the thrust force acting on the blade, and therefore induces a change in the wear rate. Thus, to reduce the wear of the blade, it is desirable to minimize the variation of the thrust force such that it maintains an approximately constant value throughout the cutting process. Accordingly, the present study proposes a thrust force feedback control methodology in which the thrust force is constantly monitored by the embedded force sensor, and the machining conditions (e.g., the cutting speed and feed rate) are adjusted as required to maintain a constant force.

The feasibility of the proposed control method was evaluated using JIS S45C and JIS S60C medium- and high-carbon steel bars with a diameter of 150 mm. Fig. 12 shows the force-time diagram obtained in three tests performed using the JIS S45C workpiece without feedback control. It is clearly seen that the thrust force varies continuously as the sawing process proceeds. Fig. 13 compares the set-point force value and actual force value when sawing the two workpieces (i.e., JIS S45C and JIS S60C carbon steel bars) using the proposed feedback control method. From inspection, the error between the two thrust force values is just 2% and 1.6% for the two materials, respectively. In other words, the feasibility of the proposed method is confirmed.

Figure 14 shows the force-time diagrams obtained in the sawing of the JIS S45C workpiece with set-point thrust force values in the range of 200 to 400 N and the feedback control method applied. For comparison purposes, the force-time diagram obtained with the absence of feedback control is also shown. The results confirm that the thrust force remains approximately constant, even under higher thrust force setting points. Fig. 15 presents the corresponding results obtained for the sawing of JIS S60C high carbon steel under thrust forces in the range of 500 to 900 N. It is again seen that the feedback control methodology achieves an approximately constant thrust force for each of the considered force settings. A final series of experiments was performed using JIS S45C O-beam and H-beam workpieces. The corresponding force-time diagrams are presented in Figs. 16 and 17, respectively. Note that the O beam had an outer diameter of 133 mm and a wall thickness of 1.4 mm, while the H beam had a height and width of 125 mm and a thickness of 10 mm. The results confirm the effectiveness of the proposed thrust control methodology even in the sawing of workpieces with more complex cross-sectional geometries.

4. Conclusion

This study has presented an embedded force sensor for detecting the cutting force generated during the cutting of medium carbon steel using a double-column horizontal sawing machine. The proposed sensor has been used to explore the effects of the cutting force, cutting rate and machining time on the wear of the band saw blade and surface roughness of the workpiece. It has been shown that the cutting force increases with an increasing machining time and results in a corresponding increase in both the tool wear

and the machined surface roughness. It has been further shown that the wear life of the band saw blade can be reliably predicted from a sudden increase in the measured cutting force or surface roughness.

The developed force sensor has been used to realize a feedback control mechanism for maintaining a stable cutting force during the sawing of carbon steel workpieces with various carbon contents and cross-sections (bar, O beam and H beam). The proposed sensor has many advantages for practical applications, including a low cost, a small size, and good robustness. Notably, the sensor is installed close to the blade within the machine tool itself, and therefore enables the cutting force to be measured directly with a high degree of precision. Moreover, the sensor allows the cutting force and cutting conditions to be monitored and controlled using only a single sensing device. It is thus suitable for practical, industrial applications. Overall, the results show that the proposed sensor provides a highly effective method for not only monitoring the tool life condition of the band saw blade, but also for adjusting the machining parameters adaptively in such a way as to maintain a constant cutting force, thereby reducing the tool wear and improving the surface roughness of the machined components.

Declarations

Acknowledgement This work was financially supported by the Ministry of Science and Technology of Taiwan (MOST 108-2221-E-006-228-MY3, 109-2923-E-006-005-MY3 and 110-2124-M-006-005) and Air Force Office of Science Research (AFOSR) under contract no. FA4869-06-1-0056 AOARD 064053. Professor Yeau-Ren Jeng would like to acknowledge Medical Device Innovation Center (MDIC) and Intelligent Manufacturing Research Center (iMRC) from The Featured Areas Research Center Program within the framework of the Higher Education Sprout Project by the Ministry of Education (MOE) in Taiwan and AC2T research GmbH (AC2T) in Austria (COMET InTribology, FFG-No.872176).

Autho contribution Conceptualization, Y. R. Jeng, P. C. Tsai, and C. W. Tseng; methodology, Y. R. Jeng, P. C. Tsai, and C. W. Tseng; formal analysis, P. C. Tsai and C. W. Tseng; investigation, P. C. Tsai and C. W. Tseng; writing-original draft preparation, Y. R. Jeng and P. C. Tsai; writing-review and editing, Y. R. Jeng and P. C. Tsai.

Ethical approval Not applicable.

Consent to participate Not applicable.

Consent to publish Not applicable.

Competing interests The authors declare no competing interests.

References

1. Zhou ZD, Chen YP, Fuh JYH, Nee AYC (2000) Integrated Condition Monitoring and Fault Diagnosis for Modern Manufacturing Systems. CIRP Ann Manuf Technol 49: 387-90

2. Jemielniak K (2000) Laboratory versus industrial cutting force sensor in tool condition monitoring. *J Manuf Sci Prod* 3: 41-7.
3. Choudhury SK (2000) Rath S. In-process tool wear estimation in milling using cutting force model. *J Mater Process Technol* 99: 113-9.
4. Gao D, Liao Z, Lv Z, Lu Y (2015) Multi-scale statistical signal processing of cutting force in cutting tool condition monitoring. *Int J Adv Manuf Technol* 80: 1843-53.
5. Freyer BH, Heyns PS, Theron NJ (2014) Comparing orthogonal force and unidirectional strain component processing for tool condition monitoring. *J Intell Manuf* 25: 473-87.
6. Kaya B, Oysu C, Ertunc HM (2011) Force-torque based on-line tool wear estimation system for CNC milling of inconel 718 using neural networks. *Adv Eng Softw* 42: 76-84.
7. Garshelis IJ, Kari RJ, Tollens SPL, Cuseo JM (2008) Monitoring cutting tool operation and condition with a magnetoelastic rate of change of torque sensor. *J Appl Phys* 103: 07E908
8. Ahmad MM, Hogan B, Goode E (1989) Effect of machining parameters and workpiece shape on a bandsawing process. *Int J Mach Tools Manuf* 29: 173-83.
9. Andersson C, Stahl JE, Hellbergh H (2001) Bandsawing. Part II: detecting positional errors, tool dynamics and wear by cutting force measurement. *Int J Mach Tools Manuf* 41: 237-53.
10. Thaler T, Bric I, Bric R, Potocnik P, Muzic P, Govekar E (2012) Characterization of band sawing based on cutting forces. *J Mach Eng* 12: 41-54.
11. Lucca DA, Brinksmeier E, Goch G. (1998) Progress in Assessing Surface and Subsurface Integrity. *CIRP Ann Manuf Technol* 47: 669-93.
12. Jawahir IS, Brinksmeier E, Saoubi RM, Aspinwall DK, Outeiro JC, Mey D, Umbrello D, Jayal AD (2011) Surface integrity in material removal processes: Recent advances. *CIRP Ann Manuf Technol* 60: 603-26.
13. Trumpold H (2001) Process related assessment and supervision of surface textures. *Int J Mach Tools Manuf* 41: 1981-93.
14. Palanikumar K (2007) Modeling and analysis for surface roughness in machining glass fibre reinforced plastics using response surface methodology. *Mater Des* 28: 2611-18
15. Wang X, Feng CX (2002) Development of empirical models for surface roughness prediction in finish turning. *Int J Adv Man Technol* 20: 348-56.
16. Bhogal SS, Sindhu C, Dhami SS, Pabla BS (2015) Minimization of surface roughness and tool vibration in CNC milling operation. *J Optim* 2015: 1-13
17. Amin AN, Patwari AU, Sharulhazrin MS, Hafizuddin I (2010) Investigation of effect of chatter amplitude on surface roughness during end milling of medium carbon steel. In: International conference on industrial engineering and operations management, Dhaka, Bangladesh, Jan 9-10.
18. Arizmendi M, Campa FJ, Fernández J, Lacalle LNL, Gil A, Bilbao E, Veiga F, Lamikiz A (2009) Model for surface topography prediction in peripheral milling considering tool vibration. *CIRP Ann Manuf Technol* 58: 93-6.

19. David C, Sagris D, Stergianni E, Tsiafis C, Tsiafis I (2018) Experimental analysis of the effect of vibration phenomena on workpiece topomorphy due to cutter runout in end-milling process. Mach 6: 27.
20. Zahoor S, Mufti NA, Saleem MQ, Mughal MP, Qureshi MAM (2017) Effect of machine tool's spindle forced vibrations on surface roughness, dimensional accuracy, and tool wear in vertical milling of AISI P₂₀. Int J Adv Manuf Technol 89: 3671-9.
21. Kim JO, Jung GL (2007) Dynamic characteristics of piezoelectric cylindrical transducers with radial polarization. J. Sound Vib 300: 241-9
22. Lee YR, Neubauer J, Kim KJ, Cha YS (2020) Multidirectional cylindrical piezoelectric force sensor: Design and experimental validation. Sensorsc 20: 4840.
23. Kim JH, Moon DK, Lee DW, Kim JS, Kang MC, Kim KH (2002) Tool wear measuring technique on the machine using CCD and exclusive jig. J Mater Process Technol 130-131: 668-74.
24. Jeng YR, Lee JT, Hwu YJ, Liu LC, Lu CY (2020) Effects of operation parameters of cold rolling on surface finish of aluminum. Tribol Int 148: 106321
25. Ong P, Lee WK, Lau RJH (2019) Tool condition monitoring in CNC end milling using wavelet neural network based on machine vision. Int J Adv Manuf Technol 104: 1369-79.
26. Groover M (2010) Fundamentals of modern manufacturing, Materials, Processes, and Systems. New York, USA: John Wiley & Sons Ltd.
27. Snr DED (2000) Sensor signals for tool-wear monitoring in metal cutting operations-a review of methods. Int J Mach Tools Manuf 40: 1073-98.
28. M Kuntğlu M, Aslan A, Pimenov DY, Usca UA, Salur E, Gupta MK, Mikolajczyk T, Giasin K, Kapłonek W, Sharma S (2021) A review of indirect tool condition monitoring systems and decision-making methods in turning: Critical analysis and trends. Sensors 20: 4840.

Figures

Figure 1

System setup of sawing process monitoring

Figure 2

The experimental setup of the *piezoelectric* sensor for the cutting force measurement. (a) Schematic of the sensor configuration, (b) Real image with the position of the *piezoelectric* sensor indicated in the band saw machine.

Figure 3

Variation of thrust force over time for the different number of sections cut during the sawing process

Figure 4

Variation of thrust force with number of sections cut from bar. (Note that labels (a), (b), and (c) indicate the wear-in region, steady-state wear region, and failure region, respectively.

Figure 5

The average wear area of blade face, (a) chip shape in initial sawing stage, and (b) chip shape in final sawing stage.

Figure 6

The average wear area of blade flank, (a) tooth tip shape in initial sawing stage, and (b) tooth tip shape in final sawing stage.

Figure 7

Variation of workpiece surface roughness with number of sections cut from bar.

Figure 8

Variation of motor current and thrust force with number of sections cut for both bandsaw blades with the same specifications.

Figure 9

Variation of cutting force overtime for different cutting rates.

Figure 10

Variation of the amplitude of thrust force with cutting rate.

Figure 11

Variation of workpiece surface roughness with cutting rate.

Figure 12

Force-time diagram for sawing of JIS S45C round bar without feedback control.

Figure 13

Comparison of set-point force value and actual force value obtained under feedback control for JIS S45C and JIS S60C carbon steel bars.

Figure 14

Force-time diagram for sawing of JIS S45C round bar under different thrust force settings with and without feedback control.

Figure 15

Force-time diagram for sawing of JIS S60C round bar under different thrust force settings with and without feedback control.

Figure 16

Force-time diagram for sawing of JIS S45C O beam under different thrust force settings with and without feedback control.

Figure 17

Force-time diagram for sawing of JIS S45C H beam under different thrust force settings with and without feedback control.