CPT to RVU Conversion Improves Model Performance in the Prediction of Surgical Case Length

Nicholas Garside (✉ nicholas.garside@duke.edu)

Duke University

Hamed Zaribafzadeh

Duke University

Ricardo Henao

Duke University

Royce Chung

Duke University

Daniel Buckland

Duke University

Research Article

Keywords: current procedural terminology (CPT) , RVU, CPT, MAE, surgical case length

Posted Date: January 25th, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-149749/v1>

License: © ⓘ This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Version of Record: A version of this preprint was published at Scientific Reports on July 8th, 2021. See the published version at <https://doi.org/10.1038/s41598-021-93573-2>.

Abstract

Methods used to predict surgical case time often rely upon the current procedural terminology (CPT) code as a nominal variable to train machine-learned models, however this limits the ability of the model to incorporate new procedures and adds complexity as the number of unique procedures increases. The relative value unit (RVU, a consensus-derived billing indicator) can serve as a proxy for procedure workload and could replace the CPT code as a primary feature for models that predict surgical case length. Using 11,696 surgical cases from Duke University Health System electronic health records data, we compared boosted decision tree models that predict individual case length, changing the method by which the model coded procedure type; CPT, RVU, and CPT-RVU combined. Performance of each model was assessed by inference time, MAE, and RMSE compared to the actual case length on a test set. Models were compared to each other and to the manual scheduler method that currently exists. RMSE for the RVU model (60.8 mins) was similar to the CPT model (61.9 mins), both of which were lower than scheduler (90.2 mins). 65.2% of our RVU model's predictions (compared to 43.2% from the current human scheduler methods) fell within 20% of actual case time. Using RVUs reduced model prediction time by 8-fold. Replacing pre-operative CPT codes with RVUs maintains model performance while decreasing overall model complexity in the prediction of surgical case length.

Introduction

Hospital systems within the United States commonly use the current procedural terminology (CPT) coding system developed by the American Medical Association (AMA) to identify specific procedures performed during surgery^{1,2}. Nationally implemented in the 1980's, CPT codes are standardized by the AMA to streamline hospital operations and billing processes. As of 2020, there exist thousands of unique 5-digit CPT codes ranging from 00100 – 99499, grouped by specialty and type. The surgical category ranges from 10021-69990. Anticipated procedures are logged by hospital operations in the form of pre-operative (pre-op) CPT codes, which may differ from procedures that end up being performed (the post-op CPT list) based on clinical findings during the operation.

These nominal CPT codes have been used extensively in the development of empirical models that predict operating room (OR) surgical case length. Wright *et al.*³, for example, showed that regression models utilizing surgeon estimates and mapped categorical CPT codes could perform as well as scheduling system estimations, with a mean absolute error (MAE) of 55 minutes. Eijkemans *et al.*⁴ used 253 unique procedure categories to develop their models, which attained a 25% reduction in MAE compared to that of human-estimated scheduling predictions. More complex machine-learned (ML) models have been developed since these early regression models^{5,6,7}, but all have relied on categorical CPTs in their predictions, which limits applicability beyond their specific training scope. Furthermore, high complexity in these ML algorithms, such as the gradient-boosted decision tree developed by Zhao *et al.*⁸ in 2019, can face longer training times and higher computational costs compared to their simpler regression predecessors.

In 1991, the AMA began reimbursing hospitals based on the relative value unit (RVU) which is a standardized index associated with each CPT that captures staff workload for a given procedure⁹. The total RVU is a combination of three separate measures: work RVU, practice expense RVU, and professional liability RVU¹⁰. In most cases, work RVU is the dominant term in the total RVU sum, while the other two terms are sufficiently small to be ignored. For sense of scale, typical RVU values fall in range [0, 100]. Like other indices meant to capture relative intensity of a single characteristic¹¹, the RVU places a lower-bound at zero and increases indefinitely. It may also provide added benefits in model simplicity, much like other clinical indices in recent work¹². We hypothesize that conversion of CPT codes into their respective work RVU indices will serve as supplement for capturing case complexity in the prediction of OR case length, maintaining model performance while increasing the model's ability to perform outside a subset of specifically trained surgical procedures.

Methods

Cohort identification and data preprocessing.

Retrospective billing data of colorectal and spinal surgeries from Duke University Health Systems (with 6 separate locations) between July 2014 and December 2019 was collected and deidentified. This work was found exempt by the Duke Institutional Review Board (Pro00104275). After removing records with missing values and/or errors in the timestamps, we obtained 11,696 inpatient/outpatient records for analysis, including 3,847 colorectal and 7,849 spinal surgery cases. This includes 27 patients under the age of 18 (min age, 13). The total time of surgery was calculated in minutes from operating room setup to cleanup time and then log-transformed to handle skewness. A best-subset regression process was followed to choose a combination of predictor variables from the retrospective billing data that could be correlated with case length as the target output of a linear regression model. This exploratory data analysis revealed nine significantly correlated pre-op features that maximized the adjusted R^2 of the tested linear regression models. These variables included: CPT code, work RVU, number of panels (surgical specialties involved), number of procedures, geographic location (buildings within Duke Health System), patient class, first case of the day (binary), day of the week, and primary physician. The nominal CPT code variable comprises a list of the top 10 CPT codes used to classify the scheduled case, which were also used to derive a summed work RVU index based on Center for Medicare and Medicaid Services (CMS) Physician Fee Schedule January 2020 released file¹³. Importantly, this is the physician work RVU, but will be referred to as "RVU" through the remainder of this study. All variable descriptions and high-level distributions are listed in Tables 1, 2 and 3.

Table 1
Feature Descriptions

Variable	Type	Description
CPT code	Nominal	Current Procedural Terminology – A five-digit code representing procedure ID
RVU	Continuous	Relative Value Unit – measure of procedure complexity for use in billing
Number of panels	Ordinal	Number of surgical specialties needed for each case
Number of procedures	Ordinal	Number of procedures performed in each case
Location	Nominal	One of six buildings within Duke Health System, both outpatient and inpatient.
Patient class	Nominal	Patient class labels as ambulatory surgery, surgery admit inpatient, inpatient, surgery bedded outpatient, emergency
First case flag	Nominal	A binary flag indicating the first case of a day for a given operating room
Day of the week	Nominal	Day that the operation was performed (Mon, Tue, Wed, Thu, Fri, Sat, Sun)
Primary physician ID	Nominal	Identifier tied to lead surgeon on case

Model development and evaluation.

Three extreme gradient boosting (XGBoost, version 1.1.1)¹⁴ models were developed in Python (version 3.7.6) to predict total time of the surgery. These models utilized either the RVU, the CPT codes, or the RVU and the CPT codes combined while the remaining features remained the same in each model. The models were trained to minimize the mean squared error (MSE) as its loss function. Training and hyper-parameters optimization were performed using a 75%-25% training-test data split and by 5-fold cross validation, in which different combination of hyper-parameters were evaluated in each of the five randomized training subsets. The best-performing hyper-parameters were selected to minimize the average mean squared error across the five subsets. These hyper-parameters include maximum tree depth, subsample ratio, and L1- and L2-regularization terms. Then, the model with the best hyper-parameters was used to predict the length of surgery within the test data (i.e. 25% of the data) and finally evaluated using mean absolute error (MAE) and root mean squared error (RMSE) as the performance metrics. To calculate the 95% confidence interval of the performance metrics, we used bootstrapping and resampling methods on the test data set.

Table 2
Continuous Variable Distributions

Variable	25% Percentile	Mean	Median	75% Percentile
RVU	13.2	34.0	33.3	48.1
Number of panels	1	1.1	1	1
Number of procedures	1	4.4	4	7

Table 3
Categorical Variable Distributions

Variable	Unique count	Most Common Value Percentage
CPT	443	17.1
Location	6	45.4
Patient class	5	42.7
First case flag	2	65.2
Day of the week	7	26.3
Primary physician	26	10.5

Results

Schedulers performance.

To provide a better perspective on scheduler performance, we first defined 20% of the actual length of surgery as the acceptable margin of error, meaning any prediction below or above this threshold was considered an under- or over-prediction, respectively. We then plotted all the data in a joint plot to visualize the distribution of each category. As shown in Figure 1A, human schedulers under-predicted surgery time more often than over-predicted, with 49.3% of cases under-predicted, 44.1% on time, and 6.6% over-predicted (Figure 1B).

Model performance.

The distributions of the model and the schedulers prediction using the test set are shown in Figure 2A, B, and C. Figure 2D then reports the over- and under-prediction percentage distributions. They show that the model correctly predicted more cases within the 20% margin of error comparing with the scheduler, with less under-prediction and more over-prediction. The model predicted 65.2% of cases within the 20% margin of error (51% improvement over the scheduler), under-predicted 16.1% of cases (67.9%

improvement over the schedulers), but over-predicted 18.7% of cases (283.3% increase over the scheduler, Figure 2C). The MAE and RMSE values of the schedulers, which were calculated from the test set, were 60.1 and 90.2 minutes, respectively. The model which uses only the RVU, outperformed the schedulers performance by 35.6% and 32.6% in terms of MAE and RMSE and reduced them to 38.5 and 60.8 minutes, respectively (Table 4). Similarly, the model which used the CPT codes instead of the RVU also improved the schedulers MAE and RMSE by 34.4% and 31.4%, respectively but required 9.4-times more time than the RVU model to predict the case length. On the other hand, the model that uses both the RVU and the CPT codes improved the RVU model MAE and RMSE only by 2.3% and 2.2%, respectively and required 8.5-times more time to predict the case length.

Feature importance.

To compare the importance of features in construction of the boosted trees, we calculated the average number of times each feature was utilized to split the data across all the trees as the “score” of each feature. Figure 3 shows the top 3 features that were most used in each model. RVU (score = 1,960) and all the CPT codes (score = 2,773) were the most important features in the RVU and CPT models, respectively (Figures 3A and 3B). Interestingly, the RVU (score = 1,880) was the second most important feature after the all the CPT codes (score = 3,509) in the model that incorporated the RVU and CPT codes (Figure 3C).

Table 4
Model and scheduler performance metrics

Prediction type	Prediction Time (relative to RVU model)	MAE (95% CI)	RMSE (95% CI)
Scheduler	N/A	60.1 (57.0-63.6)	90.2 (84.7-96.5)
RVU model	1	38.5 (36.3-40.9)	60.8 (56.3-66.0)
CPT model	9.4	39.4 (37.0-41.9)	61.9 (56.3-67.4)
RVU + CPT model	8.5	37.3 (34.9-39.6)	58.8 (54.0-63.8)

Discussion

The main goal of this study was to determine model performance effects from the CPT to RVU conversion. The RVU-based method not only succeeds in maintaining RMSE compared to the CPT-based method (Table 3) but yields a 1.1-minute reduction, pointing to the possibility that RVU usage trends toward improved performance. While CPT and RVU were initially created to serve different functions by design, these results show that both input types offer information on relative case complexity in the prediction of surgical case length. Preserving CPT codes as a nominal feature in model creation allows the algorithm to uncover case complexity implicitly, whereas conversion to RVU relies on a pre-determined magnitude of case complexity that has already been established by a board of experienced physicians.

These comparisons clearly show that replacing the CPT codes with the RVU yields similar but more efficient performance.

While performance between the CPT-based and RVU-based methods were similar, inference times (the time it takes to calculate a prediction) were not. Conversion to RVU showed a 9.4-fold reduction in total time to predict case time. This is useful when scaling dynamic models that retrain frequently.

The RVU-based model shows increased robustness compared to its CPT-based counterpart. Besides sparsity, one disadvantage of using CPT's in model creation is its dependence on familiar codes to be able to calculate an output. New CPT's that were not part of the training data cannot be used. A CPT code from the cardiothoracic subspecialty, for example, would not generate a predicted surgical case time since no CPT's were used in the training data. Other sources of model breakdown include data entry errors, non-existent CPT codes, or outdated procedure codes. RVU, on the other hand, is more robust as it is a continuous data type that avoids these sources of breakdown, enabling new and uncommon procedures to be handled with ease.

From Table 4 we see an improvement in MAE and RMSE measures for all three developed models compared to the human scheduler. In our data, human schedulers under-predict case length half of the time (Figure 1B) and over 8 times as often as over-prediction, affecting the health systems ability to efficiently schedule room allocations and staffing costs. The improved accuracy and more balanced error performance of our predictive models could reduce associated room backlog and overtime cost problems if used on a consistent basis. Based on our results we would expect any of the three models to outperform the human scheduler in accuracy. However, it is important to acknowledge potential reasons for purposeful underprediction by the human scheduler. One benefit, for example, would be reduced room latency and increased number of procedures performed during the day. It remains to be seen if predictive model usage would lead to increased net revenue for the hospital, which would be a worthwhile direction for future work.

While conversion to RVU retains case complexity information for a given procedure, it is important to acknowledge that procedure identification information is lost in the process. This implies that two completely different procedures within different subspecialties will appear indistinguishable from one another if they have similar RVU values. While this may not be important for the problem of case length prediction, it may be undesirable when extending to other types of predictive models that use CPT codes to distinguish between procedures with similar work value. Another limitation of this study is that we didn't explore every possible feature selection method (best subset regression), and future methods may use a different feature subset in training. This study only looks at two surgical subspecialties: colorectal and spine. Performance might change with data inclusion from other subspecialties and with more observations from the colorectal and spinal subspecialties. This study used data from multiple locations within a single, large hospital system which uses the same scheduling methods.

Conclusions

Converting the categorical CPT code to a RVU that captures case complexity provided similar model performance in predicting colorectal and spinal surgical case length. The conversion enabled shorter model training times and increases robustness to unanticipated procedure inputs.

Declarations

Data Availability

The data used in this study is considered privileged under HIPAA within Duke Health System due to many patient specific identifiers used in the model training and is unavailable for public release. A de-identified data set may be provided on request after institutional approval.

Acknowledgments:

We would like to acknowledge Wendy Webster (Division Administrator, Duke Dpt. of Surgery) for assisting in data acquisition.

Author Contributions:

NG is the corresponding author for this publication and was responsible for exploratory data analysis, background, and discussion. HZ was responsible for model development. DB assisted in data acquisition, study formulation, and conclusion. RH reviewed manuscript. RC assisted with initial exploratory data analysis and feature identification. All authors attest to the accuracy and originality of the content in this manuscript.

Competing Interests:

The authors declare no competing interests.

Correspondence:

Should be addressed to NG (nicholas.garside@duke.edu).

References

1. Thorwarth W. From Concept to CPT Code to Compensation: How the Payment System Works. *Journal of the American College of Radiology* 1(1), 48-53. [https://doi.org/10.1016/S1546-1440\(03\)00020-6](https://doi.org/10.1016/S1546-1440(03)00020-6) (2004).

2. CPT® overview and code approval. (n.d.). Retrieved December 02, 2020, from <https://www.ama-assn.org/practice-management/cpt/cpt-overview-and-code-approval>
3. Wright I, Kooperberg C, Bonar B, Bashein G. Statistical Modeling to Predict Elective Surgery Time: Comparison with a Computer Scheduling System and Surgeon-provided Estimates. *Anesthesiology* **85**, 1235–1245. <https://doi.org/10.1097/00000542-199612000-00003> (1996).
4. Eijkemans M, van Houdenhoven M, Nguyen T, Boersma E, Steyerberg EW, Kazemier G. Predicting the Unpredictable: A New Prediction Model for Operating Room Times Using Individual Characteristics and the Surgeon's Estimate. *Anesthesiology* **112**, 41–49. <https://doi.org/10.1097/ALN.0b013e3181c294c2> (2010).
5. Strum D.P., Vargas L.G., May J.H. *et al.* Surgical Suite Utilization and Capacity Planning: A Minimal Cost Analysis Model. *Journal of Medical Systems* **21**, 309–322. <https://doi.org/10.1023/A:1022824725691> (1997).
6. Zhao B, Waterman RS, Urman RD, Gabriel RA. A Machine Learning Approach to Predicting Case Duration for Robot-Assisted Surgery. *Journal of Medical Systems* **43**(2), 32. <https://doi.org/10.1007/s10916-018-1151-y> (2019).
7. Bartek MA, Saxena RC, Solomon S, Fong CT, Behara LD, Venigandla R, Velagapudi K, Lang JD, Nair BG. Improving Operating Room Efficiency: Machine Learning Approach to Predict Case-Time Duration. *Journal of the American College of Surgeons* **229**(4), 346-354. <https://doi.org/10.1016/j.jamcollsurg.2019.05.029> (2019).
8. Stepaniak PS, Heij C, Mannaerts GH, de Quelerij M, de Vries G. Modeling Procedure and Surgical Times for Current Procedural Terminology-Anesthesia-Surgeon Combinations and Evaluation in Terms of Case-Duration Prediction and Operating Room Efficiency: A Multicenter Study. *Anesthesia and Analgesia* **109**(4), 1232-45. <https://doi.org/10.1213/ANE.0b013e3181b5de07> (2009).
9. Nurok M, Gewertz B. Relative Value Units and the Measurement of Physician Performance. *Journal of the American Medical Association* **322**(12), 1139–1140. <https://doi.org/10.1001/jama.2019.11163> (2019).
10. Coberly, S. (Ed.). (2015, January 12). The Basics: Relative Value Units (RVUs). Retrieved December 09, 2020, from https://www.nhpf.org/library/the-basics/Basics_RVUs_01-12-15.pdf
11. Parr RG, v. Szentpály L, Liu S. Electrophilicity Index. *Journal of the American Chemical Society* **121**(9), 1922-1924. <https://doi.org/10.1021/ja983494x> (1999).
12. Glass RI, Mulvihill MN, Smith Jr. H, Peto R, Bucheister D, Stoll BJ. The 4 Score: An Index for Predicting a Patient's Non-Medical Hospital Days. *American Journal of Public Health* **67**, 751–755. <https://doi.org/10.2105/AJPH.67.8.751> (1977).
13. RVU20A Physician Fee Schedule January 2020 Release. (2020, January 31). Retrieved March, 2020, from <https://www.cms.gov/medicare/medicare-fee-service-payment/physicianfeeschedpfs-relative-value-files/2020>
14. Chen, T., & Guestrin, C. (2016). XGBoost: A Scalable Tree Boosting System. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining* (pp. 785–

Figures

Figure 1

Overview of schedulers performance. A) Distribution of the actual and the scheduler-predicted case time in minutes, B) percentage of cases predicted under, over, and within 20% of the actual case time. Scheduler-predicted case time within 20%, and >20% under or over the actual case time are depicted in black, red, and blue, respectively.

Figure 2

Overview of the models and the scheduler performance. A) Distribution of the actual and the scheduler-predicted case time in minutes, B) distribution of the actual and the RVU-model-predicted case time in minutes, C) distribution of the actual and the CPT-model-predicted case time in minutes, D) percentage of cases predicted under, over, and on-time. Predicted case time within 20%, and >20% under or over the actual case time are depicted in black, red, and blue, respectively.

Figure 3

Features importance comparison. The average number of times each feature was utilized to split the data across all the trees in the model with A) RVU-based, B) CPT-based, and C) RVU/CPT combined.