Research on nonlinear vibration control of laminated cylindrical shells with discontinuous piezoelectric layer

Chaofeng Li (✉ chfli@mail.neu.edu.cn)

Northeastern University <https://orcid.org/0000-0001-6335-5608>

Peiyong Li

Northeastern University

Xueyang Miao

Northeastern University

Original Research

Keywords: Geometrically nonlinear, piezoelectric, vibration control, elastic boundary condition

Posted Date: February 8th, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-192617/v1>

License: This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Research on nonlinear vibration control of laminated cylindrical shells with discontinuous piezoelectric layer

Chaofeng Li^{a,b,*}, Peiyong Li^a, Xueyang Miao^a

a. School of Mechanical Engineering and Automation, Northeastern University, 110819, Shenyang, China

b. Key Laboratory of Vibration and Control of Aero-Propulsion Systems Ministry of Education of China, Northeastern University, Shenyang, Liaoning, China, 110819

Abstract In this paper, the nonlinear vibration control of the piezoelectric laminated cylindrical shell with point supported elastic boundary condition is analyzed, in which the geometric nonlinearity is considered by the first-order shear nonlinear shell theory. In the model, different boundary conditions are simulated by introducing a series of artificial springs. The elastic-electrically coupled differential equations of piezoelectric laminated cylindrical shells are obtained based on the Chebyshev polynomials and Lagrange equation, and decoupled by using the negative velocity feedback adjustment. Later, the Incremental Harmonic Balance Method (IHBM) is deduced, and the frequency-amplitude response of the piezoelectric laminated cylindrical shell is obtained by IHBM. Finally, the influence of the constant gain, size and position of the piezoelectric layer on frequency-amplitude response are investigated. The results show that the position, size and constant gain of the piezoelectric layer have a significant influence on its nonlinear vibration control.

Keyword: Geometrically nonlinear, piezoelectric, vibration control, elastic boundary condition

1. Introduction

In recent years, with the development of piezoelectric materials, the piezoelectric films (PVDF) have been widely used in the fields of machinery, environmental testing, and medicine because of their functions of vibration detection, vibration control, and energy collection. The thin-walled cylindrical shell structure is an essential structure in aerospace and other fields. Because the environment of the cylindrical shell is mostly complicated, the vibration control problem has always

* Corresponding author. Tel.: +86 13514215459

E-mail address: chfli@mail.neu.edu.cn (C. Li).

1 been the focus and hotspot of scholars.

2 Since the advent of piezoelectric intelligent mechanisms, the study of the vibration characteristics
3 of piezoelectric laminated cylindrical shells has continued to attract scholar's attention [1, 2]. The
4 modeling of piezoelectric laminated shells mainly focuses on the Finite Element Method and
5 Hamilton's principle. Kerur et al. [3] presented a finite element model using a composite material
6 (AFC) as the piezoelectric actuator and a piezoelectric film (PVDF) as the piezoelectric sensor, and
7 used the negative velocity feedback control algorithm to control the dynamic response of the
8 laminated composite plate. Parashar and Kumar [4] used the Rayleigh-Ritz method to study the
9 vibration behavior of the piezoelectric shells, and the results showed that the Rayleigh-Ritz method
10 had a very high convergence rate and can be calculated with relatively less efforts. Sheng and Wang[5]
11 analyzed the dynamics characteristic of functionally graded material(FGM) cylindrical shells with a
12 surface-bonded PZT piezoelectric layer by using the first-order shear deformation theory (FSDT) and
13 Hamilton's principle, in which the thermal and moving loads are considered in the model. Qin et al.
14 [6] used Sanders shell theory combined with the artificial spring technique to study the free vibration
15 of cylindrical shells under arbitrary boundary conditions, and compared the accuracy, convergence
16 rate and computational efficiency of three different admissible displacement functions, namely the
17 modified Fourier series, the Orthogonal polynomials, and the Chebyshev polynomials, and the results
18 showed that Chebyshev polynomials obtained higher computational efficiency. Further, using
19 Chebyshev polynomials as admissible displacement functions and FSDT, Qin et al.[7] proposed a
20 general method to study the free vibration of rotating functionally graded carbon nanotube reinforced
21 composite (FG-CNTRC) cylindrical shells with arbitrary boundary conditions. The Lagrange
22 equation is simple to use and has a small dimension, which can well handle the dynamic modeling of
23 piezoelectric laminated cylindrical shells. Li et al. [8]presented a model of discontinuous piezoelectric

1 laminated shell with point supported elastic boundary conditions based on the first-order shear shell
2 theory, the Chebyshev polynomials and the Lagrange equation. Then, the location of piezoelectric
3 layer was optimized by using the Multi-Objective Particle Swarm Optimization algorithm. In
4 practical applications, the thin-walled cylindrical shell structures, such as the aero-engine casing, are
5 subjected to complex loads in a relatively complex environment. In this case, the geometric
6 nonlinearity of cylindrical shell structures is inevitable. Therefore, it is of great significance to study
7 the nonlinear amplitude-frequency response of cylindrical shells. With the deepening of the research
8 on piezoelectric laminated cylindrical shells, Many researchers have applied piezoelectric materials
9 to the vibration control of thin-walled cylindrical shell structures. Amabili [9] considered the axial
10 symmetry of laminated cylindrical shells and calculated the nonlinear forced vibration response for
11 the first time, and compared the classical Novozhilov theory, the usual version of higher-order shear
12 deformation theory, and the higher-order shear deformation theory recently developed by Amabili
13 and Reddy. The results show that the Amabili–Reddy and Novozhilov theories have good results for
14 laminated thin shells. For thick shells, the Amabili–Reddy theory should be used in order to have
15 accurate results. Jansen[10] studied the effects of static loads and imperfections on the nonlinear
16 vibration characteristics of cylindrical shells based on the Donnell-type governing equations. Przekop
17 et al. [11] used structural degrees of freedom as a framework, and established a coupled structural-
18 electrical nonlinear modal FE model for laminated composite shallow shells with embedded
19 piezoelectric sensors and actuators, aiming to suppress the large amplitude undamped free vibration.
20 According to Donnell’s shell theory, Galerkin method and Volmir assumption, Rafiee et al. [12, 13]
21 analyzed the nonlinear vibration of the FGM cylindrical shell with a piezoelectric layer subject to
22 electro-thermal-pneumatic-mechanical coupling load. Then, the effects of piezoelectric layer
23 thickness, geometric parameters, temperature, voltage and aerodynamic load on its dynamic

1 characteristics were analyzed. Sheng and Wang[14] proposed a new simplifying model of smart FG
2 laminated cylindrical shells with thin piezoelectric layers in which the inner layer is a sensing layer,
3 the functionally graded layer, and the outer layer is the active layer, and uses the Von Kármán
4 nonlinear theory, the Hamilton's principle, the FSDT and the multiterm Galerkin method to analyze
5 the active vibration control of smart FG laminated cylindrical shells. Shen and Yang [15] used the
6 higher order shear deformation shell theory with a von Kármán-type of kinematic nonlinearity to
7 study the small and large amplitude flexural vibrations of anisotropic shear deformable laminated
8 cylindrical shells with piezoelectric fiber reinforced composite (PFRC) actuators in thermal
9 environments. Zhang[16] used various geometrically nonlinear shell theories based on the FSDT,
10 including refined von Kármán nonlinear shell theory(RVK5), moderate rotation shell theory(MRT5),
11 fully geometrically nonlinear shell theory with moderate rotations(LRT5) and fully geometrically
12 nonlinear shell theory with large rotations(LRT56), the results showed that the LRT56 can get more
13 accurate results when structures undergo large rotations, and by adopting appropriate feedback
14 actuation voltages, shape and vibration control can be accomplished pretty well in the structures
15 undergoing large deformations and large rotations. Yue et al. [17] established an experimental
16 platform for adaptive modal control of precision paraboloidal shell, conducted an experimental study
17 on the active modal vibration control of a flexible paraboloidal shell with free boundary conditions,
18 and used the positive position feedback algorithm to control the first order mode as well as the first
19 and second order coupled mode of the paraboloidal shell. Ninh et al.[18] established the model of
20 functionally graded carbon nanotube reinforced composite(FG-CNTRC) cylindrical shells with the
21 piezoelectric actuators surrounded by an elastic medium and used the classical shell theory with
22 geometrical nonlinearity to investigate its electro-thermo-mechanical vibration.

23 In recent years, many scholars have proposed discontinuous elastic boundaries and nonlinear

1 flexible boundaries to replace traditional classical boundaries. Chen et al. [21] extended the improved
2 Fourier series method to the free vibration analysis of cylindrical shells, and studied the free vibration
3 of cylindrical shells with arbitrary and non-uniformly restrained boundary conditions. Xie et al. [22]
4 used the wave propagation method to study the free vibration and forced vibration of a non-uniform
5 constrained cylindrical shell. Li et al. [19, 20] studied the geometrically nonlinear vibration of non-
6 continuous elastic-supported laminated composite cylindrical thin shells by extending a new arcs-
7 supported and points-supported shell model. Tang et al. [23, 24] considered the three contact states
8 of bolted connection, including stick, slip and separation, and established a piecewise linear boundary
9 analytical model of bolted cylindrical shells, and studied its dynamic characteristics. Li et al.[25]
10 presented a model of laminated composited cylindrical shells with arc supported and point supported
11 elastic boundary condition based on Donnell's shell theory, the Chebyshev polynomials and the
12 Lagrange equation.

13 According to the above literature research, the research on the dynamic characteristic of laminated
14 shells with piezoelectric materials has attracted much attention. In addition, the vibration control of
15 cylindrical shells by piezoelectric materials has been confirmed in some researches, but the influence
16 of piezoelectric materials on the nonlinear vibration of cylindrical shell remains to be studied. Due to
17 the fabrication process and cost of the piezoelectric material, it is very difficult to completely cover
18 the piezoelectric layer on the surface of the cylindrical shell. Therefore, we innovatively proposed the
19 nonlinear dynamic model of laminated cylindrical shells with discontinuous piezoelectric layers to
20 study the influence of piezoelectric layers of different sizes and positions on the frequency-amplitude
21 response. The Chebyshev polynomial, Lagrange equation, first-order shear nonlinear shell theory and
22 Negative speed feedback strategy are used to obtain the differential equation of decoupled motion.
23 Afterward, the IHBm is used to solve the differential equation of motion, and the effects of constant

- 1 gain, piezoelectric layer size and piezoelectric layer position on the nonlinear frequency-amplitude
- 2 response of the piezoelectric laminated cylindrical shell are analyzed.

Nomenclature	
$\mathbf{A}$	Stretching stiffness matrix
$\mathbf{C}_R, \mathbf{C}_A$	Damping matrix
$\mathbf{D}$	Bending stiffness matrix
$\mathbf{D}_a, \mathbf{D}_s$	Electric displacements
E_b, E_a, E_s	Yong's modulus of the based layer, actuator layer and sensor layer
$\mathbf{E}$	Electric fields
$\mathbf{F}$	Point excitation
G_F	Constant gain
$\mathbf{K}_{qq}, \mathbf{K}_{spr}, \mathbf{K}_{q\psi}, \mathbf{K}_{\psi\psi}$	Generalized stiffness matrix, spring stiffness matrix, electrical mechanical coupled stiffness, electrical stiffness matrix
L	Length of the shell
$\mathbf{M}_{qq}$	Generalized mass matrix
$\mathbf{M}_x, \mathbf{M}_\theta, \mathbf{M}_{x\theta}$	Moments of the in-plane stresses
N	Number of terms for circumferential wave
$N_x, N_\theta, N_{x\theta}$	Force of the in-plane stresses
NA	Number of supported point
NT	Number of terms for Chevyshev polynomials
$\mathbf{P}$	Applied electrical charge for piezoelectric layers
$\mathbf{Q}^a, \mathbf{Q}^s, \mathbf{Q}^b$	Plane stresses-strain matrix
Q_θ, Q_x	Transverse shear force
$\mathbf{Q}_N$	Nonlinear item
R	Radius of the shell
T	Kinetic energy
$T_m^*(\xi)$	Admissible displacement functions
U_ε, U_{spr}	Strain energy, potential energy
$\bar{\mathbf{U}}, \bar{\mathbf{V}}, \bar{\mathbf{W}}, \bar{\boldsymbol{\Phi}}_x, \bar{\boldsymbol{\Phi}}_\theta$	Mode vector satisfying the boundary condition
$a_{mn}, b_{mn}, c_{mn}, d_{mn}, e_{mn}, f_{mn}, g_{mn}$	Unknown corresponding coefficients
$\mathbf{e}$	Piezoelectric constants
f	Amplitude of excitation
h, h_a, h_s	Thickness of the shell of the based layer, actuator layer and sensor layer
$k_u, k_v, k_w, k_x, k_\theta$	Stiffness of axial, circumferential, radial, torsional spring
k_c	Shear correction factor
n	Circumferential wave number
$u, v, w, \phi_x, \phi_\theta$	Displacement in the x, θ, z directions and rotations of the transverse normal respect to the x and θ axes
$\bar{\Psi}_a, \bar{\Psi}_s$	Distribution of electric potential along thickness coordinate
$\boldsymbol{\Phi}$	Mass normalized mode shape matrix
$\varepsilon_x, \varepsilon_\theta, \gamma_{x\theta}, \gamma_{\theta z}, \gamma_{xz}$	Strains of the shell
ζ	Dielectric constants
$\kappa_x, \kappa_\theta, \kappa_{x\theta}$	Curvature of the shell
μ_b	Poisson's ratios of based layer
ψ	Values of electric potential of actuator and sensor layer
ξ	Non-dimensional axial coordinate
$(\xi_s, \theta_s), (\xi'_s, \theta'_s)$	Starting and ending coordinates of the sth piezoelectric layer

ρ_b, ρ_a, ρ_s	Mass density of the based layer, actuator layer and sensor layer
$\sigma_x, \sigma_\theta, \tau_{xy}, \tau_{\theta y}, \tau_{xz}$	Stresses of the shell
ω	Natural frequency of the shell
ω_{EX}	Excitation frequency

2. Theoretical formulations

2.1. Description of laminated cylindrical shells mode

In Fig. 1, the schematic diagram of laminated cylindrical shells with discontinuous piezoelectric layer is presented, in which radius, length, thickness of the base layer, thickness of the piezoelectric sensor and actuator layers are defined as R , L , h , h_s and h_a , respectively. Along the axial, circumferential and radial directions of the shell, an orthogonal coordinate system (x, θ, z) is established. In the x, θ, z directions, the displacements of a point on the middle surface are denoted as u, v and w , in the rotations direction with respect to the x and θ axes, the transverse normal are denoted as ϕ_x and ϕ_θ . The number of piezoelectric layers is defined as NP . The starting and ending coordinates of the s th piezoelectric layer are (ξ_s, θ_s) and (ξ'_s, θ'_s) , respectively. NA is the number of restrained points. The arbitrary boundary conditions are represented by using artificial spring technique. $k_{u,\alpha}^0, k_{v,\alpha}^0, k_{w,\alpha}^0, k_{x,\alpha}^0$, and $k_{\theta,\alpha}^0$ are the stiffness of five groups of boundary springs at the α th point at $x=0$. Similarly, $k_{u,\alpha}^1, k_{v,\alpha}^1, k_{w,\alpha}^1, k_{x,\alpha}^1$ and $k_{\theta,\alpha}^1$ denote the stiffness of corresponding boundary springs.

Fig. 1 Schematic diagram of a piezoelectric laminated composite cylindrical shell with elastic boundary conditions: (a) coordinate system and geometry of the shell; (b) partial cross-sectional view of the shell with elastic boundary condition

2.2. Expressions of laminated cylindrical shell's energy

For the piezoelectric laminated cylindrical shells, the kinetic energy T and the strain energy U_ε are written as[8]

$$T = \frac{LR}{2} \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left[(u_{\xi}^2 + v_{\xi}^2 + w_{\xi}^2) I_0 + 2(u_{\xi} v_{\xi} + v_{\xi} w_{\xi}) I_1 + (u_{\xi}^2 + v_{\xi}^2) I_2 \right] d\xi d\theta \\ + \frac{LR}{2} \sum_{r=1}^{NP} \int_{\theta_r}^{\theta'_r} \int_{\xi_r}^{\xi'_r} \left[(u_{\xi}^2 + v_{\xi}^2 + w_{\xi}^2) \mathcal{I}_0 + 2(u_{\xi} v_{\xi} + v_{\xi} w_{\xi}) \mathcal{I}_1 + (u_{\xi}^2 + v_{\xi}^2) \mathcal{I}_2 \right] d\xi d\theta \quad (1)$$

where,

$$[I_0, I_1, I_2] = \int_{h/2}^{h/2+h_a} \rho_a [1, z, z^2] dz + \int_{-h/2}^{h/2} \rho_b [1, z, z^2] dz + \int_{-h/2-h_b}^{-h/2} \rho_s [1, z, z^2] dz \\ [\mathcal{I}_0, \mathcal{I}_1, \mathcal{I}_2] = \int_{-h/2}^{h/2} \rho_b [1, z, z^2] dz \quad (2)$$

where ρ_i is the density of each layer of the shell. The subscript (i) is used to represent the sensor layer ($i=s$), actuator layer ($i=a$), and base layer ($i=b$).

$$U = \frac{LR}{2} \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} (N_x^T \varepsilon_x + N_{\theta}^T \varepsilon_{\theta} + N_{x\theta}^T \gamma_{x\theta} + M_x^T \kappa_x + M_{\theta}^T \kappa_{\theta} + M_{x\theta}^T \kappa_{x\theta} + Q_{\theta z}^T \gamma_{\theta z} + Q_{xz}^T \gamma_{xz} \\ - \int_{h/2}^{h/2+h_a} D_a^T E_a dz - \int_{-h/2}^{-h/2-h_b} D_s^T E_s dz) d\xi d\theta + \frac{LR}{2} \sum_{r=1}^{NP} \int_{\theta_r}^{\theta'_r} \int_{\xi_r}^{\xi'_r} (N_x^T \varepsilon_x + N_{\theta}^T \varepsilon_{\theta} + N_{x\theta}^T \gamma_{x\theta} + M_x^T \kappa_x \\ + M_{\theta}^T \kappa_{\theta} + M_{x\theta}^T \kappa_{x\theta} + Q_{\theta z}^T \gamma_{\theta z} + Q_{xz}^T \gamma_{xz}) d\xi d\theta \quad (3)$$

where D_i and E_i are the electric displacements and electric fields of the piezoelectric layer[5], respectively.

$$\begin{Bmatrix} D_x^i \\ D_{\theta}^i \\ D_z^i \end{Bmatrix} = \begin{bmatrix} 0 & 0 & 0 & 0 & e_{15e}^i \\ 0 & 0 & 0 & e_{24e}^i & 0 \\ e_{31e}^i & e_{32e}^i & 0 & 0 & 0 \end{bmatrix} \begin{Bmatrix} \varepsilon_x^i \\ \varepsilon_{\theta}^i \\ \gamma_{x\theta}^i \\ \gamma_{\theta z}^i \\ \gamma_{xz}^i \end{Bmatrix} + \begin{bmatrix} \zeta_{11e}^i & 0 & 0 \\ 0 & \zeta_{22e}^i & 0 \\ 0 & 0 & \zeta_{33e}^i \end{bmatrix} \begin{Bmatrix} E_x^i \\ E_{\theta}^i \\ E_z^i \end{Bmatrix} \quad (4)$$

where e_i and ζ_i are the piezoelectric constants and dielectric constants, respectively.

Considering the poling direction of the piezoelectric layer is coincident with the thickness direction, the electric fields can be written as[5]

$$E_x^i = -\frac{\partial \varphi^i(x, \theta, z, t)}{L \partial \xi}, E_\theta^i = -\frac{\partial \varphi^i(x, \theta, z, t)}{R \partial \theta}, E_z^i = -\frac{\partial \varphi^i(x, \theta, z, t)}{\partial z} \quad (5)$$

where the piezoelectric layer potential due to elastic deformation is given as

$$\begin{aligned} \varphi^a(x, \theta, z, t) &= \left[z_a^2 - \left(\frac{h_a}{2} \right)^2 \right] \psi_a(x, \theta, t) \\ \varphi^s(x, \theta, z, t) &= \left[z_s^2 - \left(\frac{h_s}{2} \right)^2 \right] \psi_s(x, \theta, t) \end{aligned} \quad (6)$$

where $\psi_a(x, \theta, t)$ and $\psi_s(x, \theta, t)$ are the distribution of the electric potential of the actuator layer along the thickness coordinate, z_a is the coordinate relative to the middle surface of the actuator layer, $z_a = z - (h + h_a)/2$; $\psi_s(x, \theta, t)$ is the distribution of the sensor layer, z_s is the coordinate of the sensor layer, $z_s = z + (h + h_s)/2$.

In Eq.(3), the strain vector ε^T is given by[7]

$$\varepsilon^T = \left\{ \varepsilon_x \quad \varepsilon_\theta \quad \gamma_{x\theta} \quad \gamma_{\theta z} \quad \gamma_{xz} \quad \kappa_x \quad \kappa_\theta \quad \kappa_{x\theta} \quad \kappa_{xz} \quad \kappa_{\theta z} \right\} \quad (7)$$

The strains of a point of the shell are defined as[7]

$$\begin{pmatrix} \varepsilon_x \\ \varepsilon_\theta \\ \gamma_{x\theta} \\ \gamma_{\theta z} \\ \gamma_{xz} \end{pmatrix} = \begin{pmatrix} \varepsilon_x \\ \varepsilon_\theta \\ \gamma_{x\theta} \\ \gamma_{\theta z} \\ \gamma_{xz} \end{pmatrix}_{(0)} + z \begin{pmatrix} \kappa_x \\ \kappa_\theta \\ \kappa_{x\theta} \\ \kappa_{xz} \\ \kappa_{\theta z} \end{pmatrix} \quad (8)$$

where the subscript (0) is the middle surface. The strain and the curvature can be given as[7]

$$\begin{aligned} \varepsilon_{x(0)} &= \frac{\partial u_0}{L \partial \xi} + \frac{1}{2L^2} \left(\frac{\partial w_0}{\partial \xi} \right)^2, \quad \varepsilon_{\theta(0)} = \frac{1}{R} \frac{\partial v_0}{\partial \theta} + \frac{w_0}{R} + \frac{1}{2R^2} \left(\frac{\partial w_0}{\partial \theta} \right)^2, \\ \gamma_{x\theta(0)} &= \frac{1}{R} \frac{\partial u_0}{\partial \theta} + \frac{\partial v_0}{L \partial \xi} + \frac{1}{LR} \left(\frac{\partial w_0}{\partial \xi} \frac{\partial w_0}{\partial \theta} \right), \quad \gamma_{\theta z(0)} = \phi_\theta + \frac{1}{R} \frac{\partial w_0}{\partial \theta} - \frac{v_0}{R}, \quad \gamma_{xz(0)} = \phi_x + \frac{1}{L} \frac{\partial w_0}{\partial \xi} \\ \kappa_x &= \frac{\partial \phi_x}{L \partial \xi}, \quad \kappa_\theta = \frac{1}{R} \frac{\partial \phi_\theta}{\partial \theta}, \quad \kappa_{x\theta} = \frac{1}{L} \frac{\partial \phi_\theta}{\partial \xi} + \frac{1}{R} \frac{\partial \phi_x}{\partial \theta}, \quad \kappa_{xz} = 0, \quad \kappa_{\theta z} = 0 \end{aligned} \quad (9)$$

In the model, the position at which the piezoelectric layer is considered as a laminated shell, and the position at which the piezoelectric layer is not disposed is regarded as a single thin-wall cylindrical

1 shell. In the location of the base layer, the matrix form of the force and moment resultant relations to
2 the strains in the middle surface and curvature changes are defined as[8]

$$\begin{aligned}
 & \begin{Bmatrix} \bar{N}_x^o \\ \bar{N}_\theta^o \\ \bar{N}_{x\theta}^o \\ \bar{M}_x^o \\ \bar{M}_\theta^o \\ \bar{M}_{x\theta}^o \end{Bmatrix} = \begin{bmatrix} \bar{A}_{11}^o & \bar{A}_{12}^o & 0 & \bar{B}_{11}^o & \bar{B}_{12}^o & 0 \\ \bar{A}_{12}^o & \bar{A}_{22}^o & 0 & \bar{B}_{12}^o & \bar{B}_{22}^o & 0 \\ 0 & 0 & \bar{A}_{66}^o & 0 & 0 & \bar{B}_{66}^o \\ \bar{B}_{11}^o & \bar{B}_{12}^o & 0 & \bar{D}_{11}^o & \bar{D}_{12}^o & 0 \\ \bar{B}_{12}^o & \bar{B}_{22}^o & 0 & \bar{D}_{12}^o & \bar{D}_{22}^o & 0 \\ 0 & 0 & \bar{B}_{66}^o & 0 & 0 & \bar{D}_{66}^o \end{bmatrix} \begin{Bmatrix} \varepsilon_{x(0)} \\ \varepsilon_{\theta(0)} \\ \gamma_{x\theta(0)} \\ \kappa_x \\ \kappa_\theta \\ \kappa_{x\theta} \end{Bmatrix} \\
 & \begin{Bmatrix} \bar{Q}_\theta^o \\ \bar{Q}_x^o \end{Bmatrix} = k_c \begin{bmatrix} \bar{A}_{44}^o & 0 \\ 0 & \bar{A}_{55}^o \end{bmatrix} \begin{Bmatrix} \gamma_{\theta z(0)} \\ \gamma_{xz(0)} \end{Bmatrix}
 \end{aligned} \tag{10}$$

4 where, $\bar{A}_{ij}^o$, $\bar{B}_{ij}^o$ and $\bar{D}_{ij}^o$ are the stretching, coupling and bending stiffness matrixes, respectively. k_c is
5 shear correction factor, generally taken as 5/6.

$$\begin{aligned}
 & \bar{A}_{ij}^o = \int_{-h/2}^{h/2} Q_{ij}^b dz \\
 & \bar{B}_{ij}^o = \int_{-h/2}^{h/2} Q_{ij}^b z dz \\
 & \bar{D}_{ij}^o = \int_{-h/2}^{h/2} Q_{ij}^b z^2 dz
 \end{aligned} \tag{11}$$

7 where the plane stresses-strain matrix $\mathbf{Q}_b$ is as[7]

$$\mathbf{Q}_b = \begin{bmatrix} Q_{11}^b & Q_{12}^b & 0 & 0 & 0 \\ Q_{12}^b & Q_{22}^b & 0 & 0 & 0 \\ 0 & 0 & Q_{66}^b & 0 & 0 \\ 0 & 0 & 0 & Q_{44}^b & 0 \\ 0 & 0 & 0 & 0 & Q_{55}^b \end{bmatrix} \tag{12}$$

9 where the elements of Q_{ij}^b are given as

$$Q_{11}^b = Q_{22}^b = \frac{E_b}{1 - \mu_b^2}, \quad Q_{12}^b = Q_{21}^b = \frac{\mu_b E_b}{1 - \mu_b^2}, \quad Q_{66}^b = \frac{E_b}{2(1 + \mu_b)}, \quad Q_{44}^b = Q_{66}^b, \quad Q_{55}^b = Q_{66}^b \tag{13}$$

11 where E_b is Yong's moduli of the base layer. μ_b is the Poisson's ratios.

12 In the location of base-piezoelectric layers, the matrix form of the force and moment resultant
13 relations to the strains in the middle surface and curvature changes are defined as[8]

$$\begin{aligned}
1 \quad & \begin{Bmatrix} N_x \\ N_\theta \\ N_{x\theta} \\ M_x \\ M_\theta \\ M_{x\theta} \end{Bmatrix} = \begin{bmatrix} A_{11} & A_{12} & 0 & B_{11} & B_{12} & 0 \\ A_{12} & A_{22} & 0 & B_{12} & B_{22} & 0 \\ 0 & 0 & A_{66} & 0 & 0 & B_{66} \\ B_{11} & B_{12} & 0 & D_{11} & D_{12} & 0 \\ B_{12} & B_{22} & 0 & D_{12} & D_{22} & 0 \\ 0 & 0 & B_{66} & 0 & 0 & D_{66} \end{bmatrix} \begin{Bmatrix} \varepsilon_{x(0)} \\ \varepsilon_{\theta(0)} \\ \gamma_{x\theta(0)} \\ \kappa_x \\ \kappa_\theta \\ \kappa_{x\theta} \end{Bmatrix} + \begin{Bmatrix} N_x^E \\ N_\theta^E \\ N_{x\theta}^E \\ M_x^E \\ M_\theta^E \\ M_{x\theta}^E \end{Bmatrix} \\
& \begin{Bmatrix} Q_\theta \\ Q_x \end{Bmatrix} = k_c \begin{bmatrix} A_{44} & 0 \\ 0 & A_{55} \end{bmatrix} \begin{Bmatrix} \gamma_{\theta z(0)} \\ \gamma_{xz(0)} \end{Bmatrix} + \begin{Bmatrix} Q_\theta^E \\ Q_x^E \end{Bmatrix}
\end{aligned} \tag{14}$$

2 where $N_x^E, N_\theta^E, N_{x\theta}^E, M_x^E, M_\theta^E, M_{x\theta}^E, Q_\theta^E, Q_x^E$ are the piezoelectric resultants of the piezoelectric layer.

$$\begin{aligned}
& A_{ij} = \int_{h/2}^{h/2+h_a} Q_{ij}^a dz + \int_{-h/2}^{h/2} Q_{ij}^b dz + \int_{-h/2-h_s}^{-h/2} Q_{ij}^s dz \\
3 \quad & B_{ij} = \int_{h/2}^{h/2+h_a} Q_{ij}^a z dz + \int_{-h/2}^{h/2} Q_{ij}^b z dz + \int_{-h/2-h_s}^{-h/2} Q_{ij}^s z dz \\
& D_{ij} = \int_{h/2}^{h/2+h_a} Q_{ij}^a z^2 dz + \int_{-h/2}^{h/2} Q_{ij}^b z^2 dz + \int_{-h/2-h_s}^{-h/2} Q_{ij}^s z^2 dz
\end{aligned} \tag{15}$$

4 where Q_i are the elastic constants.

5 The force and moment resultant of the piezoelectric layer are given as[5]

$$\begin{aligned}
6 \quad & \begin{Bmatrix} N_x^E \\ N_\theta^E \\ N_{x\theta}^E \\ M_x^E \\ M_\theta^E \\ M_{x\theta}^E \end{Bmatrix} = \begin{Bmatrix} 2e_{31e}^a \int_{h/2}^{h/2+h_a} z_a \psi_a dz + 2e_{31e}^s \int_{-h/2-h_s}^{-h/2} z_s \psi_s dz \\ 2e_{32e}^a \int_{h/2}^{h/2+h_a} z_a \psi_a dz + 2e_{32e}^s \int_{-h/2-h_s}^{-h/2} z_s \psi_s dz \\ 0 \\ 2e_{31e}^a \int_{h/2}^{h/2+h_a} z z_a \psi_a dz + 2e_{31e}^s \int_{-h/2-h_s}^{-h/2} z z_s \psi_s dz \\ 2e_{32e}^a \int_{h/2}^{h/2+h_a} z z_a \psi_a dz + 2e_{32e}^s \int_{-h/2-h_s}^{-h/2} z z_s \psi_s dz \\ 0 \end{Bmatrix} \\
& \begin{Bmatrix} Q_\theta^E \\ Q_x^E \end{Bmatrix} = \begin{Bmatrix} e_{24e}^a \int_{h/2}^{h/2+h_a} \frac{z_a^2 - (h_a/2)^2}{R+z} \frac{\partial \psi_a}{\partial \theta} dz + e_{24e}^s \int_{-h/2-h_s}^{-h/2} \left[\frac{z_s^2 - (h_s/2)^2}{R+z} \right] dz \frac{\partial \psi_s}{\partial \theta} \\ e_{15e}^a \int_{h/2}^{h/2+h_a} \left[z_a^2 - (h_a/2)^2 \right] \frac{\partial \psi_a}{\partial x} dz + e_{15e}^s \int_{-h/2-h_s}^{-h/2} \left[z_s^2 - (h_s/2)^2 \right] dz \frac{\partial \psi_s}{\partial x} \end{Bmatrix}
\end{aligned} \tag{16}$$

7 2.3. The potential energy of the boundary springs

8 To simulate arbitrary boundary conditions, we use a series of artificial spring in five directions.

9 The potential energy U_{spr} introduced by the elastic boundary springs can be calculated as follows[25]

$$\begin{aligned}
U_{\text{spr}} = & \frac{1}{2} \sum_{\alpha=1}^{NA} \left\{ k_{u,\alpha}^0 [u(0, \theta_\alpha(t), t)]^2 + k_{v,\alpha}^0 [v(0, \theta_\alpha(t), t)]^2 + k_{w,\alpha}^0 [w(0, \theta_\alpha(t), t)]^2 \right. \\
& + k_{x,\alpha}^0 [\phi_x(0, \theta_\alpha(t), t)]^2 + k_{\theta,\alpha}^0 [\phi_\theta(0, \theta_\alpha(t), t)]^2 \Big\} \\
& + \frac{1}{2} \sum_{\alpha=1}^{NA} \left\{ k_{u,\alpha}^1 [u(1, \theta_\alpha(t), t)]^2 + k_{v,\alpha}^1 [v(1, \theta_\alpha(t), t)]^2 + k_{w,\alpha}^1 [w(1, \theta_\alpha(t), t)]^2 \right. \\
& + k_{x,\alpha}^1 [\phi_x(1, \theta_\alpha(t), t)]^2 + k_{\theta,\alpha}^1 [\phi_\theta(1, \theta_\alpha(t), t)]^2 \Big\}
\end{aligned} \tag{17}$$

where $(x_\alpha, \theta_\alpha)$ is used to represent the coordinates of the s th point.

2.4. Admissible displacement functions

In Qin's study[6], the Chebyshev polynomials show the highest computational efficiency, the higher convergence rate and the higher computational efficiency, compared with the Orthogonal polynomials and the modified Fourier series. Therefore, the admissible displacement functions in this paper use the Chebyshev polynomials. Then, the admissible displacement function is given by

$$\begin{cases}
u(\xi, \theta, t) = \sum_{m=0}^{NT} \sum_{n=1}^N a_{mn} T_m^*(\xi) \cos n\theta e^{-j\omega t} = \bar{U}^T \mathbf{q}_u \\
v(\xi, \theta, t) = \sum_{m=0}^{NT} \sum_{n=1}^N b_{mn} T_m^*(\xi) \sin n\theta e^{-j\omega t} = \bar{V}^T \mathbf{q}_v \\
w(\xi, \theta, t) = \sum_{m=0}^{NT} \sum_{n=1}^N c_{mn} T_m^*(\xi) \cos n\theta e^{-j\omega t} + \sum_{m=0}^{NT} c_m T_m^*(\xi) e^{-j\omega t} = \bar{W}^T \mathbf{q}_w \\
\phi_x(\xi, \theta, t) = \sum_{m=1}^{NT} \sum_{n=1}^N d_{mn} T_m^*(\xi) \cos n\theta e^{-j\omega t} = \bar{\Phi}_x \mathbf{q}_{\phi_x} \\
\phi_\theta(\xi, \theta, t) = \sum_{m=1}^{NT} \sum_{n=1}^N e_{mn} T_m^*(\xi) \sin n\theta e^{-j\omega t} = \bar{\Phi}_\theta \mathbf{q}_{\phi_\theta} \\
\psi_s(\xi, \theta, t) = \sum_{m=1}^{NT} \sum_{n=1}^N f_{mn} T_m^*(\xi) \cos n\theta e^{-j\omega t} = \bar{\Psi}_s \mathbf{q}_{\psi_s} \\
\psi_a(\xi, \theta, t) = \sum_{m=1}^{NT} \sum_{n=1}^N g_{mn} T_m^*(\xi) \cos n\theta e^{-j\omega t} = \bar{\Psi}_a \mathbf{q}_{\psi_a}
\end{cases} \tag{18}$$

where $a_{mn}, b_{mn}, c_{mn}, d_{mn}, e_{mn}, f_{mn}, g_{mn}$ are the unknown corresponding coefficients. $T_m^*(\xi)$ are appropriate admissible displacement functions[19], NT is the number of terms of the admissible displacement functions. ω is the natural frequency. $\mathbf{q}_u, \mathbf{q}_v, \mathbf{q}_w, \mathbf{q}_{\phi_x}, \mathbf{q}_{\phi_\theta}, \mathbf{q}_{\psi_s}, \mathbf{q}_{\psi_a}$ are the generalized coordinates. n is the circumferential wave number. $\bar{U}, \bar{V}, \bar{W}, \bar{\Phi}_x, \bar{\Phi}_\theta, \bar{\Psi}_s, \bar{\Psi}_a$ are mode vector satisfying

1 the boundary condition.

2 2.5. Energy expressions and the solution procedure

3 Substituting Eq. (18) into Eqs. (1), (3) and (17), we obtain the quadratic form of kinetic energy

4 T , the strain energy U_ε and the potential energy U_{spr} as follow

$$5 \quad T = \frac{1}{2} \mathbf{\dot{q}}_u^T \mathbf{M}^{uu} \mathbf{\dot{q}}_u + \frac{1}{2} \mathbf{\dot{q}}_v^T \mathbf{M}^{vv} \mathbf{\dot{q}}_v + \frac{1}{2} \mathbf{\dot{q}}_w^T \mathbf{M}^{ww} \mathbf{\dot{q}}_w + \frac{1}{2} \mathbf{\dot{q}}_{\phi_x}^T \mathbf{M}^{\phi_x \phi_x} \mathbf{\dot{q}}_{\phi_x} + \frac{1}{2} \mathbf{\dot{q}}_{\phi_\theta}^T \mathbf{M}^{\phi_\theta \phi_\theta} \mathbf{\dot{q}}_{\phi_\theta} + \frac{1}{2} \mathbf{\dot{q}}_u^T \mathbf{M}^{u \phi_x} \mathbf{\dot{q}}_{\phi_x} \\ + \frac{1}{2} \mathbf{\dot{q}}_v^T \mathbf{M}^{v \phi_\theta} \mathbf{\dot{q}}_{\phi_\theta} \quad (19)$$

$$6 \quad U_\varepsilon = \frac{1}{2} \mathbf{q}_u^T \mathbf{K}^{uu} \mathbf{q}_u + \frac{1}{2} \mathbf{q}_u^T \mathbf{K}^{uv} \mathbf{q}_v + \frac{1}{2} \mathbf{q}_u^T \mathbf{K}^{uw} \mathbf{q}_w + \frac{1}{2} \mathbf{q}_u^T \mathbf{K}^{u \phi_x} \mathbf{q}_{\phi_x} + \frac{1}{2} \mathbf{q}_u^T \mathbf{K}^{u \phi_\theta} \mathbf{q}_{\phi_\theta} + \frac{1}{2} \mathbf{q}_v^T \mathbf{K}^{vv} \mathbf{q}_v \\ + \frac{1}{2} \mathbf{q}_v^T \mathbf{K}^{vw} \mathbf{q}_w + \frac{1}{2} \mathbf{q}_v^T \mathbf{K}^{v \phi_x} \mathbf{q}_{\phi_x} + \frac{1}{2} \mathbf{q}_v^T \mathbf{K}^{v \phi_\theta} \mathbf{q}_{\phi_\theta} + \frac{1}{2} \mathbf{q}_w^T \mathbf{K}^{ww} \mathbf{q}_w + \frac{1}{2} \mathbf{q}_w^T \mathbf{K}^{w \phi_x} \mathbf{q}_{\phi_x} + \frac{1}{2} \mathbf{q}_w^T \mathbf{K}^{w \phi_\theta} \mathbf{q}_{\phi_\theta} \\ + \frac{1}{2} \mathbf{q}_{\phi_x}^T \mathbf{K}^{\phi_x \phi_x} \mathbf{q}_{\phi_x} + \frac{1}{2} \mathbf{q}_{\phi_x}^T \mathbf{K}^{\phi_x \phi_\theta} \mathbf{q}_{\phi_\theta} + \frac{1}{2} \mathbf{q}_{\phi_\theta}^T \mathbf{K}^{\phi_\theta \phi_x} \mathbf{q}_{\phi_x} + \frac{1}{2} \mathbf{q}_{\phi_\theta}^T \mathbf{K}^{\phi_\theta \phi_\theta} \mathbf{q}_{\phi_\theta} + \frac{1}{2} \mathbf{q}_u^T \mathbf{K}^{u \psi_a} \mathbf{q}_{\psi_a} + \frac{1}{2} \mathbf{q}_u^T \mathbf{K}^{u \psi_s} \mathbf{q}_{\psi_s} + \frac{1}{2} \mathbf{q}_v^T \mathbf{K}^{v \psi_a} \mathbf{q}_{\psi_a} \\ + \frac{1}{2} \mathbf{q}_v^T \mathbf{K}^{v \psi_s} \mathbf{q}_{\psi_s} + \frac{1}{2} \mathbf{q}_w^T \mathbf{K}^{w \psi_a} \mathbf{q}_{\psi_a} + \frac{1}{2} \mathbf{q}_w^T \mathbf{K}^{w \psi_s} \mathbf{q}_{\psi_s} + \frac{1}{2} \mathbf{q}_{\phi_x}^T \mathbf{K}^{\phi_x \psi_a} \mathbf{q}_{\psi_a} + \frac{1}{2} \mathbf{q}_{\phi_x}^T \mathbf{K}^{\phi_x \psi_s} \mathbf{q}_{\psi_s} + \frac{1}{2} \mathbf{q}_{\phi_\theta}^T \mathbf{K}^{\phi_\theta \psi_a} \mathbf{q}_{\psi_a} \\ + \frac{1}{2} \mathbf{q}_{\phi_\theta}^T \mathbf{K}^{\phi_\theta \psi_s} \mathbf{q}_{\psi_s} + \frac{1}{2} \mathbf{q}_{\psi_a}^T \mathbf{K}^{\psi_a \psi_a} \mathbf{q}_{\psi_a} + \frac{1}{2} \mathbf{q}_{\psi_a}^T \mathbf{K}^{\psi_a \psi_s} \mathbf{q}_{\psi_s} + \frac{1}{2} \mathbf{q}_{\psi_s}^T \mathbf{K}^{\psi_s \psi_s} \mathbf{q}_{\psi_s} + U_N \quad (20)$$

$$7 \quad U_{\text{spr}} = \frac{1}{2} \mathbf{q}_u^T \mathbf{K}_{\text{spr}}^{uu} \mathbf{q}_u + \frac{1}{2} \mathbf{q}_v^T \mathbf{K}_{\text{spr}}^{vv} \mathbf{q}_v + \frac{1}{2} \mathbf{q}_w^T \mathbf{K}_{\text{spr}}^{ww} \mathbf{q}_w + \frac{1}{2} \mathbf{q}_{\phi_x}^T \mathbf{K}_{\text{spr}}^{\phi_x \phi_x} \mathbf{q}_{\phi_x} + \frac{1}{2} \mathbf{q}_{\phi_\theta}^T \mathbf{K}_{\text{spr}}^{\phi_\theta \phi_\theta} \mathbf{q}_{\phi_\theta} \quad (21)$$

8 The Lagrange equation is given by

$$9 \quad \left\{ \begin{array}{l} \frac{d}{dt} \left(\frac{\partial T}{\partial \mathbf{\dot{q}}_u} \right) - \frac{\partial T}{\partial \mathbf{q}_u} + \frac{\partial (U_\varepsilon + U_{\text{spr}})}{\partial \mathbf{q}_u} + \frac{\partial D}{\partial \mathbf{\dot{q}}_u} = \mathbf{f}_u \\ \frac{d}{dt} \left(\frac{\partial T}{\partial \mathbf{\dot{q}}_v} \right) - \frac{\partial T}{\partial \mathbf{q}_v} + \frac{\partial (U_\varepsilon + U_{\text{spr}})}{\partial \mathbf{q}_v} + \frac{\partial D}{\partial \mathbf{\dot{q}}_v} = \mathbf{f}_v \\ \frac{d}{dt} \left(\frac{\partial T}{\partial \mathbf{\dot{q}}_w} \right) - \frac{\partial T}{\partial \mathbf{q}_w} + \frac{\partial (U_\varepsilon + U_{\text{spr}})}{\partial \mathbf{q}_w} + \frac{\partial D}{\partial \mathbf{\dot{q}}_w} = \mathbf{f}_w \\ \frac{d}{dt} \left(\frac{\partial T}{\partial \mathbf{\dot{q}}_{\phi_x}} \right) - \frac{\partial T}{\partial \mathbf{q}_{\phi_x}} + \frac{\partial (U_\varepsilon + U_{\text{spr}})}{\partial \mathbf{q}_{\phi_x}} + \frac{\partial D}{\partial \mathbf{\dot{q}}_{\phi_x}} = \mathbf{f}_{\phi_x} \\ \frac{d}{dt} \left(\frac{\partial T}{\partial \mathbf{\dot{q}}_{\phi_\theta}} \right) - \frac{\partial T}{\partial \mathbf{q}_{\phi_\theta}} + \frac{\partial (U_\varepsilon + U_{\text{spr}})}{\partial \mathbf{q}_{\phi_\theta}} + \frac{\partial D}{\partial \mathbf{\dot{q}}_{\phi_\theta}} = \mathbf{f}_{\phi_\theta} \\ \frac{d}{dt} \left(\frac{\partial T}{\partial \mathbf{\dot{\psi}}_a} \right) - \frac{\partial T}{\partial \mathbf{\psi}_a} + \frac{\partial (U_\varepsilon + U_{\text{spr}})}{\partial \mathbf{\psi}_a} + \frac{\partial D}{\partial \mathbf{\dot{\psi}}_a} = \mathbf{p}_a \end{array} \right. \quad (22)$$

$$\left\{ \frac{d}{dt} \left(\frac{\partial T}{\partial \dot{\psi}_s} \right) - \frac{\partial T}{\partial \psi_s} + \frac{\partial (U_\varepsilon + U_{\text{spr}})}{\partial \psi_s} + \frac{\partial D}{\partial \psi_s} \right\} = p_s$$

For the piezoelectric laminated cylindrical shell, the differential equations of electro-elastic coupling motion included the elastic displacements $\mathbf{q}$ and the electric potential vector ψ are given by[26]

$$\begin{aligned} \mathbf{M}_{qq} \ddot{\mathbf{q}} + \mathbf{C}_R \dot{\mathbf{q}} + (\mathbf{K}_{qq} + \mathbf{K}_{\text{spr}}) \mathbf{q} + \mathbf{Q}_N + \mathbf{K}_{q\psi} \psi &= \mathbf{F} \\ \mathbf{K}_{q\psi}^T \mathbf{q} - \mathbf{K}_{\psi\psi} \psi &= \mathbf{P} \end{aligned} \quad (23)$$

where $\mathbf{M}_{qq}$, $\mathbf{K}_{qq}$ and $\mathbf{K}_{\text{spr}}$ are the shell's mass matrix, stiffness matrix and spring stiffness matrix; $\mathbf{K}_{q\psi}$ is the coupled stiffness; $\mathbf{K}_{\psi\psi}$ is the electrical stiffness matrix; $\mathbf{Q}_N$ is the nonlinear item. These matrices are given in Appendix A, B, C, D, respectively. $\mathbf{P}$ is applied electrical charge for the piezoelectric layers, and $\mathbf{F}$ is the radial harmonic excitation on the position (x, θ) , in which $\bar{\mathbf{W}}_0$ is the admissible displacement functions in the shell's radial direction.

$$\begin{aligned} \mathbf{q} &= [\mathbf{q}_u \quad \mathbf{q}_v \quad \mathbf{q}_w \quad \mathbf{q}_{\phi_x} \quad \mathbf{q}_{\phi_\theta}]^T, \quad \psi = [\psi_a \quad \psi_s]^T \\ \mathbf{P} &= [\mathbf{p}_a \quad \mathbf{p}_s], \quad \mathbf{F} = [\mathbf{f}_u \quad \mathbf{f}_v \quad \mathbf{f}_w \quad \mathbf{f}_{\phi_x} \quad \mathbf{f}_{\phi_\theta}]^T \\ \begin{cases} \mathbf{f}_u(x, \theta, t) = \mathbf{O} \\ \mathbf{f}_v(x, \theta, t) = \mathbf{O} \\ \mathbf{f}_w(x, \theta, t) = \bar{\mathbf{W}}_0 f \cos \omega_{\text{EX}} t \\ \mathbf{f}_{\phi_x}(x, \theta, t) = \mathbf{O} \\ \mathbf{f}_{\phi_\theta}(x, \theta, t) = \mathbf{O} \end{cases} \end{aligned} \quad (24)$$

The differential equations of electro-elastic coupling motion can be written as following to facilitate the decoupling of the equation, this as

$$\begin{aligned} \mathbf{M}_{qq} \ddot{\mathbf{q}} + \mathbf{C}_R \dot{\mathbf{q}} + (\mathbf{K}_{qq} + \mathbf{K}_{\text{spr}}) \mathbf{q} + \mathbf{Q} + \mathbf{K}_{q\psi}^S \psi_s + \mathbf{K}_{q\psi}^A \psi_a &= \mathbf{F} \\ \mathbf{K}_{q\psi}^{A^T} \mathbf{q} - \mathbf{K}_{\psi\psi}^A \psi_a &= \mathbf{p}_a \\ \mathbf{K}_{q\psi}^{S^T} \mathbf{q} - \mathbf{K}_{\psi\psi}^S \psi_s &= \mathbf{p}_s \end{aligned} \quad (25)$$

Neglecting the converse piezoelectric effect of the sensor layer, the differential equations of motion

are given as[27]

$$\begin{aligned} M_{qq} \ddot{q} + C_R \dot{q} + (K_{qq} + K_{spr} + K_{q\psi}^S K_{\psi\psi}^{S^{-1}} K_{q\psi}^{S^T}) q + Q_N = F - K_{q\psi}^A \psi_a \\ \psi_s = K_{\psi\psi}^{S^{-1}} K_{q\psi}^{S^T} q \end{aligned} \quad (26)$$

The negative velocity feedback control is used in this study as described in Fig. 2. The input potential of the actuator layer is given as

$$\psi_a = -G_F \dot{\psi}_s = -G_F \dot{\psi}_s = -G_F K_{\psi\psi}^{S^{-1}} K_{q\psi}^{S^T} \dot{q} \quad (27)$$

where G_F is a constant gain. Then, the differential equation of decoupled motion write the next form

$$M_{qq} \ddot{q} + (C_A + C_R) \dot{q} + (K_{qq} + K_{spr} + K_{q\psi}^S K_{\psi\psi}^{S^{-1}} K_{q\psi}^{S^T}) q + Q_N = F \quad (28)$$

where C_R is the Rayleigh damping matrix. C_A is the damping matrix caused by the control potential.

$$C_R = \alpha M_{qq} + \beta (K_{qq} + K_{spr}) \quad (29)$$

$$C_A = -G_F K_{q\psi}^A K_{\psi\psi}^{S^{-1}} K_{q\psi}^{S^T} \quad (30)$$

where α and β are the Rayleigh damping parameters, which can be given as

$$\begin{aligned} \alpha &= 2 \left(\frac{\xi_2}{\omega_2^2} - \frac{\xi_1}{\omega_1^2} \right) / \left(\frac{1}{\omega_2^2} - \frac{1}{\omega_1^2} \right) \\ \beta &= 2 (\xi_2 \omega_2 - \xi_1 \omega_1) / (\omega_2^2 - \omega_1^2) \end{aligned} \quad (31)$$

where ω_1, ω_2 are the first and second order natural frequencies of the laminated cylindrical shells with discontinuous piezoelectric layer, ξ_1 , and ξ_2 are the damp coefficient. The differential equation is solved by IHBM in this paper.

The vibration differential equations are solved to obtain the nonlinear response by using the Incremental Harmonic Balance Method. The specific process of IHBM is shown in Appendix E.

Fig. 2 The schematic diagram of feedback control

3. Dynamic model verification

3.1. Linear model verification

In the previous paper[8], we have studied the time-domain response of the discontinuous piezoelectric laminated cylindrical shells subject to pulse excitation, harmonic excitation, and optimized the position of the piezoelectric layer based on the system's retained energy. In the above study, the comparison with the finite element software ANSYS is sufficient to verify the accuracy of the linear part of the model. Therefore, we believed that the linear part of the model present in this paper is right, and the verification is no longer performed here.

3.2. Nonlinear model verification

In order to verify the nonlinear part of the model established in this paper, We compare the results obtained in this paper with those in literature [9, 10]. The geometric parameters of the model in the verification process are: $L=0.09587\text{m}$, $R=0.0678\text{m}$, $H=0.678\text{ mm}$, and the damping coefficient $\xi=0.001$ has been used for $n=6$. The simply supported-simply supported boundary condition are employed, where $k_{u,\alpha}^i=k_{x,\alpha}^i=k_{\theta,\alpha}^i=0$, $k_{v,\alpha}^i=k_{w,\alpha}^i=10^{12}$ ($i=0, 1$). In the response curve in Fig. 3, ω is the excitation frequency, $\omega_{(1,6)}$ is the fundamental frequency ($m=1$, $n=6$), A is the amplitude of the mode, and H denotes the thickness of the shell.

Fig. 3 Comparison of amplitude-frequency curves with the references

It can be seen from the Fig. 3 that the amplitude-frequency curves obtained in this paper have a similar variation trend with those in the references. After the verification of both linear and nonlinear parts, it can be considered that the method we used is correct.

4. Results and Discussions

In this section, the IHBM is used to obtain the nonlinear frequency-amplitude response curves of the piezoelectric laminated cylindrical shell. The structural parameters are selected as follows: $h=0.002\text{m}$, $h_a=0.001\text{m}$, $h_s=0.001\text{m}$, $L=0.1\text{m}$, $R=0.1\text{m}$, $NT=5$, $f=2\text{e}3\text{N}$, $NA=16$, $k_{u,\alpha}^1=k_{v,\alpha}^1=k_{w,\alpha}^1=k_{\theta,\alpha}^1=k_{x,\alpha}^1=1\text{e}12\text{N/m (N/rad)}$, $k_{u,\alpha}^0=k_{v,\alpha}^0=k_{w,\alpha}^0=k_{\theta,\alpha}^0=k_{x,\alpha}^0=0\text{N/m (N/rad)}$, the exciting position (x, θ) is $(0.9, 3)$, the response position is $(0.9, 3.2)$. In order to facilitate the comparison of different results, the horizontal and vertical coordinates of the amplitude-frequency response curve are dimensionless, that is, the x -axis is $\omega/\omega_{1,4}$ (In this paper, the established model reaches the minimum frequency when $n=4$, therefore, the first-order frequency $n=4$ is selected as the research object), the y -axis is A/h . The material parameters of the base layer and the piezoelectric layer are described in Table 1.

Table 1. Material properties of base layers and piezoelectric layers

	$E_b(\text{GPa})$		$\rho_b(\text{kg}\cdot\text{m}^{-3})$			μ	
Base layer	200		7850			0.26	
	$Q_{11}(\text{GPa})$	$Q_{12}(\text{GPa})$	$Q_{22}(\text{GPa})$	$Q_{44}(\text{GPa})$	$Q_{55}(\text{GPa})$	$Q_{66}(\text{GPa})$	$\rho_c(\text{kg}\cdot\text{m}^{-3})$

PVDF	238.24	4.	23.6	2.15	4.4	6.43	1800
	$e_{31}(\text{C}\cdot\text{m}^{-2})$	$e_{32}(\text{C}\cdot\text{m}^{-2})$	$e_{24}(\text{C}\cdot\text{m}^{-2})$	$e_{15}(\text{C}\cdot\text{m}^{-2})$	$\zeta_{11}(10^{-11}\text{F}\cdot\text{m}^{-1})$	$\zeta_{22}(10^{-11}\text{F}\cdot\text{m}^{-1})$	$\zeta_{33}(10^{-11}\text{F}\cdot\text{m}^{-1})$
PVDF	-0.13	-0.14	-0.01	-0.01	0.885	0.885	10.6

4.1 Influence of the constant gain for frequency-amplitude response

The effect of constant gain G_F on the nonlinear amplitude-frequency response curve of a piezoelectric laminated cylindrical shell is discussed in this section. In Fig. 4, the range of the piezoelectric layer is: (a) the size and position of the randomly selected piezoelectric layer as $\xi \in [0.4, 0.6], \theta \in [0, 2\pi]$; (b) the piezoelectric layer is completely covered on the surface of the shell, $\xi \in [0, 1], \theta \in [0, 2\pi]$. The constant gain G_F is set as 0, 0.1, 0.2, 0.4, respectively. According to Fig. 4, when the piezoelectric layer is completely covered on the surface of the shell, the nonlinear amplitude-frequency response curve has not obvious nonlinear characteristics, and approaches the linear amplitude-frequency response. As the constant gain G_F increases, the response amplitude gradually decreases, and the nonlinear characteristics weaken, which proves that the piezoelectric layer has a large influence on the vibration response of the cylindrical shell. When the position and size of the piezoelectric layer are random, as $\xi \in [0.4, 0.6], \theta \in [0, 2\pi]$, the response curve has obvious soft nonlinear characteristics, and as the constant gain increases, the soft nonlinear characteristic weakens, and the amplitude decreases. After that, the time domain response when the excitation frequency is equal to the frequency at **A** or **B** (the peak frequency of nonlinear response when $G_F=0.4$ in Fig.4) is calculated in Fig. 5. It can be seen from Fig. 5 that the response tends to be stable with time, and the nonlinear response curve is no longer a symmetrical curve.

Fig. 4 The influence of the constant gain for frequency-amplitude response: (a) $\xi \in [0.4, 0.6]$; (b) $\xi \in [0, 1]$

The main reason for the phenomenon shown in Fig. 4 and Fig. 5 is that as the gain constant in Eq.(30) increases, the damping matrix C in Eq.(28) increases. However, the mass matrix and stiffness matrix keep unchanged, therefore, the response amplitude decrease,

Fig. 5 The influence of the constant gain for time-domain response: (a) $\xi \in [0.4, 0.6]$, **A**: $\omega_{EX} = 0.91\omega_{1,4}$; (b)

$\xi \in [0, 1]$, **B**: $\omega_{EX} = 0.98\omega_{1,4}$

4.2 Influence of the size of the piezoelectric layer for frequency-amplitude response

According to the phenomenon in Sec. 4.1, we believe that it is necessary to study the influence of the size and position of the piezoelectric layer for the frequency-amplitude response. Then, the effects of the size and position of the piezoelectric layer are analyzed. This section discusses the effect of the size of the piezoelectric layer on the nonlinear amplitude-frequency response curve of the piezoelectric laminated cylindrical shell. In Fig. 6, the circumferential range of the piezoelectric layer is set as $\theta \in [0, 2\pi]$, the axial range is respectively set as $\xi \in [0, 0.1]$, $\xi \in [0, 0.3]$, $\xi \in [0, 0.5]$, $\xi \in [0, 0.8]$, $\xi \in [0, 1]$, and the constant gain $G_F=0$ remains unchanged. It can be seen that the nonlinear amplitude-frequency response has obvious soft nonlinear characteristics, as the piezoelectric layer increases, the nonlinear characteristic of the response curve gradually decreases, and the response amplitude is reduced.

Fig. 6 The influence of the size of the piezoelectric layer for frequency-amplitude response

Fig. 7 The influences of the size of the piezoelectric layer and constant gain for frequency-amplitude response: (a) $\xi \in [0, 0.3]$; (b) $\xi \in [0, 0.5]$; (c) $\xi \in [0, 0.7]$

In Fig. 7, the effect of the piezoelectric layer's size on the nonlinear amplitude-frequency response curve of a piezoelectric laminated cylindrical shell is analyzed for different constant gain, in which, $\xi \in [0, 0.3]$, $\xi \in [0, 0.5]$, $\xi \in [0, 0.7]$. In each figure, the size of the piezoelectric layer is kept constant, and only the size of G_F is changed. In Fig. 7(a-c), when $\xi \in [0, 0.3]$, the response curve changes less with the increase of G_F ; when $\xi \in [0, 0.7]$, the response curve obviously changes with different G_F . Then, the time domain response of different piezoelectric layers with frequencies at Point A, B and C (Fig. 7) are analyzed. The response curve tends to be stable with time, and the amplitude of the response curve decreases with the increase of constant gain. According to Figs. 6~8, it can be seen that as the size of the piezoelectric layer increases, the amplitude of the

- 1 nonlinear frequency-amplitude response curve decreases, and the nonlinear characteristic decreases;
- 2 at the same time, the influence of the constant gain on the vibration response is weakened.

Fig. 8 The influences of the size of the piezoelectric layer and constant gain for time-domain response: (a)

$\xi \in [0, 0.3]$, **A**: $\omega_{\text{EX}} = 0.94\omega_{1,4}$; (b) $\xi \in [0, 0.5]$, **B**: $\omega_{\text{EX}} = 0.95\omega_{1,4}$; (c) $\xi \in [0, 0.7]$, **C**: $\omega_{\text{EX}} = 0.97\omega_{1,4}$

4.3 Influence of the position of the piezoelectric layer for frequency-amplitude response

This section discusses the effect of the position of the piezoelectric layer on the nonlinear frequency-amplitude response curve of the piezoelectric laminated cylindrical shell with the clamped-free boundary condition. The size of the piezoelectric layer remains unchanged,

$\xi \in [0, 0.1]$, $\theta \in [0, 2\pi]$. In Fig. 9, the position of the piezoelectric layer is respectively calculated as:

$\xi \in [0, 0.1]$; $\xi \in [0.5, 0.6]$; $\xi \in [0.5, 0.6]$; $\xi \in [0.7, 0.8]$, and G_F keeps unchanged. The nonlinear

frequency-amplitude response of the piezoelectric laminated cylindrical shell has obvious soft nonlinear characteristics. When the position of the piezoelectric layer is at the clamped end, the nonlinear characteristic has a weaker amplitude; near the free end, the response's nonlinear characteristic is enhanced, and the amplitude is increased.

Fig. 9 The influence of the position of the piezoelectric layer for frequency-amplitude response

In Fig. 10, the influence of the positions of the piezoelectric layer on the nonlinear frequency-amplitude response curve of the piezoelectric laminated cylindrical shell at some different constant gain is analyzed. In each of the figures, the size and position of the piezoelectric layer are kept unchanged, only G_F change. In Fig. 10(a~c), when $\xi \in [0, 0.1]$, as G_F increases, the response curve changes less. When $\xi \in [0.7, 0.8]$, with the rise of G_F , the amplitude and nonlinear characteristics of the response curve are obviously weakened. The time-domain response at different piezoelectric layer locations calculated in Fig. 11, the response curve has significant nonlinearity when the response is stabilized. It can be seen from Fig. 9~11 that as the position of the piezoelectric layer approaches the free end from the clamped end, the response amplitude increases, the nonlinear characteristic increases, and the effect of constant gain for the piezoelectric laminated cylindrical shell is enhanced.

Fig. 10 The influences of the position of the piezoelectric layer and constant gain for frequency-amplitude response: (a) $\xi \in [0, 0.1]$; (b) $\xi \in [0.5, 0.6]$; (c) $\xi \in [0.7, 0.8]$.

Fig. 11 The influences of the position of the piezoelectric layer and constant gain for time-domain response: (a)

$\xi \in [0, 0.1]$, **A**: $\omega_{\text{EX}} = 0.91\omega_{1,4}$; (b) $\xi \in [0.5, 0.6]$, **B**: $\omega_{\text{EX}} = 0.88\omega_{1,4}$; (c) $\xi \in [0.7, 0.8]$, **C**: $\omega_{\text{EX}} = 0.89\omega_{1,4}$

5. Conclusions

In this paper, we innovatively present a discontinuous piezoelectric laminated cylindrical shell model with point supported elastic boundary condition and study the effect of the discontinuous piezoelectric layer on geometric nonlinear vibration of the shell under radial harmonic excitation.

The following conclusions are drawn:

(1) With the increase of the constant gain G_F , the amplitude of the nonlinear frequency-amplitude response and time domain response decrease, at the same time, the nonlinear phenomenon weakens.

(2) As the size of the piezoelectric layer more prominent, the nonlinear phenomenon and the

1 amplitude of the nonlinear response decrease.

2 (3) The effect of the piezoelectric layer on response is enhanced by constant gain G_F when the
3 size increase.

4 (4) For the clamped-free piezoelectric laminated shells, the amplitude of amplitude-frequency
5 response increases slightly as the position of the piezoelectric layer is closer to the free end, and the
6 nonlinear characteristics are enhanced.

7 (5) The position of the piezoelectric layer is more obviously affected by the constant gain at the
8 free end.

9 **Acknowledgments**

10 This project is supported by the National Natural Science Foundation of China (No.52075086)
11 and the Fundamental Research Funds for the Central Universities (Nos. N180313008, N182410007-
12 06, and N170308028).

13 **Appendix A. Expressions for the mass matrix M**

14 The generalized mass matrix of the piezoelectric laminated shell is expressed as
15

$$16 \quad M_{qq} = \begin{bmatrix} M^{uu} & 0 & 0 & \frac{1}{2}M^{u\phi_x} & 0 \\ 0 & M^{vv} & 0 & 0 & \frac{1}{2}M^{v\phi_\theta} \\ 0 & 0 & M^{ww} & 0 & 0 \\ \frac{1}{2}M^{u\phi_x T} & 0 & 0 & M^{\phi_x\phi_x} & 0 \\ 0 & \frac{1}{2}M^{v\phi_\theta T} & 0 & 0 & M^{\phi_\theta\phi_\theta} \end{bmatrix} \quad (A.1)$$

17 where

$$\begin{aligned}
\mathbf{M}^{uu} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \bar{\mathbf{U}} \bar{\mathbf{U}}^T d\xi d\theta \cdot I_0 + LR \sum_{r=1}^{\bar{NP}} \int_{\theta_r^{\theta_0}}^{\theta_r^{\theta_1}} \int_{\xi_r^{\xi_0}}^{\xi_r^{\xi_1}} \bar{\mathbf{U}} \bar{\mathbf{U}}^T d\xi d\theta \cdot \mathcal{I}_0 \\
\mathbf{M}^{uv} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \bar{\mathbf{U}} \bar{\mathbf{U}}^T d\xi d\theta \cdot I_0 + LR \sum_{r=1}^{\bar{NP}} \int_{\theta_r^{\theta_0}}^{\theta_r^{\theta_1}} \int_{\xi_r^{\xi_0}}^{\xi_r^{\xi_1}} \bar{\mathbf{U}} \bar{\mathbf{U}}^T d\xi d\theta \cdot \mathcal{I}_0 \\
\mathbf{M}^{u\phi_x} &= 2LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \bar{\mathbf{U}} \bar{\boldsymbol{\Phi}}_x^T d\xi d\theta \cdot I_1 + 2LR \sum_{r=1}^{\bar{NP}} \int_{\theta_r^{\theta_0}}^{\theta_r^{\theta_1}} \int_{\xi_r^{\xi_0}}^{\xi_r^{\xi_1}} \bar{\mathbf{U}} \bar{\boldsymbol{\Phi}}_x^T d\xi d\theta \cdot \mathcal{I}_1 \\
\mathbf{M}^{vv} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \bar{\mathbf{V}} \bar{\mathbf{V}}^T d\xi d\theta \cdot I_0 + LR \sum_{r=1}^{\bar{NP}} \int_{\theta_r^{\theta_0}}^{\theta_r^{\theta_1}} \int_{\xi_r^{\xi_0}}^{\xi_r^{\xi_1}} \bar{\mathbf{V}} \bar{\mathbf{V}}^T d\xi d\theta \cdot \mathcal{I}_0 \\
\mathbf{M}^{v\phi_\theta} &= 2LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \bar{\mathbf{U}} \bar{\boldsymbol{\Phi}}_\theta^T d\xi d\theta \cdot I_1 + 2LR \sum_{r=1}^{\bar{NP}} \int_{\theta_r^{\theta_0}}^{\theta_r^{\theta_1}} \int_{\xi_r^{\xi_0}}^{\xi_r^{\xi_1}} \bar{\mathbf{U}} \bar{\boldsymbol{\Phi}}_\theta^T d\xi d\theta \cdot \mathcal{I}_1 \\
\mathbf{M}^{ww} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \bar{\mathbf{W}} \bar{\mathbf{W}}^T d\xi d\theta \cdot I_0 + LR \sum_{r=1}^{\bar{NP}} \int_{\theta_r^{\theta_0}}^{\theta_r^{\theta_1}} \int_{\xi_r^{\xi_0}}^{\xi_r^{\xi_1}} \bar{\mathbf{W}} \bar{\mathbf{W}}^T d\xi d\theta \cdot \mathcal{I}_0 \\
\mathbf{M}^{\phi_x\phi_x} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \bar{\boldsymbol{\Phi}}_x \bar{\boldsymbol{\Phi}}_x^T d\xi d\theta \cdot I_2 + LR \sum_{r=1}^{\bar{NP}} \int_{\theta_r^{\theta_0}}^{\theta_r^{\theta_1}} \int_{\xi_r^{\xi_0}}^{\xi_r^{\xi_1}} \bar{\boldsymbol{\Phi}}_x \bar{\boldsymbol{\Phi}}_x^T d\xi d\theta \cdot \mathcal{I}_2 \\
\mathbf{M}^{\phi_\theta\phi_\theta} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \bar{\boldsymbol{\Phi}}_\theta \bar{\boldsymbol{\Phi}}_\theta^T d\xi d\theta \cdot I_2 + LR \sum_{r=1}^{\bar{NP}} \int_{\theta_r^{\theta_0}}^{\theta_r^{\theta_1}} \int_{\xi_r^{\xi_0}}^{\xi_r^{\xi_1}} \bar{\boldsymbol{\Phi}}_\theta \bar{\boldsymbol{\Phi}}_\theta^T d\xi d\theta \cdot \mathcal{I}_2
\end{aligned}$$

2 Appendix B. Expressions of the stiffness matrix $\mathbf{K}$

3 The generalized stiffness matrix of the piezoelectric laminated shell is expressed as

4

$$\mathbf{K}_{qq} = \begin{bmatrix} \mathbf{K}^{uu} & \frac{1}{2} \mathbf{K}^{uv} & \frac{1}{2} \mathbf{K}^{uw} & \frac{1}{2} \mathbf{K}^{u\phi_x} & \frac{1}{2} \mathbf{K}^{u\phi_\theta} \\ \frac{1}{2} \mathbf{K}^{uvT} & \mathbf{K}^{vv} & \frac{1}{2} \mathbf{K}^{vw} & \frac{1}{2} \mathbf{K}^{v\phi_x} & \frac{1}{2} \mathbf{K}^{v\phi_\theta} \\ \frac{1}{2} \mathbf{K}^{uwT} & \frac{1}{2} \mathbf{K}^{vwT} & \mathbf{K}^{ww} & \frac{1}{2} \mathbf{K}^{w\phi_x} & \frac{1}{2} \mathbf{K}^{w\phi_\theta} \\ \frac{1}{2} \mathbf{K}^{u\phi_xT} & \frac{1}{2} \mathbf{K}^{v\phi_xT} & \frac{1}{2} \mathbf{K}^{w\phi_xT} & \mathbf{K}^{\phi_x\phi_x} & \frac{1}{2} \mathbf{K}^{\phi_x\phi_\theta} \\ \frac{1}{2} \mathbf{K}^{u\phi_\thetaT} & \frac{1}{2} \mathbf{K}^{v\phi_\thetaT} & \frac{1}{2} \mathbf{K}^{w\phi_\thetaT} & \frac{1}{2} \mathbf{K}^{\phi_x\phi_\thetaT} & \mathbf{K}^{\phi_\theta\phi_\theta} \end{bmatrix} \quad (\text{B.1})$$

6 where

$$\begin{aligned}
\mathbf{K}^{uu} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left(\frac{A_{11}}{L^2} \frac{\partial \bar{\mathbf{U}}}{\partial \xi} \frac{\partial \bar{\mathbf{U}}^T}{\partial \xi} + \frac{A_{66}}{R^2} \frac{\partial \bar{\mathbf{U}}}{\partial \theta} \frac{\partial \bar{\mathbf{U}}^T}{\partial \theta} \right) d\xi d\theta \\
&+ LR \sum_{r=1}^{\bar{NP}} \int_{\theta_r^{\theta_0}}^{\theta_r^{\theta_1}} \int_{\xi_r^{\xi_0}}^{\xi_r^{\xi_1}} \left(\frac{\mathcal{A}_{11}^0}{L^2} \frac{\partial \bar{\mathbf{U}}}{\partial \xi} \frac{\partial \bar{\mathbf{U}}^T}{\partial \xi} + \frac{\mathcal{A}_{66}^0}{R^2} \frac{\partial \bar{\mathbf{U}}}{\partial \theta} \frac{\partial \bar{\mathbf{U}}^T}{\partial \theta} \right) d\xi d\theta \\
\mathbf{K}^{uv} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left(\frac{2A_{12}}{LR} \frac{\partial \bar{\mathbf{U}}}{\partial \xi} \frac{\partial \bar{\mathbf{V}}^T}{\partial \theta} + \frac{2A_{66}}{LR} \frac{\partial \bar{\mathbf{U}}}{\partial \theta} \frac{\partial \bar{\mathbf{V}}^T}{\partial \xi} \right) d\xi d\theta
\end{aligned}$$

$$+LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r'}^{\theta_r} \int_{\xi_s'}^{\xi_s} \left(\frac{2\mathcal{A}_{12}^o}{LR} \frac{\partial \bar{U}}{\partial \xi} \frac{\partial \bar{V}^T}{\partial \theta} + \frac{2\mathcal{A}_{66}^o}{LR} \frac{\partial \bar{U}}{\partial \theta} \frac{\partial \bar{V}^T}{\partial \xi} \right) d\xi d\theta$$

$$\mathbf{K}^{uw} = LR \sum_{s=1}^{NP} \int_{\theta_s'}^{\theta_s} \int_{\xi_s'}^{\xi_s} \left(\frac{2A_{12}}{LR} \frac{\partial \bar{U}}{\partial \xi} \bar{\mathbf{W}}^T \right) d\xi d\theta + LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r'}^{\theta_r} \int_{\xi_r'}^{\xi_r} \left(\frac{2\mathcal{A}_{12}^o}{LR} \frac{\partial \bar{U}}{\partial \xi} \bar{\mathbf{W}}^T \right) d\xi d\theta$$

$$\mathbf{K}^{u\phi_x} = LR \sum_{s=1}^{NP} \int_{\theta_s'}^{\theta_s} \int_{\xi_s'}^{\xi_s} \left(\frac{2B_{11}}{L^2} \frac{\partial \bar{U}}{\partial \xi} \frac{\partial \bar{\Phi}_x^T}{\partial \xi} + \frac{2B_{66}}{R^2} \frac{\partial \bar{U}}{\partial \theta} \frac{\partial \bar{\Phi}_x^T}{\partial \theta} \right) d\xi d\theta$$

$$+LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r'}^{\theta_r} \int_{\xi_r'}^{\xi_r} \left(\frac{2\mathcal{B}_{11}^o}{L^2} \frac{\partial \bar{U}}{\partial \xi} \frac{\partial \bar{\Phi}_x^T}{\partial \xi} + \frac{2\mathcal{B}_{66}^o}{R^2} \frac{\partial \bar{U}}{\partial \theta} \frac{\partial \bar{\Phi}_x^T}{\partial \theta} \right) d\xi d\theta$$

$$\mathbf{K}^{u\phi_\theta} = LR \sum_{s=1}^{NP} \int_{\theta_s'}^{\theta_s} \int_{\xi_s'}^{\xi_s} \left(\frac{2B_{12}}{LR} \frac{\partial \bar{U}}{\partial \xi} \frac{\partial \bar{\Phi}_\theta^T}{\partial \theta} + \frac{2B_{66}}{LR} \frac{\partial \bar{U}}{\partial \theta} \frac{\partial \bar{\Phi}_\theta^T}{\partial \xi} \right) d\xi d\theta$$

$$+LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r'}^{\theta_r} \int_{\xi_r'}^{\xi_r} \left(\frac{2\mathcal{B}_{12}^o}{LR} \frac{\partial \bar{U}}{\partial \xi} \frac{\partial \bar{\Phi}_\theta^T}{\partial \theta} + \frac{2\mathcal{B}_{66}^o}{LR} \frac{\partial \bar{U}}{\partial \theta} \frac{\partial \bar{\Phi}_\theta^T}{\partial \xi} \right) d\xi d\theta$$

$$\mathbf{K}^{vv} = LR \sum_{s=1}^{NP} \int_{\theta_s'}^{\theta_s} \int_{\xi_s'}^{\xi_s} \left(\frac{A_{22}}{R^2} \frac{\partial \bar{V}}{\partial \theta} \frac{\partial \bar{V}^T}{\partial \theta} + \frac{k_c A_{44}}{R^2} \bar{\mathbf{V}} \bar{\mathbf{V}}^T + \frac{A_{66}}{L^2} \frac{\partial \bar{V}}{\partial \xi} \frac{\partial \bar{V}^T}{\partial \xi} \right) d\xi d\theta$$

$$+LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r'}^{\theta_r} \int_{\xi_r'}^{\xi_r} \left(\frac{\mathcal{A}_{22}^o}{R^2} \frac{\partial \bar{V}}{\partial \theta} \frac{\partial \bar{V}^T}{\partial \theta} + \frac{k_c \mathcal{A}_{44}^o}{R^2} \bar{\mathbf{V}} \bar{\mathbf{V}}^T + \frac{\mathcal{A}_{66}^o}{L^2} \frac{\partial \bar{V}}{\partial \xi} \frac{\partial \bar{V}^T}{\partial \xi} \right) d\xi d\theta$$

1

$$\mathbf{K}^{vw} = LR \sum_{s=1}^{NP} \int_{\theta_s'}^{\theta_s} \int_{\xi_s'}^{\xi_s} \left(\frac{2A_{22}}{R^2} \frac{\partial \bar{V}}{\partial \theta} \bar{\mathbf{W}}^T - \frac{2k_c A_{44}}{R^2} \bar{\mathbf{V}} \frac{\partial \bar{\mathbf{W}}^T}{\partial \theta} \right) d\xi d\theta$$

$$+LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r'}^{\theta_r} \int_{\xi_r'}^{\xi_r} \left(\frac{2\mathcal{A}_{22}^o}{R^2} \frac{\partial \bar{V}}{\partial \theta} \bar{\mathbf{W}}^T - \frac{2k_c \mathcal{A}_{44}^o}{R^2} \bar{\mathbf{V}} \frac{\partial \bar{\mathbf{W}}^T}{\partial \theta} \right) d\xi d\theta$$

$$\mathbf{K}^{v\phi_x} = LR \sum_{s=1}^{NP} \int_{\theta_s'}^{\theta_s} \int_{\xi_s'}^{\xi_s} \left(\frac{2B_{12}}{LR} \frac{\partial \bar{V}}{\partial \theta} \frac{\partial \bar{\Phi}_x^T}{\partial \xi} + \frac{2B_{66}}{LR} \frac{\partial \bar{V}}{\partial \xi} \frac{\partial \bar{\Phi}_x^T}{\partial \theta} \right) d\xi d\theta$$

$$+LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r'}^{\theta_r} \int_{\xi_r'}^{\xi_r} \left(\frac{2\mathcal{B}_{12}^o}{LR} \frac{\partial \bar{V}}{\partial \theta} \frac{\partial \bar{\Phi}_x^T}{\partial \xi} + \frac{2\mathcal{B}_{66}^o}{LR} \frac{\partial \bar{V}}{\partial \xi} \frac{\partial \bar{\Phi}_x^T}{\partial \theta} \right) d\xi d\theta$$

$$\mathbf{K}^{v\phi_\theta} = LR \sum_{s=1}^{NP} \int_{\theta_s'}^{\theta_s} \int_{\xi_s'}^{\xi_s} \left(\frac{2B_{22}}{R^2} \frac{\partial \bar{V}}{\partial \theta} \frac{\partial \bar{\Phi}_\theta^T}{\partial \theta} + \frac{2B_{66}}{L^2} \frac{\partial \bar{V}}{\partial \xi} \frac{\partial \bar{\Phi}_\theta^T}{\partial \xi} - \frac{2k_c A_{44}}{R} \bar{\mathbf{V}} \bar{\Phi}_\theta^T \right) d\xi d\theta$$

$$+LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r'}^{\theta_r} \int_{\xi_r'}^{\xi_r} \left(\frac{2\mathcal{B}_{22}^o}{R^2} \frac{\partial \bar{V}}{\partial \theta} \frac{\partial \bar{\Phi}_\theta^T}{\partial \theta} + \frac{2\mathcal{B}_{66}^o}{L^2} \frac{\partial \bar{V}}{\partial \xi} \frac{\partial \bar{\Phi}_\theta^T}{\partial \xi} - \frac{2k_c \mathcal{A}_{44}^o}{R} \bar{\mathbf{V}} \bar{\Phi}_\theta^T \right) d\xi d\theta$$

$$\mathbf{K}^{ww} = LR \sum_{s=1}^{NP} \int_{\theta_s'}^{\theta_s} \int_{\xi_s'}^{\xi_s} \left(\frac{k_c A_{44}}{R^2} \frac{\partial \bar{\mathbf{W}}}{\partial \theta} \frac{\partial \bar{\mathbf{W}}^T}{\partial \theta} + \frac{k_c A_{55}}{L^2} \frac{\partial \bar{\mathbf{W}}}{\partial \xi} \frac{\partial \bar{\mathbf{W}}^T}{\partial \xi} + \frac{A_{22}}{R^2} \bar{\mathbf{W}} \bar{\mathbf{W}}^T \right) d\xi d\theta$$

$$+LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r'}^{\theta_r} \int_{\xi_r'}^{\xi_r} \left(\frac{k_c \mathcal{A}_{44}^o}{R^2} \frac{\partial \bar{\mathbf{W}}}{\partial \theta} \frac{\partial \bar{\mathbf{W}}^T}{\partial \theta} + \frac{k_c \mathcal{A}_{55}^o}{L^2} \frac{\partial \bar{\mathbf{W}}}{\partial \xi} \frac{\partial \bar{\mathbf{W}}^T}{\partial \xi} + \frac{\mathcal{A}_{22}^o}{R^2} \bar{\mathbf{W}} \bar{\mathbf{W}}^T \right) d\xi d\theta$$

$$\mathbf{K}^{w\phi_x} = LR \sum_{s=1}^{NP} \int_{\theta_s'}^{\theta_s} \int_{\xi_s'}^{\xi_s} \left(\frac{2k_c A_{55}}{L} \frac{\partial \bar{\mathbf{W}}}{\partial \xi} \bar{\Phi}_x^T + \frac{2B_{12}}{LR} \bar{\mathbf{W}} \frac{\partial \bar{\Phi}_x^T}{\partial \xi} \right) d\xi d\theta$$

$$+LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r'}^{\theta_r} \int_{\xi_r'}^{\xi_r} \left(\frac{2k_c \mathcal{A}_{55}^o}{L} \frac{\partial \bar{\mathbf{W}}}{\partial \xi} \bar{\Phi}_x^T + \frac{2\mathcal{B}_{12}^o}{LR} \bar{\mathbf{W}} \frac{\partial \bar{\Phi}_x^T}{\partial \xi} \right) d\xi d\theta$$

$$\begin{aligned}
\mathbf{K}^{w\phi_\theta} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left(\frac{2k_c A_{44}}{R} \frac{\partial \bar{W}}{\partial \theta} \bar{\boldsymbol{\phi}}_\theta^T + \frac{2B_{22}}{R^2} \bar{W} \frac{\partial \bar{\boldsymbol{\phi}}_\theta^T}{\partial \theta} \right) d\xi d\theta \\
&\quad + LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r}^{\theta'_r} \int_{\xi_r}^{\xi'_r} \left(\frac{2k_c \bar{A}_{44}}{R} \frac{\partial \bar{W}}{\partial \theta} \bar{\boldsymbol{\phi}}_\theta^T + \frac{2\bar{B}_{22}}{R^2} \bar{W} \frac{\partial \bar{\boldsymbol{\phi}}_\theta^T}{\partial \theta} \right) d\xi d\theta \\
\mathbf{K}^{\phi_x \phi_x} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left(\frac{D_{11}}{L^2} \frac{\partial \bar{\boldsymbol{\phi}}_x}{\partial \xi} \frac{\partial \bar{\boldsymbol{\phi}}_x^T}{\partial \xi} + \frac{D_{66}}{R^2} \frac{\partial \bar{\boldsymbol{\phi}}_x}{\partial \theta} \frac{\partial \bar{\boldsymbol{\phi}}_x^T}{\partial \theta} + k_c A_{55} \bar{\boldsymbol{\phi}}_x \bar{\boldsymbol{\phi}}_x^T \right) d\xi d\theta \\
&\quad + LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r}^{\theta'_r} \int_{\xi_r}^{\xi'_r} \left(\frac{\bar{D}_{11}}{L^2} \frac{\partial \bar{\boldsymbol{\phi}}_x}{\partial \xi} \frac{\partial \bar{\boldsymbol{\phi}}_x^T}{\partial \xi} + \frac{\bar{D}_{66}}{R^2} \frac{\partial \bar{\boldsymbol{\phi}}_x}{\partial \theta} \frac{\partial \bar{\boldsymbol{\phi}}_x^T}{\partial \theta} + k_c \bar{A}_{55} \bar{\boldsymbol{\phi}}_x \bar{\boldsymbol{\phi}}_x^T \right) d\xi d\theta \\
\mathbf{K}^{\phi_x \phi_\theta} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left(\frac{2D_{12}}{LR} \frac{\partial \bar{\boldsymbol{\phi}}_x}{\partial \xi} \frac{\partial \bar{\boldsymbol{\phi}}_\theta^T}{\partial \theta} + \frac{2D_{66}}{LR} \frac{\partial \bar{\boldsymbol{\phi}}_x}{\partial \theta} \frac{\partial \bar{\boldsymbol{\phi}}_\theta^T}{\partial \xi} \right) d\xi d\theta \\
&\quad + LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r}^{\theta'_r} \int_{\xi_r}^{\xi'_r} \left(\frac{2\bar{D}_{12}}{LR} \frac{\partial \bar{\boldsymbol{\phi}}_x}{\partial \xi} \frac{\partial \bar{\boldsymbol{\phi}}_\theta^T}{\partial \theta} + \frac{2\bar{D}_{66}}{LR} \frac{\partial \bar{\boldsymbol{\phi}}_x}{\partial \theta} \frac{\partial \bar{\boldsymbol{\phi}}_\theta^T}{\partial \xi} \right) d\xi d\theta \\
\mathbf{K}^{\phi_\theta \phi_\theta} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left(\frac{D_{22}}{R^2} \frac{\partial \bar{\boldsymbol{\phi}}_\theta}{\partial \theta} \frac{\partial \bar{\boldsymbol{\phi}}_\theta^T}{\partial \theta} + k_c A_{44} \bar{\boldsymbol{\phi}}_\theta \bar{\boldsymbol{\phi}}_\theta^T + \frac{D_{66}}{L^2} \frac{\partial \bar{\boldsymbol{\phi}}_\theta}{\partial \xi} \frac{\partial \bar{\boldsymbol{\phi}}_\theta^T}{\partial \xi} \right) d\xi d\theta \\
&\quad + LR \sum_{r=1}^{\overline{NP}} \int_{\theta_r}^{\theta'_r} \int_{\xi_r}^{\xi'_r} \left(\frac{\bar{D}_{22}}{R^2} \frac{\partial \bar{\boldsymbol{\phi}}_\theta}{\partial \theta} \frac{\partial \bar{\boldsymbol{\phi}}_\theta^T}{\partial \theta} + k_c \bar{A}_{44} \bar{\boldsymbol{\phi}}_\theta \bar{\boldsymbol{\phi}}_\theta^T + \frac{\bar{D}_{66}}{L^2} \frac{\partial \bar{\boldsymbol{\phi}}_\theta}{\partial \xi} \frac{\partial \bar{\boldsymbol{\phi}}_\theta^T}{\partial \xi} \right) d\xi d\theta
\end{aligned}$$

1
2 The Electromechanical coupling stiffness and the electrical stiffness matrix of the piezoelectric
3 laminated shell is expressed as

$$\mathbf{K}_{q\psi} = \begin{bmatrix} 0 & 0 \\ \frac{1}{2} \mathbf{K}^{v\psi_a} & \frac{1}{2} \mathbf{K}^{v\psi_s} \\ \frac{1}{2} \mathbf{K}^{w\psi_a} & \frac{1}{2} \mathbf{K}^{w\psi_s} \\ \frac{1}{2} \mathbf{K}^{\phi_x \psi_a} & \frac{1}{2} \mathbf{K}^{\phi_x \psi_s} \\ \frac{1}{2} \mathbf{K}^{\phi_\theta \psi_a} & \frac{1}{2} \mathbf{K}^{\phi_\theta \psi_s} \end{bmatrix} \quad (\text{B.2})$$

$$\mathbf{K}_{\psi\psi} = \begin{bmatrix} \mathbf{K}^{\psi_a \psi_a} & 0 \\ 0 & \mathbf{K}^{\psi_s \psi_s} \end{bmatrix} \quad (\text{B.3})$$

6 where

$$\begin{aligned}
\mathbf{K}^{v\psi_a} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left(\frac{e_{24e}^a h_a^3}{3R^2} \bar{V} \frac{\partial \bar{\boldsymbol{\Psi}}_a^T}{\partial \theta} \right) d\xi d\theta \\
\mathbf{K}^{v\psi_s} &= LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left(\frac{e_{24e}^s h_s^3}{3R^2} \bar{V} \frac{\partial \bar{\boldsymbol{\Psi}}_s^T}{\partial \theta} \right) d\xi d\theta
\end{aligned}$$

7

$$\begin{aligned}
& \mathbf{K}^{w\psi_a} = LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left\{ -\frac{e_{15e}^a h_a^3}{3L^2} \frac{\partial \bar{\mathbf{W}}}{\partial \xi} \frac{\partial \bar{\boldsymbol{\Psi}}_a^T}{\partial \xi} - \frac{e_{24e}^a h_a^3}{3R^2} \frac{\partial \bar{\mathbf{W}}}{\partial \theta} \frac{\partial \bar{\boldsymbol{\Psi}}_a^T}{\partial \theta} \right\} d\xi d\theta \\
& \mathbf{K}^{w\psi_s} = LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left\{ -\frac{e_{15e}^s h_s^3}{3L^2} \frac{\partial \bar{\mathbf{W}}}{\partial \xi} \frac{\partial \bar{\boldsymbol{\Psi}}_s^T}{\partial \xi} - \frac{e_{24e}^s h_s^3}{3R^2} \frac{\partial \bar{\mathbf{W}}}{\partial \theta} \frac{\partial \bar{\boldsymbol{\Psi}}_s^T}{\partial \theta} \right\} d\xi d\theta \\
1 \quad & \mathbf{K}^{\phi_x \psi_a} = LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left\{ -\frac{e_{15e}^a h_a^3}{3L} \bar{\boldsymbol{\Phi}}_x \frac{\partial \bar{\boldsymbol{\Psi}}_a^T}{\partial \xi} + \frac{e_{31e}^a h_a^3}{3L} \frac{\partial \bar{\boldsymbol{\Phi}}_x}{\partial \xi} \bar{\boldsymbol{\Psi}}_a^T \right\} d\xi d\theta \\
& \mathbf{K}^{\phi_x \psi_s} = LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left\{ -\frac{e_{15e}^s h_s^3}{3L} \bar{\boldsymbol{\Phi}}_x \frac{\partial \bar{\boldsymbol{\Psi}}_s^T}{\partial \xi} + \frac{e_{31e}^s h_s^3}{3L} \frac{\partial \bar{\boldsymbol{\Phi}}_x}{\partial \xi} \bar{\boldsymbol{\Psi}}_s^T \right\} d\xi d\theta \\
& \mathbf{K}^{\phi_\theta \psi_a} = LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left\{ \frac{e_{32e}^a h_a^3}{3R} \frac{\partial \bar{\boldsymbol{\Phi}}_\theta}{\partial \theta} \bar{\boldsymbol{\Psi}}_a^T - \frac{e_{24e}^a h_a^3}{3R} \bar{\boldsymbol{\Phi}}_\theta \frac{\partial \bar{\boldsymbol{\Psi}}_a^T}{\partial \theta} \right\} d\xi d\theta \\
& \mathbf{K}^{\phi_\theta \psi_s} = LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left\{ \frac{e_{32e}^s h_s^3}{3R} \frac{\partial \bar{\boldsymbol{\Phi}}_\theta}{\partial \theta} \bar{\boldsymbol{\Psi}}_s^T - \frac{e_{24e}^s h_s^3}{3R} \bar{\boldsymbol{\Phi}}_\theta \frac{\partial \bar{\boldsymbol{\Psi}}_s^T}{\partial \theta} \right\} d\xi d\theta \\
2 \quad & \mathbf{K}^{\psi_a \psi_a} = LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left\{ -\frac{\zeta_{11e}^a h_a^5}{30L^2} \frac{\partial \bar{\boldsymbol{\Psi}}_a}{\partial \xi} \frac{\partial \bar{\boldsymbol{\Psi}}_a^T}{\partial \xi} - \frac{\zeta_{22e}^a h_a^5}{30R^2} \frac{\partial \bar{\boldsymbol{\Psi}}_a}{\partial \theta} \frac{\partial \bar{\boldsymbol{\Psi}}_a^T}{\partial \theta} - \frac{\zeta_{33e}^a h_a^3}{3} \bar{\boldsymbol{\Psi}}_a \bar{\boldsymbol{\Psi}}_a^T \right\} d\xi d\theta \\
& \mathbf{K}^{\psi_s \psi_s} = LR \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left\{ -\frac{\zeta_{11e}^s h_s^5}{30L^2} \frac{\partial \bar{\boldsymbol{\Psi}}_s}{\partial \xi} \frac{\partial \bar{\boldsymbol{\Psi}}_s^T}{\partial \xi} - \frac{\zeta_{22e}^s h_s^5}{30R^2} \frac{\partial \bar{\boldsymbol{\Psi}}_s}{\partial \theta} \frac{\partial \bar{\boldsymbol{\Psi}}_s^T}{\partial \theta} - \frac{\zeta_{33e}^s h_s^3}{3} \bar{\boldsymbol{\Psi}}_s \bar{\boldsymbol{\Psi}}_s^T \right\} d\xi d\theta
\end{aligned}$$

3 *Appendix C. Expressions of the spring stiffness matrix $\mathbf{K}_{spr}$*

4 The spring stiffness matrix of the piezoelectric laminated shell is shown as

$$5 \quad \mathbf{K}_{spr} = \begin{bmatrix} \mathbf{K}_{spr}^{uu} & 0 & 0 & 0 & 0 \\ 0 & \mathbf{K}_{spr}^{vv} & 0 & 0 & 0 \\ 0 & 0 & \mathbf{K}_{spr}^{ww} & 0 & 0 \\ 0 & 0 & 0 & \mathbf{K}_{spr}^{\phi_x \phi_x} & 0 \\ 0 & 0 & 0 & 0 & \mathbf{K}_{spr}^{\phi_\theta \phi_\theta} \end{bmatrix} \quad (C.1)$$

6 where

$$\begin{aligned}
& K_{spr}^{uu} = \sum_{p=1}^{NA} \left(k_{u,p}^0 \bar{\mathbf{U}}(0, \theta_p) \bar{\mathbf{U}}^T(0, \theta_p) + k_{u,p}^1 \bar{\mathbf{U}}(1, \theta_p) \bar{\mathbf{U}}^T(1, \theta_p) \right) \\
& K_{spr}^{vv} = \sum_{p=1}^{NA} \left(k_{v,p}^0 \bar{\mathbf{V}}(0, \theta_p) \bar{\mathbf{V}}^T(0, \theta_p) + k_{v,p}^1 \bar{\mathbf{V}}(1, \theta_p) \bar{\mathbf{V}}^T(1, \theta_p) \right) \\
7 \quad & K_{spr}^{ww} = \sum_{p=1}^{NA} \left(k_{w,p}^0 \bar{\mathbf{W}}(0, \theta_p) \bar{\mathbf{W}}^T(0, \theta_p) + k_{w,p}^1 \bar{\mathbf{W}}(1, \theta_p) \bar{\mathbf{W}}^T(1, \theta_p) \right) \\
& K_{spr}^{\phi_x \phi_x} = \sum_{p=1}^{NA} \left(k_{x,p}^0 \bar{\boldsymbol{\Phi}}_x(0, \theta_p) \bar{\boldsymbol{\Phi}}_x^T(0, \theta_p) + k_{x,p}^1 \bar{\boldsymbol{\Phi}}_x(1, \theta_p) \bar{\boldsymbol{\Phi}}_x^T(1, \theta_p) \right) \\
& K_{spr}^{\phi_\theta \phi_\theta} = \sum_{p=1}^{NA} \left(k_{\theta,p}^0 \bar{\boldsymbol{\Phi}}_\theta(0, \theta_p) \bar{\boldsymbol{\Phi}}_\theta^T(0, \theta_p) + k_{\theta,p}^1 \bar{\boldsymbol{\Phi}}_\theta(1, \theta_p) \bar{\boldsymbol{\Phi}}_\theta^T(1, \theta_p) \right)
\end{aligned}$$

1 **Appendix D. Expressions of the nonlinear item U_N**

$$\begin{aligned}
 2 \quad U_N = & \frac{LR}{2} \sum_{s=1}^{NP} \int_{\theta_s}^{\theta'_s} \int_{\xi_s}^{\xi'_s} \left(\begin{aligned}
 & \frac{A_{12}}{LR^2} \mathbf{q}_u^T \frac{\partial \bar{U}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} + \frac{A_{11}}{L^3} \mathbf{q}_u^T \frac{\partial \bar{U}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \\
 & + \frac{2A_{66}}{LR^2} \mathbf{q}_u^T \frac{\partial \bar{U}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} + \frac{2A_{66}}{L^2 R} \mathbf{q}_v^T \frac{\partial \bar{V}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \\
 & + \frac{A_{12}}{L^2 R} \mathbf{q}_v^T \frac{\partial \bar{V}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} + \frac{A_{22}}{R^3} \mathbf{q}_v^T \frac{\partial \bar{V}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \\
 & + \frac{A_{12}}{L^2 R} \mathbf{q}_w^T \bar{W} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} + \frac{A_{22}}{R^3} \mathbf{q}_w^T \bar{W} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \\
 & + \frac{B_{12}}{R^2 L} \mathbf{q}_{\phi_x}^T \frac{\partial \bar{\Phi}_x}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w + \frac{B_{11}}{L^3} \mathbf{q}_{\phi_x}^T \frac{\partial \bar{\Phi}_x}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \\
 & + \frac{2B_{66}}{R^2 L} \mathbf{q}_{\phi_x}^T \frac{\partial \bar{\Phi}_x}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w + \frac{2B_{66}}{L^2 R} \mathbf{q}_{\phi_\theta}^T \frac{\partial \bar{\Phi}_\theta}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \\
 & + \frac{B_{12}}{L^2 R} \mathbf{q}_{\phi_\theta}^T \frac{\partial \bar{\Phi}_\theta}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w + \frac{B_{22}}{R^3} \mathbf{q}_{\phi_\theta}^T \frac{\partial \bar{\Phi}_\theta}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \\
 & + \frac{A_{11}}{4L^4} \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \\
 & + \frac{A_{22}}{4R^4} \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \\
 & + \frac{A_{12}}{4R^2 L^2} \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \\
 & + \frac{A_{12}}{4R^2 L^2} \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \\
 & + \frac{A_{66}}{R^2 L^2} \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w
 \end{aligned} \right) d\xi d\theta
 \end{aligned}$$

$$\begin{aligned}
& + \frac{LR}{2} \sum_{r=1}^{\bar{N}P} \int_{\theta_r^a}^{\theta_r^b} \int_{\xi_r^a}^{\xi_r^b} \left(\begin{aligned}
& \frac{\bar{A}_{12}^0}{LR^2} \mathbf{q}_u^T \frac{\partial \bar{U}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} + \frac{\bar{A}_{11}^0}{L^3} \mathbf{q}_u^T \frac{\partial \bar{U}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \\
& + \frac{2\bar{A}_{66}^0}{LR^2} \mathbf{q}_u^T \frac{\partial \bar{U}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} + \frac{2\bar{A}_{66}^0}{L^2 R} \mathbf{q}_v^T \frac{\partial \bar{V}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \\
& + \frac{\bar{A}_{12}^0}{L^2 R} \mathbf{q}_v^T \frac{\partial \bar{V}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} + \frac{\bar{A}_{22}^0}{R^3} \mathbf{q}_v^T \frac{\partial \bar{V}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \\
& + \frac{\bar{A}_{12}^0}{L^2 R} \mathbf{q}_w^T \bar{W} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} + \frac{\bar{A}_{22}^0}{R^3} \mathbf{q}_w^T \bar{W} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \\
& + \frac{\bar{B}_{12}^0}{R^2 L} \mathbf{q}_{\phi_x}^T \frac{\partial \bar{\Phi}_x}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w + \frac{\bar{B}_{11}^0}{L^3} \mathbf{q}_{\phi_x}^T \frac{\partial \bar{\Phi}_x}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \\
& + \frac{2\bar{B}_{66}^0}{R^2 L} \mathbf{q}_{\phi_x}^T \frac{\partial \bar{\Phi}_x}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w + \frac{2\bar{B}_{66}^0}{L^2 R} \mathbf{q}_{\phi_\theta}^T \frac{\partial \bar{\Phi}_\theta}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \\
& + \frac{\bar{B}_{12}^0}{L^2 R} \mathbf{q}_{\phi_\theta}^T \frac{\partial \bar{\Phi}_\theta}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w + \frac{\bar{B}_{22}^0}{R^3} \mathbf{q}_{\phi_\theta}^T \frac{\partial \bar{\Phi}_\theta}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \\
& + \frac{\bar{A}_{11}^0}{4L^4} \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \\
& + \frac{\bar{A}_{22}^0}{4R^4} \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \\
& + \frac{\bar{A}_{12}^0}{4R^2 L^2} \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \\
& + \frac{\bar{A}_{12}^0}{4R^2 L^2} \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \theta} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \xi} \mathbf{q}_w \\
& + \frac{\bar{A}_{66}^0}{R^2 L^2} \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w \mathbf{q}_w^T \frac{\partial \bar{W}}{\partial \xi} \frac{\partial \bar{W}^T}{\partial \theta} \mathbf{q}_w
\end{aligned} \right) d\xi d\theta
\end{aligned}$$

1

2

3 Appendix E. Incremental Harmonic Balance Method

4 By presenting the new non-dimensional time variable τ , we write the non-linear vibration

5 differential equation to a modified form

$$\begin{aligned}
& \omega^2 \mathbf{M}_{qq} \mathbf{X}'' + \omega (\mathbf{C}_A + \mathbf{C}_R) \mathbf{X}' + \left(\mathbf{K}_{qq} + \mathbf{K}_{spr} + \mathbf{K}_{q\psi}^S \mathbf{K}_{\psi\psi}^{S^{-1}} \mathbf{K}_{q\psi}^{S^T} + \mathbf{K}_N^{(2)} + \mathbf{K}_N^{(3)} \right) \mathbf{X} = \mathbf{F} \cos \tau \\
& \tau = \omega_{EX} t, \mathbf{X} = [X_1, X_2, X_3, \dots, X_n]^T, \mathbf{F} = \begin{bmatrix} f_u & f_v & f_w & f_{\phi_x} & f_{\phi_\theta} \end{bmatrix}^T
\end{aligned} \tag{D.1}$$

7 Firstly, the differential equations are linearized by using the Newton-Raphson procedure. The

8 corresponding adding increments are used to represent the neighboring state as

$$X_j = X_{j0} + \Delta X, j=1,2,...,n$$

$$\omega = \omega_0 + \Delta \omega$$
(D.2)

Taking Eq. (D.2) to Eq.(D.1), the higher order terms are neglected, and Eq. (D.1) is written as

$$\omega_0^2 \mathbf{M}_{qq} \mathbf{X}'' + \omega_0 (\mathbf{C}_A + \mathbf{C}_R) \mathbf{X}' + \left(\mathbf{K}_{qq} + \mathbf{K}_{spr} + \mathbf{K}_{q\psi}^S \mathbf{K}_{\psi\psi}^{S^{-1}} \mathbf{K}_{q\psi}^{S^T} + 2\mathbf{K}_N^{(2)} + 3\mathbf{K}_N^{(3)} \right) \mathbf{X}$$

$$= \mathbf{Re} - \left(2\omega_0 \mathbf{M}_{qq} \mathbf{X}_0'' + (\mathbf{C}_A + \mathbf{C}_R) \mathbf{X}_0' \right) \Delta \omega$$
(D.3)

$$\mathbf{Re} = \mathbf{F} \cos \tau - \omega_0^2 \mathbf{M}_{qq} \mathbf{X}_0'' - \omega_0 (\mathbf{C}_A + \mathbf{C}_R) \mathbf{X}_0' - \left(\mathbf{K}_{qq} + \mathbf{K}_{q\psi}^S \mathbf{K}_{\psi\psi}^{S^{-1}} \mathbf{K}_{q\psi}^{S^T} + 2\mathbf{K}_N^{(2)} + 3\mathbf{K}_N^{(3)} \right) \mathbf{X}_0$$
(D.4)

where $\mathbf{X}_0 = [X_{10}, X_{20}, X_{30}, ..., X_{n0}]^T$, $\Delta \mathbf{X} = [\Delta X_1, \Delta X_2, \Delta X_3, ..., \Delta X_n]^T$. When the solution is the exact value, the residue “Re” becomes zero.

Next, by using the Galerkin’s technique, the steady state response with a truncated Fourier series are written as

$$X_{j0} = A_0 + \sum_{k=1}^r (a_{jk} \cos k\tau + b_{jk} \sin k\tau) = \mathbf{T}_c \mathbf{A}_j$$

$$\Delta X_j = \Delta A + \sum_{k=1}^r (a_{jk} \cos k\tau + b_{jk} \sin k\tau) = \mathbf{T}_c \Delta \mathbf{A}_j$$
(D.5)

where

$$\mathbf{T}_c = [1, \cos \tau, \sin \tau, \cos 2\tau, \sin 2\tau, L, \cos r\tau, \sin r\tau]$$

$$\mathbf{A}_j = \{a_{j1}, a_{j2}, ..., a_{jn}, b_{j1}, b_{j2}, ..., b_{jn}\}^T$$

$$\Delta \mathbf{A}_j = \{\Delta a_{j1}, \Delta a_{j2}, ..., \Delta a_{jn}, \Delta b_{j1}, \Delta b_{j2}, ..., \Delta b_{jn}\}^T$$
(D.6)

where a_{jk}, b_{jk} are the Fourier coefficients, and n are the numbers of cosine and sine terms. Using these vectors of Fourier coefficients $\mathbf{A}$ and its increments $\Delta \mathbf{A}$, the vectors of the unknown parameters are written as

$$\mathbf{X}_0 = \mathbf{S} \mathbf{A}$$

$$\Delta \mathbf{X} = \mathbf{S} \Delta \mathbf{A}$$
(D.7)

in which

$$S = \begin{bmatrix} T_c & & & \\ & T_c & & \\ & & O & \\ & & & T_c \end{bmatrix}, A = \{A_1, A_2, \dots, A_n\}^T, \Delta A = \{\Delta A_1, \Delta A_2, \dots, \Delta A_n\}^T \quad (D.8)$$

Taking the Eqs. (D.7) to Eq. (D.3), Galerkin's technique is used

$$\int_0^{2\pi} \delta(\Delta X)^T \left[\omega_0^2 M_{qq} X'' + \omega_0 (C_A + C_R) X' + (K_{qq} + K_{spr} + K_{q\psi}^S K_{\psi\psi}^{S^{-1}} K_{q\psi}^{S^T} + 2K_N^{(2)} + 3K_N^{(3)}) \Delta X \right] d\tau \\ = \int_0^{2\pi} \delta(\Delta X)^T \left[R_e - (2\omega_0 M_{qq} X_0'') \Delta \omega - (C_A + C_R) X_0' \right] d\tau \quad (D.9)$$

The linear equation including ΔA and $\Delta \omega$ is written as

$$K_{mc} \Delta A + R_{mc} A \Delta \omega = R_{m1} A + R_{m2} \quad (D.10)$$

where

$$K_{mc} = \int_0^{2\pi} S^T \left[\omega^2 M_{qq} S + \omega (C_A + C_R) S + (K_{qq} + K_{spr} + K_{q\psi}^S K_{\psi\psi}^{S^{-1}} K_{q\psi}^{S^T} + 2K_N^{(2)} + 3K_N^{(3)}) S \right] d\tau \\ R_{mc} = \int_0^{2\pi} S^T (2\omega M_{qq} S + (C_A + C_R) S) d\tau \\ R_{m1} = - \int_0^{2\pi} S^T \left[\omega^2 M_{qq} S + \omega (C_A + C_R) S + (K_{qq} + K_{spr} + K_{q\psi}^S K_{\psi\psi}^{S^{-1}} K_{q\psi}^{S^T} + K_N^{(2)} + K_N^{(3)}) S \right] d\tau \\ R_{m2} = \int_0^{2\pi} S^T F \cos \tau d\tau \quad (D.11)$$

Finally, we use the arc-length method to solve Eq. (D.10) for obtaining the frequency-amplitude response.

Conflict of interests

The authors declare that there is no conflict of interests regarding the publication of this article.

References

- [1] Tzou H S, Gadre M. Theoretical analysis of a multi-layered thin shell coupled with piezoelectric shell actuators for distributed vibration controls. *Journal of Sound & Vibration*. 1989;132:433-50.
- [2] Tzou H S. Piezoelectric Shells. *Solid Mechanics & Its Applications*. 1993;50:98-105.
- [3] Kerur S B, Ghosh A. Active vibration control of composite plate using afc actuator and pvd sensor. *International Journal of Structural Stability & Dynamics*. 2011;11:237-55.
- [4] Parashar S K, Kumar A. Three-dimensional analytical modeling of vibration behavior of piezoceramic cylindrical shells. *Archive of Applied Mechanics*. 2015;85:641-56.
- [5] Sheng G G, Wang X. Studies on dynamic behavior of functionally graded cylindrical shells with PZT layers under moving loads. *Journal of Sound and Vibration*. 2009;323:772-89.
- [6] Qin Z Y, Chu F L, Zu J. Free vibrations of cylindrical shells with arbitrary boundary conditions: A comparison study. *International Journal of Mechanical Sciences*. 2017;133:91-9.
- [7] Qin Z Y, Pang X J, Safaei B, Chu F L. Free vibration analysis of rotating functionally graded CNT reinforced

- composite cylindrical shells with arbitrary boundary conditions. *Composite Structures*. 2019;220:847-60.
- [8] Li C F, Li P Y, Zhang Z X, Wen B C. Optimal locations of discontinuous piezoelectric laminated cylindrical shell with point supported elastic boundary conditions for vibration control. *Composite Structures*. 2019;111575.
- [9] Amabili M. Nonlinear vibrations of laminated circular cylindrical shells: Comparison of different shell theories. *Composite Structures*. 2011;94:207-20.
- [10] Jansen E L. The effect of static loading and imperfections on the nonlinear vibrations of laminated cylindrical shells. *Journal of Sound and Vibration*. 2008;315:1035-46.
- [11] Przekop A, Phairoh T, Huang JK, Mei C. Adaptive Control of Nonlinear Free Vibration of Shallow Shell Using Piezoelectric Actuators. *AIAA Journal*. 2011;49:472-88.
- [12] Rafiee M, Mohammadi M, Aragh BS, Yaghoobi H. Nonlinear free and forced thermo-electro-aero-elastic vibration and dynamic response of piezoelectric functionally graded laminated composite shells : Part II: Numerical results. *Composite Structures*. 2013;103:188-96.
- [13] Rafiee M, Mohammadi M, Aragh B S, Yaghoobi H. Nonlinear free and forced thermo-electro-aero-elastic vibration and dynamic response of piezoelectric functionally graded laminated composite shells, Part I: Theory and analytical solutions. *Composite Structures*. 2013;103:179-87.
- [14] Sheng G G, Wang X. Nonlinear vibration control of functionally graded laminated cylindrical shells. *Composites Part B Engineering*. 2013;52:1-10.
- [15] Shen H S, Yang D Q. Nonlinear vibration of anisotropic laminated cylindrical shells with piezoelectric fiber reinforced composite actuators. *Ocean Engineering*. 2014;80:36-49.
- [16] Zhang S Q, Li Y X, Schmidt R. Active shape and vibration control for piezoelectric bonded composite structures using various geometric nonlinearities. *Composite Structures*. 2015;122:239-49.
- [17] Yue H H, Lu Y F, Deng Z Q, Tzou H. Experiments on vibration control of a piezoelectric laminated paraboloidal shell. *Mechanical Systems & Signal Processing*. 2017;82:279-95.
- [18] Ninh D G, Bich D H. Characteristics of nonlinear vibration of nanocomposite cylindrical shells with piezoelectric actuators under thermo-mechanical loads. *Aerospace Science & Technology*. 2018:S127096381830381X.
- [19] Li C F, Li P Y, Zhong B F, Wen B C. Geometrically nonlinear vibration of laminated composite cylindrical thin shells with non-continuous elastic boundary conditions. *Nonlinear Dynamics*. 2019;95:1903-21.
- [20] Li C F, Miao B Q, Tang Q S, Xi C Y, Wen B C. Nonlinear vibrations analysis of rotating drum-disk coupling structure. *Journal of Sound & Vibration*. 2018;420:35-60.
- [21] Chen Y H, Jin G Y, Liu Z G. Free vibration analysis of circular cylindrical shell with non-uniform elastic boundary constraints. *International Journal of Mechanical Sciences*. 2013;74:120-32.
- [22] Xie K, Chen M X, Zhang L, Xie D. Free and forced vibration analysis of non-uniformly supported cylindrical shells through wave based method. *International Journal of Mechanical Sciences*. 2017;128:512-26.
- [23] Tang Q S, Li C F, Wen B C. Analysis on Forced Vibration of Thin-Wall Cylindrical Shell with Nonlinear Boundary Condition. *Shock and Vibration*. 2016:22.
- [24] Tang Q S, Li C, She H X, Wen B C. Modeling and dynamic analysis of bolted joined cylindrical shell. *Nonlinear Dynamics*. 2018;93:1953-75.
- [25] Li P Y, Li C F, Qiao R H, Wen B C. Sensitivity on the non-continuous supported laminated cylindrical shell to boundary conditions and lamination schemes. *Archive of Applied Mechanics*. 2019;89:2245-64.
- [26] Zhai J J, Zhao G Z, Shang L Y. Integrated design optimization of structural size and control system of piezoelectric curved shells with respect to sound radiation. *Structural and Multidisciplinary Optimization*. 2017;56:1287-304.
- [27] To C W S, Chen T. Optimal control of random vibration in plate and shell structures with distributed piezoelectric components. *International Journal of Mechanical Sciences*. 2007;49:1389-98.

Figures

Figure 1

Schematic diagram of a piezoelectric laminated composite cylindrical shell with elastic boundary conditions: (a) coordinate system and geometry of the shell; (b) partial cross-sectional view of the shell with elastic boundary condition

Figure 2

The schematic diagram of feedback control

Figure 3

Comparison of amplitude-frequency curves with the references

Figure 4

The influence of the constant gain for frequency-amplitude response

Figure 5

The influence of the constant gain for time-domain response

Figure 6

The influence of the size of the piezoelectric layer for frequency-amplitude response

Figure 7

The influences of the size of the piezoelectric layer and constant gain for frequency-amplitude response

Figure 8

The influences of the size of the piezoelectric layer and constant gain for time-domain response

Figure 9

The influence of the position of the piezoelectric layer for frequency-amplitude respon

Figure 10

The influences of the position of the piezoelectric layer and constant gain for frequency-amplitude response

Figure 11

The influences of the position of the piezoelectric layer and constant gain for time-domain response