Updating seismic hazard models for Kuwait

Abd el-aziz Khairy Abd el-aal (✉ akabdelaal@kisr.edu.kw)

Kuwait Institute for Scientific Research <https://orcid.org/0000-0002-1380-0336>

Shaimaa Ismail Mostafa

Zagazig University Faculty of Science

Abdullah Al-Enezi

Kuwait Institute for Scientific Research

Farah Al-Jeri

Kuwait Institute for Scientific Research

Ammar Al-Sayegh

Kuwait University College of Engineering and Petroleum

Research Article

Keywords: Seismotectonic, probabilistic seismic hazard, vulnerability index, deaggregation, Kuwait

Posted Date: March 11th, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-245972/v1>

License: This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Abstract

The valuable results from this research are the first and essential step for assessing seismic risk in Kuwait. The increase in the urban development and construction of tall buildings and skyscrapers in Kuwait necessitated an estimate of the seismic risk for creating a unified seismic code for Kuwait. This research comes to make the necessarily step by assessing the seismic hazard and deaggregation in the State of Kuwait. For this purpose, the historical and instrumental seismic catalogs of Kuwait and the active Zagros Seismic Belt were primarily compiled, unifying the magnitudes, removing unnecessary earthquakes (seismicity declustering) and considering the completeness of the catalogs. Multi-seismotectonic models for Kuwait region incorporate earthquake focal mechanisms, seismicity pattern, and structural geological situation have been created to reduce epistemic uncertainty. The recurrence parameters as well as the maximum expected earthquake from each seismic source were fundamentally estimated. Appropriate ground motion attenuation relation within a logic tree formulation was mainly used in creating hazard maps. A state-of-the-art probabilistic approach is used herein to produce hazard maps at return periods of 75, 475, 975 and 2475 years (equivalent to 50%, 10%, 5% and 2%, respectively, probability of exceedance in 50 years) at periods of PGA, 0.1, 1 and 4 seconds. The computations of hazard maps were constructed using spacing grid of $0.2^\circ \times 0.2^\circ$ all over the Kuwait area. Uniform hazard spectrum and deaggregation charts have been adopted for all six governorates of Kuwait. These results with vulnerability index are the main components for estimating the seismic risk of Kuwait.

Introduction

Kuwait is located on the northeastern side of the Arabian Peninsula at the northwestern part of the Arabian Gulf, which borders it on the eastern side (Figure 1). It is bordered by Iraq to the north and the west, and Saudi Arabia to the south and west. It lies between latitudes $28^\circ 27' 0''$ and $30^\circ 3' 0''$ N and longitudes $46^\circ 18' 0''$ and $48^\circ 18' 0''$ E, and its area is 17818 km^2 (<https://en.wikipedia.org/wiki/Kuwait>). Kuwait is one of the most important oil producing and exporting countries in the world and has 10% of the world's oil reserves in its soil.

The seismic activity in the state of Kuwait is low to moderate (Abd el-aal et al 2020a 2020b and 2020c; Al-enzi et al 2007; Gu et al., 2017; Pasyanos et al., 2007). It was affected by several local earthquakes such as the January 16th, 1977 earthquake (local magnitude (MI) = 4.5) which took place at 28.8° N and 48.1° E and the June 2th, 1993 earthquake (MI = 4.8) which occurred at 29.0° N and 47.6° (Abd el-aal et al 2020a; Bou-Rabee and Nur 2002). After the earthquake that occurred in 1993, the Kuwaiti government decided to establish a national seismic network, and the establishment and operation of this network was assigned to the Kuwait Institute for Scientific Research (KISR). The network started recording earthquakes in 1997. The Kuwait National Seismic Network (KNSN) records local, regional and global earthquakes that occur in Kuwait and in the Globe. The KNSN has main center at Kuwait Institute of Scientific Research (KISR) and 8 field seismic stations distributed all over Kuwait (Abd el-aal et al 2020a; Gu et al 2018). This network has a very great impact in protecting modern urban development in the State of Kuwait. Earthquakes can cause many social and economic disasters if not well planned. Therefore, it is

important to assess the seismic hazard in Kuwait for the purpose of mitigating seismic risk and developing seismic codes to design earthquake-resistant structures and protect strategic buildings.

In this study, the epistemic uncertainty treatment seismic hazard approach is used to assess the seismic hazard considering both local seismicity of Kuwait and regional seismicity from its surrounding regions. Many seismologists (e.g. Abd el-aal et al 2015; Bommer et al. 2004; Mostafa et al 2018; Rafi et al. 2013; Reiter 1990; Ur-Rehman et al. 2013; ...etc) considered PSHA as the most valuable contribution to hazard assessment. PSHA was introduced by Cornell (1968) and modified by (McGurie 1978; Bender and Perkins 1987). It estimates the probability of exceeding or non-exceeding the ground motion at a certain level which is very important in assessing the chance of failure and designing building codes. The first step in the hazard analysis is to compile an earthquake catalog. It is followed by building a seismotectonic source model and estimating the recurrence parameters and maximum predicted magnitude in each seismic source specified in this model. Finally, a suitable ground motion attenuation relationship is applied to estimate the seismic hazard.

Seismic hazard maps were constructed using a grid of 0.2° all over the Kuwait area to produce 5 % damped spectral acceleration values on bedrock for the peak ground acceleration (PGA) and spectral periods of 0.1, 1 and 4 seconds at return periods of 75, 475, 975 and 2475 years (equivalent to 50%, 90%, 95% and 98%, respectively, probability of non-exceedance of ground motion in 50 years). Uniform hazard spectrum (UHS) was estimated at Kuwait city, Hawally, Mubarak Al-Kabeer, Sabah Al Ahmad, Al Farwaniyah and Al Jahra to determine the hazard at spectral periods ranging from 0 to 4 seconds. These periods are the most important for the earthquake engineering designer. Also, deaggregation charts were adopted in the same cities to determine the scenario events that mostly contribute to the hazard level for spectral periods of 0.1 and 2 seconds at return period of 475 years. The 475 years is the primary return period for most building codes.

Regional seismicity and seismotectonic

The State of Kuwait, being relatively located in the northeastern part of the Arabian Peninsula, was fundamentally affected by the collision of Zagros fold belt in Iran (Figure 2a). A number of scientists have studied the structural and tectonic situation of the region (Abd el-aal et al 2020a 2020b and 2020c; Al-enzi et al 2007; Carman, 1996; Pasyanos et al., 2007; Laske et al. 2013). The rate of crustal shortening along the Zagros Thrust fold belt is about 10 mm/year in the southeast and decreases to be 5 mm/year in the northwest (Allen et al. 2004; Vernant et al. 2004). Small, medium and large earthquakes with magnitudes reach to 7.5 took place along this belt at shallow, medium and deep depths (Figure 1). This high seismicity active Pliocene belt is 1500 km long and 200 to 300 km wide. It extends from eastern Turkey in the north to Oman in the south in NW-SE direction (Jackson and McKenzie 1984; Berberian 1995; Hessami et al. 2003). Due to the movement and uplift of mountains primarily caused by the convergence zone and erosion in the region, a sedimentary cover from 7 to 10 km thick was mainly formed.

Reilinger et al. (2006) has studied the focal mechanisms of some earthquakes along the Zagros belt and inferred thrust faults with dip angle of 40°-50° (Figure 2b). Carman (1996) indicated that the maximum principal horizontal stress field is trending in a NE-SW direction (Kuwait Arch). The surface topography of Kuwait is mostly mapped by the steep folding of the Zagros belt in a NW-SE direction. The anticlines, which formed during the Cretaceous period, in the Quaternary deposits of the large Burgan Oil Field in southern Kuwait showed clear evidence of continued movement and uplift in the region.

Local seismicity and structure setting

The State of Kuwait has relatively low to moderate seismic activity (Abd el-aal et al 2020a 2020b and 2020c; Gu et al., 2017; Pasyanos et al., 2007). No historical earthquakes have been accurately documented prior to 1900. In the twentieth century, earthquakes were instrumentally recorded inside Kuwait such as July 5, 1931, March 14, 1973, January 2, 1976, September 26, 1976, September 27, 1976, January 16, 1977, and July 1, 1993 earthquakes with magnitudes 4.7, 4.6, 4.1, 3.2, 3.8, 4.5, and 4.8, respectively. The 1993 Kuwait earthquake caused some damages and property in Kuwait City (Abd el-aal et al 2020a; Gu et al., 2017; Pasyanos et al., 2007). Figure (1) shows the seismicity of Kuwait, Zagros belt and their surroundings.

After the establishment of the KNSN, seismologists become able to record very small earthquakes occurring in Kuwait. Hence, they can determine the seismic sources with high accuracy. Two seismic sources were identified, namely, Minagish_Umm Gudair and Raudhatain-Sabriya sources in southwestern and northeastern Kuwait, respectively. Abd el-aal et al (2020a) and Pasyanos et al. (2007) believe that earthquakes are caused by oil extraction, particularly those that occurred near the oil fields. Figure (2c) shows that Kuwait structures consist of structural arches, anticlines, synclines, regional gradients, troughs, stylolites, fractures and faults (Carman, 1996). Al-enzi et al (2007) studied the focal mechanism of 33 earthquakes in Kuwait using the composite 1st motion polarity of P-waves. It shows that the state of Kuwait is affected by strike slip faulting with normal and reverse components (Figure 2d).

Methodology

The probabilistic seismic hazard approach (PSHA) is used to assess the seismic hazard in the state of Kuwait based on Cornell (1968) procedure. Later, this procedure was amended by McGuire (1978) and Bender and Perkins (1987). The probability for the ground motion level to be exceeded within a particular period of time is obtained from the following equation:

$$P_t(z) = \sum_{j=1}^k \int_{m=M_{min}}^{m=M_{max}} P_t(m) \int_{r=R_0}^{R_{max}} P(r) (P(A \geq Z)_{m,r}) dm dr \quad (1)$$

where $P_t(m)$ is the probability of an earthquake occurrence of magnitude m in the seismic source j over t years, $P(r)$ is the probability of an earthquake occurrence in a seismic source at a distance r from a given

site and $P(A \geq Z)$ is the probability that the ground motion A will exceed the ground motion level Z at a specific site.

The first step in the hazard analysis after compiling the earthquake catalog is to build up a seismotectonic source model to define the seismicity of each source based on all the available information about the geology, structure, tectonic and seismicity in the study area. Next, the seismicity recurrence parameters are estimated to determine the probability of occurrence of an earthquake of a certain magnitude within each seismic source during a particular time period. In addition, the maximum earthquake magnitude (M_{max}) is estimated for all the seismic sources to evaluate the seismic risk at a given site where critical structures are planned. M_{max} indicates the amount of rock displacement that is likely to occur along the fault plane. In other words, whenever a strong earthquake takes place, the amount of rocks displacement is increased and vice versa. Finally, a ground motion relation is used to attenuate earthquakes generated in each seismic source in relation to earthquake magnitude and distance to the site. In this study, the Poisson model was used to estimate the earthquake magnitude exceedance rate for each seismic source. Also, the epistemic uncertainties were reduced by using alternative seismotectonic source models and ground motion relationships within a logic tree formulation. Figure 3 illustrates the procedure chart used in this study.

Inputs for PSHA

1. Catalog Data

The first important step in any seismic hazard assessment is building a complete, uniform and reliable earthquake catalog containing all the available instrumental besides the historical earthquakes from many different sources. In this study, instrumental earthquakes from 1907 to 2019 were gathered from different sources. The local events in Kuwait from 1997 to 2019 were obtained from the KNSN (<http://www.kisr.edu.kw>).

The earthquakes data recorded by the Kuwait National Seismic Network (KNSN) was on the local magnitude scale (MI) and was converted to the moment magnitude scale using a linear regression relation which was developed for this purpose. The limited available moment earthquake data in Kuwait were used to establish the relationship between the local magnitude scale and the moment magnitude scale in Kuwait (Figure 4) with 95% confidence bounds as follows:

$$M_w = 0.87(MI) (\pm 0.07) + 0.2392 (\pm 0.2) \quad (2)$$

Where (M_w) is the moment magnitude. MI refers to local magnitude used in KNSN.

Regional and Teleseismic events from 2008 to 2019 were gathered from the European Mediterranean Seismological Center (EMSC) (<http://www.emsc-csem.org>). In addition, Regional events from 1907 to

2010 as well as the historical seismic events from 628 to 1898 were gathered from the catalog of Deif et al. (2017).

All these data were gathered in one catalog after excluding all the duplicated events. All the events were unified to the Mw scale. The Mw is the most reliable magnitude scale that takes into account the rupture are on the fault surface, the amount of displacement along the fault plane during an earthquake and the strength of the rock. The catalog declustering was applied using Gardner and Knopoff (1974) windowing technique to remove the dependent earthquakes (foreshocks and aftershocks). This technique makes the catalog look like a Poisson dataset (Van Stiphout et al. 2012). Figure (1) shows the historical and instrumental seismicity of Kuwait and its surroundings from 628 to 1898 and from 1907 to 2019, respectively. Only the medium and large earthquakes that took place outside Kuwait with a magnitude of ≥ 4 were used in the hazard analysis, but only in the state of Kuwait the small earthquakes with $M_w \geq 2.5$ were also used. The total number of earthquakes in the resultant catalog is 4957 events.

2. Seismotectonic models

The seismotectonic model defines the geographical boundaries of the seismic sources capable of generating earthquakes. Each of these seismic sources has a unique stress regime and seismicity level and each point within it is assumed to have the same probability of being the epicenter of a future earthquake. These seismic sources could be area, line (fault), point, volume sources or dipping planes (Lee and Trifunace 1985). The seismotectonic models are absolutely essential in both seismic hazard studies and earthquake forecasting.

In this study, the boundaries of the seismic sources in the seismotectonic model were made up of area sources and defined on the basis of the geographical distribution of earthquakes' epicenters, structure and tectonic settings, seismic activity and previous focal mechanism studies. Two alternative seismotectonic models were constructed to account for the epistemic uncertainties (Figure 5). The first seismotectonic source model is composed of 27 seismic sources to describe in detail the seismicity of the study area. However, the second model is composed of 12 sources and describes the regional seismicity of the area. In addition, a background seismic source has been defined in both seismotectonic models to describe the floating earthquakes outside the defined seismic sources. Both of these models were combined within a logic tree formulation to further take the epistemic uncertainties into account. Estimates of this logic tree formulation are referred to as the third seismotectonic source model in the next sections just to describe the results in an easier and more comfortable manner.

3. Recurrence parameters and M_{max}

To accurately estimate the earthquake recurrence parameters and predict the maximum earthquake magnitude in each seismic source for the seismotectonic models, the seismicity of each source should be modeled first by estimating the so-called the magnitude of completeness (M_c). The M_c is the minimum magnitude at which all earthquakes in an area have been identified over a specified period of time (Kijko and Graham 1999; Rydelek and Sacks 2003; Wiemer and Wyss 2000). The earthquakes in each seismic

source were used to build sub-catalogs where each one was subdivided to 1-unit magnitude bin. Then, the cumulative number of events in each bin was plotted versus time starting from the time of the recent earthquake (Figure 6). The time at which the slope of the cumulative plot begins to change is the level of completeness.

Now, the seismicity recurrence parameters can be estimated to indicate the probability of earthquake occurrence with time at any point in the seismic source. The recurrence parameters include β , b-value and λ and are estimated herein using the maximum likelihood method of Weichert (1980). The parameter β is very significant in defining the tectonics of each seismic source. It can be estimated from the relationship ($\beta = b \ln 10$) where b is the b-value of the Gutenberg and Richter (1956) relationship. The b-value is the relative ratio of small and large magnitude earthquakes. The variations in b-values indicate the variation in stress regimes. Low b-value indicates high stress in a specific region and vice versa. The parameter λ is the activity rate and is defined as the number of earthquakes that occur annually.

Moreover, the maximum earthquake M_{max} that can be generated in the seismic source is estimated in some sources using the Robson-Whitlock-Cooke method (Robson and Whitlock 1964; Cooke 1979; Kijko and Singh 2011). In other sources that have incomplete data, the procedure provided by Kijko (2004) is used to estimate M_{max} . Finally, the predicted M_{max} was estimated by adding 0.5 magnitude unit to the maximum observed magnitude ($M_{max \text{ obs.}}$) in the seismic sources with very few events. The seismicity recurrence parameters and M_{max} with their corresponding standard deviations (STD) for the first and the second seismotectonic source models are listed in Tables (1) and (2), respectively.

4. Ground motion attenuation relations

The attenuation models define the probabilistic relation between earthquake magnitudes, source to site distance and acceleration. It should be carefully chosen to attenuate earthquakes generated in each seismic source. The lack of ground motion records in Kuwait makes it necessary to use already developed attenuation relations to predict the ground motion from the earthquakes' epicenter to a specific site. Two alternative attenuation relations were used in the current study: the first one is the García et al. (2005) that was used to model the ground motion in the seismic sources located in the state of Kuwait and the second is the Abrahamson and Silva (1997) which was applied to model the ground motion in the sources surrounding Kuwait for the three seismotectonic source models. Also, these attenuation relations use the Mw scale to predict the ground motion on the rock sites for PGA and spectral accelerations for different periods.

Uncertainty treatment

In this study, the uncertainty was reduced using alternative seismotectonic source models within a logic tree framework (Figure 3). As is known, the statistical variability in the definition of the seismic sources in the seismotectonic model and in the attenuation relationships are the main sources of epistemic

uncertainty. Alternatives ground motion equation relations were also used to diminish the effect uncertainty in the hazard calculations. In addition, the maximum predicted earthquake magnitude was estimated using three different methods depending on the completeness of the sub-catalogs, the number of events in each seismic source and the quality of the data to ensure reliable and precise estimates of the M_{max} which is a very important parameter in the probabilistic seismic hazard assessment.

Results And Discussion

1. Seismic hazards maps

Seismic hazard was estimated using CRISIS (2015) software at 324 sites distributed over a $0.2^\circ \times 0.2^\circ$ spaced grid in Kuwait and surroundings to avoid extrapolation of the results. Hazard maps were created to produce 5 % damped spectral acceleration values for PGA and spectral periods of 0.1, 1 and 4 seconds on bedrock for the three seismotectonic source models. Figures (7 to 18) show the computed seismic hazards for return periods of 75, 475, 975 and 2475 years, which are equivalent to 50%, 10%, 5% and 2%, respectively, probability of exceeding the ground motion in 50 years which is the expected design life for a building. These return periods, especially the 475 years, are very important in most seismic building codes.

The hazard maps show that the level of the seismic hazard in Kuwait is low to moderate. It is increasing at the Sabriya and Minagish oil fields in the northeast and southwest of Kuwait, respectively, especially at the PGA and the short spectral period of 0.1 second, indicating that the origin of seismicity in this area is of induced type. The level of seismic activity at Minagish oil field is higher than at the Sabriya oil field. The seismic hazard results for the first, second and third seismotectonic source models showed that the highest PGA values are 49.1, 52.36 and 64.62 gals, respectively, at return period of 475 years in the south of Kuwait. To the northeast of Kuwait state, the hazard level increases due to the collision of Zagros fold belt in Iran. These results highly reflect the seismotectonic setting of the area.

All the seismic hazard maps show the highest acceleration values at the short spectral period 0.1 second while the lowest acceleration values appear at the long spectral period 4 second. All maps with the same spectral accelerations at different return periods for the three source models have the same contour line pattern. It is clearly observed that the hazard pattern is affected by the geometry of the seismotectonic source models especially at the PGA and 0.1 seconds spectral period. The background seismic source has a negligible effect on the hazard calculations because it represents areas of low seismicity. The hazard maps show higher acceleration values at the 2475 years return period, and by increasing the probability of exceeding ground motion in 50 years, the acceleration values become lower.

In general, the hazard results for the three seismotectonic models are close to each other, with the detailed first model showing the lowest acceleration values and the third model having the highest values at PGA and 0.1 second spectral period. However, the second model shows the lowest acceleration values at the long spectral periods of 1 and 4 seconds. In addition, the results of this study were compared with

the results of previous studies (i.e. Al-shijbi et al. 2018, Sadek 2004,etc) and showed a good agreement in the regional seismicity pattern of Kuwait and provided an accurate and detailed estimate of the seismic hazard in the state of Kuwait over a 0.2° grid taking into account the teleseismic, regional and local seismicity. The results also reflect the tectonics and seismic activity of the area confirming the accuracy and reliability of the estimates. These maps can be used by the earthquake engineer for earthquake-resistant design, national and strategic projects, building codes and seismic risk mitigation.

2. UHS

Uniform hazard spectrum (UHS) was estimated at all six governorates of Kuwait state, namely: Kuwait city, Hawally, Mubarak Al-Kabeer, Sabah Al Ahmad, Al Farwaniyah and Al Jahra (Figure 1). UHS is used to determine the seismic hazard at spectral periods ranging from 0 to 4 seconds at return periods of 75, 475, 975 and 2475 years on bedrock for the three seismotectonic models (Figures 19, 20 and 21). The results show the highest acceleration values at spectral period of 0.1 second for all return periods for the three seismotectonic models except for Kuwait city, which shows the highest acceleration at spectral period of 0.2 second for all return periods for only the second model. Also, the highest acceleration at Mubarak Al-Kabeer is shown at spectral period of 0.2 second for the 75, 475 and 975 years return periods. In addition, the highest acceleration in Hawally is shown at spectral period of 0.1 second except for the first and second models at 75 and 475 years return periods, respectively, where the highest accelerations are 43.87 and 82.68 gals, respectively, at spectral period of 0.2 second.

Al Jahra exhibits the highest level of seismic activity among the six governorates of Kuwait for the three seismotectonic models. The seismic hazard at Al Jahra for spectral period of 0.1 second at 475 years return period is 122, 95 and 130 gals for the first, second and third models, respectively. The acceleration values increase with decreasing the probability of exceeding ground motion in 50 years. As shown from the figures, the hazard is highest at 2474 years return period and lowest at 75 years return period. The first model shows the lowest acceleration values at the short periods spectral acceleration values. However, the second model gives the lowest accelerations at long periods spectral acceleration values. The third model shows the highest acceleration values at all spectral accelerations.

The first and third models show the same seismicity level for the six governorates. The order of seismic hazards in these governorates from highest to lowest is: Al Jahra, Sabah Al Ahmad, Al Farwaniyah, Kuwait city, Hawally and Mubarak Al-Kabeer. On the other hand, the arrangement of seismic hazards in these governorates from the second seismotectonic model from highest to lowest is: Sabah Al Ahmad, Al Farwaniyah, Al Jahra, Mubarak Al-Kabeer, Hawally and Kuwait city. The slight difference between the results from these alternative models reduces the uncertainties in the hazard calculation. These results are very useful in earthquake engineering designs.

3. Deaggregation

Deaggregation of seismic hazards was estimated to specify the contribution of both earthquake magnitude and source to site distance to the hazard at all six governorates of Kuwait for spectral periods

of 0.1 and 2 seconds at return period of 475 years for the three constructed seismotectonic models. These deaggregation charts are very useful in determining the dominant hazardous event at a specific site to be used by the earthquake engineer. The deaggregation of seismic hazards at the six governorates of Kuwait for the short spectral period of 0.1 second for return period of 475 years for the first, second and third seismotectonic source models are shown in Figures (22, 23 and 24, respectively). Figure (22) shows that most of the hazard comes from moderate earthquakes with M_w ranging from 4 to 5 located at very short distance from these governorates. Figures (23 and 24) show that most of the hazard comes from moderate earthquakes with M_w ranging from 4 to 5) located at very short distance from the sites. Besides, Kuwait city and Hawally show a smaller contribution to the hazard from nearby large earthquakes ($M_w > 6$) for the second and the third models. These nearby medium size earthquakes will pose a small risk due to their short duration (0.1 second) and low energy content.

Figures (25, 26 and 27) show the deaggregation of seismic hazards at the six governorates for the long spectral period of 2 second for return period of 475 years for the first, second and third seismotectonic source models, respectively. Figure (25) shows that the most severe impact on the sites come from nearby large earthquakes ($M_w > 6$). Also, a smaller contribution to the hazard comes from large events that are very far away. Figure (26) shows that the most contribution of hazard on the sites come from nearby large earthquakes ($M_w > 6$) and only Al Jahra shows that there is an additional lower hazard from large earthquakes located at large distances > 800 km. The results of the third model (Figure 27) show that the hazard is dominated by nearby large size earthquakes ($M_w > 6$) and only Al Jahra and Sabah Al Ahmed show that there is an additional lower hazard from large earthquakes that are very far away. These nearby large earthquakes will pose a high risk due to their long duration (2 second) and high energy content. The deaggregation results from the three models show that the governorates of Kuwait are affected by nearby moderate to large earthquakes which can produce high values of ground acceleration, which would pose a high risk if not well planned.

Summary and conclusions

In this study, the seismic hazard of the state of Kuwait was assessed using the epistemic uncertainty seismic technique as a first and important step before assessing seismic risk in the study area. An earthquake catalog was compiled from many different sources for use in the PSHA and for demonstrating the seismicity of Kuwait and the Zagros Thrust fold belt from the period 1907 to 2019. The catalog was unified, removed the foreshocks and aftershocks and estimated the magnitude of completeness to ensure its quality and homogeneity. Earthquakes with a moment magnitude ≥ 4 were considered in the seismic hazard analysis. In addition, local events with a moment magnitude ≥ 2.5 that occurred in Kuwait during the period from 1997 to 2019 were used as the catalog was complete during this time span due to the establishment of the KNSN stations.

Alternative seismotectonic models were built based on all the available geological, structural, tectonic, geophysical, seismotectonic and seismological data of Kuwait, Iraq, Iran, Saudi Arabia and the United

Arab Emirates to consider the effects of local and regional seismic sources. The recurrence parameters β , b-value and λ with their corresponding standard deviations were estimated for each seismic source using the maximum likelihood method. The maximum earthquake for each source was predicated as it very important input parameter in the hazard calculation. It indicates the amount of rock displacement that is likely to occur during an earthquake. The epistemic uncertainties were reduced by using alternative seismotectonic models and attenuation relations within a logic tree formulation.

Maps were created to show the seismic hazard for periods of PGA, 0.1, 1 and 4 seconds for return periods of 75, 475, 975 and 2475 years (corresponding to probabilities of 50%, 10%, 5% and 2%, respectively, for ground motion exceedance in 50 years). These maps show that Kuwait is affected by low to moderate seismic activity. The highest seismic level is at the Minagish oil field area in the southwest. Another activity is has been found at Sabriya oil field in the northeast, indicating that these areas are affected by induced seismicity. Higher values of acceleration are observed at the short spectral periods as well as at the long return periods.

UHS were estimated at six governorates to show the hazard at a set of spectral periods ranging from 0 to 4 seconds, which are the most important to the seismic engineer for return periods of 75, 475, 975 and 2475 years on bedrock. The highest acceleration is observed at spectral period of 0.1 second except for some localities which showed the highest value at 0.2 second for some return periods in the seismotectonic models. The results of the three models showed the highest hazard in the state of Kuwait at Sabah Al Ahmad which is located in the south of Kuwait at the eastern boundary of the Arabian plate.

Moreover, the seismic hazard was disaggregated as a function of magnitude and distance to indicate the scenario events that contribute more to the seismic hazard at each of the six governorates of Kuwait for spectral periods of 0.1 and 2 seconds at return period of 475 years for the three seismotectonic models. In general, the results showed that the most severe impact on the six sites is dominated by nearby medium size earthquakes at the short spectral period of 0.1 second, which means that small risks can be expected due to the short duration and low energy content. However, they are dominated by nearby large size earthquakes at the long spectral period of 2 second, which means that high risks can be expected due to the long duration and high energy content. The results of this study are consistent with the seismicity and tectonic setting of the study area. The reliable estimates of acceleration at variable spectral accelerations and different return periods provide guidance for an earthquake engineer to build safe structures that can resist ground motion in the event of an earthquake. These results can be very helpful to create a unified seismic code for Kuwait.

Declarations

- **Funding:** The authors did not receive support from any organization for the submitted work.
- **Financial interests:** The authors declare they have no financial interests.
- The authors have no conflicts of interest to declare that are relevant to the content of this article.

Acknowledgments

The authors deep thank to Kuwait National Seismic Network (KNSN) at Kuwait Institute for Scientific Research (KISR) for providing earthquake data. Figures were generated by the Generic Mapping Tool (GMT), and Grapher software. The AUE software (Kijko 2004) and The CRISIS 2015 Software was used for seismic hazard calculation. This work is a part of project no. CR20-45EV-01, project title “Kuwait Seismic Hazard Micro-Zonation” submitted to KFAS for funding and still under consideration.

References

- Abd el-aal A.K., Al-Jeri F., Al-Enezi A., Parol J.A. (2020a). Seismological aspects of the 15 November 2019 earthquakes sequence, Kuwait. *Arabian J. Geosci.* **13**, 941 (2020). <https://doi.org/10.1007/s12517-020-05919-1>.
- Abd el-aal A.K., Parol J.A., Al-Jeri F. Al-Enezi A. (2020b). Modeling and simulating ground motion from potential seismic sources to Kuwait: Local and regional scenarios. Submitted to *Geotectonics journal*.
- Abd el-aal A.K., Al-Enezi A., Al-Jeri F. (2020c). Tectonic and anthropogenic characteristics of the 15 November 2019 micro earthquakes sequence, Kuwait. Accepted, *Geotectonics journal*.
- Abd el-aal AK, Kamal H, Abdelhay M, Elzahaby K (2015). Probabilistic and stochastic seismic hazard assessment for wind turbine tower sites in Zafarana Wind Farm, Gulf of Suez, Egypt. *Bull Eng Geol Environ* 74(4):1225–1241. <https://doi.org/10.1007/s10064-015-0717-x>.
- Al-enzi A, Sadeq A, Abdel-Fattah R (2007). Assessment of the Seismic Hazard for the state of Kuwait. Int rep EC011C, submitted to KFAS 2007.
- Abrahamson NA, Silva W (1997) Empirical response spectral attenuation relations for shallow crustal earthquakes. *Seismol Res Lett* 68(1):94–127. <https://doi.org/10.1785/gssrl.68.1.94>.
- Allen M, Jackson JA, Walker R (2004) Late Cenozoic reorganization of the Arabia-Eurasia collision and the comparison of short-term and long-term deformation rates. *Tectonics* 23, TC2008.
- Bender BK, Perkins DM (1987). SEISRISK III: a computer program for seismic hazard estimation. USGS Open File Report 82–293.
- Berberian M (1995). Master ‘blind’ thrust faults hidden under the Zagros folds, active basement tectonics and surface morphotectonics. *Tectonophys* 241:193–224.
- Bommer JJ, Abrahamson NA, Strasser FO, Pecker A, Bard P-YH, Cotton F, Fäh D, Sabetta F, Scherbaum F, Studer J (2004) The challenge of defining upper bounds on earthquake ground motions. *Seismol Res Lett* 75(1):82–95. <https://doi.org/10.1785/gssrl.75.1.82>.

- Bosworth W, Huchon P, McClay K (2005) The red sea and the Gulf of Aden basins. *J Af Earth Sci* 43:334–378.
- Bou-Rabee, F., and Nur A. (2002). The 1993 M4. 7 Kuwait earthquake: Induced by the burning of the oil fields, Kuwait *J. Sci. Eng* , 29 (2), 155–163.
- Carman G. J. (1996). Structural elements of onshore Kuwait. *GeoArabia*, 1 (2), 239–266.
- Cooke P (1979) Statistical inference for bounds of random variables. *Biometrika* 66(2):367–374.
<https://doi.org/10.1093/biomet/66.2.367>.
- Cornell CA (1968) Engineering seismic risk analysis. *Bull Seismol Soc Am* 58:1583–1606
- Deif A, Al-Shijbi Y, El-Hussain I, Ezzelarab M., Mohamed A. (2017). Compiling an earthquake catalogue for the Arabian Plate, Western Asia. *Journal of Asian Earth Sciences* 147: 345–357.
<http://dx.doi.org/10.1016/j.jseaes.2017.07.033>
- García D., Singh S. K., Herráiz M., Ordaz M., and Pacheco J., (2005). Inslab Earthquakes of Central Mexico: Peak Ground-Motion Parameters and Response Spectra, *Bulletin of the Seismological Society of America*, Vol. 95, No. 6, pp. 2272–2282.
- Gardner JK, Knopoff L (1974). Is the sequence of earthquakes in Southern California, with aftershocks removed, Poissonian?. *Bull Seismol Soc Am* 64:1363–1367
- Gu C., Al-Jeri F., Al-Enezi A., Büyüköztürk O., Toksöz M.N. (2017). Source Mechanism Study of Local Earthquakes in Kuwait. *Seismological Research Letters*, 88 (6): 1465–1471.
- Gu C., Prieto G.A., Al-Enezi A., Al-Jeri F., Al-Qazweeni J., Kamal K., Kuleli S., Mordret A., Büyüköztürk O., Toksöz M.N. (2018). Ground motion in Kuwait from regional and local earthquakes: Potential effects on tall buildings. *Pure Appl. Geophys.* (2018) 175: 4183.
- Gutenberg, B., & Richter, C. F. (1956). Magnitude and energy of earthquakes. *Annali di Geofisica*, 9, 1–15.
- Hessami K, Jamali F, Tabassi H (2003). Major active faults in Iran. Ministry of Science, Research and Technology, International Institute of Earthquake Engineering and Seismol. (IIEES), 1:250000 scale map.
<http://www.emsc-csem.org>
<http://www.kisr.edu.kw>
- Jackson JA, McKenzie D (1984). Active tectonics of the Alpine-Himalayan Belt between western Turkey and Pakistan. *Geophys J R Astron Soc* 77:185–264
- Kijko A (2004). Estimation of the maximum earthquake magnitude, m_{max} . *Pure Appl Geophys* 161(8):1655–1681. <https://doi.org/10.1007/s00024-004-2531-4>.

- Kijko A, Graham G (1999). Parametric-historic procedure for probabilistic seismic hazard analysis part ii: assessment of seismic hazard at specified site. *Pure Appl Geophys* 154(1): 1–22.
<https://doi.org/10.1007/s000240050218>.
- Kijko A, Singh M (2011). Statistical tools for maximum possible earthquake magnitude estimation. *ActaGeophys* 59:674–700.
- Laske, G., Masters G., Ma Z. and Pasyanos M. (2013). Update on crust 1.0 a 1-degree global model of earths crust, in EGU General Assembly Conference Abstracts, vol. 15, p. 2658.
- Lee VW, Trifunace MD (1985) Uniform risk spectra of strong earthquake ground motion. Dept Civil Engineer Univ Southern California Los Angeles California 5–80
- McGuire RK (1978) FRISK: computer program for seismic risk analysis using faults as earthquake sources. US Geol Survey Open-File Report:78–107.
- Mostafa S.I, Abd el-aal A.K., El-Eraki M.A (2018). Multi scenario seismic hazard assessment for Egypt. *J Seismol* <https://doi.org/10.1007/s10950-018-9728-y>.
- Pasyanos M.E., Tkalcic H., Gok R., Al-Enezi A. and Rodgers A.J. (2007). Seismic structure of Kuwait. *Geophys. J. Int.* (2007) 170, 299–312, doi: 10.1111/j.1365-246X.2007.03398.x.
- Rafi Z, Ahmed N, Ur-Rehman S, Azeem T, Abd el-aal AK (2013). Analysis of Quetta-Ziarat earthquake of 29 October, 2008 in Pakistan. *Arab J Geosci* 6(6):1731–1737. <https://doi.org/10.1007/s12517-011-0485-2>
- Reilinger R, McClusky S, Vernant P, Lawrence S, Ergentav S, Cakmak R, Ozener H, Kadirov F, Guliev I, Stepanyan R, Nadariya M, Hahubia G, Mahmoud S, Sakr K, ArRajehi A, Paradissis D, Al-Aydrus A, Prilepin M, Guseva T, Evren E, Dmitrotsa A, Filikov SV, Gomez F, Al-Ghazzi R, Karam G (2006). GPS constraints on continental deformation in the Africa-Arabia-Eurasia continental collision zone and implications for the dynamics of plate interactions. *J Geophys Res* 111:B05411.
- Reiter L (1990) Earthquake hazard analysis. Columbia Univ Press, New York 254p
- Robson DS, Whitlock JH (1964). Estimation of a truncation point. *Biometrika* 51(1-2):33–39.
<https://doi.org/10.1093/biomet/51.1-2.33>.
- Rydelek PA, Sacks IS (2003). Comment on Bminimum magnitude of completeness in earthquake catalogs: examples from Alaska, the western United States, and Japan^, by Stefan Wiemer and Max Wyss. *Bull Seismol Soc Am* 93(4):1862– 1867. <https://doi.org/10.1785/0120020035>.
- Sadek A. W. (2004). Seismic map for the state of Kuwait. *Emirates Journal for Engineering Research*, 9 (2), 53-58 (2004).

Ur-Rehman S, Azeem T, Abd el-aal AK, Nasir A (2013a). Parameterization of 18th January 2011 earthquake in Dalbadin Region, Southwest Pakistan. NRIAG J Astron Geophys 2(2):203–211. <https://doi.org/10.1016/j.nrjag.2013.06.001>.

Van Stiphout, T., Zhuang, J., & Marsan, D. (2012). Seismicity declustering. Community Online resource for statistical seismicity analysis (CORSSA), <https://doi.org/10.5078/corssa-52382934>. <http://www.corssa.org>.

Vernant Ph, Nilforoushan F, Hatzfeld D, Abassi MR, Vigny C, Masson F, Nankali H, Martinod J, Ashtiani A, Bayer R, Tavakoli F, Chery J (2004) Present-day crustal deformation and plate kinematics in Middle East constrained by GPS measurements in Iran and northern Oman. Geophys J Int 157:381–398.

Weichert DH (1980) Estimation of the earthquakes recurrence parameters for unequal observation periods for different magnitudes. Bull Seismol Soc Am 70:1337–1346

Wiemer S, Wyss M (2000) Minimum magnitude of completeness reporting in earthquake catalogs: examples from Alaska, the western United States, and Japan. Bull Seismol Soc Am 90(4):859–869. <https://doi.org/10.1785/0119990114>.

Al-shijbi Y, El-hussain I., Deif A., Al-kalbani A., and Mohamed A. (2018). Probabilistic Seismic Hazard Assessment for the Arabian Peninsula. 2018. Pure Appl. Geophys. <https://doi.org/10.1007/s00024-018-2033-4>.

Tables

Table 1: Seismicity recurrence parameters and M_{max} for the first seismotectonic source model.

Seismic source	M_{min}	M_{max} obs.	M_{max}	STD	β	STD	b	STD	λ	STD
1	2.5	4.8	5.3	0.77	2.08	0.19	0.9	0.08	2.39	0.401
2	2.5	4.5	5	0.91	2.09	0.26	0.91	0.11	1.637	0.319
3	2.5	4.2	4.7	0	2.29	0.42	0.99	0.18	0.901	0.34
4	4	6.5	7.1	0.65	1.6	0.2	0.7	0.09	0.941	0.193
5	4	6.3	6.5	0.34	1.5	0.19	0.65	0.08	0.957	0.169
6	4	7.3	7.5	0.3	1.75	0.08	0.76	0.04	0.707	0.043
7	4	6.4	6.7	0.64	1.83	0.25	0.8	0.11	0.377	0.07
8	4	5.9	6.1	0.31	1.65	0.21	0.72	0.09	1	0.201
9	4	6.7	6.9	0.32	1.32	0.12	0.57	0.05	1.18	0.17
10	4	6.4	6.5	0.27	1.73	0.1	0.75	0.05	1.754	0.185
11	4	5.1	5.3	0.34	2.16	0.41	0.94	0.18	0.388	0.132
12	4	6.7	6.8	0.26	1.7	0.07	0.74	0.03	0.901	0.047
13	4	6.9	7	0.26	1.59	0.05	0.69	0.02	1.395	0.069
14	4	5.9	6.1	0.33	1.62	0.25	0.7	0.11	0.723	0.144
15	4	5.8	6.1	0.4	1.93	0.25	0.84	0.11	1.51	0.324
16	4	5.8	6.1	0.36	2.05	0.28	0.89	0.12	1.183	0.298
17	4	6.1	6.2	0.27	1.54	0.27	0.67	0.12	0.8	0.161
18	4	6.4	6.5	0.26	1.19	0.2	0.52	0.09	0.242	0.037
19	4	6.5	6.7	0.31	1.64	0.14	0.71	0.06	0.884	0.113
20	4	6.5	6.7	0.33	1.53	0.19	0.67	0.08	0.417	0.063
21	4	6.8	7.3	0.91	1.79	0.22	0.78	0.09	1.389	0.382
22	4	4.4	4.6	0.31	2	0.45	0.87	0.19	0.217	0.088
23	4	7.1	7.6	0.61	0.91	0	0.39	0	0.025	0.006
24	4	7.1	7.6	0	1.36	0.29	0.59	0.13	1.901	0.645
25	4	4.7	4.9	0.3	2.24	0.44	0.97	0.19	1.626	0.607
26	4	5	5.2	0.3	1.87	0.33	0.81	0.14	3.803	0.864
27	4	7	7.1	0.47	1.4	0.22	0.61	0.1	0.08	0.013

BG	4	5.1	5.2	0.33	1.93	0.4	0.84	0.18	0.26	0.067
----	---	-----	-----	------	------	-----	------	------	------	-------

Table 2: Seismicity recurrence parameters and M_{max} for the second seismotectonic source model.

Seismic source	M_{min}	M_{max} obs.	M_{max}	STD	β	STD	b	STD	λ	STD
1	2.5	4.8	5.3	0.63	2.11	0.19	0.91	0.08	2.919	0.542
2	2.5	4.5	5	0.81	2.09	0.25	0.91	0.11	1.734	0.329
3	4	6.5	7.1	0.62	1.59	0.2	0.69	0.09	0.953	0.195
4	4	6.3	6.5	0.3	1.56	0.18	0.68	0.08	0.162	0.017
5	4	7.3	7.5	0.29	1.75	0.08	0.76	0.03	0.866	0.055
6	4	6.7	6.8	0.26	1.68	0.08	0.73	0.03	1.654	0.142
7	4	6.7	6.8	0.26	1.69	0.06	0.74	0.03	0.994	0.054
8	4	6.9	7	0.26	1.57	0.05	0.68	0.02	2.192	0.138
9	4	6.5	6.8	0.3	1.58	0.16	0.69	0.07	0.579	0.081
10	3.8	7.1	7.6	0.91	1.39	0.15	0.6	0.07	3.929	0.839
11	3.95	6.8	7.3	0.88	1.8	0.21	0.78	0.09	1.848	0.504
12	4	7	7.1	0.49	1.21	0.24	0.53	0.1	0.054	0.011
BG	4	5.1	5.2	0.33	1.74	0.41	0.76	0.18	0.23	0.062

Figures

Figure 1

Location map of Kuwait and its seismicity.

Figure 2

(a) is the major tectonic setting of the Arabian plate and surrounding, DST is the Dead Sea transform, NAF is the north Anatolian fault and EAF is the east Anatolian fault (Bosworth et al. 2005), (b) is the focal mechanisms of some regional earthquakes (Reilinger et al. 2006). (c) is a structure map of Kuwait (Carman 1996). (d) is the composite focal mechanism of 33 earthquakes in Kuwait located at depths < 6 and > 6 denoted by S and D, respectively, ... (Al-enzi et al. 2007).

Figure 3

work chart for the epistemic uncertainty treatment procedure used in this study.

Figure 4

Data fit and relationship between local and moment magnitude scales for earthquakes recorded by KNSN in Kuwait (upper panel). Data residuals (lower panel)

Figure 5

The seismicity of Kuwait and its surroundings. (a) and (b) are the first and the second seismotectonic source models, respectively.

Figure 6

Examples of the cumulative number of earthquakes versus time for magnitude bin 4-5 to define the period of completeness for seismic sources 13 and 8 from the first (upper panel) and second (lower panel) seismotectonic source models, respectively.

Figure 7

Seismic hazard maps of Kuwait for PGA, .1, 1 and 4 seconds at return period of 75 years on rock for the first seismotectonic source model.

Figure 8

Seismic hazard maps of Kuwait for PGA, .1, 1 and 4 seconds at return period of 475 years on rock for the first seismotectonic source model.

Figure 9

Seismic hazard maps of Kuwait for PGA, .1, 1 and 4 seconds at return period of 975 years on rock for the first seismotectonic source model.

Figure 10

Seismic hazard maps of Kuwait for PGA, .1, 1 and 4 seconds at return period of 2475 years on rock for the first seismotectonic source model.

Figure 11

Seismic hazard maps of Kuwait for PGA, .1, 1 and 4 seconds at return period of 75 years on rock for the second seismotectonic source model.

Figure 12

Seismic hazard maps of Kuwait for PGA, .1, 1 and 4 seconds at return period of 475 years on rock for the second seismotectonic source model.

Figure 13

Seismic hazard maps of Kuwait for PGA, .1, 1 and 4 seconds at return period of 975 years on rock for the second seismotectonic source model.

Figure 14

Seismic hazard maps of Kuwait for PGA, .1, 1 and 4 seconds at return period of 2475 years on rock for the second seismotectonic source model.

Figure 15

Seismic hazard maps of Kuwait for PGA, .1, 1 and 4 seconds at return period of 75 years on rock for the third seismotectonic source model.

Figure 16

Seismic hazard maps of Kuwait for PGA, .1, 1 and 4 seconds at return period of 475 years on rock for the third seismotectonic source model.

Figure 17

Seismic hazard maps of Kuwait for PGA, .1, 1 and 4 seconds at return period of 975 years on rock for the third seismotectonic source model.

Figure 18

Seismic hazard maps of Kuwait for PGA, .1, 1 and 4 seconds at return period of 2475 years on rock for the third seismotectonic source model.

Figure 19

UHS at 5% damped spectral acceleration values at return periods 75, 475, 975 and 2475 years on rock for the first seismotectonic model.

Figure 20

UHS at 5% damped spectral acceleration values at return periods 75, 475, 975 and 2475 years on rock for the second seismotectonic model.

Figure 21

UHS at 5% damped spectral acceleration values at return periods 75, 475, 975 and 2475 years on rock for the third seismotectonic model.

Figure 22

Deaggregation charts showing the contribution of magnitude and distance to the seismic hazard at six rock sites in Kuwait for spectral period of 0.1 second at return period of 475 years for the first seismotectonic model.

Figure 23

Deaggregation charts showing the contribution of magnitude and distance to the seismic hazard at six rock sites in Kuwait for spectral period of 0.1 second at return period of 475 years for the second seismotectonic model.

Figure 24

Deaggregation charts showing the contribution of magnitude and distance to the seismic hazard at six rock sites in Kuwait for spectral period of 0.1 second at return period of 475 years for the third seismotectonic model.

Figure 25

Deaggregation charts showing the contribution of magnitude and distance to the seismic hazard at six rock sites in Kuwait for spectral period of 2 second at return period of 475 years for the first seismotectonic model.

Figure 26

Deaggregation charts showing the contribution of magnitude and distance to the seismic hazard at six rock sites in Kuwait for spectral period of 2 second at return period of 475 years for the second seismotectonic model.

Figure 27

Deaggregation charts showing the contribution of magnitude and distance to the seismic hazard at six rock sites in Kuwait for spectral period of 2 second at return period of 475 years for the third seismotectonic model.