Irreversibility Analysis in Darcy-Forchheimer Flow of Nanofluid by a Stretched Surface

T Hayat

Quaid-i-Azam University

Zobia Kainat

Quaid-i-Azam University

A Alsaedi

King Abdulaziz University

Sohail A. Khan (✉ sohailahmadkhan93@gmail.com)

Quaid-i-Azam University

Research Article

Keywords: Darcy-Forchheimer, Surface stretch , Unsteady boundary layer, MHD flow, Nanofluid, Heat generation / absorption and entropy analysis

Posted Date: March 1st, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-253982/v1>

License: © ⓘ This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Irreversibility analysis in Darcy-Forchheimer flow of nanofluid by a stretched surface

T. Hayat ^{a,b}, Zobia Kainat ^a Sohail A. Khan ^{a,1} and A. Alsaedi ^b

^a Department of Mathematics, Quaid-I-Azam University 45320, Islamabad 44000, Pakistan

^b Nonlinear Analysis and Applied Mathematics (NAAM) Research Group, Faculty of Science, King Abdulaziz University, P. O. Box 80207, Jeddah 21589, Saudi Arabia

(¹Corresponding author: Email: sohailahmadkhan93@gmail.com (S. A. Khan))

Abstract: The aim of this articles is to investigate the entropy optimization in unsteady MHD flow Darcy-Forchheimer nanofluids towards a stretchable sheet. The surface we tend to think about is porous and stretchy under acceleration. Flow occurs due to the stretching of the surface. Four distinct types of aqueous nanostructures are taken in this examination where copper oxide (CuO), copper (Cu), titanium dioxide (TiO_2) and aluminum oxide (Al_2O_3) are the nanoparticles. Irreversibility analysis are discussed through second law of thermodynamics. The expression of energy is mathematically designed and discussed according to heat generation / absorption, dissipation, thermal radiation, and joule heating. The nonlinear PDE (partial differential conditions) is first changed to ODE (normal differential conditions) through the use of appropriate similarity variables. Here we used the numerically embedded solution technique to develop a numerical result for the obtained nonlinear flow expression. Influence of various flow parameter velocity temperature distribution and entropy generation are discussed. Reduction occurs in velocity profile for larger porosity and magnetic parameters. An enhancement in entropy generation and temperature distribution is seen for Brinkman number. An opposite effect is noticed in velocity and temperature through solid volume friction.

Keywords: Darcy-Forchheimer; Surface stretch ; Unsteady boundary layer; MHD flow; Nanofluid; Heat generation / absorption and entropy analysis.

1: Introduction

Nanomaterials can be described as a colloidal suspension of nano-size solid particles (1-100 nm) scattered uniformly in a base liquid. Nanoparticles are made from materials that are chemically stable like metals, oxides ceramics, carbides and non-metals such as graphite and CNTs. The commonly used base fluids are ethylene, water, oils and lubricants. Choi [1] worked on the enhancement of thermal conductivity of conservatively utilizable material (base liquid) through the insertion

of nanoparticles into it. Nanofluids enhance the thermophysical properties of the base fluids used. Stability of nano liquid is more than compared to other fluids. Nguyen et al. [2] discussed thermal conduction augmentation of water (H_2O) base liquid with presence of Aluminium oxide. Thermal conductivity performance of nanomaterials depends on number of various parameter and properties scattered stages, molecule concentration, molecule measure, morphology and surfactants or dispersion. Nanofluids are produced in industries by several methods. One of the processes is where the nanoparticles are produced through gas condensation and then they are inserted into the base liquid. Ultrasound is used in process in order to make sufficient amalgamation of the particles and the base fluids [3-4]. Moreover, there is a relationship among the thermal conductivity and molecule size of nano particles' just as the temperature of the based liquid decreasing the particle size. There is an increment in the thermal transportation of nanofluid mixtures [5-6]. Irreversibility analysis in Darcy-Forchheimer CNT based nanoliquid flow with dissipation effect between rotating stretchable disk is explored by Khan et. al. [7]. Thermal transfer analysis in transient unsteady MHD flow of hybrid nanomaterials subject to porous stretching surface is illustrated by Nabwey and Mahdy [8]. Murshed et al. [9] explored the heat conductivity and consistency of nano-liquids both tentatively and hypothetically. Heat transfer analysis in magnetohydrodynamic reactive of viscous liquid with convective condition past a vertical plate is discussed by Makinde and Aziz [10]. Thermal and solutal transfer effect in ferro-nanoliquid flow with Lorentz and soret effect is highlighted by Sabu. et al. [11]. Some relevant studies about nanomaterials flow are presented in Refs [13-20]. By keeping the origin of sheet fixed the two forces are applied, which are opposite in direction but equal in magnitude. Then such type of sheet is known as stretching sheet. In fluid dynamics the flow of fluid can be carried out by moving the boundaries of plates, applying the pressure gradient and the buoyancy forces. Many researchers have worked on the problems in which the flow is induced by stretching the surface and moving the plates due to its wide application in industry and engineering. Turkyilmazoglu [21] reported the magnetohydrodynamic flow of nanoliquids through an unstable dilation/compression surface. He demonstrated an accurate and analytical solutions. Time dependent MHD flow of pseudo-plastic nanoliquid with heat source is reported by Lin et al. [22]. Crane [23] revealed an MHD stream incited by a twisting/extending surface. Rasool et al. [24] announced a Darcy connection in nanofluid stream over nonlinearly extending sheet/surface. In many traditional industrial and mechanical fields, entropy generation minimization (EGM) is applied whenever fluid flow and heat transport is involved, enhancing flow engineering along with working conditions to improve hydroelectric performance. Focused. all practical and real life applications involved the study of EG in liquids , for example generators, Air conditioners heat pumps, Heat engines and power plants. The entropy generation

(EG) depends mainly on the following factors: heat transfer, chemical reactions, mass transfer, power transmission, viscosity losses and simultaneous effects of thermal and solutal. Bianco et al. [25] investigated the entropy generation of turbulent conductive flow water nanofluids in a tube in which constant wall heat flow conditions, in which they reported that for low concentrations of nanoparticles, the total entropy generation could be minimized. The stagnation point flow of MHD nanomaterials with minimal entropy generation on a stretched surface is explored by Rashidi and Bhatti [26]. Some modern irreversibility problem are mentioned in Refs. [27-37].

The theme of this article is to investigate the entropy generation in time dependent Darcy-Forchheimer flow towards a stretch surface. Energy expression are modeled through joule heating, heat source/sink and dissipation effects. Physical features of irreversibility analysis are examined thermodynamic second law. Ordinary system are obtained through similarity transformation. The obtained system are numerically solved through bvp4c Matlab software. Influence of various flow variables on velocity field temperature distribution and entropy generation rate. Thermo physical behaviors of nanofluid and base fluid are highlighted in Tables 1 and 2.

2: Modeling

Consider magnetohydrodynamics time dependent Darcy-Forchheimer flow towards a stretchable surface. Here water is considered as base liquid and four different type of nano particles (i.e. copper oxide (CuO), copper (Cu), titanium dioxide (TiO_2) and aluminum oxide (Al_2O_3)) are considered. Energy expression are developed through joule heating, heat generation/absorption and dissipation effect. Physical description of irreversibility analysis are discusses through second law of thermodynamics. Consider $U_w = (\frac{ax}{1-ct})$ is the stretching velocity with positive rate constant ($a > 0$). Magnetic field of constant strength (B_0) is applied. Flow sketch is highlighted in Fig. 1.

Fig. 1: Flow sketch.

Governing expression satisfy

$\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0,$	(1)
$\frac{\partial u}{\partial t} + u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} = \frac{\mu_{nf}}{\rho_{nf}} \frac{\partial^2 u}{\partial y^2} - \frac{\sigma_{nf} B_0^2}{\rho_{nf}} u - \frac{\nu_{nf}}{\kappa^*} u - F u^2,$	(2)
$\left. \begin{aligned} \frac{\partial T}{\partial t} + u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} &= \frac{\kappa_{nf}}{(\rho c_p)_{nf}} \frac{\partial^2 T}{\partial y^2} + \frac{\mu_{nf}}{(\rho c_p)_{nf}} \left(\frac{\partial u}{\partial y} \right)^2 \\ &+ \frac{\sigma_{nf}}{(c_p \rho)_{nf}} B_0^2 u^2 + \frac{Q_0}{(c_p \rho)_{nf}} (T - T_\infty) \end{aligned} \right\},$	(3)

With

$\left. \begin{aligned} &\text{for } t \leq 0, u = 0 = v, T = T_\infty \text{ for all } (x, y) \\ &t > 0; u = U_w = \frac{ax}{1-ct}, v = v_w(t) = \frac{v_0}{\sqrt{1-ct}}, T = T_w(x, t) = T_\infty + \frac{bx}{(1-ct)^2}, y = 0 \\ &u \rightarrow 0, T \rightarrow T_\infty, \text{ as } y \rightarrow \infty. \end{aligned} \right\}$	(4)
---	-----

Here (x, y) denotes the Cartesian coordinates, (u, v) the velocity components, σ_{nf} the electrical conductivity, ρ_{nf} the density, μ_{nf} the dynamic viscosity, ν_{nf} kinematic viscosity, $F(= \frac{C_p}{x\sqrt{\kappa^*}})$ non-uniform inertia coefficient of porous medium, k_{nf} the thermal conductivity, T_∞ the ambient temperature, $(\rho c_p)_{nf}$ the heat

capacitance, T_w the wall temperature and Q_0 coefficient of heat generation/absorption.

here subscript nf stand for nano fluid, s for solid particles.

Table 1: Mathematical expression of thermophysical properties of nanofluids [38-39]:

Characteristic of Nanofluid	Mathematical Form
Viscosity	$\mu_{nf} = \frac{\mu_f}{(1-\phi)^{2.5}}$
Viscosity	$\rho_{nf} = \rho_f \left(1 - \phi + \phi \frac{\rho_s}{\rho_f}\right),$
Heat Capacity	$(\rho C_p)_{nf} = (1 - \phi)(\rho C_p)_s + \phi(\rho C_p)_f,$
Thermal Conductivity	$\frac{\kappa_{nf}}{\kappa_f} = \frac{(\kappa_s + 2\kappa_f) - 2\phi(\kappa_f - \kappa_s)}{(\kappa_s + \kappa_f) + \phi(\kappa_f - \kappa_s)},$
Electrical Conductivity	$\frac{\sigma_{nf}}{\sigma_f} = [1 + \frac{3(\sigma-1)\phi}{(\sigma+2) - (\sigma-1)\phi}], \sigma = \frac{\sigma_s}{\sigma_f},$

Letting

$$\left. \begin{aligned} u = \frac{\partial \psi}{\partial y} = \frac{ax}{1-ct} f'(\eta), v = -\frac{\partial \psi}{\partial x} = -\left(\frac{av_f}{1-ct}\right)^{\frac{1}{2}} f(\eta) \\ \eta = \left(\frac{a}{(1-ct)v_f}\right)^{\frac{1}{2}} y, \psi(x, y) = \left(\frac{av_f}{(1-ct)}\right)^{\frac{1}{2}} xf(\eta), \theta(\eta) = \frac{T-T_\infty}{T_w-T_\infty} \end{aligned} \right\}. \quad (5)$$

we have

$$\left. \begin{aligned} \frac{1}{(1-\phi)^{2.5}} f''' - \phi_1 (f'^2 - ff'' + A(f' + \frac{1}{2}\eta f'')) - Mf' \\ - \frac{\beta}{(1-\phi)^{2.5}} f' - \phi_1 F_r \cdot f'^2 = 0 \end{aligned} \right\}, \quad (6)$$

$$\left. \begin{aligned} \frac{1}{Pr} \frac{\kappa_{nf}}{\kappa_f} \theta'' + \phi_2 (f\theta' - \theta f' - A(\frac{1}{2}\eta\theta' + 2\theta)) + \frac{Ec}{(1-\phi)^{2.5}} f''^2 \\ + \phi_2 MEcf'^2 + \phi_2 Q_0 \theta = 0 \end{aligned} \right\}, \quad (7)$$

where

$$\phi_1 = (1 - \phi + \phi \frac{\rho_s}{\rho_f}), \phi_2 = (1 - \phi + \phi \frac{(\rho C_p)_s}{(\rho C_p)_f}), \quad (8)$$

With

$$\left. \begin{aligned} f(\eta) = f_w, f'(\eta) = 1, \theta(\eta) = 1, \text{ at } \eta = 0, \\ f'(\eta) \rightarrow 0, \theta(\eta) \rightarrow 0, \text{ as } \eta \rightarrow \infty \end{aligned} \right\} \quad (9)$$

here $A(=\frac{c}{a})$ denotes the unsteadiness parameter $M(=\frac{\sigma_f B_0^2}{a\rho_f})$ the magnetic parameter,

$\beta\left(=\frac{\nu_f}{\kappa^* \frac{a}{1-ct}}\right)$ the porosity parameter, $F_r\left(=\frac{C_b x}{\sqrt{\kappa^*}}\right)$ the Forchheimer number, $Pr\left(=\frac{\nu}{\alpha}\right)$ the Prandtl number, $Ec\left(=\frac{x^2 a^2}{(1-ct)^2 C_{pf}(T-T_\infty)}\right)$ the Eckert number, $Br(=Ec Pr)$ the Brinkman number and $Q\left(=\frac{Q_0}{(\rho C_p)_f}\right)$ the heat generation/absorption variable.

Table 2: Thermo physical behaviors of base liquid and different nano particles [38-40]:

Physical properties	H ₂ O	Cu	CuO	Al ₂ O ₃	TiO ₂
$\rho(kgm^{-3})$	997.1	8933	6500	3970	4250
$C_p(J/KgK)$	4179	385	540	765	686.2
$\kappa(WmK)$	0.613	401	18	40	8.9538
$\sigma(S/m)$	5.5×10^{-6}	59.6×10^6	2.7×10^{-8}	35×10^6	2.6×10^6

3: Engineering Quantities

Velocity and temperature gradient is given by

$C_f = \frac{\tau_w}{\rho_f u_w^2}$ with $\tau_w = \mu_{nf} \left(\frac{\partial u}{\partial y} \right) \Big _{y=0}$,	(10)
$Nu = \frac{x q_w}{k_f (T_w - T_\infty)}$ with $q_w = -(k_{nf}) \left(\frac{\partial T}{\partial y} \right) \Big _{y=0}$,	(11)

we have

$C_f Re_x^{-1/2} = \frac{f''(0)}{(1-\phi)^{2.5}}$,	(12)
$Nu_x / Re_x^{-1/2} = -\frac{k_{nf}}{k_f} \theta'(0)$,	(13)

4: Entropy Modeling

Mathematically it is expressed as

$E_G = \frac{k_f}{T_\infty^2} \left[\left(\frac{\partial T}{\partial x} \right)^2 + \left(\frac{\partial T}{\partial y} \right)^2 \right] + \frac{\mu_{nf}}{T_\infty} \left(\frac{\partial u}{\partial y} \right)^2 + \frac{\sigma_{nf} B_0^2}{T_\infty} u^2 + \frac{\mu_{nf}}{T_\infty \kappa^*} u^2$,	(14)
--	------

we get

$N_G(\eta) = \frac{E_G}{E_0} = \frac{\kappa_{nf}}{\kappa_f} \left[\frac{1}{X^2} \theta(\eta)^2 + \text{Re}_L \theta(\eta)^2 \right] + \frac{Br \text{Re}_L}{\Omega(1-\phi)^{2.5}} f''(\eta)^2 + \frac{Br M^2}{\Omega} f'(\eta)^2 + \frac{\beta Br \text{Re}_L}{\Omega(1-\phi)^{2.5}} f'(\eta)^2,$	(15)
--	------

where $E_0 \left(= \frac{\kappa_f (\Delta T)^2}{L^2 T_\infty^2} \right)$ signify the entropy generation rate, $X \left(= \frac{x}{L} \right)$ dimensionless parameter, $N_G \left(= \frac{E_G}{E_0} \right)$ Entropy generation $\text{Re} \left(= \frac{U_w L}{\nu_f} \right)$ the Reynolds number, $Br \left(= \frac{\mu_f U_w^2}{\kappa_f \Delta T} \right)$ the Brinkman number and $\Omega \left(= \frac{\Delta T}{T_\infty} \right)$ temperature difference parameter.

5: Graphical results and analysis

Non-linear system are solved through bvp4c Matlab software. Performance of various flow parameters on velocity field, temperature distribution and entropy rate are discussed. Surface drag force and Nusselt number are graphically examined. Here we studied four different class of nano particles (Cu , CuO , Al_2O_3 and TiO_2). Here our main focus is on copper (Cu) nanoparticles.

5.1: Velocity field

Performance of velocity versus volume friction is revealed in Fig.2 Large volume friction reduces the velocity profile. Large magnetic parameter correspond to improve Lorentz force which augments the resistance to the liquid flow. Therefore velocity is diminished (see Fig.3). Fig.4 elucidates the variation of Forchheimer number on velocity. Velocity is reduced against Forchheimer number. Porosity parameter impact on velocity is illustrated in Fig.5. An increment in porosity variable corresponds to decays velocity field.

Fig. 2: ϕ versus $f'(\eta)$.

Fig. 3: M versus $f'(\eta)$.

Fig. 4: Fr versus $f'(\eta)$.

Fig. 5: β versus $f'(\eta)$.

5.2: Temperature

Physical description of temperature versus volume friction variable (ϕ) is illustrated in Fig 6. An augmentation in temperature is enhanced for volume friction variable. Unsteadiness variable impact on temperature is portrayed in Fig.7. A reduction is

seen in temperature distribution with variation of unsteadiness parameter (A) . Significant effect of (M) on temperature is displayed in Fig.8. An improvement in temperature is noted for magnetic parameter. Physically larger magnetic variable augments the disturbance in liquid particles which improve collision among the liquid particles. Thus temperature is boosted. Fig.9 sketch to see the Brinkman number effect on temperature. Larger Brinkman number enhance the kinetic energy and as a result temperature is augmented.

Fig. 6: ϕ versus $\theta(\eta)$.

Fig. 7: A versus $\theta(\eta)$.

Fig. 8: M versus $\theta(\eta)$.

Fig. 9: Br versus $\theta(\eta)$.

5.3: Entropy optimization

Fig.10 sketch to show the effect of porosity variable on entropy rate. An enhancement in entropy rate is seen for porosity variable (β). Fig.11 exhibit outcome of magnetic variable on entropy optimization. An augmentation in magnetic variable improve Lorentz force, which augments the collision amongst the nano particles. Therefore entropy optimization is boosted. An increment in Brinkman number leads to augments heat generation which is created by fluid friction and as a result entropy rate is boosted (see Fig 12). Influence of Reynold number (Re) on entropy generation is revealed in Fig.13 Higher Reynold number (Re) improve the entropy rate.

Fig. 10: β versus N_G .

Fig. 11: M versus N_G .

Fig. 12: Br versus N_G .

Fig. 13: Re versus N_G .

5.4: Physical quantities

Influence of various sundry variables on surface drag force and heat transfer rate are discussed in Figs. (14-17).

5.4.1: Skin friction coefficient

Fig. 14 sketch to show the variations of skin friction coefficient against A and ϕ . Here clearly noted that velocity gradient has opposite effect for A and ϕ . Skin friction coefficient reduces versus higher magnetic parameter.

Fig. 14: A and ϕ versus C_f .

Fig. 15: M and ϕ versus C_f .

5.4.2: Nusselt number

An increment in magnetic parameter reduces the heat transfer rate (see Fig. 16). Influence of stretching parameter on Nusselt number is revealed in Fig. 17. An enhancement in stretching parameter improve the heat transfer rate.

Fig. 16: M and ϕ versus Nu .

Fig. 17: A and ϕ versus Nu .

6: Conclusions

Key observation of the present flow are given below

- Reduction in velocity field is noticed through magnetic and porosity parameters.
- Higher Forchheimer number and unsteadiness parameters leads to reduce the velocity profile.
- An augmentation in temperature distribution and entropy generation are observed with variation of Brinkman number.
- Larger Magnetic variable corresponds to augments the entropy generation rate and temperature distribution.
- Temperature distribution is reduced with variation of unsteadiness parameter.
- Similar characteristic for entropy generation rate is seen through porosity parameter.
- Magnetic parameter has reducing effect on both velocity gradient and heat transfer rate.
- An opposite effect is observed in temperature gradient and surface drag force for stretching parameter.

Declaration of Competing Interest

None.

References

- 1 S.U.S. Choi, J.A. Eastman, Enhancing thermal conductivity of fluids with nanoparticles, *Mater. Sci.* 231 (1995) 99--105.
- 2 C. T. Nguyen, G. Roy, C. Gauthier and N. Galanis, Heat transfer enhancement using Al_2O_3 --water nanofluid for an electronic liquid cooling system, *Applied Thermal Engineering* 27 (2007), no. 8-9, 1501-1506..
- 3 X. Wang, X. Xu and S. U. Choi, Thermal conductivity of nanoparticle-fluid mixture, *Journal of thermophysics and heat transfer* 13 (1999), no. 4, 474-480.
- 4 J. A. Eastman, S. Choi, S. Li, W. Yu and L. Thompson, Anomalous increased effective thermal conductivities of ethylene glycol-based nanofluids containing copper nanoparticles, *Applied physics letters* 78 (2001), no. 6, 718-720.
- 5 M.Chandrasekar, and S. Suresh, A review on the mechanisms of heat transport in nanofluids, *Heat Transfer Engineering* 30.14 (2009) 1136-1150.
- 6 H. Xie, J. Wang, T. Xi, Y. Liu and F. Ai, Dependence of the thermal conductivity of nanoparticle-fluid mixture on the base fluid, *Journal of Materials Science Letters* 21 (2002), no. 19, 1469-1471.
- 7 S. A. Khan, T. Saeed, M. I. Khan, T. Hayat, M. I. Khan and A. Alsaedi, Entropy optimized cns based darcy-forchheimer nanomaterial flow between two stretchable rotating disks, *International Journal of Hydrogen Energy* 44 (2019), no. 59, 31579-31592.
- 8 H. A. Nabwey and A. Mahdy, Transient flow of micropolar dusty hybrid nanofluid loaded with Fe_3O_4 -Ag nanoparticles through a porous stretching sheet, *Results in Physics*, 103777.
- 9 S.M.S. Murshed, K.C. Leong, C. Yang, Investigations of thermal conductivity And viscosity of nanofluids, *Int. J. Therm. Sci.* 47 (2008) 560-568.
- 10 O. Makinde and A. Aziz, Mhd mixed convection from a vertical plate embedded In a porous medium with a convective boundary condition, *Int. J. Therm. Sci.* no. 9 (2010), 1813--1820.
- 11 A. Sabu, A. Mathew, T. Neethu and K. A. George, Statistical analysis of mhd convective ferro-nanofluid flow through an inclined channel with hall current, heat source and soret effect, *Thermal Science and Engineering Progress* (2020), 100816.
- 12 W. Ibrahim, B. Shankar, M.M. Nandeppanawar MHD stagnation point flow and heat transfer due to Nano fluid towards a stretching sheeting. *J. Heat Mass Transf.*, 56 (1-- 2) (2013), 1-9.
- 13 R. Muhammad, M. I. Khan, N. B. Khan and M. Jameel, Magnetohydrodynamics (mhd) radiated nanomaterial viscous material flow by a curved surface with second order slip and entropy generation, *Computer*

methods and programs in biomedicine 189 (2020), 105294.

- 14 T. Hayat, S. Qayyum, A. Alsaedi and A. Shafiq, Inclined magnetic field and heat source/sink aspects in flow of nanofluid with nonlinear thermal radiation, *International Journal of Heat and Mass Transfer* 103 (2016), 99-107.
- 15 M. Ziaei-Rad, M. Saeedan and E. Afshari, Simulation and prediction of mhd dissipative nanofluid flow on a permeable stretching surface using artificial neural network, *Applied Thermal Engineering* 99 (2016), 373-38
- 16 T. Hayat, S. Ahmad, M. I. Khan and A. Alsaedi, Simulation of ferromagnetic nanomaterial flow of maxwell fluid, *Results in physics* 8 (2018), 34-40.
- 17 F. Gottschalk, R. W. Scholz and B. Nowack, Probabilistic material flow modeling for assessing the environmental exposure to compounds: Methodology and an application to engineered nano-tio₂ particles, *Environmental Modelling & Software* 25 (2010), no. 3, 320-332.
- 18 Y. Wang and B. Nowack, Dynamic probabilistic material flow analysis of nano-sio₂, nano iron oxides, nano-ceo₂, nano-al₂o₃, and quantum dots in seven european regions, *Environmental pollution* 235 (2018), 589-601.
- 19 M. I. Khan, T. Hayat, A. Alsaedi, S. Qayyum and M. Tamoor, Entropy optimization and quartic autocatalysis in mhd chemically reactive stagnation point flow of sisko nanomaterial, *International Journal of Heat and Mass Transfer* 127 (2018), 829-837
- 20 F. U. Rehman, S. Nadeem, H. U. Rehman and R. U. Haq, Thermophysical analysis for three-dimensional mhd stagnation-point flow of nano-material influenced by an exponential stretching surface, *Results in physics* 8 (2018), 316-323.
- 21 M. Turkyilmazoglu Exact analytical solutions for heat and mass transfer of MHD slip flow in Nano fluids. *Chem. Eng. Sci.*, 84 (2012), 182-187.
- 22 Y. Lin, L. Zheng, X. Zhang, L. Ma, G. Chen, MHD pseudo-plastic Nano fluid unsteady flow and heat transfer in a finite thin film over stretching surface with internal heat generation *Int. J. Heat Mass Transfer*, 84 (2015), 903-911.
- 23 L. J. Crane, Flow past a stretching plate, *Zeitschrift für angewandte Mathematik und Physik ZAMP* 21 (1970), no. 4, 645-647.
- 24 G. Rasool, T. Zhang, A. J. Chamkha, A. Shafiq, I. Tlili and G. Shahzadi, Entropy generation and consequences of binary chemical reaction on mhd darcy--forchheimer williamson nanofluid flow over non-linearly stretching surface, *Entropy* 22 (2020), no. 1, 18.
- 25 V. Bianco, O. Manca and S. Nardini, Performance analysis of turbulent convection heat transfer of al₂o₃ water-nanofluid in circular tubes at constant wall temperature, *Energy* 77 (2014), 403-413.
- 26 M. Bhatti, M. Sheikholeslami, A. Shahid, M. Hassan and T. Abbas, Entropy generation on the interaction of nanoparticles over a stretched surface with

thermal radiation, *Colloids and Surfaces A: Physicochemical and Engineering Aspects* 570 (2019), 368-376.

- 27 A. Bejan, A study of entropy generation in fundamental convective heat transfer, (1979).
- 28 O. Mahian, A. Kianifar, C. Kleinstreuer, A.-N. Moh'd A, I. Pop, A. Z. Sahin and S. Wongwises, A review of entropy generation in nanofluid flow, *International Journal of Heat and Mass Transfer* 65 (2013), 514-532.
- 29 A. Sciacovelli, V. Verda and E. Sciubba, Entropy generation analysis as a design tool---a review, *Renewable and Sustainable Energy Reviews* 43 (2015), 1167-1181.
- 30 T. Hayat, M. I. Khan, S. Qayyum and A. Alsaedi, Entropy generation in flow with silver and copper nanoparticles, *Colloids and Surfaces A: Physicochemical and Engineering Aspects* 539 (2018), 335-346.
- 31 M. Rashidi, M. Ali, N. Freidoonimehr and F. Nazari, Parametric analysis and optimization of entropy generation in unsteady mhd flow over a stretching rotating disk using artificial neural network and particle swarm optimization algorithm, *Energy* 55 (2013), 497-510.
- 32 S. Ahmad, M. I. Khan, T. Hayat, M. I. Khan and A. Alsaedi, Entropy generation optimization and unsteady squeezing flow of viscous fluid with five different shapes of nanoparticles, *Colloids and Surfaces A: Physicochemical and Engineering Aspects* 554 (2018), 197-210.
- 33 T. Chinyoka and O. D. Makinde, Analysis of entropy generation rate in an unsteady porous channel flow with navier slip and convective cooling, *Entropy* 15 (2013), no. 6, 2081-2099.
- 34 M. I. Khan, S. Ullah, T. Hayat, M. Waqas, M. I. Khan and A. Alsaedi, Salient aspects of entropy generation optimization in mixed convection nanomaterial flow, *International Journal of Heat and Mass Transfer* 126 (2018), 1337-1346.
- 35 M. H. Abolbashari, N. Freidoonimehr, F. Nazari and M. M. Rashidi, Entropy analysis for an unsteady mhd flow past a stretching permeable surface in nanofluid, *Powder Technology* 267 (2014), 256-267.
- 36 G. Shit, R. Haldar and S. Mandal, Entropy generation on mhd flow and convective heat transfer in a porous medium of exponentially stretching surface saturated by nanofluids, *Advanced Powder Technology* 28 (2017), no. 6, 1519-1530.
- 37 G. Seth, A. Bhattacharyya, R. Kumar and A. Chamkha, Entropy generation in hydromagnetic nanofluid flow over a non-linear stretching sheet with navier's velocity slip and convective heat transfer, *Physics of Fluids* 30 (2018), no. 12, 122003.
- 38 H. F. Oztop and E. Abu-Nada, Numerical study of natural convection in partially Heated rectangular enclosures filled with nanofluids *International*

- journal of heat And fluid flow, vol.5 (2008), pp.1326--1336.
- 39 Q. Z. Xue, Model for thermal conductivity of carbon nanotube-based composites, Physica B: Condensed Matter, 368 (2005), pp. 302-307.
- 40 A. Dogonchi, M. Waqas, S. M. Seyyedi, M. Hashemi-Tilehnoee and D. Ganji, Numerical simulation for thermal radiation and porous medium characteristics in flow of CuO-H₂O nanofluid, Journal of the Brazilian Society of Mechanical Sciences and Engineering 41 (2019) 1-13.

Figures

Figure 1

Please see the Manuscript PDF file for the complete figure caption

Figure 2

Please see the Manuscript PDF file for the complete figure caption

Figure 3

Please see the Manuscript PDF file for the complete figure caption

Figure 4

Please see the Manuscript PDF file for the complete figure caption

Figure 5

Please see the Manuscript PDF file for the complete figure caption

Figure 6

Please see the Manuscript PDF file for the complete figure caption

Figure 7

Please see the Manuscript PDF file for the complete figure caption

Figure 8

Please see the Manuscript PDF file for the complete figure caption

Figure 9

Please see the Manuscript PDF file for the complete figure caption

Figure 10

Please see the Manuscript PDF file for the complete figure caption

Figure 11

Please see the Manuscript PDF file for the complete figure caption

Figure 12

Please see the Manuscript PDF file for the complete figure caption

Figure 13

Please see the Manuscript PDF file for the complete figure caption

Figure 14

Please see the Manuscript PDF file for the complete figure caption

Figure 15

Please see the Manuscript PDF file for the complete figure caption

Figure 16

Please see the Manuscript PDF file for the complete figure caption

Figure 17

Please see the Manuscript PDF file for the complete figure caption