Failure Mechanism and Numerical Simulation of Splitting Failure for Deep High Sidewall Cavern Under High Stress

Fan Li

Shandong University

Qiangyong Zhang (✉ tianwailaike007@gmail.com)

Shandong University

Wen Xiang

Shandong University

Guangyuan Yu

Shandong University

Research Article

Keywords: High sidewall cavern, Geomechanical model test, Splitting failure, Strain gradient

Posted Date: March 11th, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-269014/v1>

License: This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Version of Record: A version of this preprint was published at Geotechnical and Geological Engineering on June 15th, 2021. See the published version at <https://doi.org/10.1007/s10706-021-01891-z>.

Failure mechanism and numerical simulation of splitting failure for deep high sidewall cavern under high stress

Fan Li ^a, Qiangyong Zhang ^{a,*}, Wen Xiang ^b, Guangyuan Yu ^a

^a *Research Center of Geotechnical and Structural Engineering, Shandong University, Jinan, China*

^b *School of Qilu Transportation, Shandong University, Jinan, China*

*Corresponding author: Qiangyong Zhang (email: qiangyongz@sdu.edu.cn)

Abstract: With the increase of the depth of the underground engineering, the phenomenon of splitting failure of the deep rock will appear, which is very different from the shallow cavern. In order to reveal the formation mechanism of splitting damage, mechanical model tests and numerical simulations of splitting damage were carried out respectively. Using the Pubugou Hydropower Station as the engineering background, a three-dimensional (3D) geomechanical model test was conducted relying on a high stress three-dimensional load test system. The splitting damage phenomenon of high sidewall cavern was observed, and the oscillation variations of displacement and stress were measured. Based on strain gradient theory and continuum damage mechanics, an elastic-plastic damage softening model for splitting damage was established. The relationship between rock damage and energy dissipation was analyzed. Based on the strain energy density theory, the splitting damage criterion based on the strain gradient is established. A numerical analysis method for splitting damage was proposed, and a regional disintegration calculation program was developed based on a commercial finite element code. The numerical simulation results are in basic agreement with the 3D geomechanical model test.

Keywords: High sidewall cavern; Geomechanical model test; Splitting failure; Strain gradient

24

25 **1. Introduction**

26 As a renewable energy source, hydropower has received increasing attention in China. Many
27 large hydropower projects are under construction or have been completed. A series of
28 complex discontinuous deformations were detected during the construction of these projects.
29 This phenomenon poses a serious threat to the construction safety and long-term stability of
30 high sidewall cavern. Among them, splitting failure is a special failure mode which is often
31 encountered.

32 The splitting failure of cavern with high sidewall is an engineering failure phenomenon
33 caused by the release of strain energy stored in rock mass due to excavation-induced
34 unloading, which results in the initiation, expansion and penetration of cracks in surrounding
35 rock. The splitting failure of hard rock has been extensively recorded and described by many
36 researchers. Ortlepp et al. (1994, 1997) considered that splitting failure is a form of failure
37 caused by excavation unloading under high geostress conditions. The splitting surface is
38 generally parallel to the direction of maximum tangential stress. As the splitting failure
39 develops, a v-shaped notch will eventually form. Martin et al. (2000) observed a field
40 statistical analysis of 178 pillar failures in Canadian hard-rock mines. The study indicates that
41 when the width-to-height ratio of hard rock pillars is less than 2.5, the dominant failure mode
42 is progressive slabbing and spalling which eventually leads to an hour-glass shape. Hibino
43 (2001) and Yoshida et al. (2004) conducted on-site observations on 16 high sidewall caverns
44 of the Japanese power system. Monitoring results show that the opening deformation of
45 splitting cracks in the cavern accounted for a considerable part of the total deformation of the
46 surrounding rock.

47 The damage mechanics method has good applicability to simulate the stiffness

degradation and strain softening characteristics of rock materials, and can simulate the nonlinear behavior of rock materials after the peak more comprehensively to be widely used in investigating the failure responses of rock caverns. Li et al. (2013) applied elastic damage mechanics to model the softening behavior of rock masses. Then they proposed a numerical method based on the maximum tensile stress criterion and strain energy density theory to simulate the zonal fracture phenomenon. Tao et al. (2013) applied a damage formulation to simulate softening and modulus reduction to propose a new method to understand the mechanisms and behaviors of high initial stress rocks. Jia et al. (2012) studied the damage evolution around deep underground openings under multiaxial stress through 3D numerical tests. The results show that biaxial stress parallel to the free surface constrained by zero or low confinement stress contributes to spalling or parallel fracture of the slab.

According to the classical continuum theory, the stress at a point of the material is only a function of the strain and deformation history at that point, independent of the strain in the region of the adjacent zone. However, the classical continuum theory is not strictly satisfied due to the imperfect nature of the rock material. The strain gradient effect does not control the deformation and strength of geotechnical materials in their elastic phase, but when the material reaches its peak strength, the strain gradient becomes large to become the cause of strain localization initiation and development. In recent years, the strain gradient theory that introduces internal length parameters of materials has gradually been developed as a non-local theory. Strain gradient theory can be used to describe the local and post-peak strain softening of rock (Steinmann, 1994; Zbib and Aifantis, 1988a and 1988b). The local strain in the rock is usually accompanied by strain softening. It is precisely because the influence of strain gradient is ignored that the previous numerical analysis methods are difficult to explain the problems of splitting failure (Zhang et al., 2017). Based on the strain gradient theory and plastic deformation theory, Gao et al. (2019) established the elastic-plastic damage softening

model and elaborated the formation mechanism and development law of ZDP.

With its advantages of visualization, intuition and realism, the geomechanical model test is of great significance to the study of damage mechanism of underground caverns (Chen et al. 2013a, 2013b and 2013c; Zhang et al. 2013 and 2017; Gao et al. 2018). The method can also simulate excavation and unloading under real three-dimensional high ground stress conditions, reproduce the damage pattern of the cavern, and capture the variations in deformation and stress (Zhang et al., 2019a, 2019b).

Although great progress has been made in studying the microscopic mechanisms of rock specimens (Tang et al., 2001; Liu et al., 2002; Fang et al., 2002; Sahouryeh et al., 2002; Dyskin et al., 2003), laboratory or field experiments (Bauch et al., 2004; Wong et al., 2004; Li et al., 2011; Jiang et al., 2017; Liu et al., 2017; Gong et al., 2012; Gong et al., 2018) and numerical simulations (Zhu et al., 2010; Wang et al., 2016; Sharif et al., 2019; Wowk et al., 2019), so far there is no widely accepted theoretical explanation for splitting failure, and further improvement of theoretical methods is still needed. In this paper, the 3D geomechanical model test of splitting failure is firstly introduced, and the variations of displacement and stress around the high sidewall cavern are given. Based on the strain gradient theory and continuous damage theory, an elastic-plastic damage model for splitting failure is established. According to the strain energy density theory, the energy damage criterion for splitting failure is proposed. In order to consider the strain gradient effect in the numerical simulation, a high-order hexahedral cell is constructed using Hermite interpolation function, and the shape function and stiffness matrix of the cell are derived. The numerical analysis method of regional rupture was proposed, and the corresponding calculation program was developed based on the ABAQUS platform. The results of numerical simulations and model tests are in general agreement. The reliability of the damage softening model and the numerical analysis method of regional rupture are proved. Finally, on the basis of theoretical

analysis and numerical simulation, the formation mechanism of deep high sidewall cavern splitting failure is described.

2. Three dimensional geomechanical model test

2.1 The scheme of the geo-mechanical model

We take the main powerhouse project of the Pubugou Hydropower Station as the engineering background. The underground powerhouse cavern is located in the granite rock mass on the left bank downstream of the dam axis. The overlying rock thickness is 360 m, and cross-section size of the main powerhouse is 26.8 m×70.1 m. According to the similarity principle (Zhang et al. (2019c)) and considering the scale of the main powerhouse and the size of the test system (0.7 m × 0.7 m × 0.7 m), the geometrical similarity of the model test is selected as $C_L=C_P/C_M=300$. The extent and in-situ stress simulated by the model test are shown in Fig. 1.

We chose IBSCM (iron-barites-silica cementation material) as the analogous material (Zhang et al. (2019)). The physical and mechanical parameters of the granite and the analogous material and its mixture proportion are provided in Tables 1 and 2, respectively. Fig. 2a shows the three typical monitoring sections to accurately reflect the deformation and stress changes of surrounding rock during the testing, in which section I and III are stress monitoring sections, and section II is deformation monitoring section. As shown in Fig. 2b, five measuring lines are arranged for each monitoring section, and each measuring line is arranged with six measuring points. Due to the size of the model, in the vertical measurement Line C is arranged five measuring points.

2.2 Construction, excavation and overloading of the geo-mechanical model

To ensure the integrity and homogeneity of the surrounding rock, the geomechanical

model is paved, compacted and air-dried layer by layer. (Zhang et al. 2017). The body of the model is divided into 10 layers of 70 mm each. When the design elevation is reached, the grooves are cut and the measuring sensors are buried. To avoid delamination at the adjacent interfaces of the model, the surface of the previous layer of material must be chiselled rough and moistened with alcohol before the next layer is constructed.

Boundary loads were applied to the model using a 3D loading system (Figure 3). The model body was loaded in increments of 0.1 times the original ground stress until the design value was reached. After the design stress was reached, the load was held constant for 24 h to produce an initial stress field in the model that was consistent with the original stress field. Due to the limitations of the cavern dimensions, the nine excavation levels were combined into three layers in the actual project, as shown in Fig. 4. Each layer was excavated in 17 steps, each with an excavation length of 40 mm (equivalent to 12 m in the prototype). When the excavation of one footage was completed, the excavation was paused and the data was observed. When the data monitored by the sensors is stable, the next step of excavation is started until the entire excavation is completed. Once the cave excavation is complete, the load is held constant until the monitored data is stable and then recorded.

2.3 Model test results

As shown in Fig. 5, the wall of high sidewall cavern is seriously damaged. There are significant longitudinal splitting cracks on both sides of the model cavern, but no obvious damage to the vault. This is a typical damage of splitting failure in high sidewall cavern. The length of the cracks near the high sidewalls is slightly less than the height of the sidewalls. The farther away from the sidewall, the shorter the cracks are. The distance from the outermost crack to the sidewall is about 20.8 m, which is consistent with the measured data at the project site.

In this section, all the model test results have been converted to the prototype according to the principles of similitude. After excavation, the deformation of the cavern perimeter all developed toward the cavern (Fig. 6). The displacement of the nearest measurement point is relatively large, indicating that the area close to the cavern wall is a fractured area of the surrounding rock in the traditional sense, which is consistent with the damage of the surrounding rock observed in the test. The displacement of the measurement point farthest from the cavern sidewall is much smaller than that of other measurement points on the line, indicating that the excavation disturbance in the high sidewall cavern at $3L$ from the cavern has almost no effect. The displacements at the sidewalls show oscillatory attenuation, which is completely different from the variation of displacements around the shallow cavern. The displacements at the vaults all show a monotonic decay trend, which is completely different from that at the sidewalls.

After excavation, due to the stress release around the high sidewall cavern chamber, the deformation was all toward the cavern, and the radial stress around the cavern decreased (Fig. 7). With the increase of the distance from the side wall of the cavern, the damage of the surrounding rock decreases. The change in radial stress is consistent with the radial displacement. The tangential stress variation shown in Fig. 8 is relatively different from the displacement and radial stress variation. The tangential stresses here are close to zero due to severe damage near the high sidewalls resulting in stress relief. Then the tangential stress increases gradually with distance until it reaches a maximum at L . Since the maximum tangential stress shifts from the periphery of the cavern wall to the junction of the elastic-plastic zone when the surrounding rock enters the plastic state. It means that the surrounding rock in the range of L is in a plastic state. The surrounding rock in the range of L to $3L$ is in the elastic state, and the fluctuation of oscillatory attenuation is small, and the variation between two adjacent points is about 15%.

170 3. Establishment of constitutive model

171 3.1 Virtual working principle and control equation

172 In Toupin-Mindlin strain gradient theory, in order to describe the state of a material, in
 173 addition to Euler strain tensor ε_{ij} and Cauchy stress tensor σ_{ij} , strain gradient term η_{ijk}
 174 and the higher order stress tensor τ_{ijk} are also needed (Zhang et al., 2017). The expressions
 175 of Euler strain and strain gradient are as follows:

$$176 \quad \varepsilon_{ij} = (u_{i,j} + u_{j,i}) / 2, \quad \eta_{ijk} = (u_{k,ij} + u_{k,ji}) / 2 \quad (1)$$

177 In the above equation, both the Eulerian strain ε_{ij} and the strain gradient η_{ijk} are
 178 symmetric tensors, as are the corresponding Cauchy stress σ_{ij} and higher order stress τ_{ijk} . It
 179 is further assumed that the strain rate and strain gradient rate can be decomposed into elastic
 180 part and plastic part respectively:

$$181 \quad \dot{\varepsilon}_{kl} = \dot{\varepsilon}_{kl}^e + \dot{\varepsilon}_{kl}^p, \quad \dot{\eta}_{lmn} = \dot{\eta}_{lmn}^e + \dot{\eta}_{lmn}^p \quad (2)$$

182 Similar to the strain gradient plasticity model proposed by previous scholars (Mentzel
 183 and Steinmann, 2000; Fleck and Hutchinson, 2001; Gurtin 2000, 2002, 2003; Gudmundson,
 184 2004), it is assumed that the plastic strain gradient contributes to the work per unit volume.
 185 Therefore, the principle of virtual work should include the work contribution of elastic strain
 186 and the work done by plastic strain and its gradient. The virtual work δW_i of internal unit
 187 volume V can be expressed as:

$$188 \quad \delta W_i = \int_V (\sigma_{ij} \delta \varepsilon_{ij}^e + q_{ij} \delta \varepsilon_{ij}^p + \tau_{ijk} \delta \varepsilon_{ij,k}^p) dV \quad (3)$$

189 where q_{ij} is called the micro-stress tensor, which is conjugate to the work of plastic
 190 strain ε_{ij}^p ; τ_{ijk} denotes the higher-order stress tensor, which is conjugate to the work of the
 191 plastic strain gradient $\varepsilon_{ij,k}^p$. It should be noted that only the deviatoric parts of q_{ij} and τ_{ijk}

192 contributes to the virtual work δW_i . Therefore, q_{ij} and τ_{ijk} in this paper are the omission of
 193 q'_{ij} and τ'_{ijk} respectively. The Eq. (3) can be expressed as follows:

$$194 \quad \delta W_i = \int_V \left(\sigma_{ij} \delta \varepsilon_{ij} + (q_{ij} - \sigma'_{ij}) \delta \varepsilon_{ij}^p + \tau_{ijk} \delta \varepsilon_{ij,k}^p \right) dV \quad (4)$$

195 Then the following formula can be obtained by applying Gauss' theorem:

$$196 \quad \delta W_i = \int_S \left(\sigma_{ij} n_j \delta u_i + \tau_{ijk} n_k \delta \varepsilon_{ij}^p \right) dS - \int_V \left[\sigma_{ij,j} \delta u_i + (\tau_{ijk,k} + \sigma'_{ij} - q_{ij}) \delta \varepsilon_{ij}^p \right] dV \quad (5)$$

197 where n_i is the normal vector outward in the direction of the surface S . Eq. (3) should
 198 be valid for any change in displacement and plastic strain. The first integral on the right side
 199 of Eq. (5) can be identified as external virtual work. The second integral on the right side of
 200 Eq. (5) should be vanished with arbitrary variations, so two sets of equilibrium equation can
 201 be determined:

$$202 \quad \begin{cases} \sigma_{ij,j} = 0 \\ \tau_{ijk,k} + \sigma'_{ij} - q_{ij} = 0 \end{cases} \quad (6)$$

203 Then, the corresponding conventional $T_i = \sigma_{ij} n_j$ and higher order $t_{ij} = \tau_{ijk} n_k$ boundary
 204 conditions can be obtained according to the principle of virtual work.

205 3.2 Constitutive equation

206 In a thermodynamically consistent manner, the dissipative work generated by
 207 higher-order strains is introduced by employing higher-order stress related to strain
 208 increments (Gudmundson, 2004; Gurtin and Anand, 2005). The key step in constructing such
 209 a constitutive equation is to define the effective stress Σ work conjugated with the
 210 gradient-enhanced effective plastic strain rate $\dot{\mathcal{E}}^p$ to ensure the plastic work rate:

$$211 \quad \Sigma \dot{\mathcal{E}}^p = q_{ij}^D \dot{\mathcal{E}}_{ij}^p + \tau_{ijk}^D \dot{\mathcal{E}}_{ij,k}^p \quad (7)$$

212 Since the effective stress work $\Sigma \dot{\mathcal{E}}^p$ is always positive, the effective plastic strain rate

213 can be defined as:

$$214 \quad \underline{\underline{E}}^e = \sqrt{\frac{2}{3} \underline{\underline{\varepsilon}}_{ij}^e \underline{\underline{\varepsilon}}_{ij}^e + L^2 \underline{\underline{\varepsilon}}_{ij,k}^e \underline{\underline{\varepsilon}}_{ij,k}^e} \quad (8)$$

215 where L is the dissipative length scale. Thus, the effective stress can be defined as:

$$216 \quad \Sigma = \sqrt{\frac{2}{3} q_{ij}^D q_{ij}^D + L^{-2} \tau_{ijk}^D \tau_{ijk}^D} \quad (9)$$

217 Then the dissipative plastic micro-stress tensor and dissipative plastic high-order stress
218 tensor can be easily obtained:

$$219 \quad q_{ij}^D = \frac{2}{3} \frac{\Sigma}{\underline{\underline{E}}^e} \underline{\underline{\varepsilon}}_{ij}^e, \quad \tau_{ijk}^D = \frac{\Sigma}{\underline{\underline{E}}^e} L^2 \underline{\underline{\varepsilon}}_{ij,k}^e \quad (10)$$

220 According to the first law of thermodynamics, when there is damage present in the
221 material, the Helmholtz free energy function is defined with the dissipative potential function
222 as:

$$223 \quad W = \Psi - \Phi = \frac{1}{2} (\varepsilon_{ij} - \varepsilon_{ij}^p) C_{ijkl}^{ed} (\varepsilon_{kl} - \varepsilon_{kl}^p) + \frac{1}{2} \eta_{ijk}^e A_{ijklmn} \eta_{lmn}^e + \frac{1}{2} \varepsilon_{ij}^p C_{ijkl}^{pd} \varepsilon_{kl}^p + \frac{1}{2} G l^2 \eta_{ijk}^p \eta_{ijk}^p \quad (11)$$

$$- \sqrt{\frac{2}{3} \underline{\underline{\varepsilon}}_{ij}^p \underline{\underline{\varepsilon}}_{ij}^p + L^2 \underline{\underline{\varepsilon}}_{ij,k}^p \underline{\underline{\varepsilon}}_{ij,k}^p} \sqrt{\frac{2}{3} q_{ij}^D q_{ij}^D + L^{-2} \tau_{ijk}^D \tau_{ijk}^D}$$

224 where C_{ijkl}^{ed} is elastic damage tensor and is a fourth-order tensor, $C_{ijkl}^{ed} = (1-d) C_{ijkl}^e$;

225 A_{ijklmn} is elastic damage tensor considering strain gradients and is a six-order tensor,

226 $A_{ijklmn} = (1-d) l^2 C_{ijlm}^e \delta_{kn}$; C_{ijkl}^{pd} is plastic damage tensor and is a fourth-order tensor,

227 $C_{ijkl}^{pd} = (1-D + \delta_{ij} D / 3) C_{ijkl}^p$; G is the shear modulus, $G = (1-d) E / [2(1+\nu)]$; l is the

228 internal length parameter of the material, which is closely related to the microcracks and

229 microdefects inside the material and is an inherent property of the material; δ_{kn} is a

230 Kronecker symbol. In the above parameters, D is the modified damage variable, $D = \delta d$,

231 δ is the damage variable correction parameter or initial damage number; d is the damage

variable. In this paper, the damage evolution law is selected to describe the mechanical properties of rock under high in-suit stress. It is considered that there is no damage in the material of elastic state, and damage begins to appear in the plastic state when the rock yield. The expression of damage evolution equation is as follows:

$$d = 1 - \frac{\kappa_i}{\kappa} \left[(1 - \alpha) + \alpha e^{-\beta(\kappa - \kappa_i)} \right] \quad (12)$$

where κ_i indicates the threshold for damage initiation; α and β are material parameters. The C_{ijlm}^e described above is the elastic tensor of an isotropic body, and its matrix expression is:

$$C_{ijlm}^e = \begin{bmatrix} \frac{E(1-\nu)}{(1+\nu)(1-2\nu)} & \frac{E\nu}{(1+\nu)(1-2\nu)} & \frac{E\nu}{(1+\nu)(1-2\nu)} & 0 & 0 & 0 \\ \frac{E\nu}{(1+\nu)(1-2\nu)} & \frac{E(1-\nu)}{(1+\nu)(1-2\nu)} & \frac{E\nu}{(1+\nu)(1-2\nu)} & 0 & 0 & 0 \\ \frac{E\nu}{(1+\nu)(1-2\nu)} & \frac{E\nu}{(1+\nu)(1-2\nu)} & \frac{E(1-\nu)}{(1+\nu)(1-2\nu)} & 0 & 0 & 0 \\ 0 & 0 & 0 & \frac{E}{2(1+\nu)} & 0 & 0 \\ 0 & 0 & 0 & 0 & \frac{E}{2(1+\nu)} & 0 \\ 0 & 0 & 0 & 0 & 0 & \frac{E}{2(1+\nu)} \end{bmatrix} \quad (13)$$

According to the incremental theory in the classical elastoplastic theory, the plastic tensor $\mathbf{C}^p$ can take the following form:

$$\mathbf{C}^p = \frac{\mathbf{C}^e \frac{\partial g}{\partial \boldsymbol{\sigma}} \left(\frac{\partial f}{\partial \boldsymbol{\sigma}} \right)^T \mathbf{C}^e}{\left(\frac{\partial f}{\partial \boldsymbol{\sigma}} \right)^T \mathbf{C}^e \frac{\partial g}{\partial \boldsymbol{\sigma}} - \frac{\partial f}{\partial H} \left(\frac{\partial H}{\partial \boldsymbol{\epsilon}^p} \right)^T \frac{\partial g}{\partial \boldsymbol{\sigma}}} \quad (14)$$

where H is the hardening function, which is a function of plastic strain. In order to reflect the characteristics of plastic hardening and plastic softening of rock materials (Fig. 9), its expression form takes the following exponential form:

$$H = H(\varepsilon_{ij}^p) = k_1 \varepsilon_{ij}^p \exp(k_2 I_1 - k_3 \varepsilon_{ij}^p) \quad (15)$$

where k_i ($i=1,2,3$) is the material parameter; I_1 is the first stress invariant, which can represent the average stress or hydrostatic stress. The f and g in Eq. (14) are the yield function and the plastic potential function, respectively. Considering the influence of the intermediate principal stress, the yield function f and plastic potential function g constructed based on the Drucker-Prager strength criterion are as follows:

$$\begin{cases} f = f(\sigma, H) = \alpha I_1(\sigma) + \sqrt{J_2(s)} - (1-d)H(\varepsilon_{ij}^p) \\ g = g(\sigma, H) = \beta I_1(\sigma) + \sqrt{J_2(s)} - (1-d)H(\varepsilon_{ij}^p) \end{cases} \quad (16)$$

where J_2 is the second invariant of stress deviation; α and β are intensity parameters, and their expressions are as follows:

$$\begin{cases} \alpha = \frac{2 \sin \varphi}{\sqrt{3}(3 - 2 \sin \varphi)} \\ \alpha = \frac{2 \sin \psi}{\sqrt{3}(3 - 2 \sin \psi)} \end{cases} \quad (17)$$

where φ and ψ represent the friction angle and expansion angle of the rock, respectively. When $\varphi = \psi$, that is, $\alpha = \beta$, it is the associated flow law.

According to the second law of thermodynamics, the stress tensor and higher-order stress tensor can be derived from the free energy function strain and strain gradient respectively:

$$\sigma_{ij} = \begin{cases} C_{ijkl}^e \varepsilon_{kl}^e \\ (1-D + \delta_{ij} D/3) C_{ijkl}^p \varepsilon_{kl}^p - \frac{2}{3} \frac{\Sigma}{E^p} \varepsilon_{kl}^p \end{cases} \quad (18)$$

$$\tau_{ijk} = \begin{cases} l^2 C_{ijkl}^e \delta_{mn} n_{lmn} \\ \frac{(1-D) C_{ijkl}^p}{2(1+\nu)} l^2 n_{ijk}^p - \frac{\Sigma}{E^p} l^2 \varepsilon_{kl}^p \end{cases} \quad (19)$$

4. Energy damage failure criterion

4.1 Rock destruction and energy dissipation

The deformation damage of rocks is essentially a damage evolution process of energy dissipation, so it will be easier to reflect the characteristics of the mechanical response of rocks by studying the relationship between the energy change law and rock damage during the damage process. The damage of rocks is a process of progressive deterioration of materials due to the gradual increase of damage, and microscopic cracks are generated and expanded until penetration. Therefore, the study of rock rupture from the perspective of microscopic mechanics, the analysis of the damage law of tiny units of rocks, and the study of unit damage through the unit energy dissipation and energy discrimination criteria can show the whole process of rock rupture in a more systematic and complete way.

Rocks exhibit significant post-peak strain softening under high stress conditions, but a criterion for determining whether damage has occurred in rocks needs to be given. Based on the damage characteristics of the material and the different loading conditions, many different damage criteria have been proposed, which can generally be divided into four main categories: stress or strain-based damage criteria, energy-based damage criteria, damage-based damage criteria and empirical damage criteria. In essence, the deformation and damage of rocks is a process of continuous energy dissipation, therefore, if the energy change in the process of rock damage can be studied in depth, the strength criterion based on the energy change will be able to describe the process and mechanism of rock damage more accurately.

4.2 Element failure criterion

In order to obtain the distribution of failure zone in the surrounding rock, it is necessary to give a criterion to determine the failure of element. In the numerical simulation, two criteria are used to determine the failure of elements: maximum tensile strain criterion and energy damage failure criterion. The maximum tensile strain of the unit is calculated

288 according to Eq. (20). If the maximum tensile strain $\varepsilon_{\max}$ is greater than or equal to the
 289 ultimate tensile strain ε_{tu} , the element is subjected to tensile failure. In order to maintain the
 290 integrity and continuity of the entire calculation during the numerical simulation, a small
 291 residual elastic modulus E_c ($E_c = 0.05E$, E is elastic modulus) is applied to the rock mass
 292 element where the tensile failure occurs.

$$293 \quad \varepsilon_{\max} = \frac{2}{\sqrt{3}} \sqrt{|J_2'|} \cos\left(\omega - \frac{\pi}{3}\right) + \frac{I_1'}{3} \quad (20)$$

294 where

$$295 \quad \omega = \frac{1}{3} \arccos\left(-\frac{3\sqrt{3}}{2} \frac{J_3'}{|J_2'| \sqrt{|J_2'|}}\right) \quad (21)$$

$$296 \quad \begin{cases} I_1' = \varepsilon_x + \varepsilon_y + \varepsilon_z \\ J_2' = -(e_1 e_2 + e_2 e_3 + e_1 e_3) \\ J_3' = e_1 e_2 e_3 \end{cases} \quad (22)$$

$$297 \quad \begin{cases} e_1 = \frac{2}{3} \varepsilon_x - \frac{1}{3} (\varepsilon_y + \varepsilon_z) \\ e_2 = \frac{2}{3} \varepsilon_y - \frac{1}{3} (\varepsilon_x + \varepsilon_z) \\ e_3 = \frac{2}{3} \varepsilon_z - \frac{1}{3} (\varepsilon_x + \varepsilon_y) \end{cases} \quad (23)$$

298 where ε_x , ε_y and ε_z are strains in X, Y and Z directions respectively.

299 If the maximum tensile strain of the element is lower than the ultimate tensile strain
 300 ($\varepsilon_{\max} < \varepsilon_{tu}$), the unit will not undergo tensile failure. In this case, the energy damage failure
 301 criterion based on strain gradient is adopted as the criterion of element failure. Considering
 302 the influence of the strain gradient term, the formula for calculating the strain energy density
 303 of the element is proposed as follows:

$$304 \quad \frac{dW}{dV} = \int_0^{\varepsilon_{ij}} \sigma_{ij} d\varepsilon_{ij} + \frac{1}{8} G l^2 (4\eta_{ijj} \eta_{ikk} + 4\eta_{iik} \eta_{kjj} + 4\eta_{iik} \eta_{jjk} + 7\eta_{ijk} \eta_{ijk} + 2\eta_{ijk} \eta_{kji}) \quad (24)$$

305 The calculation formulas of elastic strain energy density $(dW/dV)_s$, critical strain
 306 energy density $(dW/dV)_c$ and ultimate strain energy density $(dW/dV)_u$ are as follows:

$$307 \quad \begin{cases} (dW/dV)_s = \int_0^{\varepsilon_s} \sigma_{ij} d\varepsilon_{ij} \\ (dW/dV)_c = \int_0^{\varepsilon_o} \sigma_{ij} d\varepsilon_{ij} \\ (dW/dV)_u = \int_0^{\varepsilon_u} \sigma_{ij} d\varepsilon_{ij} \end{cases} \quad (25)$$

308 The energy damage failure criterion is determined by the change in strain energy
 309 density (dW/dV) . When $(dW/dV) < (dW/dV)_s = \int_0^{\varepsilon_s} \sigma_{ij} d\varepsilon_{ij}$ (ε_s is the yield strain in the
 310 process of loading), the material is in the linear elastic phase and no damage occurs inside the
 311 element. When $(dW/dV) \geq (dW/dV)_s = \int_0^{\varepsilon_s} \sigma_{ij} d\varepsilon_{ij}$, the material enters into plastic damage,
 312 indicated by the damage variable d , and micro-cracks appear and begin to expand. When
 313 $(dW/dV) \geq (dW/dV)_c = \int_0^{\varepsilon_o} \sigma_{ij} d\varepsilon_{ij}$ (ε_o is the residual strain in the process of loading), the
 314 microcracks in the material develop into macroscopic cracks, and the rock mass enters the
 315 residual stage, and there is still bearing capacity. When $(dW/dV) \geq (dW/dV)_u = \int_0^{\varepsilon_u} \sigma_{ij} d\varepsilon_{ij}$
 316 (ε_u is the ultimate strain in the process of loading), the unit is destroyed and can no longer
 317 bear the load. As with the tensile failure, residual elastic modulus E_s is imparted to the failure
 318 element to maintain the integrity and continuity of the overall calculation.

319 5. Establishment of numerical analysis methods

320 5.1 Development of the simulation program

321 We develop a program based on the finite element method to simulate splitting failure
 322 and zonal disintegration in the surrounding rock of cavern with high sidewall under high
 323 stress. The program is developed based on the elastic damage softening model and the energy

damage failure criterion which are established from the strain gradient theory and the continuous damage mechanics. In this section, we provide an introduction to the simulation program and compare the simulation results with those obtained from the geo-mechanical model test.

In numerical simulations based on elastic damage softening models, the effect of strain gradients must be taken into account. However, in general finite element analysis, the cell shape function has only first-order continuity and the second-order derivative of the displacement within the cell has a value of zero after interpolation. This cell analysis does not reflect the effects of strain gradients. Therefore, it is necessary to construct elements with higher order continuity, i.e. elements with C^1 -order continuity, and to require that the nodal displacements and their first-order derivatives maintain continuity. High-order hexahedral cells were constructed using Hermite interpolation functions, and the shape functions and stiffness matrices of the cells were derived (Zhang (2015)). This provides a technical basis for considering strain gradient effects in numerical simulations. The simulation program was developed using the finite element software ABAQUS as a platform.

In the elastic-plastic damage softening model, the total strain at any point is decomposes into the Eulerian strain ε_{ij} and the higher order strain η_{ijk} , which correspond to the Cauchy stress σ_{ij} and the higher order stress τ_{ijk} , respectively. In general, the Cauchy stress σ_{ij} and Eulerian strain ε_{ij} each have 6 independent components, while the higher order stress τ_{ijk} and higher order strain η_{ijk} each have 18 independent components, after taking symmetry into account in the 3D condition.

The relationship between Cauchy stress and Eulerian strain is given by:

$$\boldsymbol{\sigma} = \mathbf{C}\boldsymbol{\varepsilon} \quad (26)$$

where

$$\boldsymbol{\sigma} = (\sigma_{xx} \quad \sigma_{yy} \quad \sigma_{zz} \quad \sigma_{xy} \quad \sigma_{xz} \quad \sigma_{yz})^T \quad (27)$$

$$\boldsymbol{\varepsilon} = (\varepsilon_{xx} \quad \varepsilon_{yy} \quad \varepsilon_{zz} \quad \gamma_{xy} \quad \gamma_{xz} \quad \gamma_{yz})^T \quad (28)$$

where $\mathbf{C}$ is a 6 x 6 matrix divided into an elastic matrix $\mathbf{C}^e$ (Eq. (13)) and a plastic matrix $\mathbf{C}^{pd} = (1 - D + \delta_{ij} D / 3) \mathbf{C}^p - \frac{2}{3} \frac{\Sigma}{E^p}$.

The relationship between higher order stress and higher order strain in the elastic state is given by:

$$\boldsymbol{\tau} = \boldsymbol{\Lambda} \boldsymbol{\eta} \quad (29)$$

where

$$\boldsymbol{\tau} = (\tau_{xxx} \quad \tau_{yyx} \quad \tau_{zzx} \quad \tau_{xyx} \quad \tau_{yzx} \quad \tau_{xzx} \quad \tau_{xxy} \quad \tau_{yyy} \quad \tau_{zzy} \quad \tau_{xyy} \quad \tau_{yyz} \quad \tau_{xzy} \quad \tau_{xxz} \quad \tau_{yyz} \quad \tau_{zzz} \quad \tau_{xyz} \quad \tau_{yzz} \quad \tau_{xzz})^T \quad (30)$$

$$\boldsymbol{\eta} = (\eta_{xxx} \quad \eta_{yyx} \quad \eta_{zzx} \quad \eta_{xyx} \quad \eta_{yzx} \quad \eta_{xzx} \quad \eta_{xxy} \quad \eta_{yyy} \quad \eta_{zzy} \quad \eta_{xyy} \quad \eta_{yyz} \quad \eta_{xzy} \quad \eta_{xxz} \quad \eta_{yyz} \quad \eta_{zzz} \quad \eta_{xyz} \quad \eta_{yzz} \quad \eta_{xzz})^T \quad (31)$$

where $\boldsymbol{\Lambda}$ is an 18 x 18 matrix, $\boldsymbol{\Lambda} = l^2 \begin{bmatrix} D_1 & D_2 \\ D_3 & D_4 \end{bmatrix}$. Wherein D_1, D_2, D_3, D_4 as follows:

$$D_1 = \begin{bmatrix} 2\xi_1 + 4\xi_2 + \xi_3 + \xi_4 + 2\xi_5 & 2\xi_2 + \xi_3 & 2\xi_2 + \xi_3 & 0 & 0 & 0 & 0 & 0 & 0 \\ 2\xi_2 + \xi_3 & \xi_3 + \xi_4 & \xi_3 & 0 & 0 & 0 & 0 & 0 & 0 \\ 2\xi_2 + \xi_3 & \xi_3 & \xi_3 + \xi_4 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & \xi_1 + \xi_4 + \xi_5 & 0 & 0 & \xi_2 + \xi_5 & \xi_1 + \xi_2 & \xi_2 \\ 0 & 0 & 0 & 0 & \xi_4 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & \xi_1 + \xi_4 + \xi_5 & 0 & 0 & 0 \\ 0 & 0 & 0 & 2\xi_2 + 2\xi_5 & 0 & 0 & \xi_3 + \xi_4 & 2\xi_2 + \xi_3 & \xi_3 \\ 0 & 0 & 0 & 2\xi_1 + 2\xi_2 & 0 & 0 & 2\xi_2 + \xi_3 & 2\xi_1 + 4\xi_2 + \xi_3 + \xi_4 + 2\xi_5 & 2\xi_2 + \xi_3 \\ 0 & 0 & 0 & 2\xi_2 & 0 & 0 & \xi_3 & 2\xi_2 + \xi_3 & \xi_3 + \xi_4 \end{bmatrix} \quad (32)$$

$$D_2 = \begin{bmatrix} 2\xi_1 + 2\xi_2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 2\xi_1 + 2\xi_2 \\ 2\xi_2 + 2\xi_5 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 2\xi_2 \\ 2\xi_2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 2\xi_2 + 2\xi_5 \\ 0 & 0 & \xi_5 & 0 & 0 & 0 & \xi_5 & 0 & 0 \\ 0 & 0 & 0 & \xi_3 & 0 & 2\xi_2 & 0 & 0 & 0 \\ 0 & \xi_1 & 0 & \xi_2 + \xi_5 & \xi_2 & \xi_1 + \xi_2 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 2\xi_2 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 2\xi_1 + 2\xi_2 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 2\xi_2 + 2\xi_5 & 0 \end{bmatrix} \quad (33)$$

$$D_3 = \begin{bmatrix} \xi_1 + \xi_2 & \xi_2 + \xi_5 & \xi_2 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & \xi_1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & \xi_5 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 2\xi_2 + 2\xi_5 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 2\xi_2 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 2\xi_1 + 2\xi_2 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & \xi_5 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & \xi_1 & 0 & 0 & \xi_2 & \xi_1 + \xi_2 & \xi_2 + \xi_5 \\ \xi_1 + \xi_2 & \xi_2 & \xi_2 + \xi_5 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \quad (34)$$

$$D_4 = \begin{bmatrix} \xi_1 + \xi_4 + \xi_5 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \xi_1 \\ 0 & \xi_1 + \xi_4 + \xi_5 & 0 & \xi_2 & \xi_2 + \xi_5 & \xi_1 + \xi_2 & 0 & 0 & 0 \\ 0 & 0 & \xi_4 & 0 & 0 & 0 & \xi_5 & 0 & 0 \\ 0 & 2\xi_2 & 0 & \xi_3 + \xi_4 & \xi_3 & 2\xi_2 + \xi_3 & 0 & 0 & 0 \\ 0 & 2\xi_2 + \xi_5 & 0 & \xi_3 & \xi_3 + \xi_4 & 2\xi_2 + \xi_3 & 0 & 0 & 0 \\ 0 & 2\xi_1 + 2\xi_2 & 0 & 2\xi_2 + \xi_3 & 2\xi_2 + \xi_3 & 2\xi_1 + 4\xi_2 + \xi_3 + \xi_4 + 2\xi_5 & 0 & 0 & 0 \\ 0 & 0 & \xi_5 & 0 & 0 & 0 & \xi_4 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & \xi_1 + \xi_4 + \xi_5 & 0 \\ \xi_1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \xi_1 + \xi_4 + \xi_5 \end{bmatrix} \quad (35)$$

In the above matrix, l is the internal length parameter of the material, ξ_i ($i=1,5$) is the elastic constant associated with the strain gradient. According to previous scholars' research (Mindlin, 1965; Eshel and Rosenfeld, 1975; Yang et al., 2002; Lam et al., 2003), their values are $\xi_1 = \frac{1}{2}G$, $\xi_2 = \frac{1}{4}G$, $\xi_3 = G$, $\xi_4 = \frac{7}{4}G$, $\xi_5 = \frac{1}{4}G$.

The relationship between higher order stress and higher order strain in the plastic phase can be obtained from Eq. (20) as:

$$\tau = \frac{1-D}{2(1+\nu)} \Lambda \eta - \frac{\Sigma}{E^p} l^2 \epsilon^p \quad (36)$$

Fig. 10 shows the simulation program flow chart.

5.2 Setup of numerical model and selection of parameters

The scope of the numerical model is consistent with the scope of the physical model discussed in Section 2. As shown in Fig. 11, the numerical model has a scale of 210 m along X, Y and Z. The 3D computational grid consists of 60000 elements and 67769 nodes. The external loads applied on the numerical model are shown in Fig. 11. According to the laboratory experiments (Zhang et al., 2021), the initial elastic modulus is $E=41.50\text{GPa}$, the Poisson's ratio is $\nu=0.27$, the density rock is $\rho=26.60\text{KNgm}^{-3}$, the compressive strength is $\sigma_c=128.80\text{MPa}$, the tensile strength is $\sigma_t=8.00\text{MPa}$, the Lamé constant is $G=16.34\text{GPa}$, the internal length parameter of the material is $l=0.01\text{m}$. The boundary conditions and cavern construction process in the numerical model are consistent with the physical model.

5.3 Simulation results

The above external loads were applied to the numerical model shown in Fig. 11. After the calculations are balanced, the displacements and strains at each node in the model are set to zero, thus establishing the initial ground stress field of the model. The cavern was excavated to obtain the displacement, strain and stress fields of the cavern envelope. The calculated results were transformed into a column coordinate system to obtain the distribution of radial displacement, radial strain and radial stress of the surrounding rock. (Fig. 12).

As shown in Fig. 12, spaced fracture zones occur in the surrounding rock. The fracture zones are distributed on both sides of the cavern and parallel to the cavern sidewalls. Three rupture zones appear around the cavern chamber in terms of displacement, strain and stress. Near the rupture zones, deformation is concentrated in the middle of the cavern sidewalls and stresses are parallel to the height of the cavern sidewalls. This is consistent with Fig. 5, which shows a vertical fracture parallel to the wall in the vicinity of the cavern. However, the damage to the surrounding rock from the model tests is greater than that from the numerical

simulations. This may be due to the fact that the intrinsic model used in the numerical calculations does not take into account the damage effect of excavation on the surrounding rock.

In order to facilitate the comparative analysis between the numerical simulation results and the model test results, the radial displacement data of the numerical model at the corresponding locations of the test model monitoring points were read out, as shown in Table 3. A comparison of the model test and radial displacement numerical simulation results is shown in Fig. 13 for line A as an example. From the numerical model, it can be seen that the radial displacement of the surrounding rock shows an oscillatory pattern, which is characterised by alternating peaks and troughs, with the amplitude of the oscillations decreasing with distance from the wall. These characteristics are consistent with the radial displacement variation pattern measured by the model test. The reliability of the elastic damage softening model and numerical analysis method based on the ABAQUS platform is verified.

The results of the numerical simulation show that the excavation unloading leads to the rupture of the surrounding rock. The stress waves generated by the rock rupture propagate outwards from the cavern walls and form a new stress field in the cavern envelope. The rock, after superimposed with the original rock stress field, may rupture again, forming new rupture and non-ruptured zones.

6. Conclusions

Splitting failure in deeply buried high sidewall cavern is a specific and regular strain localisation phenomenon. The study of splitting failure should start with the strain localisation and strain softening of the rock behind the peak. The effect of strain gradients should also be considered.

Based on strain gradient theory and continuum damage mechanics, an elastic-plastic damage softening model for splitting failure was developed. The relationship between rock damage and energy dissipation was analysed. Based on the strain energy density theory, a strain gradient-based splitting failure criterion was established.

To account for strain gradient effects, an eight-node high-order hexahedral cell was constructed. The shape functions and stiffness matrices of the higher order cells are derived. A numerical analysis method for splitting failure is proposed. A splitting failure calculation program based on ABAQUS is also developed. The numerical simulation results based on ABAQUS and 3D geomechanical model tests are in general agreement. The reliability of the splitting failure elastic-plastic damage softening model and the numerical analysis method of splitting failure were effectively verified.

Acknowledgement

This study was financially supported by the Natural Science Foundation of China (NO:41772282) and the Taishan Scholars Project Foundation of Shandong Province and the National Key Research Development Project of China (No. 2016YFC0401804).

Conflicts of Interest: The authors declare that they have no conflict of interest.

437 **Reference**

- 438 Bauch, E., & Lempp, C., 2004. Rock splitting in the surrounds of underground openings: an
 439 experimental approach using triaxial extension tests. In *Engineering geology for infrastructure planning*
 440 in Europe (pp. 244-254). Springer, Berlin, Heidelberg.
- 441 Chen, X. G., Wang, Y., Zhang, Q. Y., Li, S. C., & Nordlund, E. (2013a). Analogical model test and
 442 theoretical analysis on zonal disintegration based on filed monitoring in deep tunnel. *European Journal*
 443 *of Environmental and Civil Engineering*, 17(sup1), s33-s52.
- 444 Chen, X. G., Zhang, Q. Y., Wang, Y., Li, S. C., & Wang, H. P. (2013b). In situ observation and model
 445 test on zonal disintegration in deep tunnels. *Journal of Testing and Evaluation*, 41(6), 990-1000.
- 446 Chen, X. G., Zhang, Q. Y., Wang, Y., Liu, D. J., & Zhang, N. (2013c). Model test of anchoring effect on
 447 zonal disintegration in deep surrounding rock masses. *The Scientific World Journal*, 2013.
- 448 Dyskin, A. V., Sahouryeh, E., Jewell, R. J., Joer, H., & Ustinov, K. B., 2003. Influence of shape and
 449 locations of initial 3-D cracks on their growth in uniaxial compression. *Engineering Fracture*
 450 *Mechanics*, 70(15), 2115-2136.
- 451 Eshel, N. N., & Rosenfeld, G. (1975). Axi-symmetric problems in elastic materials of grade two.
 452 *Journal of the Franklin Institute*, 299(1), 43-51.
- 453 Fang, Z., & Harrison, J. P., 2002. Development of a local degradation approach to the modelling of
 454 brittle fracture in heterogeneous rocks. *International Journal of Rock Mechanics and Mining Sciences*,
 455 39(4), 443-457.
- 456 Fleck, N.A., Hutchinson, J.W., 2001. A reformulation of strain gradient plasticity. *J. Mech. Phys. Solids*
 457 49, 2245–2271.
- 458 Gao, Q., Zhang, Q., & Xiang, W. (2019). Mechanism of Zonal Disintegration Phenomenon (ZDP)
 459 Around Deep Roadway Under Dynamic Excavation. *Geotechnical and Geological Engineering*, 37(1),
 460 25-41.
- 461 Gao, Q., Zhang, Q., Zhang, X., & Zhang, L. (2018). Geomechanical Model Test and Energy
 462 Mechanism Analysis of Zonal Disintegration in Deep Surrounding Rock. *Geosciences*, 8(7), 237.

463 Gong, F. Q., Luo, Y., Li, X. B., Si, X. F., & Tao, M., 2018. Experimental simulation investigation on
464 rockburst induced by spalling failure in deep circular tunnels. *Tunnelling and Underground Space*
465 *Technology*, 81, 413-427.

466 Gong, Q. M., Yin, L. J., Wu, S. Y., Zhao, J., & Ting, Y., 2012. Rock burst and slabbing failure and its
467 influence on TBM excavation at headrace tunnels in Jinping II hydropower station. *Engineering*
468 *Geology*, 124, 98-108.

469 Gudmundson, P. (2004). A unified treatment of strain gradient plasticity. *Journal of the Mechanics and*
470 *Physics of Solids*, 52(6), 1379-1406.

471 Gurtin, M.E., 2000. On the plasticity of single crystals: free energy, microforces, plastic-strain
472 gradients. *J. Mech. Phys. Solids* 48, 989–1036.

473 Gurtin, M.E., 2002. A gradient theory of single-crystal viscoplasticity that accounts for geometrically
474 necessary dislocations. *J. Mech. Phys. Solids* 50, 5–32.

475 Gurtin, M.E., 2003. On a framework for small-deformation viscoplasticity: free energy, microforces,
476 strain gradients. *Int. J. Plast.* 19, 47–90.

477 Gurtin, M. E., & Anand, L. (2005). A theory of strain-gradient plasticity for isotropic, plastically
478 irrotational materials. Part I: Small deformations. *Journal of the Mechanics and Physics of Solids*, 53(7),
479 1624-1649.

480 Hibino, S., 2001. Rock mass behavior of large-scale cavern during excavation and trend of
481 underground space use. *JOURNAL-MINING AND MATERIALS PROCESSING INSTITUTE OF*
482 *JAPAN*, 117(3), 167-176.

483 Jia, P., Yang, T. H., & Yu, Q. L. (2012). Mechanism of parallel fractures around deep underground
484 excavations. *Theoretical and Applied Fracture Mechanics*, 61, 57-65.

485 Jiang, Q., Feng, X. T., Fan, Y., Fan, Q., Liu, G., Pei, S., & Duan, S., 2017. In situ experimental
486 investigation of basalt spalling in a large underground powerhouse cavern. *Tunnelling and*
487 *Underground Space Technology*, 68, 82-94.

488 Lam, D. C., Yang, F., Chong, A. C. M., Wang, J., & Tong, P. (2003). Experiments and theory in strain
489 gradient elasticity. *Journal of the Mechanics and Physics of Solids*, 51(8), 1477-1508.

490 Li, D., Li, C. C., & Li, X., 2011. Influence of sample height-to-width ratios on failure mode for

491 rectangular prism samples of hard rock loaded in uniaxial compression. *Rock Mechanics and Rock*
 492 *Engineering*, 44(3), 253-267.

493 Li, S. C., & Feng, X. D. (2013). Numerical model for the zonal disintegration of the rock mass around
 494 deep underground workings. *Theoretical and Applied Fracture Mechanics*, 67, 65-73.

495 Liu, G, Feng, X. T., Jiang, Q., Yao, Z., & Li, S., 2017. In situ observation of spalling process of intact
 496 rock mass at large cavern excavation. *Engineering geology*, 226, 52-69.

497 Liu, H. Y., Kou, S. Q., & Lindqvist, P. A., 2002. Numerical simulation of the fracture process in cutting
 498 heterogeneous brittle material. *International journal for numerical and analytical methods in*
 499 *geomechanics*, 26(13), 1253-1278.

500 Liu, Z. Q., & Yu, D. M. (2012). Elastoplastic analytical solutions for displacements of deep-buried
 501 circular tunnels considering intermediate principal stress. *Journal of Henan Polytechnic*
 502 *University(Natural Science)*, 31(4), 469-473.

503 Martin, C. D., & Maybee, W. G., 2000. The strength of hard-rock pillars. *International Journal of Rock*
 504 *Mechanics and Mining Sciences*, 37(8), 1239-1246.

505 Mentzel, A., Steinmann, P., 2000. On the continuum formulation of higher order gradient plasticity for
 506 single and polycrystals. *J. Mech. Phys. Solids* 48, 1777–1796.

507 Mindlin, R. D. (1965). Second gradient of strain and surface-tension in linear elasticity. *International*
 508 *Journal of Solids and Structures*, 1(4), 417-438.

509 Ortlepp, W. D., & Stacey, T. R., 1994. Rockburst mechanisms in tunnels and shafts. *Tunnelling and*
 510 *Underground Space Technology*, 9(1), 59-65.

511 Ortlepp, W. D., 1997. Rock fracture and rockbursts: an illustrative study. *South African Institute of*
 512 *Mining and Metallurgy*.

513 Sahouryeh, E., Dyskin, A. V., & Germanovich, L. N., 2002. Crack growth under biaxial compression.
 514 *Engineering Fracture Mechanics*, 69(18), 2187-2198.

515 Sharif, L. K., Elmo, D., & Stead, D., 2019. Improving DFN-geomechanical model integration using a
 516 novel automated approach. *Computers and Geotechnics*, 105, 228-248.

517 Steinmann, P. (1994). A micropolar theory of finite deformation and finite rotation multiplicative
 518 elastoplasticity. *International Journal of Solids and Structures*, 31(8), 1063-1084.

519 Tang, C. A., Lin, P., Wong, R. H. C., & Chau, K. T., 2001. Analysis of crack coalescence in rock-like
520 materials containing three flaws—part II: numerical approach. *International Journal of Rock*
521 *Mechanics and Mining Sciences*, 38(7), 925-939.

522 Tao, M., Li, X., & Wu, C. (2013). 3D numerical model for dynamic loading-induced multiple fracture
523 zones around underground cavity faces. *Computers and Geotechnics*, 54, 33-45.

524 Wang, Z., Li, Y., Zhu, W., Xue, Y., & Yu, S., 2016. Splitting failure in side walls of a large-scale
525 underground cavern group: a numerical modelling and a field study. *Springerplus*, 5(1), 1528.

526 Wong, R. H. C., Law, C. M., Chau, K. T., & Zhu, W. S., 2004. Crack propagation from 3-D surface
527 fractures in PMMA and marble specimens under uniaxial compression. *International Journal of Rock*
528 *Mechanics and Mining Sciences*.

529 Wowk, D., Alousis, L., & Underhill, P. R., 2019. An adaptive remeshing technique for predicting the
530 growth of irregular crack fronts using p-version finite element analysis. *Engineering Fracture*
531 *Mechanics*, 207, 36-47.

532 Yang, F. A. C. M., Chong, A. C. M., Lam, D. C. C., & Tong, P. (2002). Couple stress based strain
533 gradient theory for elasticity. *International Journal of Solids and Structures*, 39(10), 2731-2743.

534 Yoshida, T., Ohnishi, Y., Nishiyama, S., Hirakawa, Y., & Mori, S., 2004. Behavior of discontinuities
535 during excavation of two large underground caverns. *International Journal of Rock Mechanics and*
536 *Mining Sciences*, 41(SUPPL. 1).

537 Zbib, H. M., & Aifantis, E. C. (1988a). A gradient-dependent model for the Portevin-Le Chatelier effect.
538 *Scripta metallurgica*, 22(8), 1331-1336.

539 Zbib, H. M., & Aifantis, E. C. (1988b). On the structure and width of shear bands. *Scripta metallurgica*,
540 22(5), 703-708.

541 Zhao, J., Sheng, D., & Sloan, S. W. (2007). Cavity expansion of a gradient-dependent solid cylinder.
542 *International journal of solids and structures*, 44(13), 4342-4368.

543 Zhang X T. (2015). The research on failure mechanism and numerical simulate on analysis of zonal
544 disintegration in deep tunnel. (Doctoral dissertation, Shandong University). [in Chinese]

545 Zhang, Q., Liu, C., Duan, K., Zhang, Z., & Xiang, W. (2019a). True Three-Dimensional
546 Geomechanical Model Tests for Stability Analysis of Surrounding Rock During the Excavation of a
547 Deep Underground Laboratory. *Rock Mechanics and Rock Engineering*, 1-21.

548 Zhang, Q. Y., Ren, M. Y., Duan, K., Wang, W. S., Gao, Q., Lin, H. X., ... & Jiao, Y. Y. (2019b).
549 Geo-mechanical model test on the collaborative bearing effect of rock-support system for deep tunnel
550 in complicated rock strata. *Tunnelling and Underground Space Technology*, 91, 103001.

551 Zhang, Q. Y., Zhang, Y., Duan, K., Liu, C. C., Miao, Y. S., & Wu, D. (2019c). Large-scale
552 geo-mechanical model tests for the stability assessment of deep underground complex under
553 true-triaxial stress. *Tunnelling and Underground Space Technology*, 83, 577-591.

554 Zhang, Q., Zhang, X., Wang, Z., Xiang, W., & Xue, J. (2017). Failure mechanism and numerical
555 simulation of zonal disintegration around a deep tunnel under high stress. *International Journal of Rock*
556 *Mechanics and Mining Sciences*, 93, 344-355.

557 Zhang, Q. Y., Zhang, X. T., Xiang, W., Chen, X., Cao, G., & Xu, X. (2013). Model test study of zonal
558 disintegration in deep rock mass under different cavern shapes and loading conditions. *Chinese Journal*
559 *of Rock Mechanics and Engineering*, 32(8), 1564-1571.

560 Zhu, W. S., Li, X. J., Zhang, Q. B., Zheng, W. H., Xin, X. L., Sun, A. H., & Li, S. C., 2010. A study on
561 sidewall displacement prediction and stability evaluations for large underground power station caverns.
562 *International Journal of Rock Mechanics and Mining Sciences*, 47(7), 1055-1062.

563

564

565

566 **List of Tables**

567 Table. 1 The physical and mechanical properties of the prototype and the analogous material.

568 Table. 2 Components ratio of IBSCM.

569 Table. 3 The radial displacement of model test and numerical simulation.

570

571

572 **List of Figures**

573 Fig 1. Geo-mechanical model test loading scheme. ($\sigma_1=27.30$ MPa, $\sigma_2=16.16$ MPa and
574 $\sigma_3=15.25$ MPa)

575 Fig 2. Layout of monitoring sections (a) and monitoring sensors (b) (Unit: mm). Section I: the
576 radial stress monitoring section; Section II: the radial deformation monitoring section; Section III:
577 the tangential stress monitoring section.

578 Fig 3. True 3D loading system. (a) Hydraulic 3D loading system; (b) Overview of the
579 geo-mechanical model test system. 1 – Intelligent hydraulic 3D loading system; 2 – Cavern
580 excavation window; 3 – Counter-force frame system; 4 – Displacement acquisition system.

581 Fig 4. Schematic diagram showing the excavation procedure in the main powerhouse.

582 Fig 5. Fracture patterns around the cavern with high sidewall.

583 Fig 6. Variation of the radial displacement around the cavern.

584 Fig 7. Variation of the radial stress around the cavern.

585 Fig 8. Variation of the tangential stress around the cavern.

586 Fig 9. Stress–strain curve of uniaxial compression. (Gao et al., 2019)

587 Fig 10. The flow chart of zonal disintegration calculation program.

588 Fig 11. Numerical model generated for the simulation of high sidewall cavern.

589 Fig 12. Simulation results in terms of the contour of: (a) Radial displacement; (b) Radial
590 stress; and (c) Tangential stress in the surrounding rock of the cavern.

591 Fig 13. Comparison of the radial displacement of the cavern obtained from the geomechanical
592 model test and the numerical simulation.

Figures

Figure 1

Geo-mechanical model test loading scheme. ($\sigma_1=27.30$ MPa, $\sigma_2=16.16$ MPa and $\sigma_3=15.25$ MPa)

Figure 2

Layout of monitoring sections (a) and monitoring sensors (b) (Unit: mm). Section I: the radial stress monitoring section; Section II: the radial deformation monitoring section; Section III: the tangential stress monitoring section.

Figure 3

True 3D loading system. (a) Hydraulic 3D loading system; (b) Overview of the geo-mechanical model test system. 1 – Intelligent hydraulic 3D loading system; 2 – Cavern excavation window; 3 – Counter-force frame system; 4 – Displacement acquisition system.

Figure 4

Schematic diagram showing the excavation procedure in the main powerhouse.

Figure 5

Fracture patterns around the cavern with high sidewall.

Figure 10 displays the displacement profiles of the wall and the arch. The central vertical line (Line C) shows a sharp increase in displacement as the distance from the wall decreases, reaching 63 mm at 0.1L. The horizontal lines (Line A, Line B, Line D, Line E) show a more gradual increase in displacement, peaking at 21 mm at 0.1L. The scale bar at the bottom indicates $L=90$ mm.

Figure 7

Variation of the radial stress around the cavern.

Figure 8

Variation of the tangential stress around the cavern.

Figure 9

Stress-strain curve of uniaxial compression. (Gao et al., 2019)

Figure 10

The flow chart of zonal disintegration calculation program.

Figure 11

Numerical model generated for the simulation of high sidewall cavern.

Figure 12

Simulation results in terms of the contour of: (a) Radial displacement; (b) Radial stress; and (c) Tangential stress in the surrounding rock of the cavern.

Figure 13

Comparison of the radial displacement of the cavern obtained from the geomechanical model test and the numerical simulation.