Dynamic response of multi-degree-of-freedom systems with a Coulomb friction contact under harmonic excitation

Luca Marino (✉ luca.marino@eng.ox.ac.uk)

University of Oxford <https://orcid.org/0000-0002-9178-1695>

Alice Cicirello

TU Delft: Technische Universiteit Delft

Research Article

Keywords: Coulomb damping, Finite resonance, Displacement transmissibility, Response features, Invariant points, Stick-slip

Posted Date: June 1st, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-288621/v1>

License: This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Version of Record: A version of this preprint was published at Nonlinear Dynamics on October 23rd, 2021. See the published version at <https://doi.org/10.1007/s11071-021-06966-3>.

Dynamic response of multi-degree-of-freedom systems with a Coulomb friction contact under harmonic excitation

Luca Marino · Alice Cicirello

Received: date / Accepted: date

Abstract This paper investigates the steady-state response of a multi-degree-of-freedom (MDOF) system with a Coulomb contact to harmonic excitation. Although discrete MDOF models are commonly used at early design stages to analyse the dynamic performances of engineering structures, the current understanding of the friction damping effects on MDOF behaviour is still limited due to the absence of analytical solutions. In this contribution, closed-form expressions of the continuous time response, the displacement transmissibility and the phase angle of each mass of the system are derived and validated numerically for 2DOF and 5DOF systems. Moreover, the features of the analytical response are investigated, obtaining the following results: (i) the determination of the minimum amounts of friction for which the resonant peaks become finite and (ii) for which stick-slip motion can be observed at high frequencies; (iii) an equation for the evaluation of invariant points for the displacement transmissibilities; (iv) a better understanding of phenomena such as the inversions of the transmissibility curves and the onset of additional resonant peaks due to the permanent sticking of the mass in contact. All these results show that MDOF systems exhibit significantly different dynamic behaviours depending on whether the friction contact

and the harmonic excitation are applied to the same or different masses.

Keywords Coulomb damping · Finite resonance · Displacement transmissibility · Response features · Invariant points · Stick-slip

1 Introduction

Many engineering structures are characterised by the presence of frictional interfaces. When subject to dynamic loadings, the dry friction generated by the relative motion between the structural components in contact can have detrimental effects, such as noise, wear, loss of efficiency and failures. However, friction can also enhance the performance of vibrating structures, if used for purposes such as energy dissipation and vibration control [3–5]. Friction dampers present many advantageous properties, such as the ability to perform in harsh or inaccessible environments, to operate simultaneously along different directions and to adapt to a wide excitation bandwidth [6]. Therefore, their use is common in many engineering systems, such as bladed-disks and civil buildings [6–8]. Nevertheless, the current understanding of the dynamic behaviour of friction damped structures is still limited.

One of the main challenges for the research in this field is the development of models and constitutive laws for describing the friction-related phenomena. Several models have been proposed throughout the years, in the attempt of describing the dependence of the friction force on the sliding velocity between the surfaces in contact [9–12] or introducing state variables accounting for the elastic deformation of the surface asperities [13–17]. Further details can be found in the reviews [18, 19]. Another important challenge is understanding how

L. Marino
Department of Engineering Science, University of Oxford,
Parks Road, Oxford OX1 3PJ, UK
E-mail: luca.marino@eng.ox.ac.uk

A. Cicirello
Department of Engineering Structures, Delft University of
Technology, Stevinweg 1, Delft 2628, NL
Department of Engineering Science, University of Oxford,
Parks Road, Oxford OX1 3PJ, UK
E-mail: a.cicirello@tudelft.nl

friction can affect the performances of vibrating systems. In fact, even when Coulomb friction and simplified mass-spring models are considered, the determination of closed-form solutions for the dynamic response of these systems is a difficult task, due to the nonlinearity of the problem. The limited availability of analytical solutions also poses an important limitation to the conceptual design of engineering structures. In fact, single-degree-of-freedom (SDOF) and multi-degree-of-freedom (MDOF) mechanical models are commonly used during the early design stages to explore the vibration performance of frictional damping solutions. Analytical solutions could speed-up the exploration of suitable designs, avoiding the use of more complicated and computationally expensive models while carrying out parameter investigations, optimisations and statistical model updating.

This paper proposes analytical expressions for the steady-state response of MDOF systems with a single Coulomb friction contact subjected to harmonic excitation and an exploration of their dynamic behaviour based on these derived solutions. In particular, Coulomb damping effects on the resonances and, more in general, on the response amplitude and phase of each mass of the system will be assessed. The investigation will also include the motion regimes determined by the periodic or permanent sticking of the mass in contact, focusing on their effects on these response features.

The research on the forced vibration of Coulomb damped systems has its roots in Den Hartog's work [1]. Den Hartog determined an exact solution for the steady-state time response of SDOF systems in continuous non-sticking regimes, also providing analytical expressions for the response amplitude and phase; furthermore, he also provided a formulation for the boundary between continuous and stick-slip motion regimes. SDOF systems with a ground-fixed wall contact have lately been explored by several authors [20–28]. Hong and Liu [20] proposed a different closed-form expression for the response to harmonic excitation, enabling the evaluation of the velocity transmissibility and providing a different formulation for the boundary between continuous and stick-slip regimes. Hundal [22] determined an analytical solution for base-excited systems with combined viscous and Coulomb damping. Other authors [23–25] investigated the stability of these SDOF systems. Shaw [23] also extended Den Hartog's solution taking into account different static and kinetic friction coefficients. Yeh [29] investigated a 2DOF system with viscous and Coulomb damping. Finally, SDOF systems with a friction contact between the mass and an oscillating wall have been investigated by Levitan [30] and, more recently, by Marino et al. [28, 31].

The response of more complex systems, involving more DOFs, multiple contacts or different friction models is usually investigated with approaches such as harmonic and multi-harmonic balances (see, e.g., [32–38]). However, these methods operate in the frequency domain and cannot be used to investigate directly nonlinear behaviours such as stick-slip motion [8]. Therefore, numerical integration in the time domain is still used to investigate these phenomena, despite its significant computational cost. For instance, Popp and Stelter [39] used a numerical approach to investigate the stick-slip vibration of a 2DOF system with both masses in contact with a moving rigid belt. Further details on the semi-analytical and numerical approaches used in the last decades for the investigation of friction damped systems can be found in the reviews [6, 8, 18].

In reference [8], Rizvi et al. affirm that Den Hartog's approach cannot handle systems with multiple nonlinearities due to its piecewise linear nature. Nonetheless, this approach can also be used for dealing with MDOF systems if a single friction contact is considered. In fact, Yeh [29] used Den Hartog's approach to derive a closed-form solution for the response of a harmonically base-excited 2DOF system where the masses are interconnected by two springs and two viscous dampers in parallel and a Coulomb contact is applied on the lower mass. However, to the best of the authors' knowledge, analytical expressions have not yet been derived for the response of systems with a larger number of DOFs and with the harmonic excitation and or the friction force acting on different masses. These are the focus of the present contribution.

In this paper, the continuous steady-state response of a MDOF system with a Coulomb contact under harmonic loading is investigated. In particular, exact solutions are derived for the time response of all the masses of the system and for the response amplitude and phase of the mass in contact, while approximated analytical expressions are proposed for the response amplitudes and phases of the other masses. The domain of validity of these solutions, i.e. the boundary between continuous and stick-slip regimes, is also obtained and its expression coincides with the one proposed in reference [2] if a simplifying assumption is considered. In addition, the formulation presented in this paper also holds if different static and kinetic friction forces are considered. All these solutions hold for any number of DOFs and take into account harmonic and friction forces applied to different masses of the system. Therefore, they can be applied to the analysis of early design stages of engineering systems where MDOF models with a single contact are of interest, including the implementation of a friction damper in buildings, car suspensions, brak-

ing systems, taxing of airplanes models and energy harvesters (see, e.g. [40–44]). MDOF systems with multiple friction contacts cannot be addressed with the proposed approach. Nonetheless, the general understanding developed in this work can be beneficial to a wide range of applications and support the exploration of engineering solutions exploiting the presence of a frictional damper.

The paper is structured as follows. The analytical expressions are derived in Sect.2. In Sect.3, these analytical expressions are used to investigate the features of the dynamic response, focusing on: (1) resonant, low and high frequency behaviour; (2) the presence of invariant points in the transmissibility curves; (3) the effects of the permanent sticking of the mass in contact. Finally, Sect.4 presents a numerical validation of the solutions presented in Sect.2 in the cases of a 2DOF and a 5DOF system with harmonic excitation and friction contact occurring either on the same or on different masses. The displacement transmissibilities are also evaluated numerically when stick-slip motion occurs, in order to achieve a complete overview of the dynamic response of these systems across the different motion regimes.

2 Analytical evaluation of the steady-state response

2.1 Formulation of the problem

Let us consider a MDOF system where N masses m_i are connected between each other and to the base by N springs of stiffness k_i , as shown in Fig.1. The system is subjected to a harmonic load of amplitude P and frequency ω , applied to the l -th mass; the case of a harmonic base motion of amplitude Y can be accounted for by assuming that a harmonic load of amplitude $P = k_1 Y$ is applied to the mass m_1 . A Coulomb contact characterised by a friction force of amplitude F occurs on the j -th mass of the system. The generic i -th governing equation of this system can be written as:

$$m_i \ddot{x}_i - k_i x_{i-1} + (k_i + k_{i+1})x_i - k_{i+1}x_{i+1} + \delta_{ji} F \text{sgn}(\dot{x}_j) = \delta_{li} P \cos(\omega t) \quad (1)$$

where $x_{i-1} = 0$ for $i = 1$, $x_{i+1} = k_{i+1} = 0$ for $i = N$ and:

$$\delta_{qs} = \begin{cases} 1 & \text{if } q = s \\ 0 & \text{otherwise} \end{cases} \quad (2)$$

The $\text{sgn}()$ function is defined as follows:

$$\text{sgn}(\dot{x}_j) = \begin{cases} 1 & \text{if } \dot{x}_j > 0 \\ [-\mu, \mu] & \text{if } \dot{x}_j = 0 \\ -1 & \text{if } \dot{x}_j < 0 \end{cases} \quad (3)$$

Fig. 1 MDOF system with a friction contact on the j -th mass subjected to a harmonic excitation on the l -th mass.

where $\mu \geq 1$ is the ratio between the static and the kinetic values of the friction force. The so-defined function is mathematically undetermined when $\dot{x}_j = 0$. The value assumed in this static condition, included between $-\mu$ and μ , will be such that the system is in equilibrium when the mass m_j is stuck on the wall.

The dynamic behaviour of this system can be described by referring to $2N + 1$ non-dimensional groups only:

- the frequency ratio $r_1 = \omega \sqrt{m_1/k_1}$;
- the friction ratio $\beta = F/P$;
- the ratio between static and kinetic friction forces μ ;
- the $N - 1$ mass ratios $\gamma_i = m_i/m_1$;
- the $N - 1$ stiffness ratios $\kappa_i = k_i/k_1$.

It is worth noting that γ_1 and κ_1 are equal to 1, by definition, and therefore will not be considered as parameters of the system. By introducing the non-dimensional time:

$$\tau = \omega t \quad (4)$$

and the non-dimensional mass displacements:

$$\bar{x}_i = \frac{x_i}{P/k_1} \quad (5)$$

Fig. 2 Harmonic excitation and continuous responses of the mass in contact m_j and of the generic mass not in contact m_k in the steady-state period included between two maxima of the response $\bar{x}_j$ of the mass in contact.

it is possible to rewrite Eq.(1) in a non-dimensional form where these parameters appear explicitly:

$$\gamma_i r_1^2 \bar{x}_i'' - \kappa_i \bar{x}_{i-1} + (\kappa_i + \kappa_{i+1}) \bar{x}_i - \kappa_{i+1} \bar{x}_{i+1} + \delta_{ji} \beta \text{sgn}(\bar{x}_j') = \delta_{li} \cos \tau \quad (6)$$

The symbol ' will be used to indicate derivatives with respect to the non-dimensional time τ .

2.2 General assumptions and limitations

The assumptions required for the analytical approach proposed in this paper for MDOF systems are the same used by Den Hartog for the SDOF case [1]:

- periodic and continuous steady-state response
- presence of a single nonlinearity in the system

The existence of a periodic steady-state response and its independence of the assigned initial conditions have been investigated by several authors (see, e.g, [23–25]) for SDOF systems; however, to the best of the authors' knowledge, stability properties have not been explored for MDOF systems with a friction contact. Nevertheless, the numerical investigations carried out in this study have shown a convergence of the response to a unique steady-state solutions for most sets of parameters. Specific exceptions, including the case of infinite resonant peaks, are reported and discussed in the following sections.

The second assumption is satisfied if only a single contact is considered. Therefore, the proposed approach cannot deal with MDOF systems with multiple Coulomb contacts occurring simultaneously on different masses.

The harmonic excitation and the motions of the mass in contact m_j and of a generic mass m_k are shown in Fig.2 in the steady-state period included between two maxima of $\bar{x}_j$. If the above assumptions are verified, the governing equations of the MDOF system will be linear in each interval included between two subsequent stationary points of $\bar{x}_j$, independently of the number of DOFs of the system. If the non-dimensional time interval $[0, \pi]$ is considered, where $\tau = 0$ coincides with a maximum of the periodic displacement of the mass in contact and $\tau = \pi$ with the subsequent minimum, the velocity of m_j will be equal to zero at both ends of the interval and negative in all the internal points. Therefore, the non-dimensional friction force will be constant within the interval and equal to $-\beta$. Thus, it will be possible to rewrite Eq.(6) as:

$$\gamma_i r_1^2 \bar{x}_i'' - \kappa_i \bar{x}_{i-1} + (\kappa_i + \kappa_{i+1}) \bar{x}_i - \kappa_{i+1} \bar{x}_{i+1} = \delta_{ji} \beta + \delta_{li} \cos(\tau + \phi_j) \quad (7)$$

where it is assumed that an unknown phase angle ϕ_j is present between the maxima of the excitation and of the response of m_j when a steady-state condition is reached, due to friction damping effect. It is worth underlying that this phase angle only refers to the maxima of the harmonic excitation and of the j -th response. Since the response is not a monoharmonic function, the phase angle between their zeros will be, in general, different from ϕ_j .

2.3 Modal analysis procedure

The linearity of the non-dimensional governing equations in Eq.(7) enables the use of standard modal analysis for its resolution. These equations can be written in a matrix form as:

$$\bar{\mathbf{M}} \bar{\mathbf{x}}'' + \bar{\mathbf{K}} \bar{\mathbf{x}} = \bar{\mathbf{f}} + \bar{\mathbf{p}} \quad (8)$$

where:

- $\bar{\mathbf{M}}$ is the mass matrix:

$$\bar{\mathbf{M}} = \begin{bmatrix} r_1^2 & 0 & \dots & 0 \\ 0 & \gamma_2 r_1^2 & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & \gamma_N r_1^2 \end{bmatrix} \quad (9)$$

- $\bar{\mathbf{K}}$ is the stiffness matrix:

$$\bar{\mathbf{K}} = \begin{bmatrix} 1 + \kappa_2 & -\kappa_2 & 0 & \dots & 0 \\ -\kappa_2 & \kappa_2 + \kappa_3 & -\kappa_3 & \dots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & -\kappa_N & \kappa_N \end{bmatrix} \quad (10)$$

- $\bar{\mathbf{f}}$ is the friction force vector, whose only non-zero component is β in the j -th position;
- $\bar{\mathbf{p}}$ is the harmonic force vector, whose only non-zero component is $\cos(\tau + \phi_j)$ in the l -th position;

The N non-dimensional natural frequencies Ω_i and the corresponding N mode shapes $\boldsymbol{\psi}_i = [\psi_{1i} \ \psi_{2i} \ \dots \ \psi_{Ni}]^T$ of the system described by Eq.(7) can be found as solutions of the generalised eigenvalue problem [45]:

$$(\bar{\mathbf{K}} - \Omega_i^2 \bar{\mathbf{M}}) \boldsymbol{\psi}_i = \mathbf{0} \quad (11)$$

The obtained mode shapes $\boldsymbol{\psi}_i$ are defined up to a constant [45] and, therefore, they need to be normalised according to some criteria in order to have a unique definition. In this paper, a mass-normalisation is considered, i.e. it is imposed that the modal mass:

$$\hat{m}_i = \boldsymbol{\psi}_i^T \bar{\mathbf{M}} \boldsymbol{\psi}_i \quad (12)$$

is unitary.

Standard modal analysis allows the rewriting of the governing equations of a linear system with N DOFs as a set of N uncoupled equations, which can be considered as the governing equations of N separate SDOF systems [45]. This transformation is performed by using the modal matrix $\boldsymbol{\Psi} = [\boldsymbol{\psi}_1 \ \boldsymbol{\psi}_2 \ \dots \ \boldsymbol{\psi}_N]$, which is defined as the matrix whose columns are the mode shapes of the system. Thus, it is possible to introduce the modal coordinates η_i as the components of the vector $\boldsymbol{\eta}$ obtained from the linear transformation:

$$\bar{\mathbf{x}} = \boldsymbol{\Psi} \boldsymbol{\eta} \quad (13)$$

By introducing Eq.(13) into Eq.(8) and pre-multiplying both sides by $\boldsymbol{\Psi}^T$, it is possible to write:

$$\boldsymbol{\Psi}^T \bar{\mathbf{M}} \boldsymbol{\Psi} \boldsymbol{\eta}'' + \boldsymbol{\Psi}^T \bar{\mathbf{K}} \boldsymbol{\Psi} \boldsymbol{\eta} = \boldsymbol{\Psi}^T \bar{\mathbf{f}} + \boldsymbol{\Psi}^T \bar{\mathbf{p}} \quad (14)$$

As the mode-shapes are mass-normalised, $\boldsymbol{\Psi}^T \bar{\mathbf{M}} \boldsymbol{\Psi}$ is equal to an identity matrix and $\boldsymbol{\Psi}^T \bar{\mathbf{K}} \boldsymbol{\Psi}$ is a diagonal matrix whose non-zero elements are equal to Ω_i^2 . Therefore, the i -th equation of the system in Eq.(14) can be written as:

$$\eta_i'' + \Omega_i^2 \eta_i = \psi_{ji} \beta + \psi_{li} \cos(\tau + \phi_j) \quad (15)$$

Eq.(15) can be seen as the governing equation of a SDOF system of unitary mass and stiffness equal to Ω_i^2 , subjected to a constant force of amplitude $\psi_{ji} \beta$ and to a harmonic load $\psi_{li} \cos(\tau + \phi_j)$.

2.4 Solution of the modal problem

The forced vibration problem formulated in Eq.(15) is similar to that solved by Den Hartog [1] and its general solution can be written as:

$$\eta_i = A_i \cos\left(\frac{\tau}{R_i}\right) + B_i \sin\left(\frac{\tau}{R_i}\right) + \psi_{ji} R_i^2 \beta + \psi_{li} R_i^2 v_i \cos(\tau + \phi_j) \quad (16)$$

In this expression, the i -th modal frequency ratio has been introduced as:

$$R_i = \frac{1}{\Omega_i} \quad (17)$$

while the function:

$$v_i = \frac{1}{1 - R_i^2} \quad (18)$$

is the response function associated to the i -th mode. Finally, A_i and B_i are two unknown constants whose expression can be determined by considering the initial conditions of this problem.

The initial and the final conditions to be imposed on η_i are, in general, different from those considered by Den Hartog for the response of a SDOF system. In fact, in the SDOF case, the non-dimensional time instants $\tau = 0$ and $\tau = \pi$ coincide with a maximum and a minimum of the response. However, this is not the case, in general, for the i -th modal coordinate a MDOF system. Therefore, the initial conditions will be:

$$\begin{cases} \eta_i(0) = \eta_{i0} \\ \eta_i'(0) = \eta_{i0}' \end{cases} \quad (19a)$$

$$\begin{cases} \eta_i(0) = \eta_{i0} \\ \eta_i'(0) = \eta_{i0}' \end{cases} \quad (19b)$$

where the terms η_{i0} and η_{i0}' are both unknown at this stage.

Substituting Eq.(16) into Eq.(19) and rearranging the terms, the expressions of A_i and B_i are obtained:

$$\begin{cases} A_i = \eta_{i0} - \psi_{ji} R_i^2 \beta - \psi_{li} R_i^2 v_i \cos \phi_j \\ B_i = R_i \eta_{i0}' + \psi_{li} R_i^3 v_i \sin \phi_j \end{cases} \quad (20a)$$

$$\begin{cases} A_i = \eta_{i0} - \psi_{ji} R_i^2 \beta - \psi_{li} R_i^2 v_i \cos \phi_j \\ B_i = R_i \eta_{i0}' + \psi_{li} R_i^3 v_i \sin \phi_j \end{cases} \quad (20b)$$

Substituting these expressions into Eq.(16), it is possible to express the i -th modal displacement as:

$$\begin{aligned} \eta_i = & \eta_{i0} \cos\left(\frac{\tau}{R_i}\right) + \eta_{i0}' R_i \sin\left(\frac{\tau}{R_i}\right) \\ & + \psi_{ji} R_i^2 \left[1 - \cos\left(\frac{\tau}{R_i}\right)\right] \beta \\ & + \psi_{li} R_i^2 v_i \left[\cos \tau - \cos\left(\frac{\tau}{R_i}\right)\right] \cos \phi_j \\ & + \psi_{li} R_i^2 v_i \left[R_i \sin\left(\frac{\tau}{R_i}\right) - \sin \tau\right] \sin \phi_j \end{aligned} \quad (21)$$

Due to the symmetry of the steady-state response, the final values of η_i and η'_i in the interval considered will be equal to:

$$\begin{cases} \eta_i(\pi) = -\eta_{i0} \\ \eta'_i(\pi) = -\eta'_{i0} \end{cases} \quad (22a)$$

$$(22b)$$

Therefore, substituting Eq.(21) into Eq.(22), a system of algebraic equations is obtained in the form:

$$\begin{cases} \mathcal{A} \cos \phi_j + \mathcal{B} \sin \phi_j + \mathcal{C} = 0 \\ \mathcal{P} \cos \phi_j + \mathcal{Q} \sin \phi_j + \mathcal{R} = 0 \end{cases} \quad (23a)$$

$$(23b)$$

where:

$$\mathcal{A} = -\psi_{li} R_i^2 v_i \left[1 + \cos \left(\frac{\pi}{R_i} \right) \right] \quad (24a)$$

$$\mathcal{B} = \psi_{li} R_i^3 v_i \sin \left(\frac{\pi}{R_i} \right) \quad (24b)$$

$$\mathcal{C} = \left[1 + \cos \left(\frac{\pi}{R_i} \right) \right] \eta_{i0} \quad (24c)$$

$$+ R_i \sin \left(\frac{\pi}{R_i} \right) \eta'_{i0} + \psi_{ji} R_i^2 \left[1 - \cos \left(\frac{\pi}{R_i} \right) \right] \beta \quad (24c)$$

$$\mathcal{P} = \psi_{li} R_i v_i \sin \left(\frac{\pi}{R_i} \right) \quad (24d)$$

$$\mathcal{Q} = \psi_{li} R_i^2 v_i \left[1 + \cos \left(\frac{\pi}{R_i} \right) \right] \quad (24e)$$

$$\mathcal{R} = -\frac{1}{R_i} \sin \left(\frac{\pi}{R_i} \right) \eta_{i0} \quad (24f)$$

$$+ \left[1 + \cos \left(\frac{\pi}{R_i} \right) \right] \eta'_{i0} + \psi_{ji} R_i \sin \left(\frac{\pi}{R_i} \right) \beta \quad (24f)$$

The unknown values of $\cos \phi_j$ and $\sin \phi_j$ can be obtained from Eq.(23) as:

$$\cos \phi_j = \frac{\mathcal{B}\mathcal{R} - \mathcal{C}\mathcal{Q}}{\mathcal{A}\mathcal{Q} - \mathcal{B}\mathcal{P}} \quad \sin \phi_j = \frac{\mathcal{C}\mathcal{P} - \mathcal{A}\mathcal{R}}{\mathcal{A}\mathcal{Q} - \mathcal{B}\mathcal{P}} \quad (25)$$

Substituting Eq.(24) into Eq.(25), it is obtained that:

$$\cos \phi_j = \frac{\eta_{i0}}{\psi_{li} R_i^2 v_i} \quad (26)$$

and:

$$\sin \phi_j = -\frac{\eta'_{i0}}{\psi_{li} R_i^2 v_i} - \frac{\psi_{ji} \sin(\pi/R_i)}{\psi_{li} R_i v_i [1 + \cos(\pi/R_i)]} \beta \quad (27)$$

Let us introduce the damping function of the i -th mode of the system as:

$$u_i = \frac{\sin(\pi/R_i)}{R_i [1 + \cos(\pi/R_i)]} \quad (28)$$

in the same form as the damping function introduced by Den Hartog [1] for SDOF systems. Thus, it is possible to rewrite Eq.(27) as:

$$\sin \phi_j = -\frac{\eta'_{i0} + \psi_{ji} R_i^2 u_i \beta}{\psi_{li} R_i^2 v_i} \quad (29)$$

By substituting Eq.(26) and Eq.(29) into Eq.(21), it is possible to express the i -th modal coordinate as:

$$\eta_i = \eta_{i0} \cos \tau + (\eta'_{i0} + \psi_{ji} R_i^2 u_i) \sin \tau + \psi_{ji} R_i^2 \left[1 - \cos \left(\frac{\tau}{R_i} \right) - u_i R_i \sin \left(\frac{\tau}{R_i} \right) \right] \beta \quad (30)$$

In this expression, the initial values of the modal coordinate and of its derivative are still to be determined.

2.5 Response of the mass in contact

As specified in Sect.2.2, the extremes of the non-dimensional time interval $[0, \pi]$ coincide, respectively, with a maximum and a minimum of the response of the mass in contact m_j . Therefore, the initial conditions for this motion can be expressed as:

$$\begin{cases} \bar{x}_j(0) = \bar{X}_j \\ \bar{x}'_j(0) = 0 \end{cases} \quad (31a)$$

$$(31b)$$

where $\bar{X}_j$ indicates the amplitude of the non-dimensional displacement of the mass m_j . As the amplitude of the non-dimensional excitation is unitary, this value also represents the j -th magnification factor or displacement transmissibility of the system. These initial conditions can be imposed to determine the unknown amplitude and phase angle of the response $\bar{x}_j$. By introducing the j -th coordinate transformation from Eq.(13) into Eq.(31), it is obtained that η_{i0} and η'_{i0} must verify the conditions:

$$\sum_{i=1}^N \psi_{ji} \eta_{i0} = \bar{X}_j \quad (32)$$

and:

$$\sum_{i=1}^N \psi_{ji} \eta'_{i0} = 0 \quad (33)$$

respectively. These relations can be used to eliminate η_{i0} and η'_{i0} from the expression of the phase angle ϕ_j . Let us multiply both numerator and denominator of the RHS of Eq.(26) by ψ_{ji} , obtaining:

$$\cos \phi_j = \frac{\psi_{ji} \eta_{i0}}{\psi_{ji} \psi_{li} R_i^2 v_i} \quad (34)$$

For each modal contribution, the quantity on the RHS of Eq.(34) is constant. As a result, by taking the sum of the N modal contributions of the numerator and denominator, the ratio will remain unchanged:

$$\cos \phi_j = \frac{\sum_{i=1}^N \psi_{ji} \eta_{i0}}{\sum_{i=1}^N \psi_{ji} \psi_{li} R_i^2 v_i} \quad (35)$$

Similarly, the generic k -th response function of an undamped MDOF system of N masses subjected to a harmonic load acting on the l -th mass can be expressed as [2]:

$$V_k = \sum_{i=1}^N \psi_{ki} \psi_{li} R_i^2 v_i \quad (36)$$

Substituting Eq.(32) and Eq.(36) for $j = k$, it is possible to rewrite Eq.(35) as:

$$\cos \phi_j = \frac{\bar{X}_j}{V_j} \quad (37)$$

In a similar fashion, starting from Eq.(29), it is possible to obtain the relation:

$$\sin \phi_j = -\frac{\sum_{i=1}^N \psi_{ji} \eta'_{i0} + \beta \sum_{i=1}^N \psi_{ji}^2 R_i^2 u_i}{\sum_{i=1}^N \psi_{ji} \psi_{li} R_i^2 v_i} \quad (38)$$

Let us introduce the generic k -th damping function of a MDOF system of N masses with a contact on the j -th mass as:

$$U_k = \sum_{i=1}^N \psi_{ki} \psi_{ji} R_i^2 u_i \quad (39)$$

consistently with the formulation used in Eq.(36) for the response function. Substituting Eq.(33), Eq.(36) and Eq.(39) into Eq.(38) for $j = k$, it can be obtained that:

$$\sin \phi_j = -\frac{\beta U_j}{V_j} \quad (40)$$

Substituting Eq.(37) and Eq.(40) in the relation $\cos^2 \phi_j + \sin^2 \phi_j = 1$ and rearranging, it is possible to obtain the j -th displacement transmissibility as:

$$\bar{X}_j = \sqrt{V_j^2 - (\beta U_j)^2} \quad (41)$$

It is worth observing that these expressions of the displacement transmissibility and of the phase angle are formally identical to those obtained by Den Hartog for SDOF systems [1] and reduce to the same expressions if $N = 1$.

Finally, the following expression is obtained for the non-dimensional time response of the mass m_j in the interval $[0, \pi]$ by applying the j -th equation of the transformation from modal to physical coordinates from Eq.(13) to Eq.(30):

$$\begin{aligned} \bar{x}_j &= \sum_{i=1}^N \psi_{ji} \eta_{i0} \cos \tau \\ &+ \left(\sum_{i=1}^N \psi_{ji} \eta'_{i0} + \beta \sum_{i=1}^N \psi_{ji}^2 R_i^2 u_i \right) \sin \tau \\ &+ \beta \sum_{i=1}^N \psi_{ji}^2 R_i^2 \left[1 - \cos \left(\frac{\tau}{R_i} \right) - u_i R_i \sin \left(\frac{\tau}{R_i} \right) \right] \end{aligned} \quad (42)$$

Considering Eq.(32), Eq.(33) and Eq.(39), it is possible to rewrite the above expression as:

$$\begin{aligned} \bar{x}_j &= \bar{X}_j \cos \tau + \beta U_j \sin \tau \\ &+ \beta \sum_{i=1}^N \psi_{ji}^2 R_i^2 \left[1 - \cos \left(\frac{\tau}{R_i} \right) - u_i R_i \sin \left(\frac{\tau}{R_i} \right) \right] \end{aligned} \quad (43)$$

Also in this case, Den Hartog's expression for the time response of a SDOF system [1] is retrieved for $N = 1$.

2.6 Response of a generic mass of the system

The time response of the generic mass m_k of the MDOF system can be found with a similar approach. In fact, by introducing the k -th equation from Eq.(13) into Eq.(30), it is obtained that:

$$\begin{aligned} \bar{x}_k &= \bar{x}_{k0} \cos \tau + (\bar{x}'_{k0} + \beta U_k) \sin \tau \\ &+ \beta \sum_{i=1}^N \psi_{ji} \psi_{ki} R_i^2 \left[1 - \cos \left(\frac{\tau}{R_i} \right) - u_i R_i \sin \left(\frac{\tau}{R_i} \right) \right] \end{aligned} \quad (44)$$

where $\bar{x}_{k0}$ and $\bar{x}'_{k0}$ are, respectively, the initial values of the displacement and of the velocity of m_k in the interval considered; these values are unknown at this stage.

In order to determine $\bar{x}_{k0}$ and $\bar{x}'_{k0}$, let us multiply numerator and denominator of the RHS of Eq.(26) and Eq.(29) by ψ_{ki} and consider their summations from $i = 1$ to N , proceeding as in Sect.2.5. The expressions obtained are:

$$\cos \phi_j = \frac{\sum_{i=1}^N \psi_{ki} \eta_{i0}}{\sum_{i=1}^N \psi_{ki} \psi_{li} R_i^2 v_i} = \frac{\bar{x}_{k0}}{V_k} \quad (45)$$

from Eq.(26) and:

$$\sin \phi_j = -\frac{\bar{x}'_{k0} + \beta U_k}{V_k} \quad (46)$$

from Eq.(29). The initial displacement of m_k can be determined by substituting Eq.(37) into Eq.(45):

$$\bar{x}_{k0} = \frac{V_k}{V_j} \bar{X}_j = \frac{V_k}{V_j} \sqrt{V_j^2 - (\beta U_j)^2} \quad (47)$$

Similarly, considering Eq.(40) and Eq.(46), the initial velocity can be formulated as:

$$\bar{x}'_{k0} = \beta \left(\frac{V_k}{V_j} U_j - U_k \right) \quad (48)$$

The time response of the generic mass m_k can now be evaluated by substituting Eq.(47) and Eq.(48) into Eq.(44), obtaining:

$$\begin{aligned} \bar{x}_k &= \frac{V_k}{V_j} (\bar{X}_j \cos \tau + \beta U_j \sin \tau) \\ &+ \beta \sum_{i=1}^N \psi_{ji} \psi_{ki} R_i^2 \left[1 - \cos \left(\frac{\tau}{R_i} \right) - u_i R_i \sin \left(\frac{\tau}{R_i} \right) \right] \end{aligned} \quad (49)$$

It can be observed that this expression reduces to Eq.(43) if $j = k$.

The amplitude and the phase angle of $\bar{x}_k$ cannot be easily determined from the expression of the time response $\bar{x}_k$. In general, the evaluation of the maximum absolute value of $\bar{x}_k$ within the non-dimensional time interval $[0, \pi]$ can be performed numerically and its value will coincide with the k -th displacement transmissibility. Moreover, if the maximum value of $|\bar{x}_k|$ is verified at $\tau = \tau_{k,\max}$, the phase angle between the excitation and the displacement of the mass m_k can be calculated as:

$$\begin{cases} \phi_k = \phi_j + \tau_{k,\max} & \text{if } \bar{x}_k(\tau_{k,\max}) \geq 0 \\ \phi_k = \phi_j + \tau_{k,\max} + \pi & \text{if } \bar{x}_k(\tau_{k,\max}) < 0 \end{cases} \quad (50a)$$

$$(50b)$$

This approach for the determination of $\bar{X}_k$ and ϕ_k does not yield information on their dependency on the parameters of the problem. Therefore, an approximated approach for determining explicit analytical expressions for the displacement transmissibility and the phase angle of a generic mass of the system is proposed in what follows.

A mono-harmonic approximation of the motion of the mass m_j in the interval $[0, \pi]$ could simply be obtained as $\bar{x}_j \cong \bar{X}_j \cos \tau$. Such a formulation would neglect the non-harmonic behaviour of the response due to nonlinearity but would agree with the exact solution from Eq.(43) at both ends of the interval, thus

providing the exact amplitude and phase angle of the response. Nevertheless, the same approximation cannot directly introduced for the motion of the generic mass m_k . In fact, a certain phase shift ϕ_{kj} is generally present between the displacements of m_j and m_k ; as a consequence, the initial and the final points of $\bar{x}_k$ in $[0, \pi]$ are not stationary points. Comparing Eq.(43) and Eq.(44), it is possible to observe that this effect is expressed by the term $\bar{x}'_{k0} \sin \tau$, which is equal to zero in the case $j = k$. This term cannot be disregarded in a mono-harmonic approximation. Thus, the formulation hereby proposed is:

$$\bar{x}_k \cong \bar{x}_{k0} \cos \tau + \bar{x}'_{k0} \sin \tau = \bar{X}_k \cos(\tau - \phi_{kj}) \quad (51)$$

where:

$$\bar{X}_k = \sqrt{\bar{x}_{k0}^2 + \bar{x}_{k0}'^2} = \sqrt{V_k^2 + \left(1 - 2 \frac{V_k}{V_j} \frac{U_j}{U_k} \right) (\beta U_k)^2} \quad (52)$$

is the approximated k -th displacement transmissibility of the MDOF system, while the phase angle ϕ_{kj} can be determined as:

$$\cos \phi_{kj} = \frac{\bar{x}_{k0}}{\bar{X}_k} \quad \sin \phi_{kj} = \frac{\bar{x}'_{k0}}{\bar{X}_k} \quad (53)$$

The phase angle between the excitation and the displacement of the k -th mass will be finally obtained as $\phi_k = \phi_j + \phi_{kj}$. Eq.(52) and Eq.(53) offer a very good approximation of the exact transmissibilities and phase angles of the mass not in contact and will be used in the remaining of the paper. The absolute errors introduced with the respect to the exact quantities are mostly negligible for all the cases investigated.

2.7 Boundaries between continuous and stick-slip motion regimes

The solutions presented in this section have been determined under the assumption of continuous non-sticking response. In Sect.2.2, it has been specified that the proposed mathematical procedure only holds if the velocity of the mass in contact m_j is negative in all the internal points of the non-dimensional time interval $[0, \pi]$. In addition, in order to observe a continuous response, it is also required that the sum of all the non-inertial forces acting on the mass m_j is larger than the static friction force at both ends of this time interval, where $\bar{x}'_j = 0$. Differently, a sticking phase would take place.

These non-sticking conditions can be expressed as:

$$\begin{cases} \bar{x}_j' < 0 & \text{if } 0 < \tau < \pi \quad (54a) \\ \left| \sum_{i=1}^N \bar{K}_{ji} \bar{x}_i - \delta_{li} \cos(\tau + \phi_j) \right| > \mu\beta & \text{if } \tau = 0 \text{ or } \tau = \pi \quad (54b) \end{cases}$$

These two conditions can be used to obtain the maximum value of the friction ratio for which the steady-state response is non-sticking.

Let us consider the derivative of the j -th mass motion from Eq.(43), so that Eq.(54a) can be rewritten as:

$$\begin{aligned} & -\bar{X}_j \sin \tau + \beta U_j \cos \tau \\ & + \beta \sum_{i=1}^N \psi_{ji}^2 R_i^2 \left[\frac{1}{R_i} \sin \left(\frac{\tau}{R_i} \right) - u_i \cos \left(\frac{\tau}{R_i} \right) \right] < 0 \end{aligned} \quad (55)$$

from which:

$$\bar{X}_j > \beta \sum_{i=1}^N \psi_{ji}^2 \frac{R_i \sin(\tau/R_i) - u_i R_i^2 [\cos \tau - \cos(\tau/R_i)]}{\sin \tau} \quad (56)$$

This relation is verified if $\bar{X}_j$ is larger than the maximum value assumed by the RHS in the interval $]0, \pi[$. Thus, introducing the function:

$$S_j = \sum_{i=1}^N \psi_{ji}^2 s_i \quad (57)$$

where:

$$s_i = \max_{0 < \tau < \pi} \frac{R_i \sin(\tau/R_i) - u_i R_i^2 [\cos \tau - \cos(\tau/R_i)]}{\sin \tau} \quad (58)$$

it is possible to rewrite Eq.(56) as:

$$\bar{X}_j > \beta S_j \quad (59)$$

Substituting Eq.(41) into Eq.(59) and rearranging, it is possible to express this relation in terms of the friction ratio as:

$$\beta < \sqrt{\frac{V_j^2}{U_j^2 + S_j^2}} \quad (60)$$

Let us now consider the second non-sticking condition, expressed in Eq.(54b). Due to the symmetry of the steady-state response, only the case $\tau = 0$ needs to be considered. By introducing the transformation from

Eq.(13), it is possible to rewrite this condition in terms of the i -th modal coordinate as:

$$|\Omega_i^2 \eta_{i0} - \psi_{li} \cos \phi_j| > \psi_{ji} \mu \beta \quad (61)$$

By substituting Eq.(26) into Eq.(61), it is obtained that:

$$|\eta_{i0}| > \psi_{ji} \mu \beta \quad (62)$$

from which, multiplying both sides by ψ_{ji} and considering the sums from 1 to N , it can be written that:

$$\bar{X}_j > \mu \beta \sum_{i=1}^N \psi_{ji}^2 \quad (63)$$

Considering that, from the j -th equation of the system in Eq.(12):

$$\sum_{i=1}^N \psi_{ji}^2 = \frac{1}{\gamma_j r_1^2} \quad (64)$$

and substituting Eq.(41), it is possible to express this condition in terms of the friction ratio as:

$$\beta < \sqrt{\frac{V_j^2}{U_j^2 + \left(\frac{\mu}{\gamma_j r_1^2} \right)^2}} \quad (65)$$

Finally, Eq.(60) and Eq.(65) can be merged in the following overall condition for obtaining a continuous non-sticking response:

$$\beta < \sqrt{\frac{V_j^2}{U_j^2 + \left[\max \left(S_j, \frac{\mu}{\gamma_j r_1^2} \right) \right]^2}} \quad (66)$$

The RHS of the above inequality represents the value of the friction ratio at the boundary between continuous and stick-slip motion regimes and will be referred to as β_{lim} in the remaining of this paper. Furthermore, it is possible to express the boundary between continuous and stick-slip motion in terms of any of the displacement transmissibilities or phase angles of the MDOF system by simply substituting Eq.(66) into their expression.

It is worth observing that in the limit case of $\mu = 1$, when static and kinetic friction forces are assumed to be equal, the boundary can simply be expressed referring to Eq.(60). In fact, as stated by Den Hartog [1], the function s_i is always equal or larger than unity and therefore, from Eq.(57) and Eq.(64):

$$S_j \geq \frac{1}{\gamma_j r_1^2} \quad (67)$$

This implies that the condition in Eq.(54b) is always verified if Eq.(54a) is verified. Moreover, Den Hartog

affirms that s_i is unitary for most values frequency ratio [1]. If the assumption of $s_i = 1$ is considered, the expression of the upper bound for continuous motion reduces to:

$$\beta < \sqrt{\frac{V_j^2}{U_j^2 + \left(\frac{1}{\gamma_j r_1^2}\right)^2}} \quad (68)$$

which is the expression of the boundary proposed in [2]. This approximated expression can be advantageous since it does not require to compute s_i from the time response for each value of r_1 . Although it has been observed that Eq.(60) and Eq.(68) give slightly different results only when low frequency ratios are considered, the exact formulation will be used in this paper.

3 Features of the dynamic response

This section focuses on investigating features of the dynamic response of a MDOF system with a contact on the j -th mass and subjected to a harmonic excitation acting on the l -th mass. This investigation is based on the analytical solutions derived in Sect.2 for its continuous steady-state response and the boundaries between continuous and stick-slip motion regimes and focuses on: (i) resonant, low and high frequency behaviours, (ii) the presence of invariant points in the transmissibility curves and (iii) the effect of stuck friction contacts on the dynamic response of the system. A 3DOF system with unitary stiffness and mass ratios, a friction contact occurring on the m_2 , characterised by equal static and kinetic friction forces, and a harmonic load applied on m_1 , shown in Fig.3a, will be used to show these response features.

3.1 Resonant behaviour

The effect of friction damping on the resonant behaviour of a system is very different from that provided, for instance, by viscous or hysteretic damping (see, e.g., [46]). In the case of SDOF systems, it is well-known that friction does not affect the damped natural frequency of the system and does not provide a finite resonance if $\beta < \pi/4$ (see, e.g., [1,25]). This value represents the minimum friction ratio for which stick-slip occurs in the response of a SDOF system when the ratio between driving and natural frequency is unitary [31]. Thus, it can be deduced that friction can avoid infinite resonant peaks only by introducing stick-slip in the response.

Let us denote with $\beta_{n,i}$ the threshold value of the friction ratio for which the i -th resonant peak of a MDOF

system with a Coulomb contact becomes finite. $\beta_{n,i}$ can be determined by evaluating the value of the boundary between continuous and stick-slip motion from Eq.(60) for $R_i \rightarrow 1$. Observing that in the expressions of the response and of the damping functions, in Eq.(36) and Eq.(39) respectively, only the i -th terms of the summations tend to infinity, it is possible to write:

$$\beta_{n,i} = \lim_{R_i \rightarrow 1} \beta_{\text{lim}} = \left| \frac{\psi_{li}}{\psi_{ji}} \right| \lim_{R_i \rightarrow 1} \frac{\frac{1}{1 - R_i^2}}{\frac{\sin(\pi/R_i)}{R_i[1 + \cos(\pi/R_i)]}} \quad (69)$$

The limit in Eq.(69) has already been evaluated in [31] and it is equal to $\pi/4$. Therefore, the minimum friction ratio required for observing a finite i -th resonant peak will be:

$$\beta_{n,i} = \frac{\pi}{4} \left| \frac{\psi_{li}}{\psi_{ji}} \right| \quad (70)$$

It must be observed that, in the above equation, the ratio between ψ_{li} and ψ_{ji} is always independent of the frequency ratio.

In the 3DOF system shown in Fig.3a, the threshold values of the friction ratio calculated from Eq.(70) are equal to $\beta_{n,1} = 0.436$, $\beta_{n,2} = 1.765$ and $\beta_{n,3} = 0.630$. These results are in agreement with the resonant behaviour exhibited by the transmissibility curves shown in Fig.3b for the mass m_1 of this system.

Eq.(70) shows that, in general, the different resonant peaks of a MDOF system will become finite for different values of β . However, if the harmonic excitation and the friction force act on the same mass, i.e. if $j = l$, $\beta_{n,i}$ will be equal to:

$$\beta_{n,i} = \frac{\pi}{4} \cong 0.785 \quad (71)$$

for any i , meaning that all the resonant peaks of the system will become finite for the same threshold value of the friction ratio.

3.2 Quasi-static conditions

The dynamic response of SDOF systems with Coulomb friction in quasi-static conditions is usually characterised by the occurrence of stick-slip motion. Moreover, when the frequency ratio approaches to zero, the number of stops per cycle can increase significantly, as shown by many authors (see, e.g., [21,47]).

It can be shown that stick-slip motion usually occurs at very low frequency ratios also in the MDOF case. In fact, the evaluation of the boundary friction ratio from Eq.(60) for $\omega \rightarrow 0$ and, therefore, for $R_i \rightarrow 0$ yields:

$$\beta_0 = \lim_{R_i \rightarrow 0} \beta_{\text{lim}} = 0 \quad (72)$$

Fig. 3 3DOF system with unitary mass and stiffness ratios, a Coulomb friction contact on m_2 and a harmonic excitation on m_1 : (a) schematic representation of the system, (b) analytical displacement transmissibility on m_1 for varying r_1 and β in continuous motion regime and (c) stuck configuration of the system. The black dashed line represents the boundary between continuous and stick-slip regimes, while the black dotted line portrays the transmissibility in stuck configuration. The invariant points P_1 and P_2 are highlighted in magenta.

This equation reveals that any non-zero value of the friction ratio would lead to stick-slip in quasi-static conditions.

The numerical investigations carried out in this study showed that the dynamic response of MDOF systems is characterised, as in the SDOF case, by an increasing number of stops for $r_1 \rightarrow 0$. However, the starting point of the transmissibility curves at $r_1 = 0$ can be evaluated analytically, avoiding the complications which may arise in numerical approaches due to the large number of stops per cycle.

Let us rewrite the governing equations of the problem from Eq.(8) in static conditions. If $\omega = 0$, then both r_1 and τ will also be equal to zero. Thus, the harmonic excitation will reduce to a constant force, which will be opposed by a constant friction force. Therefore, the governing equations will reduce to:

$$\bar{\mathbf{K}}\bar{\mathbf{x}}_0 = \bar{\mathbf{p}}_0 - \bar{\mathbf{f}}_0 \quad (73)$$

where:

- $\bar{\mathbf{x}}_0 = [\bar{X}_{10}, \dots, \bar{X}_{N0}]^T$ is the vector of the displacement transmissibilities for $r_1 = 0$;
- $\bar{\mathbf{p}}_0$ is a vector whose only non-zero component is equal to 1 in the l -th position;
- $\bar{\mathbf{f}}_0$ is a vector whose only non-zero component is equal to β in the j -th position.

The starting points of the transmissibilities curves can be evaluated as solutions of the linear algebraic system expressed in Eq.(73). In the case of a SDOF system, the solution is given by $\bar{X}_0 = 1 - \beta$, in agreement with the starting value observed by Csernak et al.

in reference [25], while for the 3DOF system in Fig.3a the values obtained are $\bar{X}_{10} = 1 - \beta$, $\bar{X}_{20} = 1 - 2\beta$ and $\bar{X}_{30} = 1 - 2\beta$.

The validity of these results is limited to the cases where either continuous and stick-slip motion regimes occur in quasi-static conditions, while a different approach is required if the mass in contact is permanently stuck. This case will be discussed in Sect.3.5.

3.3 High-frequency behaviour

In reference [31], the behaviour at high frequency ratios of a SDOF system with Coulomb friction subjected to harmonic excitation is analysed. This investigation revealed that, although the amplitude of the response always converges to zero when the driving frequency tends to infinity, the boundary between continuous and stick-slip motion converges to a specific value, which is:

$$\beta_\infty = \frac{2}{\sqrt{4 + \pi^2}} \quad (74)$$

The meaning of this result is that stick-slip can occur at high frequencies in SDOF systems only if the friction ratio is larger than the above value.

The occurrence of stick-slip motion at high frequency ratios in the response of a MDOF system can be investigated by evaluating the limit of the boundary friction ratio from Eq.(60) for $\omega \rightarrow \infty$. Considering that R_i will

also tend to infinity in this case, it is possible to write:

$$\beta_\infty = \lim_{R_i \rightarrow \infty} \beta_{\text{lim}} = \sqrt{\frac{\left(\sum_{i=1}^N \psi_{li} \psi_{ji}\right)^2}{\left(1 + \frac{\pi^2}{4}\right) \left(\sum_{i=1}^N \psi_{ji}^2\right)^2}} \quad (75)$$

Given the orthogonality conditions of the mode shapes, the boundary friction ratio will be equal to:

$$\beta_\infty = \begin{cases} \frac{2}{\sqrt{4 + \pi^2}} \cong 0.537 & \text{if } j = l \\ 0 & \text{if } j \neq l \end{cases} \quad (76)$$

Therefore:

- when the harmonic and the friction forces act on the same mass of the MDOF system, stick-slip will occur at high frequencies only if the friction ratio is larger than 0.537;
- otherwise, stick-slip will occur for $r_1 \rightarrow \infty$ for any non-zero value of β .

In the case of the 3DOF system shown in Fig.3a, the harmonic load and the friction contact are applied on different masses and, therefore, stick-slip occurs at high frequencies for any value of the friction ratio; this can also be observed from Fig.3b.

3.4 Invariant points

In Fig.3b, it can be observed that the transmissibility curves, illustrated for the bottom mass of the 3DOF system in continuous motion regime, pass through two points denoted as P_1 and P_2 , which are commonly defined as invariant points. In these points, the response amplitude is independent of the damping, which is represented in this case by the friction ratio.

The presence of invariant points in the transmissibility curves is regarded as an important aspect in the design of mechanical systems such as dynamic vibration absorbers [48–50] and car suspensions [51, 52]. In particular, according to the Den Hartog's theory illustrated in reference [53], these points can be used to determine the optimal configuration of a viscous damper acting as vibration absorber for a main undamped SDOF system. An approach for determining the presence of invariant points in the transmissibilities of the MDOF system investigated in this section is proposed in what follows.

Let us consider the expression of the displacement transmissibility provided by Eq.(41) for mass in contact of the MDOF system. It appears clear that the transmissibility will not depend on the friction ratio if:

$$U_j = 0 \quad (77)$$

Thus, this equation can be used to find the invariant points for the response of the mass m_j . From the Eq.(41), it can also be deduced that, at any other frequency ratios, $\bar{X}_j$ will always decrease for increasing β ; therefore, no inversion of the transmissibility curves will be observed across the invariant points in this case. Moreover, from Eq.(37) and Eq.(40), it is possible to observe that the points determined from Eq.(77) will also be invariant for the phase angle ϕ_j . Particularly, from Eq.(40), it can be deduced that the corresponding value of ϕ_j will be equal to 0 or 180 degrees, i.e. the excitation and the j -th mass motion will be in phase or in phase-opposition. The phase angle curves will also exhibit an inversion across these points.

Let us now consider the generic k -th displacement transmissibility of the system. From Eq.(52), it is possible to deduce that the invariant points can be obtained not only from the equation $U_k = 0$, but also from:

$$1 - 2 \frac{V_k}{V_j} \frac{U_j}{U_k} = 0 \quad (78)$$

The points determined as solutions of the latter equation are associated to an inversion of the transmissibility curves. This behaviour can only be observed in the transmissibilities of the masses not in contact. Furthermore, these points are not invariant for the phase angle ϕ_k .

It is important to note that Eq.(77) and Eq.(78) hold only for a continuous response of the MDOF system. In general, transmissibility curves will not pass through an invariant point if stick-slip or permanent sticking of the mass in contact occur at the corresponding frequency ratio. Finally, it is worth observing Eq.(77) and Eq.(78) are transcendental equations and have infinite solutions. Nevertheless, as shown in Sect.5, the vast majority of these solutions are characterised by very small values of frequency ratio, where usually stick-slip motion occurs, and can therefore be disregarded.

3.5 Stuck configurations

In friction damped systems, sliding can occur between two components in contact either continuously or in alternation with sticking phases. However, it is well-known that friction contacts can also become permanently stuck under certain conditions (see, e.g., [2]).

In the case of a SDOF system with a fixed wall contact under harmonic excitation, mass motion occurs only when the amplitude of the harmonic load exceeds the value of the static friction force, i.e. if $\mu\beta < 1$ [2]. The same principle holds, more in general, for the mass in contact of a MDOF system. In this case, the static friction force must be compared to the sum of all the

spring and harmonic forces acting directly on this mass [2]. However, even when the mass in contact is stuck, some masses of the system can still exhibit a dynamic response, depending on where the harmonic and the friction forces are applied. The reduced system which remains active when m_j is stuck will be referred to as stuck configuration of the MDOF system and its response can be evaluated as proposed in reference [2]:

- if $j > l$, only the masses $m_1, \dots, m_{j-1}$ will be excited. Thus, the stuck configuration of the system will be represented by an undamped system with $j - 1$ DOFs, where the stuck j -th mass is replaced by a fixed wall. The response of this system can be evaluated from standard modal analysis and will be characterised by the presence of $j - 1$ infinite resonant peaks located, in general, at different frequencies with respect to those of the original system;
- if $j < l$, only the masses $m_{j+1}, \dots, m_N$ will be excited and, therefore, the stuck configuration of the system will include $N - j$ DOFs. All the above considerations apply, except that, in this case, the stuck system will exhibit $N - j$ infinite resonant peaks;
- finally, if $j = l$, the harmonic excitation is applied to the stuck mass and, therefore, is not transmitted to any of the other masses, leaving the MDOF system fully stuck. Obviously, this is also the case for a SDOF system.

Denoting with $\bar{X}_i^*$ the i -th displacement transmissibility of the system in stuck configuration, it is therefore possible to write the conditions for observing sliding motion between the mass m_j and the wall as:

$$\begin{cases} \beta < (\kappa_j \bar{X}_{j-1}^*)/\mu & \text{if } j > l \\ \beta < (\kappa_{j+1} \bar{X}_{j+1}^*)/\mu & \text{if } j < l \\ \beta < 1/\mu & \text{if } j = l \end{cases} \quad (79a)$$

$$\begin{cases} \beta < (\kappa_{j+1} \bar{X}_{j+1}^*)/\mu & \text{if } j < l \\ \beta < 1/\mu & \text{if } j = l \end{cases} \quad (79b)$$

$$\beta < 1/\mu \quad \text{if } j = l \quad (79c)$$

In the example of the 3DOF system in Fig.3a, the stuck configuration consists in the SDOF system shown in Fig.3c, where the bottom mass is the only remaining active DOF, while the intermediate mass is replaced by a fixed wall. The displacement transmissibility for m_1 in stuck conditions can be obtained as:

$$\bar{X}_1^* = \frac{1}{|2 - r_1^2|} \quad (80)$$

and is represented by a dotted line in Fig.3b. According to Eq.(79), sliding occurs between the mass m_2 and the wall if $\bar{X}_1^* > \beta$. This implies that, for each value of β , the system will operate in a non-stuck configuration only in the frequency ratio range:

$$\sqrt{\frac{2\beta - 1}{\beta}} < r_1 < \sqrt{\frac{1 + 2\beta}{\beta}} \quad (81)$$

The lower bound of Eq.(81) reduces to $r_1 = 0$ if $\beta \leq 0.5$, while the upper bound is defined for any non-zero value of β . Therefore, in the presence of friction damping, the mass m_2 will always become stuck at high frequency ratios beyond the threshold expressed in the above inequality. Moreover, these bounds will converge to a single point at $r_1 = \sqrt{2}$ only for $\beta \rightarrow \infty$. Therefore, even when the friction ratio is very large, sliding motion will always occur in the contact in a small range of frequencies around the resonance of the stuck configuration and the transmissibility will assume a finite value in this range; this behaviour can clearly be observed in Figs.9-14 in Sect.4.

The last two properties, regarding high-frequency and resonant behaviours, can easily be generalised to any MDOF systems with $j \neq l$. In fact, since the transmissibility curves of any undamped system tend to zero for $r_1 \rightarrow \infty$ and tend to infinity at resonance, Eq.(79a) and Eq.(79b) are not verified for any value of β in the first case and always met in the latter.

4 Numerical validation and stick-slip response

In this section, the analytical solutions introduced in Sect.2 for the continuous response of MDOF systems are compared to the results yielded by the numerical approach introduced in reference [2]. Moreover, the response is also evaluated numerically in stick-slip regimes, providing a validation of the analytical boundaries between continuous and stick-slip motion regimes and a complete overview of the dynamic behaviour for varying frequency and friction ratios. The stick-slip responses have been evaluated, for simplicity, in the case of $\mu = 1$; different results would be obtained, in general, if a different value of the static friction force is considered.

In Sect.3, it has been shown that the continuous response features can be significantly different depending on whether the friction and the harmonic forces are applied on the same or on different masses. Therefore, these two different classes of MDOF systems will be dealt with separately. In each case, analytical and numerical results will be first compared and discussed in detail for the 2DOF case and then generalised to systems with a larger number of DOFs, referring to the case of a 5DOF system. Moreover, for each of these systems, the analytical boundaries among continuous, stick-slip and permanent sticking regimes will be represented in a 2-D parameter space for varying frequency and friction ratios in the assumption of $\mu = 1$, while their variation with the static friction force is shown in Appendix A.

Fig. 4 2DOF system with a friction contact and a harmonic load on the lower mass (a) and comparison between analytical (continuous lines) and numerical (round markers) steady-state time responses for two different sets of mass, stiffness, friction and frequency ratios (b-c).

4.1 Systems with excitation and contact on the same mass

4.1.1 2DOF system with excitation and contact on m_1

The analytical and numerical results for the dynamic response of the 2DOF system with $j = l = 1$ shown in Fig.4a are discussed in what follows.

Figs.4b-c present a comparison between the analytical and numerical time responses of the masses m_1 and m_2 . These results have been plotted in the non-dimensional time interval $[0, \pi]$ for two different sets of the parameters r_1, β, κ and γ , exhibiting in both cases an excellent agreement. The harmonic excitation $\cos(\tau + \phi_1)$ is also represented and appears perfectly aligned to the numerical forcing function, showing that a very good agreement is also achieved for the phase angle ϕ_1 .

The analytical and the numerical displacement transmissibilities and phase angles are shown in Figs.5a-b for varying frequency and friction ratios and unitary stiffness and mass ratios. Specifically, the frequency ratio varies in the range $0 : 2.5$ and the friction ratios $0 : 0.2 : 0.8$ are considered. In these figures, it is possible to observe an excellent agreement between the analytical (continuous lines) and numerical results (rounded markers) when the motion of m_1 is continuous. The analytical boundaries between continuous and stick-slip regimes are represented by a black dashed line. Numerical transmissibilities for stick-slip responses are also included (diamond markers). It can be observed that stick-slip motion occurs in the numerical responses only when the transmissibility is smaller than the boundary value, showing that the motion regimes occurring in the numerical results are in agreement with the analytical prediction. Numerical phase angles have only been eval-

uated for continuous responses. In fact, in this paper, the phase angle between the excitation and the response of each mass is referred to their maxima (see Sect.2.2), but this definition cannot be used for stick-slip motion, where the maximum response of the mass in contact usually coincides with a sticking phase rather than a single point.

The following features of the dynamic response of this 2DOF system can be observed from Fig.5.

- Both resonant peaks are finite only in the case $\beta = 0.8$, in agreement with Eq.(71).
- From Eq.(73), it can be calculated the starting values of the transmissibility curves at $r_1 = 0$ are $\bar{X}_{10} = \bar{X}_{20} = 1 - \beta$. These values are in agreement with those displayed in both transmissibility plots.
- At low frequency ratios, the response of the system is characterised by the occurrence of stick-slip motion. For most values of the friction ratio, the response is continuous starting from $r_1 = 0.559$. Among those displayed, only in the case $\beta = 0.2$ continuous motion occurs at lower frequencies, specifically in the range $0.372 < r_1 < 0.524$. The patterns exhibited by the transmissibility curves in the low frequency ratio range are very similar to those observed for SDOF systems (see, e.g. Fig.11 in reference [28]).
- It can be observed that stick-slip motion occurs at high frequencies for $\beta = 0.8$ and it has been verified that this is also the case for $\beta = 0.6$, even though the transition from continuous to stick-slip regime does not occur within the range of frequencies displayed in Fig.5. This behaviour is in agreement with Eq.(76).
- The invariant points of $\bar{X}_1$ can be evaluated from Eq.(77). These points can be observed in Fig.5a as the intersections between the undamped and the

Fig. 5 Displacement transmissibilities and phase angles of a 2DOF system with a Coulomb contact and a harmonic load on m_1 for varying friction ratio and unitary mass and stiffness ratios, displayed on m_1 (a) and on m_2 (b). Analytical results are represented by the continuous lines, while numerical results are represented with round (continuous motion) and with diamond markers (stick-slip motion). The black dashed line represents the boundary between continuous and stick-slip regimes.

Fig. 6 Motion regimes of a 2DOF system with a Coulomb contact and a harmonic load on m_1 for varying frequency and friction ratios. The black continuous lines represent the exact boundaries, while the red dashed curve represents the approximated boundary proposed in [2].

boundary curves, which are particularly well-visible in the phase angle plot. As anticipated in Sect.3.2, most of these points are located in the low-frequency region, where the response is discontinuous for most values of β . Since Eq.(77) only holds for continu-

ous regime, the transmissibility and the phase angle curves will not pass through these points, which can therefore be disregarded. The only relevant solutions are $r_1 = 0.559$ and $r_1 = 1.123$, which represent the main points of transition from continuous to stick-slip regime for most curves.

- The invariant points of $\bar{X}_2$, which can be obtained from Eq.(78), are associated to local inversions of the transmissibility curves, occurring at $0.527 < r_1 < 0.576$ and $1 < r_1 < 1.201$. However, as can be seen in Fig.5b, none of these is associated to a significant increase of $\bar{X}_2$ with β .
- It can be observed that $\phi_2 \cong \phi_1$ for $r_1 < \sqrt{\kappa/\gamma}$ and $\phi_2 \cong \phi_1 + \pi$ for $r_1 \geq \sqrt{\kappa/\gamma}$. This result can be explained by observing that mass m_2 is only excited, through the upper spring, by the motion of the lower mass, which is nearly mono-harmonic in most cases.

Finally, Fig.6 shows the analytical boundaries among continuous, stick-slip and permanent sticking motion regimes, obtained by using Eq.(66) and Eq.(79), respectively. The boundary between continuous and stick-slip regimes obtained using the approximated formulation from Eq.(68), which had already been proposed and numerically validated in reference [2], is represented by the red curve. The exact and approximated boundary curves are very similar but some differences can be observed at low frequency ratios, where the exact bound-

Fig. 7 5DOF system with a Coulomb contact and a harmonic load on m_1 and unitary mass and stiffness ratios (a), displacement transmissibilities (b) and phase angles (c) for varying friction ratio. Analytical results for continuous motions are represented with continuous lines, while numerical results for stick-slip motions with dashed lines. The black dashed line represents the boundary between continuous and stick-slip regimes.

Fig. 8 Analytical (continuous lines) and numerical (round markers) steady-state time response (a) and phase angle curves (b) of a 5DOF system with a Coulomb contact and a harmonic load on m_1 and unitary mass and stiffness ratios. The grey regions indicate stick-slip and stuck regimes.

ary presents a smoother pattern and does not intersect the boundary between sliding and permanent sticking regimes.

4.1.2 5DOF system with excitation and contact on m_1

Most of the response features discussed for the 2DOF case can also be observed in systems with a larger number of DOFs if excitation and contact are applied to the same mass.

Fig. 9 Motion regimes of a 5DOF system with equal masses and springs, with a Coulomb contact and a harmonic load on m_1 for varying frequency and friction ratios.

Let us consider, for instance, the case of a 5DOF system with unitary stiffness and mass ratios where $j = l = 1$, as shown in Fig.7a. The analytical transmissibilities and phase angles are plotted in Figs.7b-c, for the same frequency ratio range and values of friction ratio considered in Sect.4.1.1; in Fig.7b, the numerical transmissibilities in stick-slip regime have also been included. The analytical and the numerical time responses of this system are shown, for a specific set of parameters, in Fig.8a, exhibiting an excellent agreement. Analytical and numerical phase angles curves, associated to the different masses of the system, are shown in Fig. 8b for varying r_1 and $\beta = 0.4$; also in this case, a very good agreement can be observed. Finally, the boundaries among continuous, stick-slip and permanent sticking motion regimes are represented in Fig.9.

From these figures, the following behaviours can be observed:

- the transmissibility curves present finite resonant peaks only in the case $\beta = 0.8$, among those considered;
- the displacement transmissibilities are generally decreasing for increasing values of β . Local inversions can be observed for the masses not in contact, but they always occur in small intervals of r_1 and only present a slight increase in the transmissibility;
- the motion of each mass of the system is approximately in phase or in phase-opposition with the motion of the other masses. This can be clearly observed from Figs.8a-b.
- the boundary between continuous and stick-slip regimes exhibits a similar pattern to that observed for

the 2DOF case in Fig.6. In particular, the boundary has an irregular behaviour at low frequency ratios and presents five maxima which are all characterised by the friction ratio $\beta \cong 0.83$. All these maxima are reached smoothly, except the one occurring at the lowest frequency ratio.

Fig.8b shows that the phase angle curves, particularly those of the mass in contact m_1 , present slightly different patterns only in proximity of the transition to stick-slip regimes and at high frequency ratios. This behaviour can be explained observing that in these two cases the response of the mass in contact, which is usually nearly mono-harmonic in continuous regime, is significantly affected by the higher harmonics.

4.2 Systems with harmonic excitation applied to a mass not in contact

4.2.1 2DOF system excited on m_1 with m_2 in contact

Let us consider a 2DOF system with a friction contact on the mass m_2 and excited by a harmonic load applied on m_1 , as shown in Fig.10a. A comparison between the analytical and the numerical time responses of this system in the non-dimensional time interval $[0, \pi]$ is portrayed in Figs.10b-c for two different sets of parameters, showing an excellent agreement. Analytical and numerical results for the displacement transmissibilities and the phase angles are compared in Figs.11a-b, for varying frequency ratios within the range $0 : 2.5$ and for the friction ratios $[0, 0.2, 0.4, 0.5, 1, 1.5, 2, 5]$. Also in this case, the agreement between analytical and numerical results in continuous motion regime is very good. Furthermore, stick-slip motion occurs in the numerical responses only when the transmissibility of the mass in contact is smaller than the boundary value, as expected.

The main features of the dynamic response of this 2DOF system, which can be observed from Fig.11, are summarised in what follows.

- It can be observed that the first and the second resonant peaks become finite starting from the cases $\beta = 0.5$ and $\beta = 1.5$, respectively. This result agrees with the values obtained from Eq.(71), which are $\beta_{n,1} = 0.485$ and $\beta_{n,2} = 1.271$.
- The stuck configuration of this 2DOF system is represented by an undamped SDOF system where the mass m_1 is connected to a fixed wall on both sides through the springs k_1 and k_2 , respectively. The transmissibility and the phase angle associated to this stuck configuration are represented in Fig.11a with a black dotted line. Particularly, the displace-

Fig. 10 2DOF system with a friction contact on m_1 and a harmonic load on m_2 (a) and comparison between analytical (continuous lines) and numerical (round markers) steady-state time responses for two different sets of mass, stiffness, friction and frequency ratios (b-c).

ment transmissibility can be expressed as [2]:

$$\bar{X}_1^* = \frac{1}{|1 + \kappa - r_1^2|} \quad (82)$$

and the phase angle is equal to 0 degrees before the natural frequency ratio $r_1 = \sqrt{1 + \kappa}$ and 180 degrees afterwards. It can be observed as the transitions between stuck and sliding configurations always occur at $\bar{X}_1^* = \beta/\kappa$, as predicted from Eq.(79a).

- According to Eq.(73), the starting values of the transmissibility curves are $\bar{X}_{10} = 1 - \beta$ and $\bar{X}_{20} = 1 - (1 + \kappa)\beta/\kappa$. These values agree well with those shown from the transmissibilities curves up to $\beta = 0.4$. Starting from $\beta = 0.5$, the mass m_2 will be stuck for $r_1 \rightarrow 0$.
- As discussed in Sect.3.2 and Sect.3.5 respectively, both boundaries between continuous and stick-slip regimes and between sliding and stuck regimes tend to zero for $r_1 \rightarrow \infty$ when $j \neq l$. In Figs.11 and 12, it is possible to observe that stick-slip motion always occurs at high frequencies before the transition to the stuck configuration.
- All the transmissibility and the phase angle curves associated to the mass in contact m_2 , shown in Fig.11b, intersect at $r_1 = 1.450$. This value corresponds to the larger solution of Eq.(77), while the other solutions of this equation represent the other intersections occurring between the undamped and the boundary curves, as already observed in the 2DOF case discussed in Sect.4.2.1.
- Two main invariant points for $\bar{X}_1$ can be observed in Fig.11a at $r_1 = 0.828$ and $r_1 = 1.549$. These values of r_1 correspond to the two largest solutions of Eq.(78) and are associated to a significant inversion of the transmissibility curves. In fact, in the fre-

quency ratio interval included between these points, the transmissibility increases with β , leading the gradual onset of the resonant peak associated to the stuck configuration.

- The evolution of the phase angle ϕ_1 is quite irregular for varying friction ratios. However, it can be observed that its value is always smaller than ϕ_2 , showing that m_1 oscillate with an intermediate phase angle between those of the excitation and of the response of m_2 .

Finally, Fig.12 shows the boundaries among continuous and stick-slip regimes and between sliding and permanent sticking regimes. It can be observed that also in this case the exact and the approximated boundary between continuous and stick-slip regimes are nearly identical. The boundary between sliding and permanent sticking regimes exhibits the same infinite peak shown in the transmissibility curves of the stuck configuration, as expected from Eq.(79a).

4.2.2 5DOF system excited on m_1 with m_3 in contact

The 5DOF system with a contact on m_3 and a harmonically load on m_1 shown in Fig.13a represents a more general example of system with $j \neq l$. The displacement transmissibility curves, obtained analytically for continuous motion and numerically in stick-slip regime, are plotted in Fig.13b, while the analytical phase angles are depicted in Fig.13c for continuous response only. Analytical and numerical time responses are compared in Fig.14a for a specified set of parameters, showing an excellent agreement. Analytical and numerical phase angles on the different masses of the system are represented in Fig.14b. Finally, the boundaries among continuous, stick-slip and permanent sticking regimes are shown in Fig.15. In these figures, many of the patterns

Fig. 11 Displacement transmissibilities and phase angles of a 2DOF system with a contact on m_2 and a harmonic load on m_1 for varying friction ratio and unitary mass and stiffness ratios, displayed on m_1 (a) and on m_2 (b). Analytical results are represented by the continuous lines, while numerical results are represented with round (continuous motion) and with diamond markers (stick-slip motion). The black dashed line represents the boundary between continuous and stick-slip regimes, while the dotted black line represents the response in stuck configuration.

Fig. 12 Motion regimes of a 2DOF system with a Coulomb contact on m_2 and a harmonic load on m_1 for varying frequency and friction ratios. The black continuous lines represent the exact boundaries, while the red dashed curve represents the approximated boundary proposed in [2].

and features described in the 2DOF case can be observed. In particular:

- the transmissibility of the mass in contact m_3 always decreases with β , except that in the invariant points.

- In Fig.11, it can be observed that all the curves pass through two invariant points, located in proximity of the natural frequencies of the stuck configuration. In general, it has been verified that the number of these invariant points is always equal to the number of peaks of the stuck configuration. Despite this, invariant points and stuck resonant peaks occur at close but not coincident frequency ratios;
- the masses m_4 and m_5 oscillate in phase or in-phase opposition with m_3 for most values of frequency and friction ratios and their transmissibility curves have similar patterns to those of $\bar{X}_3$. This behaviour is typical of the masses located on the opposite side of the harmonic excitation with respect to the mass in contact and has already been described for the 5DOF system investigated in Sect.4.2.2.
 - the masses m_1 and m_2 do not oscillate in phase with m_3 or between each other. Their transmissibility curves exhibit significant inversions which lead to the onset of the two resonant peaks of the stuck configuration. In general, this behaviour is observed in the masses located on the same side of the excitation with respect to the mass in contact. The inversions of the transmissibility curves leading to the stuck resonant peaks always occur through two invariant points.

Fig. 13 5DOF system with a Coulomb contact on m_3 , a harmonic load on m_1 and unitary mass and stiffness ratios (a), displacement transmissibilities (b) and phase angles (c) for varying friction ratio. Analytical results for continuous motions are represented with continuous lines, numerical results for stick-slip motions with dashed lines. The black dashed line represents the boundary between continuous and stick-slip regimes, while the dotted black line represents the response in stuck configuration.

Fig. 14 Analytical (continuous lines) and numerical (round markers) steady-state continuous time response (a) and phase angle curves (b) of a 5DOF system with a Coulomb contact on m_3 , a harmonic load on m_1 and unitary mass and stiffness ratios. The grey regions indicate stick-slip and stuck regimes.

5 Concluding remarks

Analytical solutions have been derived for the continuous steady-state response of a MDOF system with a Coulomb friction contact under harmonic excitation. In particular, the expressions of the displacement transmissibility, the phase angle and the time response have

been obtained for all the masses of the system. Moreover, the domain of validity of these solutions has also been determined, providing an analytical formulation for the boundary between continuous and stick-slip regimes which also takes into account the case where different static and kinetic friction forces are considered.

Fig. 15 Motion regimes of a 5DOF system with equal masses and springs, with a Coulomb contact on m_3 and a harmonic load on m_1 for varying frequency and friction ratios.

The closed-form expressions of the continuous response and of the boundaries have been used to investigate the features of the dynamic response of these MDOF systems. Specifically, the resonant, low and high frequency behaviours have been analysed and an analytical approach for the determination of the invariant points for the transmissibility and the phase angle curves have been proposed. Moreover, the response to harmonic excitation has also been determined in the case where the mass in contact is permanently stuck.

Finally, the analytical solutions for the continuous response have been validated numerically in the cases of: (i) a 2DOF system with a harmonic load on the lower mass and a friction contact on either on the lower or the upper mass; (ii) a 5DOF system with a harmonic load on the bottom mass and a friction contact either on the same or on the third mass. Numerical transmissibilities have also been evaluated in stick-slip regime for all these systems, providing a complete overview of their dynamic behaviour for varying non-dimensional exciting frequencies and friction forces. The comparison between analytical and numerical results showed an excellent agreement in all the cases investigated.

The main results obtained from investigation of the response features were: (i) the determination of the minimum friction ratio for which the generic i -th resonant peak of the response becomes finite; (ii) the determination of starting values of the transmissibility curves in quasi-static regime; (iii) the evaluation of the asymptotic values assumed from the boundary between continuous and stick-slip regimes when the exciting frequency tends to infinity. In addition, the presence of invariant points, inversions across the transmissibility

curves for varying non-dimensional friction force and the onset of additional resonant peaks due to the transition from the sliding to the stuck configurations have been observed in both analytical and numerical curves. All these results have shown that MDOF system can exhibit a significantly different dynamic behaviour depending on whether the contact and the harmonic excitation occur on the same or on different masses.

In conclusion, the results presented in this paper contribute to the development of a fundamental understanding of the Coulomb damping effects on mechanical systems. These solutions have been obtained under the assumptions that dry friction is the only source of damping in the system and that Coulomb's law can be used to model friction. Experimental investigations carried out on a single-storey shear frame with a brass-to-steel contact [28] have shown that these assumptions can be considered when describing the dynamic behaviour of simple structures where damping effects are mainly due to the presence of a friction contact. The shear frame setup has been extended to include two storeys to investigate the behaviour of a 2DOF system and preliminary results have shown a good agreement with the analytical results presented in this paper. These experimental results will be presented in a separate publication.

Overall, the presented results can be used for exploring design solutions of structures that can be modelled as MDOF mass-spring systems with a friction damper required to operate in a non-sticking continuous vibration regime. For example, they can be implemented to investigate the performance of a car suspension system with a friction damper. Moreover, the proposed analytical solutions for such systems can be exploited for carrying out parameter investigations, optimisations and statistical model updating with a reduced computational cost compared to numerical approaches.

Further work on this topic is currently focusing on: (i) the extension of the results presented in this contribution to MDOF systems with a friction contact between two oscillating components; (ii) the comparison of the dynamic response features observed by considering different friction models. Moreover, future work will focus on MDOF systems with multiple friction contacts and with combined Coulomb and viscous damping.

Appendix A

The boundaries among continuous, stick-slip and permanent sticking motion regimes of a 2DOF system with unitary stiffness and mass ratios are represented in Figs. 16-17 for varying ratios between static and friction forces. In particular, Fig.16 refers to case of the lower mass in

Fig. 16 Motion regimes of a 2DOF system with a Coulomb contact and a harmonic load on m_1 for varying frequency, friction ratios and static friction forces.

Fig. 17 Motion regimes of a 2DOF system with a Coulomb contact on m_2 and a harmonic load on m_1 for varying frequency, friction ratios and static friction forces.

contact shown in Fig.4a, while in Fig.17 the case of the upper mass in contact shown in Fig.10a is considered. In these figures, it can be observed that intersections between the boundaries may occur when $\mu \neq 1$. In this case, the portion of the boundary between continuous and stick-slip regimes falling into the permanent sticking region will be disregarded and there will be a direct transition from continuous motion to permanent sticking.

Acknowledgements Luca Marino thanks the EPSRC and Rolls-Royce for an industrial CASE postgraduate scholarship. Alice Cicirello gratefully acknowledges Rolls-Royce plc and the EPSRC for the support under the Prosperity Partnership Grant Cornerstone: Mechanical Engineering Science to Enable Aero Propulsion Futures, Grant Ref: EP/R004951/1.

Funding This work was supported by Engineering and Physical Sciences Research Council (EPSRC) and Rolls-Royce plc under grants 16000036 and EP/R004951/1.

Data availability All the results published in this paper were achieved using the data presented herein and may be reproduced in the same manner.

Compliance with ethical standards

Conflicts of interest The authors declare that they have no conflict of interest.

References

1. Den Hartog, J.P.: Forced vibrations with combined viscous and Coulomb damping. *Trans. Am. Soc. Mech. Eng.* **53**, 107-115 (1931)
2. Marino, L., Cicirello, A.: Multi-degree-of-freedom systems with a Coulomb friction contact: analytical boundaries of motion regimes. *Nonlinear Dyn.* (2021) <https://doi.org/10.1007/s11071-021-06278-6>
3. Ibrahim, R.A.: Friction-induced vibration, chatter, squeal, and chaos. *Appl. Mech. Rev.* **47**, 209-253 (1994)
4. Berman, A.D., Ducker, W.A., Israelachvili, J.N.: Experimental and theoretical investigations of stick-slip friction mechanisms. In: Persson, B.N.J., Tosatti E.: *Physics of Sliding Friction*. NATO ASI Series (Series E: Applied Sciences), vol. 311. Springer, Dordrecht (1996)
5. Ferri, A.A.: Friction damping and isolation systems. *Trans. Am. Soc. Mech. Eng.* **117**, 196-206 (1995)
6. Gagnon L., Morandini M. and Ghiringhelli G.. A review of friction damping modeling and testing. *Arch. Appl. Mech.* **90**, 107-126 (2020)
7. Brake, M.R.W.: *The Mechanics of Jointed Structures*. Springer, Houston, TX (2018).

8. Rizvi, A., Smith, C.W., Rajasekaran R., Evans, K.E.: Dynamics of dry friction damping in gas turbines: literature survey. *J. Vib. Control* **22**, 296-305 (2016)
9. Jacobson, B.: The Stribeck memorial lecture. *Tribol. Int.* **36**, 781-789 (2003)
10. Woydt, M., Wsche, R.: The history of the Stribeck curve and ball bearing steels: The role of Adolf Martens. *Wear* **268**, 1542-1546 (2010)
11. Kikuuwe, R., Takesue, N., Sano, A., Mochiyama, H., Fujimoto, H.: Fixed-step friction simulation: from classical coulomb model to modern continuous models. *IEEE Int. Conf. Intel. Robot Syst.* **1**, 1009-1016 (2005)
12. Karnopp, D.: Computer simulation of stick slip friction in mechanical dynamic systems. *J. Dyn. Syst. Meas. Control* **107**, 100-103 (1985)
13. Dahl, P.R.: Solid friction damping of mechanical vibrations. *AIAA J.* **14**, 167501682 (1976)
14. Piatkowski, T.: Dahl and LuGre dynamic friction models - The analysis of selected properties. *Mech. Mach. Theory* **73**, 91-100 (2014)
15. Canudas de Wit, C., Olsson, H., Astrom, K.J., Lischinsky, P.: A new model for control of systems with friction. *IEEE Trans. Automat. Control* **40**, 419-425 (1995)
16. Putelat, T., Dawes, J.H.P., Willis, J.R.: On the microphysical foundations of rate-and-state friction. *J. Mech. Phys. Solids* **59**, 1062-1075 (2011)
17. Cabboi, A., Putelat, T., Woodhouse, J.: The frequency response of dynamic friction: enhanced rate-and-state models. *J. Mech. Phys. Solids* **92**, 210-236 (2016)
18. Awrejcewicz, J., Olejnik, P.: Analysis of dynamic systems with various friction laws. *Appl. Mech. Rev.* **58**, 389-411 (2005)
19. Pennestri, E., Rossi, V., Salvini, P., Valentini, P.P.: Review and comparison of dry friction force models. *Nonlinear Dyn.* **83**, 1785-1801 (2016)
20. Hong, H.-K., Liu, C.-S.: Coulomb friction oscillator: modelling and responses to harmonic loads and base excitations. *J. Sound Vib.* **229**, 1171-1192 (2000)
21. Hong, H.-K., Liu, C.-S.: Non-sticking oscillation formulae for Coulomb friction under harmonic loading. *J. Sound Vib.* **244**, 883-898 (2001)
22. Hundal, M.S.: Response of a base excited system with Coulomb and viscous friction. *J. Sound Vib.* **64**, 371-378 (1979)
23. Shaw, S.W.: On the dynamic response of a system with dry friction. *J. Sound Vib.* **108**, 305-325 (1986)
24. Natsiavas, S.: Stability of piecewise linear oscillators with viscous and dry friction damping. *J. Sound Vib.* **217**, 507-522 (1998)
25. Csernak, G., Stepan, G., Shaw, S.W.: Sub-harmonic resonant solutions of a harmonically excited dry friction oscillator. *Nonlinear Dyn.* **50**, 93-109 (2007)
26. Csernak, G., Stepan, G.: On the periodic response of a harmonically excited dry friction oscillator. *J. Sound Vib.* **295**, 649-658 (2006)
27. Papangelo, A., Ciavarella, M.: Effect of normal load variation on the frictional behavior of a simple Coulomb frictional oscillator. *J. Sound Vib.* **348**, 282-293 (2015)
28. Marino, L., Cicirello, A.: Experimental investigation of a single-degree-of-freedom system with Coulomb friction. *Nonlinear Dyn.* **99**, 1781-1799 (2020)
29. Yeh, G.C.K.: Forced vibrations of a two-degree-of-freedom system with combined Coulomb and viscous damping. *J. Acoust. Soc. Am.* **39**, 1424 (1966)
30. Levitan, E.S.: Forced oscillation of a spring-mass system having combined Coulomb and viscous damping. *J. Acoust. Soc. Am.* **32**, 1265-1269. (1960)
31. Marino, L., Cicirello, A., Hills, D.A.: Displacement transmissibility of a Coulomb friction oscillator subject to joined base-wall motion. *Nonlinear Dyn.* **98**, 2595-2612 (2019)
32. Griffin, J.H.: Friction damping of resonant stresses in gas turbine engine airfoils. *ASME J. Eng. Power* **102**, 329-333 (1980)
33. Dowell, E.H., Schwartz, H.B.: Forced response of a cantilever beam with a dry friction damper attached (I Theory). *J. Sound Vib.* **91**, 255-267 (1983)
34. Dowell, E.H., Schwartz, H.B.: Forced response of a cantilever beam with a dry friction damper attached (II Experiment). *J. Sound Vib.* **91**, 269-291 (1983)
35. Ferri, A.A.: The dynamics of dry friction damped systems. A dissertation presented to the Faculty of Princeton University in Candidacy for the Degree of Doctor of Philosophy (1985)
36. Ferri, A.A., Dowell, E.H.: Frequency domain solutions to multi-degree-of-freedom, dry friction damped systems. *J. Sound Vib.* **124**, 207-224 (1988)
37. Ostachowicz, W.: The harmonic balance method for determining the vibration parameters in damped dynamic systems. *J. Sound Vib.* **131**, 465-473 (1989)
38. Liu T., Zhang D., Xie Y.: A nonlinear vibration analysis of forced response for a bladed-disk with dry friction dampers. *J. Low Freq. Noise V. A.* **38**, 1522-1539 (2019)
39. Popp, K., Stelzer, P.: Stick-slip vibrations and chaos. *Philos. Trans. A. Math. Phys. Eng. Sci.* **332**, 89-105 (1990)
40. Pinal, A.Y., Jangid, R.S.: Dynamic response of structure with tuned mass friction damper. *Int. J. Adv. Struct. Eng.* **8**, 363-377 (2016).
41. Guglielmino, E., Edge, K.A.: A controlled friction damper for vehicle applications. *Control Eng. Pract.* **12**, 431-443 (2004)
42. Shin, K., Brennan, M.J., Oh, J.-E., Harris, C.J.: Analysis of disc brake noise using a two-degree-of-freedom model. *J. Sound Vib.* **254**, 837-848 (2002)
43. Huang, M., Ochieng, W.Y., Nie, H., Zhang, M.: Main wheel prerotation and ground taxi driven by electric taxi system. *J. Aerosp. Eng.* **32** (2019)
44. Thein, C.K., Foong, F.M., Shu, Y.-C.: Spring amplification and dynamic friction modelling of a 2DOF/2SDOF system in an electromagnetic vibration energy harvester Experiment, simulation, and analytical analysis. *Mech. Syst. Signal Process.* **132**, 232-252 (2019)
45. Craig, R.R., Kurdila, A.J.: Fundamentals of Structural Dynamics. Wiley (2006)
46. Worden, K., Tomlinson, G.R.: Nonlinearity in structural dynamics. Institute of Physics, Bristol (2001)
47. Papangelo, A., Ciavarella, M.: On the limits of quasi-static analysis for a simple Coulomb frictional oscillator in response to harmonic loads. *J. Sound Vib.* **339**, 280-289 (2014)
48. Ormondroyd, J., Den Hartog, J.P.: The theory of the dynamic vibration absorber. *ASME J. Appl. Mech.* **50**, 9-22 (1928)
49. Warburton, G.B., Ayorinde, E.O.: Optimum absorber parameters for simple systems. *Earthq. Eng. Struct. Dyn.* **8**, 197-217 (1980)
50. Ozer, M.B., Royston, T.J.: Extending Den Hartogs vibration absorber technique to multi-degree-of-freedom systems. *ASME J. Vib. Acoust.* **127**, 341-350 (2005)
51. Hurel, J., Mandow, A., Garca-Cerezo, A.: Kinematic and dynamic analysis of the McPherson suspension with a planar quarter-car model. *Vehicle Syst. Dyn.* **51**, 1422-1437 (2013)
52. Nie, S., Zhuang, Y., Chen, F., Xie, J.: Invariant points of semi-active suspensions. *Advances in Mechanical Engineering* **10**, 1-14 (2018)

-
53. Den Hartog, J.P.: Mechanical Vibration (Chap. 3). McGraw Hill, NY (1934)