L2MXception: An Improved Xception Network for Classification of Peach diseases

¹Na Yao^{1,2,3}, Fuchuan Ni^{1,2*}, Ziyang Wang¹, Jun Luo^{1,2}, Wing-Kin Sung^{1,4,5}, Chaoxi Luo⁶, Guoliang Li^{1,2}

Abstract

Background: Peach diseases can cause severe yield reduction and decreased quality for peach production. Rapid and accurate detection and identification of peach diseases is of great importance. Deep learning has been applied to detect peach diseases using imaging data. However, peach disease image data is difficult to collect and samples are imbalance.

Results: This paper proposed an improved Xception network named as L2MXception which ensembles regularization term of L2-norm and mean. With the peach disease image dataset collected, results on six mainstream deep learning models were compared in details and an improved loss function was integrated with regularization term L2-norm and mean (L2M Loss). Experiments showed that the Xception model with L2M Loss outperformed the current best method for peach disease prediction. Compared to the original Xception model, the validation accuracy of L2MXception was up to 93.85%, increased by 28.48%.

Conclusions: The proposed L2MXception network may have great potential in early identification of peach diseases.

Keywords: deep learning; identification; peach diseases

Background

Peach is an important fruit and its production is affected by peach diseases. The major peach diseases are brown rot, anthracnose, scab, bacterial shot hole, gummosis, powdery mildew, leaf curl, and so on. The diseases deduce the peach production, and thus it is urgently needed to find rapid and accurate methods to identify peach diseases in earlier stage.

There are several ways for diagnosing plant diseases in general and peach diseases in particular. The first way is visual assessment relying on the farmer's experience; however, it is a subjective task, so that it may cause deviations or even errors. The second way is using spectrometer to diagnose the plant diseases by wavelength (BLAZQUEZ et al., 1986; Sasaki et al., 1998) ^[1-2]; however, the spectrometer cannot be popularized due to its high price. The third way is applying polymerase chain reaction (Henson and French, 1993; Schaad et al. 2002; Koo et al., 2013) ^[3-5] by biological operation; however, the experimental procedure is complicated for ordinary farmers. With the development of computer vision, another way is image-based recognition of plant disease, which is proposed and applied widely ^[6-14]. Bo Li et al, 2015 ^[15] proposed a shallow artificial neural network model to analyse images of cherry and plum shoots. These methods use traditional image processing algorithm, and can achieve high performance for a certain type of research objects. However, such computer methods are semiautomatic because different images

*Correspondence: fcni_cn@mail.hzau.edu.cn

¹College of Informatics, Huazhong Agricultural University, Wuhan, Hubei, 430070, China

²Hubei Engineering Technology Research Center of Agricultural Big Data, Wuhan, Hubei, 430070, China

need different operations, such as the threshold-based segmentation of the lesion areas. Recently, deep learning is rapidly developed and solves the disadvantages of traditional computer vision methods, although it also has its own imperfections, such as relying on a large number of samples. Deep learning has been successfully applied in various fields, such as transportation (Zhang et al., 2016)^[16], medical image analysis (Tajbakhsh et al., 2016)^[17], signal processing (Xie et al., 2017)^[18]. Furthermore, the deep learning is also used in agriculture, such as weed identification (Tang et al., 2017)^[19], plant identification (Sun et al., 2017)^[20], pest identification (Cheng et al., 2017)^[21], and plant disease detection (Mehdipour et al., 2017; Amanda et al., 2017; Mwebaze et al., 2017; Picon et al., 2018; Ferentinos et al., 2018)^[22-26]. Nagasubramanian, K. et al 2019^[27] demonstrated that a 3D CNN model can be used effectively to learn from hyperspectral data to identify charcoal rot disease in soybean stems. Especially, Zhang et al., 2019^[28] compared deep learning and traditional methods in identification of peach leaf disease infected by *Xanthomonas campestris*, drawing a conclusion that convolutional neural network is significantly superior than the traditional methods, such as Support Vector Machine, Nearest Neighbor and Back Propagation neural network.

In this paper, we focus on the identification of 7 major peach diseases (brown rot, anthracnose, scab, bacterial shot hole, gummosis, powdery mildew, leaf curl, as shown in Fig. 1) with deep convolutional neural networks (CNN) Models. The peach disease image dataset, was collected *from peach orchards by Prof. Luo's team, College of Plant Science and Technology, HZAU*, which includes 7 categories of peach disease images. The 7 categories are 1) Brown rot fungi infecting fruits and leaves, 2) Anthracnose fungi infecting fruits and leaves, 3) Scab fungus infecting fruits, branches and leaves, 4) Shot hole bacterium infecting fruits, branches and leaves, 5) Gummosis fungi infecting branches, 6) Powdery mildew fungus infecting fruits and leaves and 7) Leaf curl fungus infecting leaves. These diseases bring damages to different parts of the peach plant (see Fig. 1). For example, the brown rot disease mainly harms the fruit, causing the fruit to rot, which also harms the leaves and causes the leaves to dry up. Gummosis mainly harms branches, causing tree weakness, affecting fruit quality, and even causing death of branches and trees.

Comparing with six existing deep CNN models, the results showed that DenseNet169 had the highest validation accuracy (89.32%). In order to improve accuracy, by analyzing data distribution of peach disease image dataset and the results based on six existing deep learning models, we proposed to apply regularization to six existing models. The Xception model with regularization term of L2-norm achieved the highest validation accuracy of 92.23%. Furthermore, when regularization term was changed to L2-norm and mean, the validation accuracy was further improved to 93.85%.

(a) Brown rot

(b) Brown rot

(c) Brown rot

(d) Anthracnose

Fig. 1 Major plant diseases of peach.

(a) Brown rot for fruit. (b) Brown rot for fruit. (c) Brown rot for leaf. (d) anthrax for fruit. (e) anthrax for leaf. (f) Scab for fruit. (g) Scab for leaf. (h) Bacterial perforation for fruit. (i) powdery mildew for fruit. (j) powdery mildew for leaf. (k) leaf-curl for leaf. (l) Gummosis for branch.

Result and Discussion

The results presented in Fig.2 show that the models applying regularization with L2-norm achieved better performance compared to original CNN models except AlexNet, DenseNet and HRNet.

For the original models, DenseNet had the highest validation accuracy of 89.32% and SENet had the lowest validation accuracy of 56.63%.

For the methods with L2-norm regularization, validation accuracy increased by 26.86%, 13.41% and 5.51% for Xception, ResNet and SENet, respectively. However, the validation accuracy decreased by 14.24%, 4.21% and 3.88% for AlexNet, HRNet and DenseNet, respectively. The validation accuracy of DenseNet was slightly reduced after L2-normalization. The highest validation accuracy was 92.23% for Xception after applying regularization with L2-norm.

Regularization with L2-norm was most effective for Xception, and the regularization term $\lambda \|w\|_2$ in Equation (1) was changed to Expression (2) consequently. After testing different parameter values of γ_1 and γ_2 as shown in Table 1, we found that when $\gamma_1 = 0.7$ and $\gamma_2 = 0.3$, the validation accuracy of Xception was up to 93.85% as shown in Fig.2. Thus, it can be seen that regularization can make the performance of Xception better. The training accuracy and validation accuracy in the original Xception and Xception with different regularization term was shown in Fig. 3. The training accuracy was average accuracy per epoch, and so was the validation accuracy. The results also showed that regularization for Xception can greatly improve training accuracy and validation accuracy. The training accuracy of Xception with L2-norm is not much different from that of Xception with L2-norm and mean, but the validation accuracy of Xception with L2-norm and mean was obviously higher than that of Xception with L2-norm. Furthermore, training loss and validation loss in the original Xception and Xception with different regularization term was shown in Fig.4. Receiver operating characteristic (ROC) of the original

Xception and Xception with different regularization term was shown in Fig.5, which also showed area under curve (AUC) of the original Xception and Xception with different regularization term in the legend at the bottom right. The AUC of L2MXception model outperformed the other two methods

Table 1 Different results corresponding to different parameters based on Xception

Parameters value(γ_1, γ_2)	validation accuracy
$\gamma_1 = 0, \gamma_2 = 1$	92.23%
$\gamma_1 = 0.5, \gamma_2 = 0.5$	92.88%
$\gamma_1 = 0.6, \gamma_2 = 0.4$	91.64%
$\gamma_1 = 0.7, \gamma_2 = 0.3$	93.85%
$\gamma_1 = 0.8, \gamma_2 = 0.2$	92.88%
$\gamma_1 = 1, \gamma_2 = 0$	92.56%
$\gamma_1 = 0, \gamma_2 = 0$	65.37%

Fig. 2 Validation accuracies of six models and six improved models

Fig. 3 Training accuracy and validation accuracy in the original Xception and the Xception with different regularization term

Fig. 4 Training loss and validation loss in the original Xception and the Xception with different regularization term

Fig. 5 ROC of the original Xception and the Xception with different regularization term

Conclusions

In this paper, an improved Xception Network ensemble with L2M Loss was proposed for classification of peach diseases. And six deep learning models were applied to identify peach diseases from images. The disease image dataset has 7 kinds of diseases and 1560 images, including infected different parts such as fruits, branches and leaves. The highest validation accuracy was 89.32% based on original DenseNet169 model. By analyzing the data distribution and classification results of six deep learning models, the improved methods with regularization were proposed to improve accuracy. After experiments, the highest validation accuracy is 93.85% from

Xception model with regularization term of L2-norm and mean.

The experiments show that regularization is highly suitable for Xception model. Furthermore, when regularization term was changed to L2M loss from L2 loss, the validation accuracy was up to 93.85% based on Xception. The proposed method can help to identify peach plant diseases in earlier stage, rapidly and accurately. We will tailor the improved Xception network into mobiles.

Methods

peach disease image dataset

The images of peach diseases were formed into the Peach Disease Image Dataset (PDID). the numbers of each categories in PDID are shown in Fig. 6. The numbers of images of brown rot disease, anthracnose disease, scab disease, bacterial shot hole disease, gummosis disease, powdery mildew disease and leaf curl disease are 94, 157, 654, 427, 91, 50 and 87, respectively. Fig. 2 shows that the distribution of the numbers of images of different disease classes are extremely imbalanced.

Fig. 6 Distribution of sample of each disease

Convolutional neural network

Convolutional neural network (CNN) has become one of the research hotspots in the field of pattern classification. Since the method avoids the complicated pre-processing of images, CNN can directly deal with the original images, and extract features automatically. Convolutional neural networks are very similar to ordinary back-propagation neural networks, and they all consist of neurons with learnable weights and constant bias. Each neuron receives inputs and make mathematical calculations. The output is the score of each classification. The default input of convolutional neural network is an image that allows us to encode specific properties into the network structure, making the feedforward functions more efficient and reducing a large number of parameters.

The basic structure of CNN is composed of convolutional layer, rectified linear units layer, pooling layer and fully connected layer. Each convolutional layer consists of several convolutional units, and the parameters of each convolutional unit are optimized by a backpropagation algorithm. The convolution operation is to extract different features of the input. The first layer of convolutional layer may only extract some low-level features such as edges, lines and corners. The

following layers can iteratively extract more complex features from low-level features. The Rectified Linear units (ReLU) layers mainly perform a nonlinear mapping on the output of the convolutional layer. The excitation function used in this layer is generally a ReLU function: $ReLU(x) = \max(0, x)$. The pool layers reduce the dimension of each feature map, and the depth of the output remains the same as the number of feature maps. The fully connected layers combine all the local features into global features to calculate the score for each class lastly.

CNN was proposed in LeNet network (Lecun et al., 1998)^[29] with four typical layers. The AlexNet (Krizhevsky et al., 2012)^[30] detonates the application boom of convolutional neural networks, which was the champion of the Large Scale Visual Recognition Challenge 2012 (ILSVRC2012). Since then, more deeper convolutional neural networks are proposed, such as VGG (Simonyan K and Zisserman A, 2014)^[31], GoogLeNet (Szegedy et al., 2014)^[32], ResNet (He et al., 2016)^[33], Xception (Chollet and François, 2016)^[34], SENet (Hu et al., 2017)^[35], DenseNet (Gao Huang et al., 2017)^[36], HRNet (Sun et al., 2019)^[37], and so on. GoogLeNet was the champion of the ILSVRC-2014 competition. The VGG describes that the depth of the network is the key factor for the performance of the algorithm and performs better than GoogLeNet in some Transfer Learning tasks. The ResNet proposes the idea of residual learning and many later models are designed on ResNet network. The structure of Xception is based on ResNet, but the convolutional layer is replaced by separable convolution. Although separable convolution can bring about an increase in accuracy or a significant drop in theoretical calculations, due to the scattered calculation process, the efficiency is not high enough. Owing to feature reuse and setting bypassing, the parameter amount of DenseNet network is greatly reduced, and the problem of the gradient vanishing is alleviated, while the network has a certain effect of regularization. HRNet, based on residual unit, connects high-to-low resolution convolutions in parallel, where there are repeated multi-scale fusions across parallel convolutions. AlexNet, ResNet, Xception, SENet, DenseNet and HRNet were applied for classifying peach diseases in this paper. Transfer learning was used to initialize weights for AlexNet, ResNet, Xception, SENet and DenseNet, while HRNet was trained directly by the peach disease image dataset.

Image preprocessing

The samples in the dataset are RGB images. Generally, deep learning models have four image preprocessing steps. Images were processed as following stages: firstly, all the images were resized to 224×224 pixels for AlexNet, ResNet50, SENet, DenseNet, 299×299 for Xception, and 256×256 for HRNet. Model optimization and prediction were performed on the rescaled images. Secondly, all pixel values were divided by 255 to [0.0, 1.0]. Thirdly, Z-Score normalization was performed, which was carried out as follows: for each pixel value x as input, mean value m_x and standard deviation s_x were calculated and then input x is turned to $x' = (x - m_x) / s_x$, so that the normalized data was a standard normal distribution with zero mean and unit variance. Finally, several augmentations including random rotation, cropping, and flipping were used on the training and validating dataset. The augmentation was helpful for enhancing generalization ability of model and preventing overfitting.

Regularization to improve CNN models

This paper applied six CNN models (AlexNet, ResNet, Xception, SENet, DenseNet and HRNet) for classifying peach disease images. The parameters and prediction accuracies of all models are shown in Table 2. The best validation accuracy was 89.32% in DenseNet169 and the lowest validation accuracy was 56.63% in SENet. Samples in this dataset were imbalanced, and the number of samples was relatively small. So, simple model may not work well for this dataset.

To avoid overfitting due to imbalanced samples, when we learn the models, we proposed to include a regularization terms to the loss function, the loss has two parts:

$$loss = CrossEntropyLoss + \lambda \|w\|_2 \quad (1)$$

where λ is a weight decay constant that controls the balance between better fitting of the training data using the term $CrossEntropyLoss$ and minimizing the parameter values using the regularization term $\lambda \|w\|_2$. To further improve the regularization, we replace $\lambda \|w\|_2$ by two terms:

$$\gamma_1 \frac{1}{N} \sum_{i=0}^{N-1} w_i + \gamma_2 \|w\|_2 \quad (2)$$

where γ_1 and γ_2 are constant coefficients for the first term and the second term, $\frac{1}{N} \sum_{i=0}^{N-1} w_i$ is the mean of w .

In total, our L2M loss function is:

$$loss = CrossEntropyLoss + \gamma_1 \frac{1}{N} \sum_{i=0}^{N-1} w_i + \gamma_2 \|w\|_2 \quad (3)$$

Based on experiments, when $\gamma_1 = 0.7$ and $\gamma_2 = 0.3$, the validation accuracy of L2MXception network is up to 93.85%. (Shown as Table 1.)

Implementation

The experiment of classification was performed on a CentOS workstation equipped with two Intel(R) Xeon(R) E5-2683 v4 CPU (55G RAM), accelerated by two Tesla P100-PCIE GPU (16 GB memory). The model implementation in this paper was powered by deep learning framework of Pytorch.

All applied CNN models in this paper were trained using parameters shown in Table 2. All CNN models used the same training parameters (epoch, learning rate and batch size). These parameters gave the best results during training after appropriate experimentation.

Table 2 Results and parameters based on six original models

network	batch size	epoch	learning rate	training accuracy	validation accuracy
AlexNet	64	60	0.001	72.02%	70.55%
ResNet50	64	60	0.001	68.28%	65.23%
Xception	64	60	0.001	67.86%	65.37%
SENet154	64	60	0.001	53.00%	56.63%
DenseNet169	32	60	0.001	90.49%	89.32%
HRNet-w48	64	100	0.05	89.06%	80.91%

Authors' contributions

Fuchuan Ni devised the study in collaboration with Wing-Kin Sung and Guoliang Li. Ziyang Wang carried out experimental work partly and Jun Luo gave some helpful advices respectively. Chaoxi Luo provided the images of peaches and labeled the images. All authors read and approved the final manuscript.

Funding

This work is supported by the Key Special Project National Key R&D Program of China (2018YFC1604000), partly by the earmarked fund for Modern Agro-Industry Technology Research System (no. CARS-30), partly by Supported by "the Fundamental Research Funds for the Central Universities", Huazhong Agricultural University (Grant Number: 2662017PY119).

Acknowledgements

We thank all the colleagues from *Prof. Luo's team, College of Plant Science and Technology, HZAU* for helping collecting and labelling the peaches' images.

Competing interests

The authors declare that they have no competing interests.

Availability of data and materials

The datasets used and/or analyzed during the current study available from the corresponding author on reasonable request.

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Author details

¹College of Informatics, Huazhong Agricultural University, Wuhan, Hubei, 430070, China

²Hubei Engineering Technology Research Center of Agricultural Big Data, Wuhan, Hubei, 430070, China

³College of Information Engineering, Tarim University, Alaer, Xinjiang, 843300, China

⁴Department of Computer Science, National University of Singapore, Singapore, 117417, Singapore

⁵Department of Computational and Systems Biology, Genome Institute of Singapore, Singapore, 138672, Singapore

⁶College of Plant Science & Technology, Huazhong Agricultural University, Wuhan, Hubei, 430070, China.

References

- [1] CARLOS H. BLAZQUEZ, GEORGE J. EDWARDS. Spectral reflectance of healthy and diseased watermelon leaves[J]. *Annals of Applied Biology*, 2008, 108(2):243-249.
- [2] Sasaki, Y., Okamoto, T., Imou, K., Torii, T. Automatic Diagnosis of Plant Disease Spectral Reflectance of Healthy and Diseased Leaves[J]. *IFAC Artificial Intelligence in Agriculture*, Makuhari, Chiba, Japan, 1998,31(5): 145–150.
- [3] Henson J M, French R. The Polymerase Chain Reaction and Plant Disease Diagnosis[J]. *Annual Review of Phytopathology*, 1993, 31(1):81-109.
- [4] Schaad N W, Ogenorth D, Gaush P. Real-Time Polymerase Chain Reaction for One-Hour On-Site Diagnosis of Pierce's Disease of Grape in Early Season Asymptomatic Vines[J]. *Phytopathology*, 2002, 92(7):721-728.
- [5] Chiwan K , Martha M W , Soo K H , et al. Development of a Real-Time Microchip PCR System for Portable Plant Disease Diagnosis[J]. *Plos One*, 2013, 8(12):e82704-.
- [6] Barbedo, Arnal J G . An Automatic Method to Detect and Measure Leaf Disease Symptoms Using Digital Image Processing[J]. *Plant Disease*, 2014, 98(12):1709-1716.
- [7] Atoum Y, Afridi M J , Liu X , et al. On developing and enhancing plant-level disease rating systems in real fields[J]. *Pattern Recognition*, 2016, 53:287-299.
- [8] Feng Q , Dongxia L , Bingda S , et al. Identification of Alfalfa Leaf Diseases Using Image Recognition Technology[J]. *Plos One*, 2016, 11(12):e0168274-.
- [9] H. Al Hiary, S. Bani Ahmad, M. Reyat, et al. Fast and Accurate Detection and Classification of

- Plant Diseases[J]. International Journal of Computer Applications, 2011, 17(1):31-38.
- [10] Omrani E, Khoshnevisan B, Shamshirband S , et al. Potential of radial basis function-based support vector regression for apple disease detection[J]. Measurement, 2014, 55:512-519.
- [11] Hernández-Rabadán Deny Lizbeth, Fernando R Q , Julian G J . Integrating SOMs and a Bayesian Classifier for Segmenting Diseased Plants in Uncontrolled Environments[J]. Scientific World Journal, 2014, 2014:1-13.
- [12] Correa-Tome, Fernando E . Comparison of perceptual color spaces for natural image segmentation tasks[J]. Optical Engineering, 2011, 50(11):p.117203.1-117203.11.
- [13] Marek Schikora, Adam Schikora, Karl-Heinz Kogel, et al. Probabilistic Classification of Disease symptoms caused by Salmonella on Arabidopsis Plants[C]// Informatik 2010: Service Science - Neue Perspektiven für die Informatik, Beiträge der 40. Jahrestagung der Gesellschaft für Informatik e.V. (GI), Band 2, 27.09. - 1.10.2010, Leipzig. DBLP, 2010.
- [14] Barbedo J G A . A new automatic method for disease symptom segmentation in digital photographs of plant leaves[J]. European Journal of Plant Pathology, 2017, 147(2):349-364.
- [15] Li, B., Hulin, M.T., Brain, P. et al. Rapid, automated detection of stem canker symptoms in woody perennials using artificial neural network analysis. Plant Methods 11, 57 (2015). <https://doi.org/10.1186/s13007-015-0100-8>
- [16] Zhang L, Yang F , Zhang D, et al. Road crack detection using deep convolutional neural network[C]// IEEE International Conference on Image Processing (ICIP 2016). IEEE, 2016.
- [17] Tajbakhsh N , Shin J Y , Gurudu S R , et al. Convolutional Neural Networks for Medical Image Analysis: Full Training or Fine Tuning?[J]. IEEE Transactions on Medical Imaging, 2016, 35(5):1299-1312.
- [18] Xie D , Zhang L , Bai L . Deep Learning in Visual Computing and Signal Processing[M]. Hindawi Limited, 2017.
- [19] Tang J L , Wang D , Zhang Z G , et al. Weed identification based on K-means feature learning combined with convolutional neural network[J]. Computers & Electronics in Agriculture, 2017, 135:63-70.
- [20] Yu S , Yuan L , Guan W , et al. Deep Learning for Plant Identification in Natural Environment[J]. Computational Intelligence & Neuroscience, 2017, 2017:1-6.
- [21] Cheng, X., Zhang, Y.H., Chen, Y.Q., Wu, Y.Z., Yue, Y. Pest identification via deep residual learning in complex background[J]. Computers and Electronics in Agriculture. 2017,141: 351–356.
- [22] Mehdipour Ghazi M , Yanikoglu B , Aptoula E . Plant identification using deep neural networks via optimization of transfer learning parameters[J]. Neurocomputing, 2017, 235:228-235.
- [23] Amanda R , Kelsee B , Peter M C , et al. Deep Learning for Image-Based Cassava Disease Detection[J]. Frontiers in Plant Science, 2017, 8:1852-.
- [24] Mwebaze E , Owomugisha G . Machine Learning for Plant Disease Incidence and Severity Measurements from Leaf Images[C]// IEEE International Conference on Machine Learning & Applications. IEEE, 2017.
- [25] Ferentinos, Konstantinos P . Deep learning models for plant disease detection and diagnosis[J]. Computers and Electronics in Agriculture, 2018, 145:311-318.
- [26] Picon A , Alvarez-Gila A , Seitz M , et al. Deep convolutional neural networks for mobile capture device-based crop disease classification in the wild[J]. Computers and Electronics in Agriculture, 2018:S0168169917312619.
- [27] Nagasubramanian, K., Jones, S., Singh, A.K. *et al.* Plant disease identification using

explainable 3D deep learning on hyperspectral images. *Plant Methods* **15**, 98 (2019).
<https://doi.org/10.1186/s13007-019-0479-8>

[28] Keke Zhang, et al. Identification of peach leaf disease infected by *Xanthomonas campestris* with deep learning[J]. *Engineering in Agriculture, Environment and Food*, 2019.
<https://doi.org/10.1016/j.eaef.2019.05.001>.

[29] Lecun Y , Bottou L , Bengio Y , et al. Gradient-based learning applied to document recognition[J]. *Proceedings of the IEEE*, 1998, 86(11):2278-2324.

[30] Krizhevsky A , Sutskever I , Hinton G . ImageNet Classification with Deep Convolutional Neural Networks[C]// NIPS. Curran Associates Inc. 2012.

[31] Simonyan K , Zisserman A . Very Deep Convolutional Networks for Large-Scale Image Recognition[J]. *Computer Science*, 2014.

[32] Szegedy C , Liu W , Jia Y , et al. Going Deeper with Convolutions[J]. 2014.

[33] He K , Zhang X , Ren S , et al. Deep Residual Learning for Image Recognition[C]// 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR). IEEE Computer Society, 2016.

[34] Chollet, François. Xception: Deep Learning with Depthwise Separable Convolutions[J]. 2016.

[35] Hu J , Shen L , Albanie S , et al. Squeeze-and-Excitation Networks[J]. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2017.

[36] Gao Huang, Zhuang Liu, Laurens Van De Maaten. Densely Connected Convolutional Networks[C]// CVPR. 2017.

[37] Ke Sun, Yang Zhao, Borui Jiang, Tianheng Cheng, Bin Xiao, Dong Liu, Yadong Mu, Xinggang Wang, Wenyu Liu, Jingdong Wang. High-Resolution Representations for Labeling Pixels and Regions. *CoRR*, abs/1904.04514, 2019. arXiv:1904.04514v1 [cs.CV]