Developing Horizontal Subsurface Flow Constructed Wetland using Pumice and *Chrysopogon zizanioides* for Tannery Wastewater Treatment

Mekonnen Birhanie Aregu (✉ mokebir16@gmail.com)

Dilla University <https://orcid.org/0000-0002-4110-0345>

Research Article

Keywords: Tannery wastewater, Pumice, Constructed wetland, *Chrysopogon zizanioides*

Posted Date: April 19th, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-358265/v1>

License: © ⓘ This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Developing Horizontal Subsurface Flow Constructed Wetland using Pumice and *Chrysopogon zizanioides* for Tannery Wastewater Treatment

Study Design: Plug flow experimental study design was carried out.

Mekonnen Birhanie Aregu^{1}, Seyoum Leta Asfaw² Mohammed Mazharuddin Khan³*

Email address

1. Mokebir16@gmail.com

2. seyoum.leta@aau.edu.et

3. mohammed.mazharuddin@aau.edu.et

1 School of public health, Dilla university, Ethiopia

2,3 Environmental Pollution and Sanitation, Centre for Environmental Sciences, Addis Ababa University, Ethiopia.

Abstract

Background: High-strength wastewater defined by elevated levels of hazardous pollutants measured in BOD, heavy metals, nutrients and other toxic substances. This kind of wastewater discharged to water body without treatment from different industrial sectors that adversely affects aquatic environment and downstream water consumers. The general objective of this study is to investigate efficient substrate with selected plant type for constructed wetland to remove hazardous pollutants from tannery wastewater. This study was conducted at Modjo town from 2016 to 2018. Plug flow experimental study design was carried out. The substrate (Pumice) was collected around the study area and chemical characteristics were determined. *Chrysopogon zizanioides* was planted and grown for five months before running tannery wastewater for the treatment. The composite wastewater was introduced to the constructed wetland from Modjo leather industry, Ethiopia. The physicochemical analysis of the sample wastewater was done before and after treatment at four different hydraulic retention time.

Results: Characterization of the untreated tannery wastewater revealed that the mean concentration of BOD₅, COD, TSS, PO₄-P, TP, NO₃-N, TN and total chromium were 1641±373.6, 6953.33±339.4, 1868±863.1, 88.06 ±40.8, 144.53 ±20.8, 116.66 ±26.6, 650.33 ±93.6 and 18.33±6.7 mg/l respectively beyond the permissible limits. The maximum removal efficiency of the constructed wetland in pumice bed revealed that BOD₅ at HRT 7 and 9 days (96.42%, 96.30%), COD at HRT 5 and 7 days (96.76%, 96.91%), NO₃-N at HRT 5 and 7 days (99.99%, 99.68%), TN (98.67%, 99.00%), PO₄-P HRT 7 and 9 days (96.97%, 100%), TP at HRT 5 and 7 days (94.79%, 96.17%) and total Chromium at HRT 5 and 7 days (98.36%, 98.91%) respectively. Whereas, the removal efficiency of constructed wetland bed with gravel substrate used as a control subject with similar condition to pumice showed lower performance. The result between pumice and gravel

bed was tested for their significance difference using two sample t-test statistics. Based on the test statistics, the pumice substrate perform better than the gravel significantly at 95% confidence interval, p-value = 0.01.

Conclusion: Pumice substrate and *Chrysopogon zizanioides* have a potential ability to remove hazardous pollutants from tannery wastewater in horizontal subsurface constructed wetlands.

Key Words: Tannery wastewater, Pumice, Constructed wetland, *Chrysopogon zizanioides*

Background

Industrial wastewater is the most common source of environmental pollution in the current situation. Industrial wastes are discharged commonly with hydrocarbons, heavy metals, surfactants, toxins and salts, which may pollute receiving waters rendering them unsuitable as a water supply or pose a threat to aquatic life. In receiving waters, excessive nutrients can lead to algal blooms, oxygen deficits and increase color and turbidity. Tannery effluent is among one of the most hazardous pollutants of industry. Major problems caused by tannery wastewater containing heavy metals, nutrients, toxic chemicals, chloride, lime with high dissolved and suspended salts, and other pollutants.

Tanning is one of the oldest industries in the world. During ancient times, tanning activities were organized to meet the local demands of leather footwear, drums and musical instruments. With the growth of population, the increasing requirement of leather and its products led to the establishment of large commercial tanneries. Two methods are adopted for tanning of raw hide/skin, vegetable tanning, and chrome tanning. Tanneries are typically characterized as pollution intensive industrial complexes which generate widely varying, high-strength

wastewaters. Nearly 30 m³ of wastewater is generated during processing of one tone of raw skin/hide (Suthanthararajan *et al.*, 2004).

Tannery operation consists of converting of the raw hide or skin into leather which consume huge amount of water in several stages, generating an enormous amount of liquid effluents which are hazardous to the environment to which they are discharged, consequently, make it as a potentially pollution intensive industry. Tannery effluents again compromise the physical, chemical and biological properties of aquatic environment. Apart from the most toxic heavy metals like Chromium (Cr) chemical impurities of tannery effluents mostly includes the following dissolved substances such as inorganic salt cations (Fe, Zn, Cu, Ca, Na, etc.); anions such as SO₄²⁻, NO₃⁻, PO₄³⁻ and parameters such as, BOD, COD, TSS, TDS etc (Kawser *et al.*, 2011). Therefore treating tannery wastewater using natural adsorbents is very important to protect the surrounding environment.

In Ethiopia currently, there are more than 30 tannery industries in operation. Among them the majority found in Oromia region especially Mojo town and around six established in the capital city Addis Ababa. These tanneries have 153,650 sheep and goat skin soaking capacity and 9,725 cowhides soaking capacity per day. Together they also employ 4577 persons (UNIDO, 2012).

Leather is one of the most important export item of Ethiopia earning foreign exchange. On the other hand, the leather tanning industry has been recognized as one of the main causes of water and environmental pollution. With the high adoption of chrome tanning in most of the tanning industries in the country, efficient methods of chromium, nutrients and other pollutant removal from tannery wastewater are important to attain environmental quality standards.

Conventional wastewater treatment processes such as activated sludge and biofilms are used seldom in Africa including Ethiopia due to lack of energy and financial resources. Therefore in

90 this case constructed wetland is sustainable option for industrial wastewater treatment. Because,
91 constructed wetlands can provide an energy-efficient, cost-effective, and low maintenance
92 alternative to conventional wastewater treatment technologies (Kadlec and Knight, 1996). They
93 also have additional benefits that include creating habitat for plants and wildlife and an aesthetic
94 green space in communities.

95 Kivaisi (2001) assured that there is potential for the development of CWs in developing
96 countries like Ethiopia. The author points out this to the location of many developing countries in
97 warm tropical and sub-tropical climates (Ethiopia located in Tropics), which are favorable to
98 higher biological activity and productivity, and hence better treatment performance.

99 Compared with the conventional wastewater treatment system currently in use the constructed
100 wetland has its own advantage. Constructed wetlands are natural wastewater treatment systems
101 that typically have lower construction, operation and maintenance costs than conventional
102 mechanical treatment systems. Constructed wetlands are therefore cost effective, eco-friendly and
103 technically feasible approach for treating industrial wastewater including high strength tannery
104 wastewater.

105 Even though literature cannot found in Ethiopia on the cost comparison of constructed wetland
106 and conventional wastewater treatment, Study conducted in Ireland by Reddy (2004) showed that
107 the cost of a typical constructed wetland cheaper by 30% than conventional treatment methods of
108 the same size considering the lifespan and replacement value of the wetland. The above case
109 studies confirmed that the maintenance cost for constructed wetlands was eight times lower than
110 the conventional treatment system. Furthermore, operation and maintenance require only periodic
111 rather than continues.

The result of another study indicated that the total annual cost for waste stabilization pond was 21% more than that of the constructed wetlands (Tomokin, 2000). Based on the overall results of the treatment performance and costs, these researchers concluded that the application of constructed wetlands can be considered both technically and economically viable option for wastewater treatment.

Conventional wastewater treatment systems contains energy demanding and mechanical treatment components which require substantial investment and high operating costs. Experience has shown that existing wastewater treatment systems in most of the developing countries failed to treat wastewater effectively it is because of high operating and maintenance costs, lack of local expertise and poor institutional governance. Compared to conventional treatment systems, constructed wetlands are low cost, easy to operate and maintain, and have a strong prospective for application in developing countries (Vymazal, 2010).

On the other hand, adsorption has been identified as one of the most promising mechanism for removal of dissolved heavy metal fractions and nutrients from wastewater. Although commercial adsorbents are available for use in adsorption, they are very expensive, resulting in various new low-cost adsorbents being studied by researchers. Babel and Kurniawan (2003), reviewed the technical feasibility of various low-cost adsorbents for heavy metals removal from wastewater and concluded that the use of low-cost adsorbents may contribute to the sustainability of the surrounding environment and offer promising benefits for commercial purpose in the future. Therefore identifying potentially efficient substrate for constructed wetland as an adsorbent is critical for proper practice of environmental management by tanning industries.

Materials and Methods

Study Area and Period: This study was conducted in Oromia region east Showa zone, Modjo town at Modjo tanning industry PLC (Fig.1) from 2016 to 2018.

Study Design: Plug flow experimental study design was carried out to determine the efficiency of pumice substrate and *Chrysopogon zizanioides* plant species in horizontal subsurface constructed wetland to remove hazardous pollutants from high-strength tannery wastewater.

Experimental materials, Design and setup Establishments

Pumice was collected from volcanic cones of refit valley area of Oromia region east showa zone (8°28'36"N and 39°14'29"E), Ethiopia 20-30 km far from Modjo Tannery (8°35'13"N and 39°07'23"E) approximately 70 km East of Addis Ababa (Fig. 1). The chemical characteristics of this substrate was determined by using XRF analysis.

The plant (*Chrysopogon zizanioides*) was collected from Holeta Agricultural research institute and transported to Modjo tanning industry. It was planted in the horizontal subsurface constructed wetland and grown for five months before running high-strength wastewater for the treatment.

The horizontal subsurface constructed wetland was installed at Modjo tanning industry compound for the treatment of tannery wastewater (Fig. 2). The treatment system consists of: a primary screening and a grit removal tank; sedimentation tank for sludge settling and equalization tank connected with horizontal subsurface flow constructed wetland (HSSFCW), with an effective volume of 1.92 m³ each which is a length of 4 m, width of 0.8 m and effective depth of 0.6 m.

The CWs are filled with medium-sized gravel, ranging in size from 6 to 20 mm as a control and pumice 10 – 25 mm grain size substrate vegetated with *Chrysopogon zizanioides* in separate

constructed wetland cell with similar size and dimensions (Fig 3). The pumice substrate was crushed and graded. Effective size was determined by using standard sieve. Based on the analysis the effective size (ES) (d_{10}) of the media was 1.5-4.5 and the uniformity coefficient (UC) (d_{60}/d_{10}) was 3.5 - 4.

The raw wastewater is fed into a sedimentation tank from the factory after 24 hour retention time pumped to the equalization tank with volume of 5000 liter then the CWs fed from this tank through 3/4th inch pipe with control valve for each cell. Performance of this constructed wetland was recorded for two years based on four different hydraulic retention time (3, 5, 7 and 9 days).

Sample Collection and Laboratory Analysis

The on-site measurement of the physicochemical parameters was undertaken. The physicochemical analysis of wastewater samples was done before and after the treatment with the two different hydraulic retention time, using standard methods. The analytical parameters were pH, BOD₅, COD, Ammonium N, Nitrite N, Nitrate N, Total N, Phosphate, Total P, TSS, TDS, Salinity and Chromium. On-site measurement of the wastewater like temperature, pH and DO were carried out at the site in the tannery environmental quality control laboratory using portable pH meter (Wagtech International N374, M128/03IM, USA) and DO meter (Hach P/N HQ30d, Loveland, CO, USA) for Dissolved oxygen and temperature.

COD, Ammonium-nitrogen, Nitrite-nitrogen, Nitrate-nitrogen, Phosphate, Chloride, Sulfide and Sulfate were measured by using spectrophotometer (Hach model DR/3900 portable spectrophotometer, Germany) according to Hach instructions. BOD₅ and total Chromium were analyzed using BOD sensor and inductive stirring system AQUA LYTIC model type ET618-4 and Flame Atomic Absorption Spectrophotometer (AAS), (model AAS NOUA-400, Germany) respectively. Total suspended solids (TSS) were determined according to the Standard Methods

for the Examination of Water and Wastewater gravimetric method. Heavy metal uptake capacity of the plant and adsorption potential of the pumice were determined by Ash-Modified AOAC 923.03 and Minerals-Modified AOAAC 985.35 (APHA, 2005).

The removal efficiency of the filter media for the selected parameters were calculated as:

$$\% \text{ removal} = \frac{C_i - C_f}{C_i} \times 100$$

Where C_i is the parameter concentration in the untreated wastewater and C_f is the parameter concentration in the treated wastewater.

Statistical Data Analysis: Mean and standard deviations were calculated to estimate the concentration of each parameter of the samples. The hypothesis has been tested by two sample t-test using R statistical software: R version 3.2.2 (2015-08-14), Platform: x86_64-w64-mingw32/x64 (64-bit) and Originlab pro 2017 to determine whether an observed difference between the means of the groups is statistically significant or not, based on the two hydraulic retention time.

Data Quality Management: To assure quality of the data by minimizing the errors the following measures had been undertaken: Apparatuses were calibrated; expiry date of reagents had been checked before starting the real analysis and standard control also prepared. Each test had been triplicated.

Result and Discussion

Physicochemical Characteristics of Modjo Tannery Wastewater

The raw wastewater was taken from Modjo tannery for physicochemical analysis. Based on this investigation the mean concentration of selected physicochemical parameters were presented at Table 1.

201 Table 1 Characteristics of Modjo Tannery Wastewater (Concentrations are in mg/L, except pH)

Parameters	Mean value	Range
pH	10.166±2.02	8-12
BOD₅	1641±373.6	1243-1984
COD	6953.333±339.4	6593-7267
NH₄-N	253.3333±11.6	240-261
NO₂-N	1.913333±0.12	1.77-1.99
NO₃-N	116.6667±26.6	94-146
TN	650.3333±93.6	546-727
PO₄-P	88.06667±40.8	46.5-128
TP	144.5333±20.8	128.6-168
TSS	1868±863.1	1217-2847
TDS	5877.3±2294.8	3250-7489
TCr	18.33±6.7	14-26

202

203 This study revealed that the mean concentration of BOD₅, COD and TSS were 1641±375.6,
 204 6953±339.4 and 1868±863.1 mg/l respectively (Table 1). This result is basically similar to
 205 different studies in Ethiopia with slight difference for different parameters for example a study

done at the same tannery industry indicated that the mean concentration of COD was laid between 7950 to 15240 mg/l with the mean of 11123 ± 563.9 mg/l (Seyoum Leta, *et al.*, 2003). Another study also undertaken with same tannery wastewater showed that the mean concentration of BOD₅ was 1054 ± 448 mg/l (Tadesse Alemu and Seyoum Leta, 2015) and the concentration of total suspended solid was found from 1217 to 2847 (Table 3.1) this is a bit greater than some studies for instance a study done in India indicated that 1244 mg/l (Tamal *et al.*, 2010).

Nutrients like orthophosphate, ammonium, nitrite and nitrate concentration of Modjo tannery were characterized in this study, the result revealed that 88 ± 40.8 , 253.3 ± 11.6 , 1.9 ± 0.12 , 116.7 ± 26.6 mg/l respectively. This result is comparable to a study done by Sivakumar *et al.*, (2015) which indicates the concentration of nitrate in untreated tannery effluent was 116mg/l. The result of ammonium is also similar to that of the results done at Bahir Dar tannery wastewater characterization (96-420 mg/l) (Aseessefa and Ayalew, 2014). According to Arasappan and Kalyanaraman (2015), the nitrite concentration of untreated tannery wastewater was 1.3 mg/l almost parallel to this study finding which accounts 1.9 ± 0.12 mg/l (Table 1). Some variation have been seen in some parameters. This variation may be due to the utilization of chemicals for different purposes and different tanning activities among tanneries.

In terms of chromium concentration, Modjo tannery comprised 18.33 ± 6.7 mg/l is similar to other different results presented from same tannery wastewater by Tadesse Alemu et al. (2016) the mean influent wastewater to the constructed wetland was 18.67 mg/l.

Likewise a variation exists in values of physicochemical parameters in general like BOD₅, COD, TSS, phosphate, sulfide, sulfate, etc. in every tannery wastewater characteristics, this may

be because of different tanning process, methods, technology and raw material utilization by various tanning industries.

Tannery Wastewater Treatment Efficiency of Horizontal Subsurface Flow Constructed Wetland with Pumice Substrate Planted with *Chrysopogon zizanioides*(CZ)

The pollutant removal efficiency of horizontal subsurface constructed wetland under this investigation was high this may be due to the high adsorption capacity of pumice and the uptake potential of *Chrysopogon zizanioides* from tannery wastewater. The characteristics of tannery wastewater after treatment was alongside with the standard guideline value of the Ethiopian environmental protection authority and WHO irrigation water quality standard (Table 2).

BOD₅, COD and TSS Removal Efficiency of HSSFCW with Pumice Substrate and Planted with *Chrysopogon Zizanioides*

The three important pollutant of the tannery wastewater were analyzed before and after treatment of four hydraulic retention time, based on the finding the final effluent concentration of BOD₅, COD and TSS in mg/l were (273±91, 532.50±177.5 and 99.72±80.93) for 3 days HRT, (74±2, 225.41±11.13 and 79±13.53) for 5 days HRT, (58.67±6.5, 214.67±32.33 and 80±4.58) for 7 days HRT and (60.67±4.93, 234.67±38.79 and 74±21.65) for 9 days HRT (Table 2).

Both BOD and COD result of 5, 7 and 9 HRT were met the standard value of WHO water quality for irrigation and EEPA (200 and 500 mg/l) but they are beyond the standard at hydraulic retention time of 3 days this is because of the time shortage to degrade organic matter. In all the allotted hydraulic retention time TSS was not achieved good result as compared to the Both WHO and EEPA guideline (50mg/l) (EEPA 2003;WHO 2011).

248 **Table 2 Characteristics of Treated Wastewater by HSSFCW with Pumice Substrate and CZ at Different HRT**

Parameters	Influent (mg/L, except for pH, EC and salinity)	Effluent Conc. at Different HRT(mg/L, except pH, EC & salinity)				EEPA &WHO irrigation WQS
		3 days	5 days	7 days	9 days	
BOD₅	1641±373.55	273±91	74±2	58.67±6.5	60.67±4.93	200
COD	6953.33 ±339.41	532.50±177.5	225.41±11.13	214.67±32.33	234.67±38.79	500
NH₄-N	253.33±11.6	26.83±2.93	5.00±4.36	4.67±1.53	6.83±1.44	30
NO₃-N	116.66 ±26.63	10.83±2.75	0±0	0.37±0.15	0.57±0.21	10
TN	650.33 ±93.62	42±15.72	8.67±5.7	6.50±1.32	9.33±2.1	60
PO₄-P	88.06 ±40.77	6.33±2.1	3.04±1	2.67±1.26	0±0	5
TP	144.53 ±20.75	19.67±3.05	7.53±2.33	5.53±0.5	83.87±11.37	10
TSS	1868±863.1	99.72±80.93	79±13.53	80±4.58	74±21.65	50
TDS	5877.3±2294.77	1504.97±1286.16	1279±75	768.67±45.54	798±17.43	2100
TCr	18.33±6.66	0.88±0.03	0.30±0.1	0.20±0.1	0.35±0.13	2

The removal efficiency of this horizontal flow subsurface constructed wetland filled with pumice substrate and planted with *Chrysopogon zozanioides* was high for the purification of tannery wastewater considering the three polluting agents with specific hydraulic retention time. During the first 3 and 5 days retention time BOD₅, COD and TSS were reduced by (83.36%, 92.34% and 94.66%) and (95.49%, 96.76% and 95.77%) respectively. After the second 7 and 9 days retention time also it reduced by (96.42%, 96.91% and 95.72%) and (96.30%, 96.62% and 96.02%) respectively (Table 3).

The result achieved due to the activities of the microorganisms and the networked and spongy tuft roots of the plant to make comfortable environment for the growth of the organism in addition to absorption. The aerobic condition in the superficial wetland bed and anaerobic condition in the bottom allow for efficient removal of organic pollutants and the filtration of the wastewater is the main reason for the removal of suspended solids. A vertical subsurface wetland planted with *Scirpus Alternifolios* and red ferralitic soil substrate was evaluated by scholars for its wastewater purification capacity and reported as BOD, COD and TSS were reduced by (84.9%, 89.8% and 98.1%) respectively (Villara *et al.*, 2012), the result is almost similar to this investigation especially with the first 3 and 5 hours retention time.

266 Table 3 Efficiency of HSSFCW with Pumice Substrate and CZ at Different HRT (Conc. in mg/L, except pH)

Param eters	Influent conc.	Percentage Removal at Different HRT							
		3 days		5 days		7 days		9 days	
		Mean Conc.	%	Mean	%	Mean	%	Mean	%
			Removal	Conc.	Removal	Conc.	Removal	Conc.	Removal
BOD₅	1641±373.55	273±91	83.36	74±2	95.49	58.67±6.5	96.42	60.67±4.93	96.30
COD	6953.33 ±339.41	532.50±177. 5	92.34	225.41±11.1 3	96.76	214.67±32 .33	96.91	234.67±38.7 9	96.62
NH₄-N	253.33±11.6	26.83±2.93	89.41	5.00±4.36	98.03	4.67±1.53	98.16	6.83±1.44	97.30
NO₃-N	116.66 ±26.63	10.83±2.75	90.72	0±0	100	0.37±0.15	99.68	0.57±0.21	99.51
TN	650.33 ±93.62	42±15.72	93.54	8.67±5.7	98.67	6.50±1.32	99.00	9.33±2.1	98.56
PO₄-P	88.06 ±40.77	6.33±2.1	92.81	3.04±1	96.55	2.67±1.26	96.97	0±0	100
TSS	1868±863.1	99.72±80.93	94.66	79±13.53	95.77	80±4.58	95.72	74±21.65	96.04
TCr	18.33±6.66	0.88±0.03	95.20	0.30±0.1	98.36	0.20±0.1	98.91	0.35±0.13	98.09

Nutrient Removal Efficiency of HSSFCW with Pumice Substrate and Planted with *Chrysopogon Zizanioides* (NH₄-N, NO₃-N, TN, PO₄-P, TP)

The plant (*Chrysopogon zizanioides*) used in this study possesses unique characteristics suitable for wastewater purification. Now a days various research findings showed its exceptional ability to absorb and to tolerate extreme levels of nutrients, to consume large quantities of water in the process of producing a massive biomass growth. These attributes indicated that this plant is highly suitable for treating high strength wastewater from different industries like tanning industries. In addition to the plant type, selection of best efficient substrate based on the selection criteria including its chemical composition is important for effective application of horizontal subsurface flow constructed wetland for the treatment of high strength industrial wastewater.

The main nutrient component concentrations like NH₄-N, NO₃-N, TN, PO₄-P and TP in Modjo tannery wastewater were determined before and after treatment using this horizontal subsurface constructed wetland to evaluate its treatment performance at four different hydraulic retention time. In the final effluent, the concentration of NH₄-N, NO₃-N, TN, PO₄-P and TP in mg/l become (26.83±2.93, 10.83±2.75, 42±15.72, 6.33±2.1 and 19.67±3.05) at 3 days HRT, (5.00±4.36, 0±0, 8.67±5.7, 3.04±1 and 7.53±2.33) at 5 days HRT, (4.67±1.53, 0.37±0.15, 6.50±1.32, 2.67±1.26 and 5.53±0.5) at 7 days HRT and (6.83±1.44, 0.57±0.21, 9.33±2.1, 0±0 and 83.87±11.37) at 9 days HRT respectively (Table 2).

When the result finding evaluated with the standard guideline value of WHO water quality standard and EEPA at different hydraulic retention time, NH₄-N and TN were under the maximum permissible limit at all retention time and NO₃-N and PO₄-P were met the specified limit value at 5, 7 and 9 days retention time only. But TP removal was good only at 5 and 7 days retention time. Therefore contact time of 5 days and greater are efficient retention time for the removal of major

nutrients from tannery wastewater using horizontal subsurface constructed wetland filled with pumice substrate and planted with *Chrysopogon zizanioides*. Substrate composition, plant type and some microorganisms in the constructed wetland were play great role for the reduction of those nutrient components.

As various scholars reported, the removal of pollutants from wastewater are achieved by different mechanisms like sedimentation, filtration, chemical precipitation, adsorption, microbial interactions, and uptake of vegetation. The nutrient removal efficiency of this subsurface constructed wetland was generally effective. The maximum removal efficiency was seen at 5, 7 and 9 days retention time. The minimum (89.41%) and maximum (98.16%) of $\text{NH}_4\text{-N}$ removal efficiency was achieved at 3 and 7 days retention time respectively. Almost all of $\text{NO}_3\text{-N}$ also removed after 5 days treatment, more than 93.5% of TN was removed, $\text{PO}_4\text{-P}$ and TP were also effectively removed in this constructed wetland, a minimum of 92.81% at 3 days HRT and maximum of 100% at 9 days HRT of $\text{PO}_4\text{-P}$ was removed likewise TP from 41.97% at 9 days HRT up to 96.17% at 7 days HRT was removed (Figure 4).

This effective result was seen mainly because of the adsorption capacity of the substrate pumice and uptake potential ability of the plant. Especially pumice is effective to remove phosphate since it contains sufficient amount of aluminum and iron that favors for the removal of phosphorus (Villara *et al.*, 2012). This study results again shows that the same trend to a study done by Nese and Ennil (2004) that indicates more than 95% nitrate removal efficiency from aqueous solution by adsorption mechanism.

On the other hand *Chrysopogon zizanioides* has high level of tolerance for high strength wastewater and very effective in removing pollutants from landfill leachates, particularly N and P. Nitrogen and Phosphorus absorption is also expedited because roots have direct exposure to

effluents (Xia *et al.*, 2000). Another study report which could support this findings also indicated that, the vetiver system is based on the use of vetiver grass (*Chrysopogon zizanioides*), which was first recognized early in the 1990s for having “super absorbent” characteristics suitable for the treatment of wastewater and leachate generated from landfill (Truong and Stone, 1996).

The efficiency of this constructed wetland in this pilot study to remove most of the hazardous pollutants from tannery wastewater was excellent. This is may be due to the cumulative effect of the plant ability and the substrate potential. The use of plants for wastewater treatment is not a new fashion. But the issue is how to improve pollutant removal efficiency. For example a project was done to examine the phytoremediation potential of water hyacinth (*Eichhornia crassipes*), water lettuce (*Pistia stratiotes*) and Vetiver (*chrysopogon zizanioides*) for the removal of Total dissolved solids from brine solution of textile industry by shallow pond system. The result reported after 10 days of operational period, water hyacinth showed maximum removal of 55.6% on 6th day, 48.7% using water lettuce on 7th day and 39.6 % on 3rd day under Vetiver treatment system (Abinaya *et al.*, 2018). Another study also was carried on constructed wetland to treat an aquaculture effluent using four species, *Cyperus giganteus* Vahl, *Typha domingensis* Pers., *Pontederia cordata* L. e *Eichhornia crassipes* in Brazil, in this study the constructed wetland perform 85.5% removal of total dissolved solid (Travaini and Sipaubu, 2012).

Chromium Removal Efficiency of HSSFCW with Pumice Substrate and Planted with *Chrysopogon zizanioides*

Chromium is a toxic heavy metal which is found in tannery wastewater and causes serious environmental problem. Constructed wetland recently used for the removal of wastewater pollutants including heavy metals like chromium, the result of this investigation presents the chromium removal efficiency of horizontal subsurface flow constructed wetland from tannery

wastewater. Based on the finding the concentration of total chromium in the tannery wastewater effluent after 3 and 5 days treatment time was (0.88 ± 0.03 mg/l and 0.30 ± 0.1 mg/l) respectively and this concentration further reduced to 0.20 ± 0.1 mg/l and 0.35 ± 0.13 mg/l after 7 and 9 days retention time respectively (Table 2). The effluent concentration at all retention time was under the standard guideline value of 2 mg/l set by WHO.

The total chromium removal efficiency of this constructed wetland with pumice substrate and *Chrysopogon zizanioides* was calculated and become 95.20 %, 98.36%, 98.91% and 98.09% at 3,5,7 and 9 days retention time respectively (Figure 5). In previous study it was observed that through increasing contact time, the removal efficiency of chromium in predetermined optimum dose of substrate powder increased significantly from 73.28% to 86.63 % (Masoud *et al.*, 2015).

In this investigation the chromium adsorption capacity of pumice was analyzed, the result showed that 58.15mg of total chromium was adsorbed per one kilogram of pumice substrate. This result is similar to the previous research finding on phytoremediation of chromium by model constructed wetland which accounts 97-99.6% at all system of the constructed wetland with different plant species (Catherine *et al.*, 2006).

The mechanism of heavy metals removal in horizontal subsurface constructed wetlands is a combination of different processes mainly physicochemical and biological which includes filtration, sedimentation, straining on the substrate, plant uptake, and precipitation as insoluble forms (Kadlec and Wallace, 2009). The most important reaction zone in constructed wetlands is the root zone (rhizosphere) where physicochemical and biological processes take place (Stottmeister *et al.*, 2003). For this reason, this high chromium removal efficiency was achieved because of the metal adsorption potential ability of pumice substrate and the uptake capacity of the plant *Chrysopogon zizanioides*. Various research works and experiments were done in both laboratory and full scale on the chromium removal efficiency of constructed wetland, for example

Dotro *et al.*, (2011) reported that 90-99% of chromium removed from tannery wastewater by subsurface constructed wetland with pea gravel substrate and Typha spp.

Comparison between Pumice (test substrate) and Gravel (Control substrate) on the Tanner Wastewater Treatment efficiency of HSSFCW Planted with CZ

The treatment efficiency of constructed wetland varied according to the type of substrate, plant type, seasonal variation, climatic change and other factors. Even though the plant type is similar in both two beds (control and study), the result of this investigation also varied between the gravel and pumice substrate (Table 4). In this investigation at the first 3 days HRT only BOD₅ and COD were removed by gravel substrate (89.05% and 93.82%) better than pumice substrate (83.36% and 92.34%) but in all other retention time the pumice substrate showed better result than gravel (Table 4; Figure 6).

381

382 Table 4 TWW Treatment Efficiency of HSSFCW with Gravel and Pumice Substrate and Planted
 383 with CZ at Different HRT

Parameters	Influent conc.(mg/l)	3days HRT		5days HRT		7days HRT		9days HRT	
		Pumice (%)	Gravel (%)	Pumice (%)	Gravel (%)	Pumice (%)	Gravel (%)	Pumice (%)	Gravel (%)
BOD₅	1641±373.55	83.36	89.05	95.49	89.58	96.42	90.96	96.30	91.85
COD	6953.33 ±339.41	92.34	93.82	96.76	95.81	96.91	95.94	96.62	96.33
NH₄-N	253.33±11.6	89.41	19.08	98.03	34.47	98.16	52.63	97.30	61.97
NO₃-N	116.66 ±26.63	90.72	66.29	100	77.15	99.68	80.86	99.51	86.00
TN	650.33 ±93.62	93.54	68.27	98.67	86.11	99.00	90.42	98.56	88.67
PO₄-P	88.06 ±40.77	92.81	90.92	96.55	95.20	96.97	95.68	100	96.33
TP	144.53 ±20.75	86.39	88.47	94.79	88.93	96.17	91.47	41.97	92.16
TSS	1868±863.1	94.66	95.41	95.77	95.93	95.72	96.09	96.04	96.25
TDS	5877.3±2294.7	74.39	79.96	78.24	79.95	86.92	81.96	86.42	81.23
TCr	18.33±6.66	95.20	96.40	98.36	97.27	98.91	97.44	98.09	97.27

384

385 The result between the study and control bed was tested using Two-Sample t-Test, the result
 386 showed that significantly differ at 95% confidence interval, p-value=0.01 and hence, this substrate

can be useful for the treatment of high strength wastewater in horizontal subsurface constructed wetland better than the conventional gravel substrate. Chromium removal efficiency of pumice substrate was better than gravel at all hydraulic time except the first three days that pumice achieved 95.2% while gravel achieved 96.4% (Table 4 and Figure 7).

The Plant Biometry and Chromium Uptake Capacity of CZ in Gravel and Pumice Substrate Beds

The biometry data of the plant *Chrysopogon zizanioides* was analyzed for both gravel and pumice substrate. The result showed that the growth of the plant at the sixth month above the ground in cm was 58.66 and 113.33 and below the ground was 43.33 and 24.33 in gravel and pumice substrate bed respectively. The plant dry weight also indicate that 77, 130.8 gm above ground and 80, 89 gm below the ground in gravel and pumice substrate respectively (Table 5).

The chromium uptake capacity of the plant in both substrate beds was evaluated and revealed that, the plant below the ground uptake more chromium than above the ground that was (8.88, 36.62mg/kg) and 10.24, 39.72gm/kg) in gravel and pumice substrate bed respectively (Table 5).

Table 5 Biometry Data of *Chrysopogon zizanioides* in Gravel and Pumice Substrate Bed

Substrate	Above Ground			Below Ground		
	Length (cm)	Dry weight (gm)	Cr Uptake (mg/kg)	Length (cm)	Dry weight (gm)	Cr Uptake (mg/kg)
Gravel	58.66	77	8.88	43.33	80	36.62
Pumice	113.33	130.8	10.24	24.33	89	39.72

Based on the result found from the biometry data, The Cr bioaccumulation factor (BAF) and Translocation factor (TF) of *Chrysopogon Zizanioides* plant species was estimated, (as a method described by Baker, *et. al.*, 2000 and Shanker *et al.*, 2004):

$$BAF = \frac{mg\ Cr/kg\ dw\ plant}{mg\ Cr/L\ Wastewater}$$

Translocation factor of Cr was also calculated as:

$$TF = \frac{mg\ Cr/kg\ dw\ above\ ground}{mg\ Cr/kg\ dw\ below\ ground}$$

Therefore BAF of this plant were above the ground (0.48, 0.56 Lkg⁻¹) and below the ground (1.99, 2.17 Lkg⁻¹) in gravel and pumice substrate beds respectively. Whereas TF were (0.24 and 0.26) in gravel and pumice substrate bed respectively.

Plants with more BAF and TF values can remove metals like chromium from the wastewater in the constructed wetland that may be due to the harvesting the areal part of the plant removes chromium from the bed. Plant species with high capacity to translocate chromium from below the ground to above the ground enhances absorption of chromium from the constructed wetland bed (Skiffington, *et al.*, 1976; Perk, 2006). Translocation can reduce again chromium concentration and hence that reduce toxicity potential of the metal ions to the root.

Conclusion

Modjo tannery wastewater characteristics was very high strength wastewater with different hazardous pollutants. The bioaccumulation and translocation factor of *Chrysopogon zizanioides* were greater in pumice substrate bed than the gravel which means that this plant can remove more chromium in pumice media than gravel one. The tannery wastewater treatment efficiency of pumice substrate was better than gravel substrate.

426 Horizontal subsurface flow constructed wetland with pumice substrate and *Chrysopogon*
427 *zizanioides* plant species has a potential to treat high strength tannery wastewater by different
428 mechanisms including adsorption, filtration, microbial activities and plant uptake. Therefore the
429 use of such kind of constructed wetland with locally-available low-cost substrate and potential
430 plant type may contribute to the low technology solution for sustainable industrial wastewater
431 management in ecofriendly manner.

432 **Declarations**

433 **List of abbreviations**

434 APHA: American Public Health Association; BOD: Biological Oxygen Demand; COD: Chemical
435 Oxygen Demand; DO: Dissolved Oxygen; EPA: Environmental Protection Authority; ES:
436 Effective Size; FAAS: Flame Atomic Absorption Spectrophotometer; HRT: Hydraulic Retention
437 Time; HSSFCW: Horizontal Subsurface Flow Constructed Wetland; TSS: Total Suspended
438 Solids; TWW: Tannery Wastewater; UC: Uniformity Coefficient; UNIDO: United Nations
439 Industrial Development Organization;

440 **Ethics approval and consent to participate**

441 Not applicable

442 **Consent for publication**

443 Not applicable

444 **Availability of data and materials**

The dataset and materials used for this manuscript is available and can be shared whenever necessary. Data was generated by the author from the field substrate and plant sample collection, Constructed wetland design, construction and laboratory analysis.

Competing interests

The authors declare that they have no competing interests

Funding

The first author is grateful to Dilla and Addis Ababa University in supporting for expenditures during laboratory analysis.

Authors Contribution

All authors have made an essential intellectual contribution to this study. MBA designed the study, conducted the experiments, Collected, analyzed and interpreted the data and wrote the manuscript. SLA supervised the experiment, provided comments and suggestion for the whole work. MMK supervised and provided pertinent comments and suggestion on the manuscript. All authors read and approved the final manuscript.

Acknowledgements

The principal investigator would like to thank Dilla and Addis Ababa University for financial support

Authors' information

Mekonnen Birhanie Aregu is Assistant professor of Environmental health, school of public health, college of health science and medicine, Dilla University. He has given Public health, Environmental health science and technology courses and also contribute in community services

and problem solving applied research activities and published several articles in the internationally peer reviewed journals. He is also a senior consultant in environmental health, waste management and emission control.

Seyoum Leta Asfaw (PhD) is an Associate professor of environmental pollution and sanitation stream, Center for environmental sciences, Addis Ababa University. He has given various courses in the stream. He is also supervising and monitoring several PhDs and MSc students in the areas of environmental biotechnology, wastewater treatment and water quality studies, waste to energy (resource recovery and climate change mitigation and adaptation studies), bioremediation, phytoremediation, microbial ecological studies, environmental sanitation. He has published several peer reviewed papers in different international reputable journals. Currently, he is also executive Director for Horn of Africa Regional Environmental Centre and Network (HOARECN).

He has more than 20 years of experience in environmental science and technology studies and management. He had also been a regional program manager for the Bio-resources innovation network for Eastern Africa development. He has also been the principal investigator for a number of research projects such as “Development of innovative technologies for the sustainable treatment of high strength wastewater in East Africa”, a regional research program involving Ethiopia, Kenya, Tanzania and Uganda funded by Sida. He developed an innovative, integrated pilot technology for the treatment of agro-process wastewater, generating biogas, biofertilizer, and clean water at Modjo Tannery, Addis Ababa, Ethiopia.

Professor Mohammed Mazharuddin Khan (PhD) is a professor of Environmental Science at Center for Environmental Sciences, Addis Ababa University. He is the CHARLES DARWIN GOLD MEDAL was conferred on the 27th day of June, 2009 towards the contribution made in

the field of Life Science by International society for Ecological communication at Vinoba Bhave university, Hazaribagh, Jharkhand, India. He has given several courses like Botany, Biotechnology, Environmental sciences, Ecology, Microbiology, and Environmental Microbiology at postgraduate and undergraduate level. He is also a founder of different organizations, moreover he is a member of more than eight international professional associations and societies and served in different positions. Professor Khan has published several internationally peer reviewed papers.

References

- Abinaya, S., Saraswathi, R., Rajamohan, S. and Mohammed S.A.M. (2018): Phyto-remediation of total dissolved solids (TDS) by *Eichhornia Crassipes*, *Pistia Stratiotes* and *Chrysopogon Zizanioides* from second stage RO-Brine solution, Res. J. Chem. Environ., 22 (5): 36-41.
- APHA (2005): Standard Methods for the Examination of Water and Wastewater, 21stedn. American Public health association, Washington.
- Arasappan, S. and Kalyanaraman, R. (2015): Characterization of Physicochemical Parameters and heavy metal Analysis of Tannery Effluent. Int.J.Curr.Microbiol.App.Sci 4(9): 349-359.
- Assefa Wosnie, Ayalew Wondie (2014): Bahir Dar tannery effluent characterization and its impact on the head of Blue Nile River. Afr. J Environ. Sci. Technol 8 (6):312-318.
- Babel, S. and Kurniawan, T.A. (2003): Low-cost adsorbents for heavy metal uptake from contaminated water: A review, *J. Hazard. Mat.* , 97:219-243.
- Baker, ATM. Mcgranth, Reeves, RD. and Smith, JAC. (2000): Metal Hyper Accumulator Plants. A review of the Ecology and Physiology of Biochemical Resource for Phytoremediation of

510 Contaminated Soil and Water: PP.85-107.

511 Catherine, M., Sylvia, C., John, W., Elias, T. (2006): Phytoremediation of chromium by model
512 constructed wetland, *Bioresource Technology* 97: 1767-1772.

513 Dotro, G., Larsen, D., Paul, P. (2011): Preliminary evaluation of biological and physical chemical
514 chromium removal mechanisms in gravel Media used in constructed wetlands. *Water Air Soil*
515 *Pollut.* 215: 507-515.

516 EEPA (Federal Environmental Protection Authority of Ethiopia) (2003): Standards for industrial
517 pollution control in Ethiopia, Part Three: Standards for Industrial effluents. ESIS project
518 US/ETH/99/ 068/ETHIOPIA, EPA/UNIDO, Addis Ababa.

519 Kadlec R. H., and Knight R. L. (1996): *Treatment Wetlands*. Lewis Publishers, Boca Raton, FL.

520 Kadlec, R.H., Wallace, S. (2009): *Treatment Wetlands*, second ed. Boca Raton: CRC press, Boca
521 Raton, Florida, USA.

522 Kawser, A.M.d., Monika, D., Monirul, I.M., Mosammat, S.A., Shahidul, I. and Muhammad A.A.
523 (2011): Physicochemical Properties of Tannery and Textile Effluents and Surface Water of
524 River Buriganga and Karnatoli, Bangladesh, *World Applied Sciences Journal* 12 (2): 152-159,
525 ISSN 1818-4952.

526 Kivaisi, A. K. (2001): The potential for constructed wetlands for wastewater treatment and reuse
527 in developing countries: A review. *Ecological Engineering*, Vol.16.

528 Masoud Moradi, Lida Hemati, Meghdad Pirsahab and Kiomars Sharafi, (2015). Removal of
529 Hexavalent Chromium from Aqueous Solution by Powdered Scoria-Equilibrium Isotherms and
530 Kinetic Studies, *World Applied Sciences Journal* 33 (3): 393-400.

531

532 Nese and Ennil (2004) Nitrate removal from aqueous solution by adsorption onto various
533 materials, *Journal of Hazardous Materials*, B112: 155-162.

534 Perk, M.V.D. (2006): Soil and Water Contamination: From Molecular to Catchments Scale.
535 London; JK.

536 Reddy, K. (2004): Phosphorus Cycling in Wetlands Associated with Agricultural Water Shades.
537 Nutrient Management in Agricultural Watersheds—A wetland Solution- ‘A symposium
538 conducted at Teagases Research Center, Johnstown Castle, Cowexford, Ireland 24-25.

539 Seyoum Leta, Fassil Asefa, Gunnel, D. (2003): Characterization of tannery wastewater and
540 assessment of downstream pollution profiles along ModjoRiver in Ethiopia, *Ethiopian Journal*
541 *of Biological Sciences* 2 (2): 157-168.

542 Shanker, A.K., Djanaguiraman, M., Sudhagar, R., Chandrashekar, C.N. and Pathmanabhan, G.
543 (2004): *Plant Science*. 166:1035.

544 Sivakumar, P., Kanagappan, M. and Sam M.D.S. (2015): Physicochemical Characteristics of
545 Untreated Effluent from Tannery Industries in TamMil Nadu: A Comparative Study, *Int J*
546 *Pharm Bio Sci.*, 6(1): (B) 446-451.

547 Skeffington, R., Shwery, PA., Peterson, PJ. (1976): Chromium Uptake and Transport in Barely
548 Seedlings (*Hordeum vulgare* L.). *Plantrta (Ber)* 132:209-214.

549 Stottmeister, U., Wiebner, A., Kuschik, P., Kappelmeyer, U., Kastner, M., Bederski, O., Muller,
550 R.A., Moormann, H. (2003): Effects of plants and microorganisms in constructed wetlands for
551 wastewater treatment. *Biotechnol. Adv.* 22:93-117.

552 Suthanthararajan, R., Ravindranath, E., Chits, K., Umamaheswari, B., Ramesh, T., Rajamam, S.
553 (2004): Membrane application for recovery and reuse of water from treated tannery wastewater,

554 *Desalination* 164:151-156.

555 Tadesse Alemu and Seyoum Leta (2015): Evaluation of selected wetland plants for removal of

556 chromium from tannery wastewater in constructed wetland, Ethiopia. *A J Environmental*

557 *science and technology* 9 (5): 420-427.

558 Tadesse Alemu, Eshetu Lemma, Andualem Mekonnen, Seyoum Leta (2016): Performance of Pilot

559 Scale Anaerobic-SBR System Integrated with Constructed Wetlands for the Treatment of

560 Tannery Wastewater, *Environ. Process.* 3:815–827, DOI 10.1007/s40710-016-0171-1.

561 Tamal, M., Dalia, D., Subhasis, M., Siddhartha, D. (2010): Treatment of leather industry

562 wastewater by aerobic biological and Fenton oxidation process, *J Hazardous Materials* 180:

563 204-211.

564 Tomokin, O. (2000): A Pilot Study on Municipal Wastewater Treatment Using a Constructed

565 Wetland in Uganda. UNESCO-IHE Dissertation, Serious Information J. Taylor & Francis

566 Engineering, Water and Earth Sciences. www.blakema.nl/series.

567 Travaini, L.F. and Sipaubu, T.L.H. (2012): Efficiency of a constructed wetland for wastewaters

568 treatment, *Acta Limnologica Brasiliensia*, 24 (3): 255-265.

569 Truong, P. and Stone, R. (1996): Vetiver grass for landfill rehabilitation: Erosion and leachate

570 control, Report to DNR and Redland Shire Council, Queensland, Australia.

571 UNIDO (2012): Technical assistance project for the upgrading of the Ethiopian leather and leather

572 products industry, Independent Evaluation Report Ethiopia.

573 https://www.unido.org/fileadmin/user/Evaluation/Ethiopia_leather_valuation

574 FINAL_report_131302.pdf. Accessed Sep 2016.

575 Villara, M.M., Domínguez, E.R., Tackb, F., Ruiza, J.M, Moralesa, R.S., Arteaga, L.E (2012):

576 Vertical subsurface wetlands for wastewater purification, 20th International Congress of
577 Chemical and Process Engineering CHISA 2012, 25-29 August 2012, Prague, Czech Republic,
578 Procedia Engineering 42: 1960 -1968, Available online at www.sciencedirect.com.
579 Vymazal J. (2010): Constructed wetlands for wastewater treatment: five decades of experience
580 *Environmental Science and Technology*, vol. 45.
581 WHO (1996): Guidelines for drinking water quality, vol 2: Health criteria and other supporting
582 information, Geneva.
583 Xia, H., Liu, S. and Ao, H. (2000): Study on purification and uptake of garbage leachate by vetiver
584 grass., In: Proc. of the 2nd International Conference on Vetiver, Thailand.