

A robust LU polynomial matrix decomposition for spatial multiplexing

Moustapha Mbaye

Universite Cheikh Anta Diop

Moussa Diallo

Universite Cheikh Anta Diop

Mamadou Mboup (✉ mamadou.mboup@univ-reims.fr)

Universite de Reims Champagne-Ardenne <https://orcid.org/0000-0002-9212-7038>

Research

Keywords: Polynomial matrix decomposition, LU decomposition, Beamforming, MIMO wideband system, time-domain spatial multiplexing

Posted Date: August 4th, 2020

DOI: <https://doi.org/10.21203/rs.3.rs-50211/v1>

License:   This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Version of Record: A version of this preprint was published on November 10th, 2020. See the published version at <https://doi.org/10.1186/s13634-020-00705-3>.

RESEARCH

A robust LU polynomial matrix decomposition for spatial multiplexing

Moustapha Mbaye¹, Moussa Diallo¹ and Mamadou Mboup^{2*}

*Correspondence:

Mamadou.Mboup@univ-reims.fr

²CRESTIC–Université de Reims

Champagne Ardenne, BP 1039

Moulin de la Housse, 51687,

Reims cedex 2, France

Full list of author information is available at the end of the article

Abstract

This paper considers time-domain spatial multiplexing in MIMO wideband system, using an LU-based polynomial matrix decomposition. Because the corresponding pre- and post-filters are not paraunitary, the noise output power is amplified and the performance of the system is degraded, compared to QR-based spatial multiplexing approach. Degradations are important as the post-filter polynomial matrix is ill-conditioned. In this paper, we introduce simple transformations on the decomposition that solve the ill-conditioning problem. We show that this results in a MIMO spatial multiplexing scheme that is robust to noise and channel estimation errors. In the latter context, the proposed LU-based beamforming compares favorably to the QR-based counterpart in terms of complexity and bit error rate.

Keywords: Polynomial matrix decomposition; LU decomposition; Beamforming; MIMO wideband system; time-domain spatial multiplexing

1 Introduction

Multiple-input multiple-output (MIMO) technique can provide high spatial freedom to increase reliability and throughput. This technique has attracted a lot of attentions [1] and has been widely used in various wireless communication standards. One of the key advantages of MIMO spatial multiplexing is the fact that it is able to provide additional data capacity. MIMO spatial multiplexing achieves this by exploiting the multiple paths and effectively using them as additional “channels” to carry data.

In wideband, due to the delay spread of the different multipath components, the received signal can no longer be characterized by just an amplitude and phase random processes [2]. The effect of multipath on wideband signals must therefore take into account the multipath delay spread variations. The wireless channel between a single transmit-receive pair is therefore finite impulse response (FIR) filter in nature. This is due to the transmitted signal arriving at the receiver over multiple paths and with different time delays [3]. This FIR filter will take the form of a polynomial in the indeterminate variable z^{-1} , which is used to represent a unit delay. In this case, for a wireless system consisting of N_t transmit antennas and N_r receive antennas, the multipath channel transfer function can be represented by a $N_r \times N_t$ polynomial matrix, denoted $H(z)$. The received signal on each antenna is a superposition of signals from the different transmit antennas called co-channel interference (CCI).

In order to recover the transmitted data sequence corrupted by channel interference, a conventional method is the spatio-temporal vector coding (STVC) [4]. STVC

structure is suggested as a theoretical means for achieving capacity and a reduced complexity discrete matrix multitone (DMMT) technique is implemented by the authors to exploit the frequency selective MIMO channel. It is based on discrete multitone which is a technique that uses the discrete Fourier transform (DFT) to implement frequency-division multiplexing (FDM). DMMT is essentially analogous to OFDM [5] approach : the wideband problem is reduced to a narrowband form by using a DFT or FFT to split the data into narrower frequency bands and applying an SVD at each frequency to decorrelate the signals [6]. This approach ignores correlations between frequency bands and the SVD will order the output channels according to power in each individual band leading to a lack of phase coherence [7]. An alternative is to consider time-domain scheme for which the diagonalization of the temporal MIMO channel can be performed once for the entire system [8]. This design, based on polynomial matrix decomposition, transforms the MIMO channel into a number of independent single-input single output (SISO) sub-channels. This is one of the most efficient techniques which is done by a factorization of the MIMO channel polynomial matrix as:

$$H(z) = U(z)D(z)V(z), \quad (1)$$

where $U(z)$ and $V(z)$ are square matrices of sizes N_r and N_t respectively. If the inverses of $V(z)$ and $U(z)$, assuming they are stable and causal, are inserted into the transmission chain respectively as pre- and post-filters, then the original MIMO channel becomes equivalent to $D(z)$. Diagonalization of $H(z)$, *viz.* the factorization in (1) with $D(z)$ diagonal, therefore reduces the MIMO wideband channel to $N = \min(N_t, N_r)$ independent SISO sub-channels, thereby cancelling the CCI. Such decomposition is most commonly achieved using the popular Polynomial Singular Value Decomposition (PSVD) method, leading to para-unitary factors $U(z)$ and $V(z)$. This paraunitaryness assures that the power distributions of the signal and noise remain unaltered after post-filtering. However, given a polynomial matrix, a PSVD factorization as described above does not exist in general [9]. By contrast, the MIMO spatial multiplexing scheme presented in [10], [11], completely eliminates the CCI. This beamforming method is inspired from a blind equalization method exploiting the Bezout identity [12], [13]. It is based on a combination of the classical Smith canonical form and LU (Gauss elimination). The decomposition method in [11], called LU-PMD (LU-Polynomial Matrix Decomposition), is effective and does not require any iteration: the algorithm ends up after a finite and prescribed number of steps, with a matrix $D(z)$ which is exactly diagonal. Moreover, it was shown in [11] that unless for some improbable original MIMO channel, all but except the last resulting independent SISO subchannels reduce to simple additive noise channels. Therefore, in addition to completely cancelling the CCI, this decomposition also inherently avoids the ISI problem.

However the corresponding factors $U(z)$ and $V(z)$ are unimodular and not para-unitary as in the QR-based methods. The loss of the latter property induces a serious limitation consisting in an output noise enhancement. The role of the post-filter in this performance degradation was clarified: The degradation becomes severe as the norm and the condition number of the post-filter matrix-valued transfer function

increase. Improving the post-filter matrix conditioning by a simple row balancing was proposed in [14]. Significant improvement of the performance, in terms of bit error rate, has been observed.

In this paper, we revisit the LU-based factorization in [11], in combination with the row balancing trick in [14]. We show that the resulting transformations solve the ill-conditioning problem and lead to a MIMO spatial multiplexing scheme that is robust to noise and channel estimation errors. In the latter context, the proposed LU-based beamforming compares favorably to the QR-based counterpart in terms of both complexity and bit error rate.

The structure of this paper is as follow. Section 2 is devoted to the LU-based decomposition method for MIMO spatial multiplexing scheme. The noise enhancement problem is also explained. Two solutions, and a combination of both, are presented in section 3. Simulation results showing that the proposed LU-Based decomposition significantly reduces the noise enhancement are given in section 3.2 with comparison with the QR-based scheme. The robustness of the proposed scheme to channel estimation errors is discussed in section 4 with comparison with the QR-based scheme. Finally, concluding remarks are given in section 5.

2 Methods

2.1 MIMO spatial multiplexing scheme

Let us consider a MIMO communication system which has N_t transmitting antennas and N_r receiving antennas through a channel represented by its transfert matrix-valued function $H(z) \in \mathbb{C}^{N_r \times N_t}$. Let $\{x_{i,k}\}_{k \in \mathbb{N}}$ denote the equivalent discrete-time causal signal on the transmit antenna $i \in \{1, \dots, N_t\}$ and define by

$$x_i(z) = \sum_{k \geq 0} x_{i,k} z^{-k} \quad (2)$$

its associated Z -transform. We use the boldface notation $\mathbf{x}(z)$ for the column vector of size N_t given by $\mathbf{x}(z) = [x_1(z) \ \dots \ x_{N_t}(z)]^T$, where the superscript T stands for the transpose operator. Likewise, we denote by $\mathbf{y}(z)$, the vector collecting the z -transforms of the discrete-time signals recorded on the N_r receiving antennas. The MIMO channel input-output relation can therefore be described in the z -transform domain by

$$\mathbf{y}(z) = H(z)\mathbf{x}(z) + \mathbf{n}(z), \quad (3)$$

where $\mathbf{n}(z)$ stands for the z -transform of a sample realisation of the noise corruption $\mathbf{n} \in \mathbb{C}^{N_r \times 1}$. Assume that the channel's transfert matrix $H(z)$ admits a factorization as in (1), *i.e.* $H(z) = U(z)D(z)V(z)$. Then, using the inverse of the factors $U(z)$ and $V(z)$, noted by

$$U_{po}(z) \triangleq U(z)^{-1} \quad \text{and} \quad V_{pr}(z) \triangleq V(z)^{-1}$$

respectively as post- and pre-filters, allows one to reduce the original MIMO channel into the simpler form $D(z)$. Indeed, if the original signal is pre-filtered before

transmission as in $\hat{\mathbf{x}}(z) = V_{pr}(z)\mathbf{x}(z) = [\hat{x}_1(z) \cdots \hat{x}_{N_t}(z)]^T$, then the corresponding channel's output becomes $\hat{\mathbf{y}}(z) = H(z)\hat{\mathbf{x}}(z) + \mathbf{n}(z)$. Thus, the post-filtering step $\tilde{\mathbf{y}}(z) = U_{po}(z)\hat{\mathbf{y}}(z)$ yields the final equivalent system

$$\tilde{\mathbf{y}}(z) = D(z)\mathbf{x}(z) + \tilde{\mathbf{n}}(z), \quad (4)$$

where we have set $\tilde{\mathbf{n}}(z) \triangleq U_{po}(z)\mathbf{n}(z)$ for the noise after post-filtering.

The decomposition in equation (1) is mostly performed by polynomial matrix SVD decomposition. The corresponding factors $V(z)$ and $U(z)$ are then expected to be para-unitary, which means that they satisfy

$$U(z)^*U(z) = I \text{ and } V(z)V(z)^* = I, \quad \text{for all } z \in \mathbb{C},$$

where the notation $*$ stands for the para-Hermitian conjugation, that is $F(z)^* \triangleq \overline{F(1/\bar{z})}^T$ and I is the identity matrix of appropriate size. Thereby the pre- and post-filters $V_{pr}(z) = V(z)^*$ and $U_{po}(z) = U(z)^*$ are also para-unitary and setting $\mathbb{E}(\cdot)$ for the mathematical expectation, we have

$$\begin{aligned} \|\tilde{\mathbf{n}}(z)\|_2^2 &\triangleq \int_{|z|=1} \mathbb{E}[\tilde{\mathbf{n}}(z)^*\tilde{\mathbf{n}}(z)] \frac{dz}{z} = \int_{|z|=1} \mathbb{E}[\mathbf{n}(z)^*U_{po}(z)^*U_{po}(z)\mathbf{n}(z)] \frac{dz}{z} \\ &= \int_{|z|=1} \mathbb{E}[\mathbf{n}(z)^*\mathbf{n}(z)] \frac{dz}{z} \triangleq \|\mathbf{n}(z)\|_2^2. \end{aligned}$$

Likewise, we obtain $\|\hat{\mathbf{x}}(z)\|_2^2 = \|\mathbf{x}(z)\|_2^2$ showing that, in this case, the pre- and post-filtering do not modify the mean power of the original signal and noise stochastic processes. Unfortunately, polynomial matrix SVD does not exist in general. Of course an SVD decomposition is clearly feasible if one relaxes the constrain of the factors being polynomial. But then, the presence of poles can lead to instability. Instead, a common solution is to consider a Laurent polynomial matrix decomposition. Several iterative algorithms have been proposed to obtain approximate Laurent polynomial matrix SVD [15], [16], [17], [18]. These methods can only generate approximately diagonal matrices $D(z)$, leading to inevitable residual CCI. The residual CCI may be drastically reduced by increasing the number of iterations in the algorithms but at the expense of large order of the polynomial $D(z)$, which translates into increased complexity and more intersymbol interference (ISI) on each resulting SISO channel. Polynomial order truncation is introduced to limit the degrees of the polynomials. But, this truncation can affect the paraunitarity property of the pre- and post-filters.

In this regard, a MIMO beamforming scheme based on a combination of the classical Smith canonical form and LU (Gauss elimination) was presented in [11] as alternative solution.

2.2 LU-Based polynomial matrix decomposition (LU-PMD)

This approach follows the same steps as the classical LU factorization. However in each step, a preprocessing by the first step of the decomposition in Smith canonical

form is considered. This preprocessing solves a Bezout equation in order to reduce the pivot element to a constant. We first obtain

$$H(z) = U(z)R(z) \quad (5)$$

where $U(z)$ and $R(z)$ are respectively $N_r \times N_r$ -unimodular and $N_r \times N_t$ -upper triangular polynomial matrices. Next, the same decomposition is applied to $R(z)^T$ to obtain

$$R(z)^T = V(z)^T D(z), \quad (6)$$

where $V(z)$ is $N_t \times N_t$ -unimodular like $U(z)$ in (5). Then, for $N_r \geq N_t$, a common setting in MIMO systems, the factorization (1) follows with

$$D(z) = \begin{bmatrix} \tilde{D}(z) \\ \dots\dots\dots \\ O_{N_r-N_t, N_t} \end{bmatrix}. \quad (7)$$


where $\tilde{D}(z)$ is an $N_t \times N_t$ -diagonal matrix and where $O_{i,j}$ denotes the zero matrix of size $i \times j$.

2.3 Noise amplification problem

First, observe as in [14], that if the channel's output noise \mathbf{n} is spatially and temporally white, *i.e.* with power spectral density matrix $E[\mathbf{n}(z)\mathbf{n}(z)^*] = \sigma^2 I_{N_r}$, then the post-filtered noise power reads as

$$\|\tilde{\mathbf{n}}(z)\|_2^2 = \sigma^2 \|U_{po}(z)\|_2^2. \quad (8)$$

The noise component in the equivalent reduced system (*i.e.* after pre- and post-filtering) is thus amplified with respect to the original system whenever the norm of the post-filter is high. This is illustrated in figure 2.3 below.



In this experiment, a complete OFDM communication system is simulated with a 4-QAM modulation. The sequence $\{x_{i,k}\}_{k \geq 0}$ in (2) then represents the i^{th} OFDM signal, including a cyclic prefix. The performance of the LU-based spatial multiplexing is measured by the corresponding bit error rate versus the SNR. Four different 3×3 MIMO channels, each corrupted by a unit-variance spacial-temporal white noise are considered. The performance significantly degrades as the norm of the post-filter increases.

Clearly, this performance loss cannot be explained only by the noise power enhancement since the output signal $\tilde{\mathbf{y}}$ also undergoes the same post-filtering. Therefore, an analysis based on signal-to-noise ratios is more relevant.


To proceed, note that the post-filtering operation amounts to the resolution of the linear perturbed system $U(z)\tilde{\mathbf{y}}(z) = H(z)\tilde{\mathbf{x}}(z) + \mathbf{n}(z)$, with the error term $\tilde{\mathbf{n}}(z)$. Let us denote by $\kappa(U) \triangleq \|U(z)\| \|U(z)^{-1}\|$ the condition number of the matrix $U(z)$ with respect to the L_2 matrix norm

$$\|U(\cdot)\|^2 \triangleq \frac{1}{2\pi} \int_0^{2\pi} \text{Tr} \left[\overline{U(e^{i\omega})}^T U(e^{i\omega}) \right] d\omega = \int_{|z|=1} \text{Tr} [U(z)^* U(z)] \frac{dz}{z}$$

where $\text{Tr}(\cdot)$ is the trace operator. Now, compare the communication systems in (3) and (4) in the light of classical perturbation analysis [19]. The corresponding noise-to-signal ratios are then related by (see [14]):



$$\frac{\|\tilde{\mathbf{n}}(z)\|_2}{\|D(z)\mathbf{x}(z)\|_2} \leq \kappa(U) \frac{\|\mathbf{n}(z)\|_2}{\|H(z)\tilde{\mathbf{x}}(z)\|_2}. \quad (9)$$

When the post-filter $U(z)$ is ill-conditioned, *i.e.* $\kappa(U) \gg 1$, the noise-to-signal ratio can be significantly higher for the reduced system than for the original system. This explains the performance degradation observed in the experiment reported in figure 2.



In this experiment, we have considered again the previous setting, with 3×3 randomly selected MIMO channels with Rayleigh distribution. The system's performance is measured by the corresponding bit error rate versus the SNR. The same

experiment is then repeated with 4×4 and 5×5 MIMO channels in figures 3 and 4, respectively. All these experiments confirm a drop in performance as the condition number of the post-filter increases.



A row balancing of the post-filter was proposed in [14] as a solution to keep both the norm and the condition number of the post-filter low (see [20]). This method consists in replacing the preceding post-filter $U_{po}(z)$ by

$$S(z) = WU_{po}(z), \tag{10}$$

where W is a diagonal constant matrix selected such that each row of $S(z)$ has unit norm. The diagonal elements $W_{i,i}$ of W then read as:

$$W_{i,i} = \frac{1}{\| [U_{po}(z)]_i \|_2}, \quad i = 1, \dots, N_r \tag{11}$$

where $[A]_i$ denotes the i^{th} row of matrix A . Accordingly, the channel's output signal, after this modified post-filtering would read as:

$$\check{\mathbf{y}}(z) = W\tilde{\mathbf{y}}(z) = WD(z)\mathbf{x}(z) + S(z)\mathbf{n}(z). \quad (12)$$

Good performance in terms of bit error rate was observed.

Despite this improvement, the LU-based polynomial matrix decomposition for MIMO beamforming remains less competitive than the state-of-the-art methods because of the post-filter noise amplification.

3 Results

3.1 A robust decomposition

3.1.1 Source of ill-conditioning

To identify where the above mentioned ill-conditioning stems from, let us recall one iteration of the LU-based factorization (see [11]). Indeed, the decomposition of $H(z)$ in (5) derives from a recursion of the form

$$H_k(z) = \Phi_{k-1}(z)H_{k-1}(z) = \Phi_{k-1}(z)\Phi_{k-2}(z) \cdots \Phi_{k-m}(z)H_{k-m}(z) \quad (13)$$

$$= \Phi^{(k-1)}(z)H_0(z) \quad (14)$$

initialized to $H_0(z) = H(z)$ and ending at $H_N(z) = R(z)$, with $N = \min(N_r - 1, N_t)$. The $(k-1)^{\text{th}}$ iterate leads to

$$H_{k-1}(z) = \begin{bmatrix} d_1(z) & h_{1,2}^{(k)}(z) & \cdots & h_{1,k-1}^{(k)}(z) & \vdots & h_{1,k}^{(k)}(z) & \cdots & h_{1,N_t}^{(k)}(z) \\ 0 & d_2(z) & \ddots & \vdots & \vdots & \vdots & \cdots & \vdots \\ \vdots & & \ddots & h_{k-2,k-1}^{(k)}(z) & \vdots & \vdots & \cdots & \vdots \\ 0 & & \ddots & d_{k-1}(z) & h_{k-1,k}^{(k)}(z) & \cdots & h_{k-1,N_t}^{(k)}(z) \\ \hline 0 & \ddots & 0 & \vdots & h_{k,k}^{(k)}(z) & \cdots & h_{k,N_t}^{(k)}(z) \\ \vdots & & \vdots & \vdots & \vdots & & \vdots \\ 0 & \cdots & 0 & \vdots & h_{N_r,k}^{(k)}(z) & \cdots & h_{N_r,N_t}^{(k)}(z) \end{bmatrix}. \quad (15)$$

Then, the k^{th} diagonal entry $h_{k,k}^{(k)}(z)$ is reduced to the greatest common divisor (gcd) of the polynomials $h_{k+\ell,k}^{(k)}(z), \ell = 0, \dots, N_r - k$, through the recursion

$$\begin{cases} d_{k,0}(z) = h_{k,k}^{(k)}(z) \\ d_{k,\ell}(z) = \text{gcd}(d_{k,\ell-1}(z), h_{k+\ell,k}^{(k)}(z)) \end{cases}$$

which runs until $\ell = \ell_k$ such that either $1 \leq \ell_k < N_r - k$ and $d_{k,\ell_k}(z) = 1$ or $\ell_k = N_r - k$. Each iteration ℓ of this recursion is implemented in matrix form by a

left multiplication by

$$\bar{A}_{k,\ell}(z) = \begin{bmatrix} I_{k-1} & & & \\ & h_{k,k}^\#(z) & & h_{k+\ell,k}^\#(z) \\ & & I_{\ell-1} & \\ & -\hat{d}_{k,\ell-1}(z) & & \hat{h}_{k+\ell,k}^{(k)}(z) \\ & & & I_{N_r-k-\ell} \end{bmatrix}, \quad (16)$$

where $\hat{d}_{k,\ell-1}(z)$ and $\hat{h}_{k+\ell,k}^{(k)}(z)$ are respectively the quotients of $d_{k,\ell-1}(z)$ and $h_{k+\ell,k}^{(k)}(z)$ by their gcd $d_{k,\ell}(z)$ and where $h_{k,k}^\#(z)$ and $h_{k+\ell,k}^\#(z)$ are obtained from the Bezout equation

$$h_{k,k}^\#(z)d_{k,\ell-1}(z) + h_{k+\ell,k}^\#(z)h_{k+\ell,k}^{(k)}(z) = d_{k,\ell}(z).$$

Next, the k^{th} iteration of the recursion (13) is completed by a Gaussian elimination step. This is achieved by left multiplying $\bar{A}_k(z) = \bar{A}_{k,\ell_k}(z)\bar{A}_{k,\ell_k-1}(z)\cdots\bar{A}_{k,1}(z)$ by the polynomial matrix

$$\bar{L}_k(z) = \begin{bmatrix} I_{k-1} & & \\ & 1 & \\ & \mathbf{f}_k(z) & I_{N_r-k} \end{bmatrix} \quad (17)$$

where $\mathbf{f}_k(z) = [0 \cdots 0 \underbrace{\quad}_{\ell_k-1 \text{ zeros}} h_{k+\ell_k+1,k}^{(k)}(z) \cdots h_{N_r,k}^{(k)}(z)]^t$. The polynomial transition matrix in the recursion (13) then readily reads as $\Phi_k(z) = \bar{L}_k(z)\bar{A}_k(z)$ and has the block diagonal form

$$\Phi_k(z) = \begin{bmatrix} I_{k-1} & \\ & \Psi_k(z) \end{bmatrix} \quad (18)$$

for some polynomial matrix $\Psi_k(z)$. The first $k-1$ rows of $\Phi^{(k)}(z) = \Phi_k(z)\Phi^{(k-1)}(z)$ are therefore identical to that of $\Phi^{(k-1)}(z)$. Meanwhile, the degrees of the remaining rows are increased, compared to $\Phi^{(k-1)}(z)$, because of the left multiplication by the polynomial matrix $\Psi_k(z)$. As a consequence, the final matrix

$$\Phi^{(N-1)}(z) = \Phi_{N-1}(z)\Phi_{N-2}(z)\cdots\Phi_0(z),$$

which coincides with $U_{po}(z) = U(z)^{-1} = \Phi^{(N-1)}(z)$ is badly scaled. This explains why the post-filter is ill-conditioned [20].

3.1.2 A robust post-filter

As explained above, the row unbalancing induced by the iterations of the decomposition leads to an ill-conditioned post-filter. Observe that the reduction steps of the decomposition, implemented by the multiplications by the polynomial matrices $\bar{A}_k(z)$, is one of the main sources of the row unbalance. Recall that these steps are applied to each iteration k , to reduce the pivot (diagonal element of column k) to the

greatest common divisor of the pivot and the polynomials in column k beneath the diagonal. As already mentioned, the iterations described in the preceding subsection are applied to $R(z)^T$ to complete the decomposition (1). Consider the iteration k in this context and call $d(z)$ the gcd of the pivot and the polynomials in column k of $R(z)^T$, beneath the diagonal. As a result of the factorization (5) described above, the corresponding pivot is already the greatest common divisor of all the subchannels from the original k^{th} transmit antenna to the receive antennas k, \dots, N_r . Now, the reduction step for this iteration seeks $d(z)$ as the gcd of 1) all subchannels from the original k^{th} transmit antenna to the receive antennas k, \dots, N_r and 2) all the subchannels linking the transmit antennas k, \dots, N_t with the k^{th} receive antenna. Most likely, $d(z)$ will be equal to one, leading to $\bar{A}_k(z) \equiv I_N$. A direct consequence is that the pre-filter $V_{pr}(z)$ is better conditioned than the post-filter $U_{po}(z)$.

We thus come to the conclusion that the noise amplification can be avoided by a simple modification in the decomposition by swapping the order in which the pre- and post-filters are computed. To see this, let us consider the decomposition in (1) applied to $G(z) = H(z)^T$ instead of $H(z)$, i.e.

$$G(z) = H(z)^T = U(z)D(z)V(z). \quad (19)$$

Then transposing back again, we obtain

$$H(z) = V(z)^T D(z) U(z)^T. \quad (20)$$

The post-filter becomes $V(z)^T$. Now since the design of $V(z)$ is most likely free from the reduction step, the output noise enhancement is avoided. This allows the post-filter to have improved properties. Since the pre-filter has no effect on the noise component, its conditioning properties will not affect the system's performance.

3.2 Performance comparison

3.2.1 Performance analysis

The proposed “left-right swapping” scheme is compared to the “row balancing” solution described in [14]. The condition number of this new post-filter $V(z)^{-1}$ and that of the post-filter $S(z)$ in (10) obtained with the “row balancing” technique, are computed. Also, the output noise power after post-filtering is computed via (8) with $\sigma^2 = 1$. Thereby we consider several $(p \times p)$ -MIMO systems, for $p = 3, 4, \dots, 15$. For each system, we thus calculate the average power and the average^[1] condition number on 100 randomly simulated Rayleigh fading channels $H(z)$. With the row balancing, the output noise power is readily given by \sqrt{p} . Table 1 displays the obtained results.

The results show that the proposed “left-right swapping” scheme provides a better conditioned post-filter matrix, with a reasonable norm (output noise power). It is therefore expected that this translates into enhanced MIMO-OFDM performance. The effect in terms of bit error rate is now studied in MIMO-OFDM system. For the simulation, we consider a spatial multiplexing scheme using V-BLAST algorithm,


^[1]Actually, the table displays the median values instead of the mean values because the computed condition numbers exhibit very high variances.

Table 1 Left-right Swapping vs Row balancing: Comparison of powers and condition numbers

| MIMO | Post-filter Power | | Post-filter Condition Number | |
|----------------|-------------------|-------------|------------------------------|-------------|
| | $S(z)$ | $V(z)^{-1}$ | $S(z)$ | $V(z)^{-1}$ |
| 3×3 | 1.732 | 2.8 | 14 | 3 |
| 4×4 | 2.000 | 6.3 | 56 | 14 |
| 5×5 | 2.236 | 10.1 | 156 | 23 |
| 6×6 | 2.449 | 22.4 | 400 | 51 |
| 7×7 | 2.646 | 42.2 | 4648 | 287 |
| 8×8 | 2.828 | 76.1 | 9382 | 520 |
| 9×9 | 3.000 | 120 | 35 463 | 927 |
| 10×10 | 3.162 | 180 | 135 843 | 3631 |
| 11×11 | 3.317 | 247 | 191 350 | 3671 |
| 12×12 | 3.464 | 424 | 385 776 | 21 104 |
| 13×13 | 3.605 | 593 | 908 480 | 32 509 |
| 14×14 | 3.742 | 955 | 1 177 939 | 39 579 |
| 15×15 | 3.873 | 1733 | 809 090 | 65 055 |

with the ITU Pedestrian-A channel model with the following parameters: 20 MHz of bandwidth, $N_s = 512$ sub-carriers, $CP = N_s/8 = 64$ for cyclic prefix length and 4-QAM modulation.


Figures 5 and 6 show the BER comparison in MIMO-OFDM time domain spatial multiplexing, between classical the LU-PMD post-filtering, the modified post-filter based on “row balancing” and this “left-right swapping” scheme.



Significant improvement is obtained with the proposed method in both MIMO 3×3 contexts: indoor (5) and outdoor (6). Observe how the performance gain is very important in the more severe outdoor context. For example, the same BER level of 10^{-3} is reached with the proposed solution with about 5dB drop in SNR compared to the “row balancing” trick. This is due to the fact that the post-filter matrix is better conditioned now, while the output filtering power remains reasonably high.

3.2.2 Comparison with QR-based Spatial Multiplexing

In this subsection, we compare the performance of the improved scheme in MIMO-OFDM system with those of the QR-Based spatial multiplexing [18]. For the QR



decomposition, we have set the tolerance parameter $\varepsilon = 10^{-3}$ for the off diagonal elements. With this value, the residual CCI is insignificant. The truncation parameter is selected as $\mu = 10^{-3}$ to limit the growth of the degrees of the Laurent polynomials in the final reduced equivalent channel $D(z)$. We refer to [17] for more details on the meaning and roles of these parameters. For the purpose of the comparison we have simulated a complete transmission chain from the encoding/interleaving block of the original binary source to the final demodulation block, through an outdoor pedestrian ITU MIMO 3×3 channel. The different BER are displayed in figure 7.




Figure 7 shows that, in terms of BER in MIMO wideband spatial multiplexing, the LU-PMD using “left-right swapping” compares favorably to the QR approach, even for weak SNR. The interesting properties of the LU-PMD decomposition (low complexity, CCI cancellation and ISI mitigation), are now becoming apparent.


3.3 A robust and unitary post-filter



As already mentioned before and observed in [14], the “row-balancing” trick improves the conditioning of the post-filter matrix. Swapping the pre- and post-filter matrices also results in an improved beamforming system as argued above. We therefore propose in this section a combination of both improvements, that is 1) to swap the left and right factors of the decomposition to obtain a better conditioned post-filter at the reception and 2) to apply a row balancing to improve further its conditioning. The final resulting post-filter matrix is subsequently denoted by $Q(z)$. The following table 2 shows how this combination allows one to enhance the good conditioning of the post-filter matrix. These results are obtained with the same simulation setting as in table 1.

Table 2 Comparison of condition numbers: Row balancing schemes, Left-right Swapping and combination of both

| MIMO | Post-filter Condition Number | | |
|----------------|------------------------------|-------------|--------|
| | $S(z)$ | $V(z)^{-1}$ | $Q(z)$ |
| 4×4 | 34 | 23 | 16 |
| 5×5 | 145 | 86 | 46 |
| 6×6 | 269 | 194 | 96 |
| 7×7 | 915 | 684 | 257 |
| 8×8 | 2908 | 3339 | 1002 |
| 9×9 | 4028 | 2863 | 1187 |
| 10×10 | 21983 | 17495 | 6399 |
| 11×11 | 30620 | 21384 | 10075 |
| 13×13 | 101547 | 59609 | 40134 |

The performance in terms of BER in 3×3 , 4×4 and 5×5 MIMO systems is studied with an ITU Pedestrian-A channel model. The results presented respectively in figures 8, 9 and 10 confirm the expectation that the combination of the two methods improves the performance compared to each one taken separately.





4 Discussion

In a spatial multiplexing problem, a common and underlying assumption is that the coefficients of the polynomial matrix representing the MIMO channel are available. Accordingly, in all the preceding experiments, the pre- and post-filters correspond exactly to the right and left factors of the decomposition of the channel that is actually used to simulated the transmission system. However, the channel coefficients result from an estimation procedure. The pre- and post-filters therefore do not stem from the decomposition of the exact transmission MIMO channel. In this section, we thus study the impact of channel estimation errors in a MIMO wideband system using LU-based spatial multiplexing. The exact channel polynomial matrix is still denoted by $H(z)$ and its estimation will be denoted by $\hat{H}(z) = H(z) + \Delta H(z)$. The estimation error is given by the L_2 matrix norm

$$E = \|\Delta H(z)\|_2 = \|H(z) - \hat{H}(z)\|_2. \quad (21)$$

In the sequel, we compute the pre- and post-filters from the decomposition of $\hat{H}(z)$ but the MIMO transmission system is still simulated using the exact channel matrix $H(z)$. QR-based decomposition is also implemented in this channel-pre/post-filters mismatch setting for comparison. We evaluate the BER performance for different values of the relative error $E_r = E/\|H(z)\|_2$. The results are presented in figures 11 and 12.




Figure 11 LU-PMD: BER Performance with imperfect Channel estimation.




Figure 12 QR: BER Performance with imperfect Channel estimation.

For $E_r = 0.01$, we observe that for both the LU-based and QR-based methods, the BER curves obtained with the exact channel coincide with that corresponding to the estimated channel. Very small channel estimation errors do not affect the BER for both methods. However the BER performance drops significantly as the estimation errors increase, and this is particularly visible for high SNR, when the noise effect is no longer dominant. The proposed LU spatial multiplexing scheme appears to be more robust to channel estimation imperfection than the QR-based method. Therefore the proposed LU-PMD with “Left-right swapping” scheme is more real-

istic than the QR-based approach because it provides better BER performance in presence of channel estimation errors.

5 Conclusion

Unlike the QR-based decompositions of polynomial matrix, the LU-based decomposition is simple and exact. Nonetheless, this approach was hitherto discarded in MIMO wideband spatial multiplexing applications, due to an amplification of the output noise. We have presented in this paper a simple but effective solution to this problem of output noise enhancement. We have clearly established in previous studies that performance limitation of the LU-based spatial multiplexing was essentially due to an ill-conditioning of the corresponding post-filter polynomial matrix. Matrix row balancing has then been proposed and a significant reduction of the noise amplification was observed. Here, we have shown that the ill-conditioning of the post-filter matrix is caused by the pivot reduction step during the polynomial matrix factorization. A simple permutation of the left and right factors of the decomposition was sufficient to significantly improve the BER performance compared to the previous row balancing solution. Then, a combination of both solutions results in an LU-based polynomial matrix decomposition approach for MIMO spatial multiplexing in which the noise amplification is now avoided. Finally, we have shown that this proposed LU-based multiplexing scheme compares favorably to the state-of-the-art QR-based methods, in the realistic setting where knowledge of the channel's coefficient matrices is corrupted by estimation errors.

List of abbreviations

| | |
|---------|--|
| MIMO | Multiple Input Multiple Output |
| SISO | Single Input Single Output |
| LU | "Lower Upper" matrix factorisation |
| LU-PMD | LU Polynomial Matrix Decomposition |
| QR | QR matrix factorisation |
| FIR | Finite Impulse Response |
| CCI | Co-Channel Interference |
| ISI | InterSymbol Interference |
| STVC | Spatio-Temporal Vector Coding |
| DMMT | Discrete Matrix MultiTone |
| (D/F)FT | (Discrete/Fast) Fourier Transform |
| (O)FDM | (Orthogonal) Frequency-Division Multiplexing |
| CP | Cyclic Prefix |
| (P)SVD | (Polynomial) Singular Value Decomposition |
| QAM | Quadrature Amplitude Modulation |
| SNR | Signal-to-Noise Ratio |
| BER | Bit Error Rate |

Availability of data and materials

The Matlab and Scilab codes used to generate the simulation results are available to reviewers upon request.

Competing interests

The authors declare that they have no competing interests.

Funding

Not applicable.

Author's contributions

M. Mbaye and M. Mboup wrote the paper. M. Diallo contibuted by providing the choice and motivation of the simulation contexts and settings, he also validated the BER vs SNR simulation results.

Acknowledgements

Not applicable.

Author details

¹Université Cheikh Anta Diop, BP 5005, Dakar Fann, Sénégal. ²CRESTIC–Université de Reims Champagne Ardenne, BP 1039 Moulin de la Housse, 51687, Reims cedex 2, France.

References

1. Paulraj, A.J., Gore, D.A., Nabar, R.U., Bolcskei, H.: An overview of mimo communications - a key to gigabit wireless. *Proceedings of the IEEE* **92**(2), 198–218 (2004).
2. Foschini, G.J., Gans, M.J.: On limits of wireless communications in a fading environment when using multiple antennas. *Wireless Personal Communications* **6**(3), 311–335 (1998).
3. Lambert, R.: Multichannel blind deconvolution : FIR matrix algebra and separation of multipath mixtures. PhD thesis, University of Southern California, Department of Electrical Engineering, Los Angeles (1996)
4. Raleigh, G.G., Cioffi, J.M.: Spatio-temporal coding for wireless communication. *IEEE Transactions on Communications* **46**(3), 357–366 (1998).
5. Bolcskei, H.: MIMO-OFDM wireless systems: basics, perspectives, and challenges. *IEEE Wireless Communications* **13**(4), 31–37 (2006).
6. Liang, Y.-., Schober, R., Gerstacker, W.: Time-domain transmit beamforming for MIMO-OFDM systems with finite rate feedback. *IEEE Transactions on Communications* **57**(9), 2828–2838 (2009).
7. Baxter, P.D., McWhirter, J.G.: Blind signal separation of convolutive mixtures. In: *Proc 37th Asilomar Conference on Circuits Systems and Computers* (2003)
8. Brandt, R., Bengtsson, M.: Wideband mimo channel diagonalization in the time domain. In: *Proc. Int. Symp. Pers. Indoor Mobile Radio Commn*, pp. 1914–1918 (2011)
9. Icart, S., Comon, P.: Some properties of laurent polynomial matrices. In: *9th IMA Intern. Conf. on Math. in Sig. Proc.* (2012)
10. Mbaye, M., Diallo, M., Mboup, M.: Unimodular-upper polynomial matrix decomposition for MIMO spatial multiplexing. In: *IEEE SPAWC, Toronto* (2014)
11. Mbaye, M., Diallo, M., Mboup, M.: LU based beamforming schemes for MIMO system. *IEEE Trans. on Vehicular Technology* **66**(3), 2214–2222 (2017)
12. Mboup, M., Miranda, M.: A polynomial approach to the blind multichannel deconvolution problem. In: *International Telecomm. Symp. (ITS2002, Natal, Brazil)* (2002)
13. Mboup, M.: Sur la résolution de l'identité de Bezout pour l'égalisation autodidacte de systèmes mono-entrée–multi-sorties. In: *Colloquium GRETSI*, vol. 4, pp. 1113–1116 (1999)
14. Mboup, M., Diallo, M., Mbaye, M.: Efficient postcoding filter in LU-based beamforming scheme. In: *ICASSP'17, New Orleans, USA* (2017)
15. Cescato, D., Bolcskei, H.: QR decomposition of Laurent polynomial matrices sampled on the unit circle. *IEEE Trans. on Inf. Theory* **56**, 4754–4761 (2010)
16. McWhirter, J.G., Baxter, P.D.: A novel technique for broadband SVD. In: *Proc. 12th Annual Workshop of Adaptive Sensor Array Signal Processing*, Lexington, USA (2004)
17. Foster, J.A., McWhirter, J.G., Chamber, J.A.: A novel algorithm for calculating the QR decomposition of a polynomial matrix. In: *ICASSP'09* (2009)
18. Foster, J.A., McWhirter, J.G., Davies, M.R., Chambers, J.A.: An algorithm for calculating the QR and Singular Value Decompositions of polynomial matrices. *IEEE Trans. Signal Processing* **58**(3), 1263–1274 (2010)
19. Horn, R.A., Johnson, C.R.: *Matrix Analysis*, 2nd edn. Cambridge University Press, USA (2012)
20. Osborne, E.E.: On pre-conditioning of matrices. *J. Assoc. Comput. Mach.* **7**, 338–345 (1960)

Figures

Figure 1 Effect of the post-filter norm on the system's performance: BER vs SNR

Figure 2 Effect of the postcoder's condition number on the BER vs SNR – 3×3 -MIMO channel

Figure 3 Effect of the postcoder's condition number on the BER vs SNR – 4×4 -MIMO channel.

Figure 4 Effect of the postcoder's condition number on the BER vs SNR – 5×5 -MIMO channel.

Figure 5 BER comparison of the two beamformers: Indoor ITU channel model.

Figure 6 BER comparison of the two beamformers: Outdoor ITU channel model.

Figure 7 BER comparison of LU-based scheme and QR-based scheme.

Figure 8 BER Performance in MIMO 3×3 by combining “Row balancing” and “Left-right swapping” methods.

Figure 9 BER Performance in MIMO 4×4 by combining “Row balancing” and “Left-right swapping” methods.

Figure 10 BER Performance in MIMO 5×5 by combining “Row balancing” and “Left-right swapping” methods.

Figure 11 LU-PMD: BER Performance with imperfect Channel estimation.

Figure 12 QR: BER Performance with imperfect Channel estimation.

Figures




Figure 1

Effect of the post-filter norm on the system's performance: BER vs SNR




Figure 2

Effect of the postcoder's condition number on the BER vs SNR – 3 x 3-MIMO channel




Figure 3

Effect of the postcoder's condition number on the BER vs SNR – 4 x 4-MIMO channel.




Figure 4

Effect of the postcoder's condition number on the BER vs SNR – 5 x 5-MIMO channel.




Figure 5

BER comparison of the two beamformers: Indoor ITU channel model.




Figure 6

BER comparison of the two beamformers: Outdoor ITU channel model.




Figure 7

BER comparison of LU-based scheme and QR-based scheme.




Figure 8

BER Performance in MIMO 3 x 3 by combining "Row balancing" and "Left-right swapping" methods.




Figure 9

BER Performance in MIMO 4 x 4 by combining "Row balancing" and "Left-right swapping" methods.




Figure 10

BER Performance in MIMO 5 x 5 by combining "Row balancing" and "Left-right swapping" methods.




Figure 11

LU-PMD: BER Performance with imperfect Channel estimation.




Figure 12

QR: BER Performance with imperfect Channel estimation.