Spatio-Temporal Classification and Prediction of Land Use and Land Cover Change for the Vembanad Lake System, Kerala – a Machine Learning Approach

Parthasarathy Kulithalai Shiyam Sundar (✉ parthas1993@gmail.com)

National Institute of Technology Karnataka <https://orcid.org/0000-0003-0936-4065>

Paresh Chandra Deka

National Institute of Technology Karnataka

Research Article

Keywords: Google Earth Engine, Random Forest, Support Vector Machines, Machine Learning, Land use and land cover, CA-Markov chain analysis, LULC prediction

Posted Date: June 15th, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-581788/v1>

License: © ⓘ This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

1 **Spatio-temporal classification and prediction of land use and land cover**
2 **change for the Vembanad Lake System, Kerala – A machine learning**
3 **approach**

4
5 Parthasarathy Kulithalai Shiyam Sundar* and Paresh Chandra Deka

6 Department of Water Resources and Ocean Engineering, National Institute of Technology
7 Karnataka, Surathkal, Mangalore, India

* Contact: Parthasarathy K.S.S.
Mail id: parthas1993@gmail.com
Phone: +91-8973533057

8 **Abstract**

9 Land use and land cover (LULC) change has become a critical issue for decision planners and
10 conservationists due to inappropriate growth and its effect on natural ecosystems. As a result, the
11 goal of this study is to identify the LULC for the Vembanad Lake System (VLS), Kerala in the
12 short term, i.e., within a decade, utilizing two standard machine learning approaches, Random
13 Forest (RF) and Support Vector Machines (SVM), on the Google Earth Engine (GEE) platform.
14 When comparing the two techniques, SVM is classified at an average accuracy of around 84.5%,
15 while RF is classified at 89%. The RF outperformed the SVM in almost identical spectral classes
16 such as barren land and built-up areas. As a result, RF classified LULC is considered to predict
17 the Spatio-temporal distribution of LULC transition analysis for 2035 and 2050. The study was
18 conducted in Idrisi TerrSet software using the Cellular Automata (CA)-Markov chain analysis.
19 The model's efficiency is evaluated by comparing the projected 2019 image to the actual 2019
20 classified image. The efficiency was good with more than 94% accuracy for the classes except for
21 barren land, which might have resulted from the recent natural calamities and the accelerated
22 anthropogenic activity in the area.

23 **Keywords:** Google Earth Engine, Random Forest, Support Vector Machines, Machine Learning,
24 Land use and land cover, CA-Markov chain analysis, LULC prediction

1. INTRODUCTION

The natural and anthropogenic activities worldwide influence the land cover, resulting in modifying its landscapes and the subsequent dynamics of natural processes (Silva et al. 2020). Monitoring and assessing urban growth aid in the planning and utilization of natural resources for the foreseeable future. Anthropogenic processes have altered almost half of the Earth's land surfaces (Tayyebi and Pijanowski 2014). These changes are called land use and land cover (LULC) changes. Over the last few decades, economic prosperity and population growth have resulted in unplanned urbanization and industrialization to meet livelihood and job needs. These enormous increases in need boosted the demand for critical infrastructures such as water supplies, sewage services, and recreational activities. It also causes road congestion, pollution, climate change-related problems, urban floods, and Urban Heat Island (UHI) impacts (Saxena et al. 2021). As a result, LULC change is regarded as a critical environmental issue of global significance. Major causes of biodiversity loss and related habitat loss are human-induced effects such as urbanization, erosion, overgrazing, and resulting land degradation. Besides, nature also contributes to this alteration (Halmy et al. 2015; Lambin 1997). The complex interaction of the factors like policy management, human needs, environment, culture, and economics results in changing LULC. Alteration in the LULC can significantly alter the water quality as the increase in urban and agriculture results in nitrates and phosphates in the freshwater (Álvarez-Cabria et al. 2016; Krishnaraj and Deka 2020).

Rapid urbanization in different parts of cities has been a severe threat to developed countries such as India, Indonesia, Malaysia, and Sri Lanka. India is the second-most populous country in the world, with 1.38 billion people. According to the Composite Water Management Index (CWMI) report released by Niti Aayog in August 2019 under the Government Of India (GOI) stated that

many cities in India, such as Delhi, Bengaluru, and Chennai, may face "Day Zero" in the upcoming years (Abijith et al. 2020). Due to the country's rapid population growth and subsequent urbanization, policies for planning, analyzing, and tracking land-use transitions are required to meet the people's basic needs. As a result, enormous areas of forest cover are being converted to other land uses, causing severe soil erosion. Such rapid soil erosion will lead to a catastrophic flood that will impact the residents downstream. Consequently, sustainable LULC is critical for long-term livelihood and environmental improvement (Mishra et al. 2020).

1.1 Role of Geospatial Technology

Geospatial technology is a significant finding of humanity that has evolved since prehistoric times. The main types of geospatial technology involve Remote Sensing (RS), Geographical Information System (GIS) and Global Positioning System (GPS). RS is an excellent tool for regular monitoring and assessing the LULC change in the natural ecosystem, the evolution of landforms by analyzing the geomorphological changes. Likewise, it has played a major role in geography, geology, and environment for the researchers and scientists (Ghosh et al. 2017). It is also more cost-effective and less time-consuming than the traditional method. It has very long spectral bands, and good spatial resolution helps distinguish a significant change in land cover (Abijith et al. 2020). RS and GIS gained much attention from the government and the public due to their ability to map the vulnerabilities during the disaster on a larger scale. The primary goal of GIS is to make it useful to the public and improve their community's needs (Parthasarathy and Deka 2019).

One of the most extensively utilized sources for analysis is satellite images. In 1972 Earth Resources Technology Satellite (ERTS-1) was launched and renamed "Landsat" in 1975. Landsat has launched eight series of satellites and has data contiguity for almost 50 years. As of now, Landsat 7 and 8 are functional. This series of satellites has become one of the important long-term

freely available data for the civilian purpose and used widely in fields like coastal monitoring (Parthasarathy et al. 2020), LULC (Shi and Yang 2015), Vegetation phenology (Senf et al. 2017), and hydrology (Abijith et al. 2020). Thus, Landsat offers a deeper understanding of LULC changes for better decision-making and resource management. Several methods for detecting change using remotely sensed data have been established during the last three decades (Hua et al. 2014; Jat et al. 2017; Rienow and Goetzke 2015; Saxena and Jat 2020; Serasinghe Pathirana et al. 2018).

1.2 Characteristics of Google Earth Engine

Google earth engine (GEE) is a multi-petabyte collection of geospatial data co-located with high performance and intrinsically parallel computation service. In recent years it has been in RS big data processing spotlight. GEE is an interactive development environment (IDE) to enable rapid visualization and analysis controlled through an application program interface (API) accessed via the internet. It contains large publicly available datasets of satellite and aerial imagery in both optical and non-optical wavelengths. It consisted of the most freely available RS imagery of entire Landsat archives and Sentinel-1 and Sentinel-2 (Gorelick et al. 2017). The major advantage of GEE is that it provides large sets of data, including land cover, environmental variables, weather, and climate forecast, which is already pre-processed to access the data. Besides, the raw data is also pre-processed, cloud removed, and mosaicked in the GEE to reduce the computational time. Earth engine code editor is handled by the client libraries handled via JavaScript and Python (Gomes et al. 2020). GEE utilizes the parallel processing technique using MapReduce architecture. It is a method to process a large amount of data into several smaller chunks in several machines. Thus, the data processed as several chunks were recompiled for the final result. As the data can be accessed through the API, it is less labor-intensive and requires less storage space to save the data, and also, its simple yet effective architecture does not require high power computing machines

(Noi Phan et al. 2020). Thus, the use of GEE has significantly increased within the RS community (Tamiminia et al. 2020).

1.3 CA-Markov chain analysis

As the population grows, so does the need for land. As the demand for land increases, it eventually increases urban. This further increases urban areas on LULC, causing disturbance in the ecosystem affecting sustainability (Aburas et al. 2018). Thus, Cellular Automata (CA) – Markov chain model is used to understand the factors affecting the Spatio-temporal distribution of LULC and to predict the future LULC changes. It is one of the most widely used models to predict the LULC change (Ozturk 2015). This model was created using Idrisi TerrSet's Land Change Modeler (LCM). This software aids in analyzing and developing models in the event of stable land cover as opposed to a rapidly changing environment. LCM facilitates the comparison of LULC categories and the net change observed by every class and the contributor to the net change observed by every other LULC category (Hamad et al. 2018). Predicting LULC transition has been used in several applications, including environmental planning by modeling rural development and urban growth, identifying conservation target areas and establishing alternate conservation strategies, analyzing the dynamics of changing agriculture, and simulating rangeland dynamics under various climate change scenarios (Halmy et al. 2015).

To summarise, it was found that GEE aids in the study of LULC shift in a cost-effective and time-consuming manner, and it is commonly used in the literature (Agarwal and Nagendra 2019; Gomes et al. 2020; Noi Phan et al. 2020; Sidhu et al. 2018; Tamiminia et al. 2020; Tassi and Vizzari 2020; Xing et al. 2021). CA – Markov chain model helps in determining the future land cover change and their land-use patterns for decision-makers to provide sustainable development (Aburas et al.

2018; Ansari and Golabi 2019; Bose and Chowdhury 2020; Faichia et al. 2020; Fu et al. 2018; Ghosh et al. 2017; Gidey et al. 2017; Halmy et al. 2015; Hamad et al. 2018; Ozturk 2015).

In this work, LULC was classified in the GEE platform using two standard machine learning approaches, the Random Forest (RF) classifier and the Support Vector Machines (SVM). We attempted to understand the performance of both models using the same collection of training and validation points. Then, using the CA – Markov chain model, forecast the future Spatio-temporal LULC transition analysis and comprehend the changes in LULC for the years 2035 and 2050.

2. MATERIALS AND METHODS

2.1 Study Area

The field of study comprises six watersheds, including Periyar, Muvattupuzha, Meenachil, Manimala, Pamba, and Achenkovil, draining into the Vembanad Lake System (VLS) in Kerala, India (Fig. 1). It falls in six districts, namely Ernakulam, Idukki, Kottayam, Alappuzha, Pathanamthitta, and Kollam. It is located in between latitude of 9° 1' 9" N to 10° 20' 22" N and longitude of 76° 16' 47" E and 77° 24' 43" E comprising of area 12,183 Km². An area of 398.12 Km² is situated below the MSL, and a total of 763.23 Km² is located below 1 meter MSL. The eastern part of the study consists of Western Ghats, whereas the Arabian Sea binds the western part. The area in and around the VLS flooded recently in the 2018 and 2019 Kerala floods. Lots of built-up and agricultural land flooded completely, causing lots of damage to the resources. In which the state took quite a lot of damage due to this unprecedented rainfall. It has a moist, tropical climate, with an average of 150 rainy days each year. The southwest summer monsoon, as well as the northeast winter monsoon, brings rain to this state. From May to August, the southwest monsoon season takes place. Whereas between September and November, the Northeast winter monsoon arrives,

bringing cool winds with it. As a result, the state receives around 3000 mm of rainfall on average. (CWC 2018). The mean annual temperature in the state's coastal lowlands is around 25°C-27.5°C, compared to 20°C-22.5°C in the eastern highlands. The geology of the study is characterized by charnockites, charnockitic gneisses, and pyroxene-bearing granulite in the Western Ghats and central areas of the study. The sedimentary deposits of the Neogene and Quaternary periods dominate the western sections of the sample. Alluvial deposits from the recent past can be found along the coast.

<Fig. 1 Keymap of the study>

2.2 Data Sources and Preparation

The data prepared from various sources have shown in Table 1. Landsat 7 and Landsat 8 images were mainly used in the GEE environment for LULC classification. Landsat 7 was chosen for 2009, while Landsat 8 was chosen for 2013, 2015, 2017, and 2019. A cloud mask was used to choose the image covering the months of January to December for their respective years. Digital Elevation Model (DEM) is prepared using the ASTER data in the ArcGIS environment. Slope and stream networks are derived from the DEM using hydrology tools in the ArcGIS environment. OpenStreetMap is an open licensed map to create a free editable map worldwide that allows users to download all the features like road, river, streams to the desired vector file. Hence road layer is downloaded from the OpenStreetMap. The built-up area is extracted from the LULC 2019 using the Raster Tool in ArcGIS.

2.3 Land Use and Land Cover classification

GEE helps analyze the data at a planetary scale and helps the researchers and developers detect changes in the map trends and quantity differences in the Earth's surface. In recent years, machine learning techniques for high precision classification have developed in the area of RS. LULC is categorized using two machine learning techniques in the GEE environment: Random Forest (RF) classifier and Support Vector Machines (SVM). The RF classifier has attracted the interest of the RS community (Belgiu and Drăgu 2016; Gislason et al. 2006; Hamad et al. 2018; Mahdianpari et al. 2018). Whereas the SVM, a novel algorithm based on statistical learning theory, has not exploited much within the RS community (Adam et al. 2014; Adelabu et al. 2014; Shi and Yang 2015). As a result, we aimed to test, investigate, and compare the performance of these machine learning algorithms in the categorization of LULCs.

2.3.1 The Random Forest classifier

An RF classifier is a multi-decision tree ensemble classifier that creates many decision trees using a random selection of training samples and variables. In recent years, these ensemble learning approaches have been frequently applied in the RS. It is introduced by Breiman (2001) that combines K binary Classification And Regression Trees (CART) as it is a non-parametric classifier, so no statistical assumptions have to be made before the distribution of the data. Input sample subgroup used to build each tree obtained from the bootstrapping. The input variable splits into subgroups based on the testing from the individual algorithm in each tree. RF trees are different from the Decision Trees by selecting each node in a subgroup of the input variables in a random manner and built without pruning (Pelletier et al. 2016). Hence this is a recursive process till the samples are similar or the splitting no longer enriches the model in each subgroup.

2.3.2 Support Vector Machines

SVM, introduced by Cortes and Vapnik (1995), is based on statistical learning theory. By minimizing the empirical risk and confidence interval of learning derived from the systemic risk minimization hypothesis, it aimed to achieve strong generalization capability. It is an efficient and robust algorithm for both classification and regression. The SVM concept uses the support vectors at the class domain's edges to create hyperplanes between classes in feature space. The model seeks optimal hyperplane to separate the classes at maximum margins (Shi and Yang 2015). SVM was designed to handle linearly separable classes by bilinear classification, but hyperplane may not be located between the two cases in most cases. In such cases, the model converts the highly inseparable data into a higher dimension or even infinite-dimensional feature space to separate it linearly (Raghavendra and Deka 2014). In theory, the error penalty, which allows for misclassification, substantially impacts SVM classification accuracy (Ustuner et al. 2015).

The classification, once done using the above machine learning techniques, error matrix has been generated for each year to identify the accuracy of the classifications. The degree to which the results are close to values accepted as true is referred to as accuracy. Error matrix allows calculating overall accuracy, consumer accuracy, producer accuracy, and kappa statistics. The overall accuracy (OA) can be derived using the equation (1)

$$OA = \left(\frac{P_c}{P_n} \right) \times 100 \quad (1)$$

Where P_c is the number of correctly classified pixels, and P_n is the total number of pixels.

Consumer accuracy of each class depends on the number of correctly classified pixels in the class to the number of pixels belonging to this class in the classification. Simultaneously, the producer

accuracy depends on the number of correctly classified pixels to that of the number of pixels belonging to each class in the reference data. The notation similar to Cohen (1960), the kappa coefficient κ is estimated. The proportional reduction of errors by the classification classes to the error of the completely random class (Forghani et al. 2007; Tassi and Vizzari 2020). The magnitude of κ usually lies between -1 to +1. The values more than +0.5 indicate it is in good agreement with the classification (Taati et al. 2015). The best-performing model is analyzed. Then the classified model is further future predicted to analyze the Spatio-temporal change in the model.

2.4 CA-Markov model

CA (Cellular Automata)-Markov is one of the most extensively utilized models predicting LULC's future spatial and temporal changes. To forecast the change in LULC, this hybrid model combines the CA with the Markov Chain model (Aburas et al. 2018). As the Markov Chain model is stochastic, it predicts one cell transformation to another, i.e., the transition probability of the cell. However, the disadvantage of the Markov Chain model is that it does not consider the effect of the neighboring cells over the other. Thus, it lacks spatial modeling capability (Ozturk 2015). CA model considers only the neighboring cell of interest for the estimation of the future. Thus, both the model combined to make the CA-Markov model analyze the Spatio-temporal changes in the land cover. It takes two time periods of LULC (i.e., earlier and later dates) as the input to analyze the change in trend. The LULC class distribution was predicted using the transition probabilities between class i and j using P_{ij} . It was determined over a period from time t to time $t+1$.

$$P_{ij} = \frac{n_{ij}}{n_i} \quad (2)$$

$$\sum_{j=1}^k P_{ij} = 1 \quad (3)$$

Where n_i is the total number of pixels transformed from class i over the transition period and n_{ij} is the number of pixels transformed from class i to j . k is the total number of classes. Using the transition probability P and the LULC distribution at the beginning of time t (T_t), the change in LULC over time $t+1$ (T_{t+1}) using the equation (4).

$$T_{t+1} = P \times T_t \quad (4)$$

CA assesses the contiguity configuration as well as transition probabilities (Hamad et al. 2018). The CA-Markov model, which consists of the basic LULC layer, transition potential areas for future change formed by the Markov Chain model, and transitional potential layers for LULC such as road network, built-up regions, and stream network, is used to determine the appropriate transition from one class to the other (Halmy et al. 2015). In this study, a typical 5x5 pixel contiguity filter had a considerable impact on the cellular center. As a result, each cell is surrounded by a 5x5 matrix space that defines the neighborhood of each land class. The standard contiguity filter is given as

$$\text{contiguity filter } 5 \times 5 = \begin{bmatrix} 0 & 0 & 1 & 0 & 0 \\ 0 & 1 & 1 & 1 & 0 \\ 1 & 1 & 1 & 1 & 1 \\ 0 & 1 & 1 & 1 & 0 \\ 0 & 0 & 1 & 0 & 0 \end{bmatrix}$$

The LULC layer of 2009 and 2015 is given as the input to predict the LULC for 2019. This is performed to prove the model's accuracy under the given conditions. Then the model is further used to predict the future Spatio-temporal changes of LULC change.

3. RESULTS AND DISCUSSION

3.1 LULC using GEE

The LULC for 2009, 2013, 2015, 2017, and 2019 were classified using RF and SVM in GEE, as shown in Fig. 2 and Fig. 3. For providing a better region of interest (ROI), 15-35 pixels in each sample were selected. Both models were given the same collection of training and validation points as input to examine their results closely. It is classified into 5 major classes like waterbody, built-up, vegetation, barren land, and forest. Every class was trained with 75-95 ROI for classification and 60-75 ROI for validation. It also ensured that the information was normally distributed and spectrally pure. According to Lillesand and Kiefer (1979) minimum of 50 samples per class is required as a rule of thumb. Random stratified sampling is used to determine accuracy, with the minimal number of observations put in each segment at random.

<Fig. 2 Classification using RF>

<Fig. 3 Classification using SVM>

The consumers and producers accuracy for RF classification is shown in Table 2. Overall accuracy and kappa statistics of RF classification are shown in Table 3. Previous studies of Cánovas-García et al. (2017); Ghimire et al. (2012); Noi Phan et al. (2020) stated that ntree of 100 gives better results. However, the current analysis found that the ntree of 30 worked better and had a higher accuracy than the 100. During the classification, ntree values greater than 100 failed to do better. For 2009, this model accurately categorized the waterbody, built-up, and barren land, but there was a misclassification between the forest and vegetation type. In 2015, there was a very close misclassification of built-up and barren land, with the former being listed as the latter. Using Landsat 8 images, the differentiation between forest and vegetation was clear and precise. This may be attributed to the Landsat 8's (level 1 products) higher radiometric resolution, i.e., twice the predecessor Landsat 7.

<Table 2 Consumers accuracy and Producers accuracy in RF for each year of LULC>

<Table 3 Overall accuracy and Kappa statistics in RF for each year of LULC>

Over the image, an SVM model is trained with the same collection of ROI and validation points. The importance of the SVM settings has a significant impact on classification results (Huang et al. 2002; Shi and Yang 2015). The kernel type, cost parameter, and gamma value are the critical parameters in the model. Hence kernel type is assigned with radial basis function (RBF), cost parameter (C) is assigned with the value of 100, and gamma value is given as 0.143 (Kavzoglu and Colkesen 2009; Yang 2011). Thus, the consumers and producers accuracy is shown in Table 4. The overall accuracy and kappa statistics were shown in Table 5.

<Table 4 Consumers accuracy and Producers accuracy in SVM for each year of LULC>

<Table 5 Overall accuracy and Kappa statistics in SVM for each year of LULC>

Table 3 and Table 5 show that the RF algorithm performs more accurately than that of the SVM. RF is more suited to multiclass problems so that it can handle small differences in classification. In contrast, SVM misclassified between the built-up and the barren land. Their reflectance remains slightly identical, and the SVM model shows some class misclassification in the region around the water bodies. This is evident in Table 4, resulting in very less consumers accuracy of the barren land. The RF algorithm performed poorly in images obtained during the rainy season (2015), misclassifying built-up areas as barren land. During the dry season, the classification is accurate despite RF's outperforming SVM in terms of efficiency. As a result, the RF algorithm-based classification is being proposed for further analysis.

Table 6 shows the change in area from the year 2009 to 2019. The waterbody area decreased steadily from 2013 to 2017, but after the flooding, the area of the waterbody increased significantly

in the study. It has also been observed that the vegetation has declined by 8% between 2017 and 2019. There is a boom in the built-up area from the year 2009 to 2019. This is also the main reason for the study, as Kerala cities have the highest rate of urbanization. In a decade, the urban area has grown by almost 100%. Fig. 4 shows the rapid increase in barren land in the year 2019. This may be attributed to the combined effect of the anthropogenic activities and the state's floods in 2018 and 2019, which caused landslides. It accounts for a 117% increase in barren land from 2009 to 2019, resulting in decreased vegetation cover and forest cover combined. Thus, the RF classified image in GEE gives very effective insight into the LULC study transition over a decadal period.

<Table 6 Areal change in the LULC from 2009 to 2019>

<Fig. 4 Graphical visualization of areal change in the LULC from 2009 to 2019>

The classified image based on the RF algorithm is then used to forecast and interpret the LULC change in 2019, 2035, and 2050 using CA-Markov analysis in LCM.

3.2 Future prediction using CA-Markov

CA-Markov analysis has been carried out using the Idrisi TerrSet software in the LCM module. The LULC map 2009 and 2015 is given as the earlier land cover image and later land cover image. The transition probabilities from 2009 to 2015 and the 2015 LULC base map were used to model the 2019 LULC using the CA-Markov approach. The potential for transition probability is calculated based on the area of each LULC class (preferably barren land, forest, and vegetation) that can be converted into the built-up (Fig. 5). The transition of these areas was divided into the number of timesteps (as an iteration) given by the simulation, which provided the areas to be transitioned each iteration. Land suitability maps show the most suitable pixel to each LULC class. Down-weighted pixels are those that are further apart from the pixel to be converted. These neighborhood rules were defined using the contiguity filter of 5x5 pixels. Assignment of the pixels

in the future depends on the pixel's suitability to a specific LULC class. This simulation continues till each pixel of the LULC class is iterated.

<Fig. 5 Potential for the transition from barren land (1), forest (2), and Vegetation (3) to built-up>

LULC class changes are influenced by various driver variables such as DEM, slope, road network, distance from the road, distance from built-up areas, and distance from stream network (Fig. 6). The DEM and slope reveal that the built-up class has a higher probability in areas with a lower elevation and a lesser degree of slope. Distance from the road, distance from the built-up, and distance from the stream are the driver variables that signify the likelihood of a rise in the built-up classes that are very close to the road, current built-up, and stream, respectively those that are farther apart. In this analysis, the distance from the road, DEM, slope, and distance from built-up areas was generated and used to predict the increase in built-up areas. The resulting map is poor and has much less accuracy. The inclusion of distance from the stream to the model increased the forecast map's accuracy for 2019. Thus, it reveals that urban area is heavily reliant on the river valley, as many residents depend on agriculture.

The association between the driver variables and the distribution of LULC classes in later year image (2015) has been derived by finding the Cramer's V. Although it is an imprecise fishing tool, higher Cramer's V shows that the variable's possible explanatory value is good. However, it does not guarantee good results because it does not account for the mathematical constraints of the modeling technique utilized and the relationship's complexity. The Cramer's V for the driver variables is given in Table 7. $V < 0.3$ shows the weak association, $V \in [0.3-0.5]$ shows the medium association, and $V > 0.5$ shows the strong association. Distance from built-up and slope shows the medium association whereas DEM, distance from road, and stream shows potentially high Cramer's V.

<Fig. 6 Driver variables for CA-Markov model>

<Table 7 Cramer's V for driver variables>

Table 8 compares the predicted map of 2019 to the classified map of 2019, and the accuracy for each class in LULC is evaluated. The LULC classes have a high correlation, with more than 95% confidence precision in the waterbody, built-up area, and forest cover. The vegetational cover is 94% compared to the barren land, which is the least accurate than the actual 2019 LULC map, 48.99%. This is because the study area was one of the most severely damaged and devastated areas during the 2018 and 2019 Kerala floods. These heavy floods caused landslides and erosion along the river banks in the Western Ghats section. This may be one of the key explanations for more barren land than predicted by the model.

<Table 8 Accuracy assessment of the predicted 2019 LULC with actual 2019 LULC>

The areal change in the predicted LULC of 2019, 2035, and 2050 are shown in Table 9. Following 2019, there is a gradual growth in built-up and barren land in 2035 and 2050. The estimated barren land area for 2019 is 391.7 Km², while the total area is 799.5 Km². For the same forecast rate, the annual rise in barren land accounts for just 422.67 and 458.84 Km², respectively. There is a slight reduction in built-up area from 549.16 Km² in 2019 (predicted) to 564.14 Km² in 2019 (actual). The estimated growth in a built-up area for 2035 and 2050 is 657.64 and 773.01 Km², respectively. In the long run, there is a considerable decrease in vegetation cover. Thus, the graphical representation with the LULC 2019 (actual), predicted 2019, 2035, and 2050 is shown in Fig. 7.

<Table 9 Areal change in the predicted LULC 2019, 2035 and 2050>

Fig. 8 shows the Spatio-temporal prediction of the LULC maps for 2019, 2035, and 2050. The map depicts the rise in the built-up area along the stream until 2035; in 2050, only the density of built-up rises rather than moving spatially. Thus, the Spatio-temporal trend indicates that by 2050,

almost 773 Km² of land would be transformed to a built-up area, with a density significantly higher than the current LULC.

<Fig. 7 Graphical visualization of areal change in the actual LULC 2019 with that of the predicted LULC for 2019, 2035 and 2050>

<Fig. 8 Predicted LULC for the year 2019, 2035 and 2050>

Only the trend of anthropogenic presence on the land affects the expected LULC transition. It can vary mainly due to natural disasters such as the 2018 and 2019 floods, which increased the amount of barren land. The current pattern of LULC transition is primarily due to development practices, and it may result in land deterioration, resulting in pollution, a decline in groundwater quality, tension in coastal areas, and so on. These predicted maps can be seen as a prospectus for stakeholders to better understand the impact of land use patterns on land cover. It can help them demonstrate an interest in environmental planning and decision-making for potential land use management and sustainable land cover utilization.

4. CONCLUSION

As urbanization in developed countries becomes uncontrollable and unsustainable, determining the spatial pattern and patterns of urban development is a crucial problem to solve to achieve a sustainable environment. As a result, there is a need to raise public consciousness about the dramatic improvements and degradation of natural environments. In this regard, the research was carried out to examine the transition in the urban environment. Since the study area was seriously impacted by the Kerala floods in 2018 and 2019, this study will help society understand the changes in the LULC due to anthropogenic and flood-related factors. This will assist planners in doing the requisite precautionary plans for the current and potential urban growth trend for sustainable development.

380 GEE has a powerful scripting language that works in tandem with its cloud infrastructure and user-
381 friendly API. It aided in the efficient study of the classification based on machine learning. This
382 open-source tool offers an outstanding opportunity for users to explore time series data over a
383 longer span of time to observe shift trends such as LULC, shoreline-related problems, and urban
384 heat, among others. The availability of free accessible Satellite data like Landsat, ASTER DEM,
385 and Sentinel series of satellites allows the RS community to explore the vast possibilities that
386 remain unexplored. We found out that the average accuracy of the SVM model is 84.5%, while
387 RF accuracy is 89%. This demonstrates the RF algorithm's ability to tackle multiclass classification
388 and outperform the SVM. In diverse spatial and spectral land covers, RF performs well and
389 dramatically increases mapping precision. The transition study in the LULC groups reveals a
390 dramatic growth in the built-up area and barren land, followed by a steady decline in vegetation
391 and forest cover.

392 The machine learning application in the CA-Markov model of Idrisi TerrSet software helps to
393 analyze the Spatio-temporal change prediction of the LULC using the LCM module. Except for
394 barren land, this model had more than 94% accuracy for all LULC classes. Supporting layers such
395 as distance from the stream, road network, distance from the road, distance from the built-up area,
396 DEM, and slope were critical in forecasting future land cover. The lower prediction accuracy may
397 be influenced by an increase in both anthropogenic and natural disasters. This might be a potential
398 limitation of the analysis since the Spatio-temporal variation is limited to the current trend of
399 transition in the LULC, which can differ over time. This research can also be investigated using
400 high-resolution images such as Sentinel to observe the evolving trend. As of now, the Sentinel
401 collection of satellite data is not available for more than a half-decade; this may be the potential
402 reach of the analysis.

403 **Acknowledgements:** The authors would like to acknowledge the Department of Water Resources
404 and Ocean Engineering, National Institute of Technology Karnataka Surathkal, India, for
405 providing infrastructural support.

406 **Author contribution** The Participation of P.K.S.S. includes data collection, analyzing the results
407 and writing the article and the participation of PCD includes supervision, conceptualization,
408 reviewing and editing the article.

409 **Funding** There was no funding provided for the work.

410 **Availability of data and materials** The data used in this research are available by the
411 corresponding author upon reasonable request.

412 **Declarations**

413 **Ethics approval** The authors confirm that this article is original research and has not been
414 published or presented previously in any journal or conference in any language (in whole or in
415 part).

416 **Consent to participate** Not applicable.

417 **Consent for publication** Not applicable.

418 **Competing interests** The authors declare no competing interests.

REFERENCE

- Abijith, D., Saravanan, S., Singh, L., Jennifer, J. J., Saranya, T., and Parthasarathy, K. S. S. (2020). "GIS-based multi-criteria analysis for identification of potential groundwater recharge zones - a case study from Ponnaniyar watershed, Tamil Nadu, India." *HydroResearch*, Elsevier BV, 3, 1–14.
- Aburas, M. M., Abdullah, S. H., Ramli, M. F., Ash'aari, Z. H., and Ahamad, M. S. S. (2018). "Simulating and monitoring future land-use trends using CA-Markov and LCM models." *IOP Conference Series: Earth and Environmental Science*, 169(1), 012050.
- Adam, E., Mutanga, O., Odindi, J., and Abdel-Rahman, E. M. (2014). "Land-use/cover classification in a heterogeneous coastal landscape using RapidEye imagery: evaluating the performance of random forest and support vector machines classifiers." *International Journal of Remote Sensing*, Taylor & Francis, 35(10), 3440–3458.
- Adelabu, S., Mutanga, O., and Adam, E. (2014). "Evaluating the impact of red-edge band from Rapideye image for classifying insect defoliation levels." *ISPRS Journal of Photogrammetry and Remote Sensing*, International Society for Photogrammetry and Remote Sensing, Inc. (ISPRS), 95, 34–41.
- Agarwal, S., and Nagendra, H. (2019). "Classification of Indian cities using Google Earth Engine." *Journal of Land Use Science*, Taylor & Francis, 14(4–6), 425–439.
- Álvarez-Cabria, M., Barquín, J., and Peñas, F. J. (2016). "Modelling the spatial and seasonal variability of water quality for entire river networks: Relationships with natural and anthropogenic factors." *Science of the Total Environment*.

440 Ansari, A., and Golabi, M. H. (2019). "Prediction of spatial land use changes based on LCM in a
 441 GIS environment for Desert Wetlands – A case study: Meighan Wetland, Iran." *International*
 442 *Soil and Water Conservation Research*, Elsevier B.V., 7(1), 64–70.

443 Belgiu, M., and Drăgu, L. (2016). "Random forest in remote sensing: A review of applications and
 444 future directions." *ISPRS Journal of Photogrammetry and Remote Sensing*, 114, 24–31.

445 Bose, A., and Chowdhury, I. R. (2020). "Monitoring and modeling of spatio-temporal urban
 446 expansion and land-use/land-cover change using markov chain model: a case study in Siliguri
 447 Metropolitan area, West Bengal, India." *Modeling Earth Systems and Environment*, Springer
 448 International Publishing, 6(4), 2235–2249.

449 Breiman, L. (2001). "Random forests." *Machine Learning*, Springer, 45(1), 5–32.

450 Cánovas-García, F., Alonso-Sarría, F., Gomariz-Castillo, F., and Oñate-Valdivieso, F. (2017).
 451 "Modification of the random forest algorithm to avoid statistical dependence problems when
 452 classifying remote sensing imagery." *Computers and Geosciences*, Elsevier Ltd, 103, 1–11.

453 Cohen, J. (1960). "A Coefficient of Agreement for Nominal Scales." *Educational and*
 454 *Psychological Measurement*, Sage PublicationsSage CA: Thousand Oaks, CA, 20(1), 37–46.

455 Cortes, C., and Vapnik, V. (1995). "Support-Vector Networks." *Machine Learning*.

456 CWC. (2018). "Kerala Floods of August 2018." (August), 46.

457 Faichia, C., Tong, Z., Zhang, J., Liu, X., Kazuva, E., Ullah, K., and Al-Shaibah, B. (2020). "Using
 458 rs data-based ca-markov model for dynamic simulation of historical and future lucc in
 459 Vientiane, Laos." *Sustainability (Switzerland)*, 12(20), 1–20.

460 Forghani, A., Cechet, B., and Nadimpalli, K. (2007). "Object-based classification of multi-sensor

optical imagery to generate terrain surface roughness information for input to wind risk simulation." *International Geoscience and Remote Sensing Symposium (IGARSS)*, 3090–3095.

Fu, X., Wang, X., and Yang, Y. J. (2018). "Deriving suitability factors for CA-Markov land use simulation model based on local historical data." *Journal of Environmental Management*, Academic Press, 206, 10–19.

Ghimire, B., Rogan, J., Galiano, V., Panday, P., and Neeti, N. (2012). "An evaluation of bagging, boosting, and random forests for land-cover classification in Cape Cod, Massachusetts, USA." *GIScience and Remote Sensing*, Taylor & Francis Group , 49(5), 623–643.

Ghosh, P., Mukhopadhyay, A., Chanda, A., Mondal, P., Akhand, A., Mukherjee, S., Nayak, S. K., Ghosh, S., Mitra, D., Ghosh, T., and Hazra, S. (2017). "Application of Cellular automata and Markov-chain model in geospatial environmental modeling- A review." *Remote Sensing Applications: Society and Environment*, Elsevier B.V., 5(October 2016), 64–77.

Gidey, E., Dikinya, O., Sebege, R., Segosebe, · Eagilwe, and Zenebe, · Amanuel. (2017). "Cellular automata and Markov Chain (CA_Markov) model-based predictions of future land use and land cover scenarios (2015-2033) in Raya, northern Ethiopia." *Modeling Earth Systems and Environment*, 3, 1245–1262.

Gislason, P. O., Benediktsson, J. A., and Sveinsson, J. R. (2006). "Random forests for land cover classification." *Pattern Recognition Letters*, 27(4), 294–300.

Gomes, V. C. F., Queiroz, G. R., and Ferreira, K. R. (2020). "An overview of platforms for big earth observation data management and analysis." *Remote Sensing*, 12(8), 1–25.

482 Gorelick, N., Hancher, M., Dixon, M., Ilyushchenko, S., Thau, D., and Moore, R. (2017). "Google
 483 Earth Engine: Planetary-scale geospatial analysis for everyone." *Remote Sensing of*
 484 *Environment*, The Author(s), 202, 18–27.

485 Halmy, M. W. A., Gessler, P. E., Hicke, J. A., and Salem, B. B. (2015). "Land use/land cover
 486 change detection and prediction in the north-western coastal desert of Egypt using Markov-
 487 CA." *Applied Geography*, Elsevier Ltd, 63, 101–112.

488 Hamad, R., Balzter, H., and Kolo, K. (2018). "Predicting Land Use/Land Cover Changes Using a
 489 CA-Markov Model under Two Different Scenarios." *Sustainability*, 10(10), 3421.

490 Hua, L., Tang, L., Cui, S., and Yin, K. (2014). "Simulating urban growth using the SLEUTH model
 491 in a coastal peri-urban district in China." *Sustainability (Switzerland)*, 6(6), 3899–3914.

492 Huang, C., Davis, L. S., and Townshend, J. R. G. (2002). "An assessment of support vector
 493 machines for land cover classification." *International Journal of Remote Sensing*, Taylor &
 494 Francis Group , 23(4), 725–749.

495 Jat, M. K., Choudhary, M., and Saxena, A. (2017). "Application of geospatial techniques and
 496 cellular automata for modelling urban growth of a heterogeneous urban fringe." *Egyptian*
 497 *Journal of Remote Sensing and Space Science*, National Authority for Remote Sensing and
 498 Space Sciences, 20(2), 223–241.

499 Kavzoglu, T., and Colkesen, I. (2009). "A kernel functions analysis for support vector machines
 500 for land cover classification." *International Journal of Applied Earth Observation and*
 501 *Geoinformation*, Elsevier, 11(5), 352–359.

502 Krishnaraj, A., and Deka, P. C. (2020). "Spatial and temporal variations in river water quality of

503 the Middle Ganga Basin using unsupervised machine learning techniques." *Environmental*
504 *Monitoring and Assessment*, Springer Science and Business Media Deutschland GmbH,
505 192(12).

506 Lambin, E. F. (1997). "Modelling and monitoring land-cover change processes in tropical
507 regions." *Progress in Physical Geography*.

508 Lillesand, T. M., and Kiefer, R. W. (1979). *Remote sensing and image interpretation. Remote*
509 *sensing and image interpretation*.

510 Mahdianpari, M., Salehi, B., Rezaee, M., Mohammadimanesh, F., and Zhang, Y. (2018). "Very
511 deep convolutional neural networks for complex land cover mapping using multispectral
512 remote sensing imagery." *Remote Sensing*, 10(7).

513 Mishra, P. K., Rai, A., and Rai, S. C. (2020). "Land use and land cover change detection using
514 geospatial techniques in the Sikkim Himalaya, India." *Egyptian Journal of Remote Sensing*
515 *and Space Science*, National Authority for Remote Sensing and Space Sciences., 23(2), 133–
516 143.

517 Noi Phan, T., Kuch, V., and Lehnert, L. W. (2020). "Land cover classification using google earth
518 engine and random forest classifier-the role of image composition." *Remote Sensing*, 12(15).

519 Ozturk, D. (2015). "Urban growth simulation of Atakum (Samsun, Turkey) using cellular
520 automata-Markov chain and Multi-layer Perceptron-Markov chain models." *Remote Sensing*,
521 7(5), 5918–5950.

522 Parthasarathy, K. S. S., and Deka, P. C. (2019). "Remote sensing and GIS application in
523 assessment of coastal vulnerability and shoreline changes: a review." *ISH Journal of*

524 *Hydraulic Engineering*, 1–13.

525 Parthasarathy, K. S. S., Saravanan, S., Deka, P. C., and Devanantham, A. (2020). "Assessment of
526 potentially vulnerable zones using geospatial approach along the coast of Cuddalore district,
527 East coast of India." *ISH Journal of Hydraulic Engineering*, Taylor & Francis, 1–11.

528 Pelletier, C., Valero, S., Inglada, J., Champion, N., and Dedieu, G. (2016). "Assessing the
529 robustness of Random Forests to map land cover with high resolution satellite image time
530 series over large areas." *Remote Sensing of Environment*, Elsevier Inc., 187, 156–168.

531 Raghavendra, S., and Deka, P. C. (2014). "Support vector machine applications in the field of
532 hydrology: A review." *Applied Soft Computing Journal*, Elsevier BV.

533 Rienow, A., and Goetzke, R. (2015). "Supporting SLEUTH - Enhancing a cellular automaton with
534 support vector machines for urban growth modeling." *Computers, Environment and Urban
535 Systems*, Elsevier Ltd, 49, 66–81.

536 Saxena, A., and Jat, M. K. (2020). "Land suitability and urban growth modeling: Development of
537 SLEUTH-Suitability." *Computers, Environment and Urban Systems*, Elsevier, 81(February),
538 101475.

539 Saxena, A., Jat, M. K., and Clarke, K. C. (2021). "Development of SLEUTH-Density for the
540 simulation of built-up land density." *Computers, Environment and Urban Systems*, Elsevier
541 Ltd, 86(November 2020), 101586.

542 Senf, C., Seidl, R., and Hostert, P. (2017). "Remote sensing of forest insect disturbances: Current
543 state and future directions." *International Journal of Applied Earth Observation and
544 Geoinformation*, Elsevier B.V.

545 Serasinghe Pathiranage, I. S., Kantakumar, L. N., and Sundaramoorthy, S. (2018). "Remote
546 Sensing Data and SLEUTH Urban Growth Model: As Decision Support Tools for Urban
547 Planning." *Chinese Geographical Science*, 28(2), 274–286.

548 Shi, D., and Yang, X. (2015). "Support Vector Machines for Land Cover Mapping from Remote
549 Sensor Imagery." (December), 265–279.

550 Sidhu, N., Pebesma, E., and Câmara, G. (2018). "Using Google Earth Engine to detect land cover
551 change: Singapore as a use case." *European Journal of Remote Sensing*, Taylor & Francis,
552 51(1), 486–500.

553 Silva, L. P. e., Xavier, A. P. C., da Silva, R. M., and Santos, C. A. G. (2020). "Modeling land cover
554 change based on an artificial neural network for a semiarid river basin in northeastern Brazil."
555 *Global Ecology and Conservation*, 21.

556 Taati, A., Sarmadian, F., Mousavi, A., Pour, C. T. H., and Shahir, A. H. E. (2015). "Land use
557 classification using support vector machine and maximum likelihood algorithms by landsat 5
558 TM images." *Walailak Journal of Science and Technology*, 12(8), 681–687.

559 Tamiminia, H., Salehi, B., Mahdianpari, M., Quackenbush, L., Adeli, S., and Brisco, B. (2020).
560 "Google Earth Engine for geo-big data applications: A meta-analysis and systematic review."
561 *ISPRS Journal of Photogrammetry and Remote Sensing*, Elsevier B.V., 164, 152–170.

562 Tassi, A., and Vizzari, M. (2020). "Object-Oriented LULC Classification in Google Earth
563 Learning Algorithms." *Remote Sensing*, 2020(12), 3776.

564 Tayyebi, A., and Pijanowski, B. C. (2014). "Modeling multiple land use changes using ANN,
565 CART and MARS: Comparing tradeoffs in goodness of fit and explanatory power of data

566 mining tools." *International Journal of Applied Earth Observation and Geoinformation*,
567 Elsevier B.V., 28(1), 102–116.

568 Ustuner, M., Sanli, F. B., and Dixon, B. (2015). "Application of support vector machines for
569 landuse classification using high-resolution rapideye images: A sensitivity analysis."
570 *European Journal of Remote Sensing*, 48, 403–422.

571 Xing, H., Hou, D., Wang, S., Yu, M., and Meng, F. (2021). "O-LCMapping: a Google Earth
572 Engine-based web toolkit for supporting online land cover classification." *Earth Science*
573 *Informatics*, Earth Science Informatics, 529–541.

574 Yang, X. (2011). "Parameterizing support vector machines for land cover classification."
575 *Photogrammetric Engineering and Remote Sensing*, American Society for Photogrammetry
576 and Remote Sensing, 77(1), 27–38.

577

Figures

Figure 1

Keymap of the study Note: The designations employed and the presentation of the material on this map do not imply the expression of any opinion whatsoever on the part of Research Square concerning the legal status of any country, territory, city or area or of its authorities, or concerning the delimitation of its frontiers or boundaries. This map has been provided by the authors.

LULC using Random Forest

Figure 2

Classification using RF Note: The designations employed and the presentation of the material on this map do not imply the expression of any opinion whatsoever on the part of Research Square concerning the legal status of any country, territory, city or area or of its authorities, or concerning the delimitation of its frontiers or boundaries. This map has been provided by the authors.

LULC using Support Vector Machine

Figure 3

Classification using SVM Note: The designations employed and the presentation of the material on this map do not imply the expression of any opinion whatsoever on the part of Research Square concerning the legal status of any country, territory, city or area or of its authorities, or concerning the delimitation of its frontiers or boundaries. This map has been provided by the authors.

Figure 4

Graphical visualization of areal change in the LULC from 2009 to 2019

Figure 5

Potential for the transition from barren land (1), forest (2), and Vegetation (3) to built-up

Figure 6

Driver variables for CA-Markov model Note: The designations employed and the presentation of the material on this map do not imply the expression of any opinion whatsoever on the part of Research Square concerning the legal status of any country, territory, city or area or of its authorities, or concerning the delimitation of its frontiers or boundaries. This map has been provided by the authors.

Figure 7

Graphical visualization of areal change in the actual LULC 2019 with that of the predicted LULC for 2019, 2035 and 2050

Predicted LULC for the year 2019, 2035 and 2050

Figure 8

Predicted LULC for the year 2019, 2035 and 2050 Note: The designations employed and the presentation of the material on this map do not imply the expression of any opinion whatsoever on the part of Research Square concerning the legal status of any country, territory, city or area or of its authorities, or concerning the delimitation of its frontiers or boundaries. This map has been provided by the authors.