A Framework to Predict the Load-Settlement Behavior of Shallow Foundations in a Range of Soils from Silty Clays to Sands using CPT Records

Hossein MolaAbasi

Gonbad Kavous University

Aghileh Khajeh

University of Guilan

REZA JAMSHIDI CHENARI (✉ jamshidi_reza@yahoo.com)

University of Guilan <https://orcid.org/0000-0002-7950-322X>

Meghdad Payan

University of Guilan

Research Article

Keywords: Load-settlement curve, CPT, Ultimate bearing capacity, Volterra series, Sensitivity analysis.

Posted Date: July 12th, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-697719/v1>

License: This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Version of Record: A version of this preprint was published at Soft Computing on October 31st, 2021. See the published version at <https://doi.org/10.1007/s00500-021-06485-8>.

A Framework to Predict the Load-Settlement Behavior of Shallow Foundations in a Range of Soils from Silty Clays to Sands using CPT Records

Hossein MolaAbasi¹, Aghileh Khajeh², Reza Jamshidi Chenari^{3*}, Meghdad Payan⁴

¹ Assistant Professor, Department of Civil Engineering, Gonbad University, Gonbad, Iran.

² PhD Candidate, Department of Civil Engineering, Faculty of Engineering, University of Guilan, Rasht, Iran.

^{3,*} Associate Professor, Department of Civil Engineering, Faculty of Engineering, University of Guilan, Rasht, Iran

(corresponding Author: jamshidi_reza@guilan.ac.ir).

⁴ Assistant Professor, Department of Civil Engineering, Faculty of Engineering, University of Guilan, Rasht, Iran

Abstract

Using a set of cone penetration test (*CPT*) records, the current paper develops a general framework based on regression analyses to model the load-settlement (*q-s*) behavior of shallow foundations resting on a variety of soils ranging from silty clays to sands. A three-parameter hyperbolic function is employed to rigorously examine the obtained *q-s* curves, and to determine the model parameters. Also, the results of some *CPT* soundings, including the corrected cone tip resistance (q_t) and the skin friction (R_f), are adopted to predict the results of plate load tests (*PLT*). The findings corroborate the high accuracy of the proposed model, the reasonable performance of the hyperbolic function and the use of the Volterra series to predict the *q-s* curves. Moreover, the obtained curves from the newly developed model are compared to those from other methods in the literature which cross-confirms the efficacy of the current model. A sensitivity analysis is also conducted and the exclusive effects of all the contributing parameters are assessed among which R_f is shown to be the most influential. Ultimately, simple solutions are

adopted to determine various key geotechnical parameters, like the ultimate bearing capacity (q_{ult}), the allowable bearing capacity (q_a) and the modulus of subgrade reaction (k_s).

Keywords: Load-settlement curve; *CPT*; Ultimate bearing capacity; Volterra series; Sensitivity analysis.

Nomenclature

a	Net area ratio of cone tip	q_i	Bearing pressure of an arbitrary point
a_i	Constant coefficient of Volterra series	q_{max}	Maximum value of applied pressure
B_f	Foundation width	q_{net}	Net cone resistance
B_p	Plate diameter	q_t	Corrected q_c
<i>CPT</i>	Cone penetration test	q_{ult}	Ultimate bearing capacity
D_e	Effective depth	$q_{ult,f}$	Ultimate bearing capacity of the foundation
D_f	Embedment depth	$q_{ult,p}$	Ultimate bearing capacity of the plate
f_s	Shaft resistance	R_f	Skin friction
FS	Factor of safety	R_{kl}	Coefficient for ultimate bearing capacity calculation
h_s	Empirical fitting term that depends on the soil type	$RMSE$	Root mean square error
I_c	Soil material index	R^2	Absolute fraction of variance
k_s	Modulus of subgrade reaction	s	Settlement
k_{sf}	Modulus of subgrade reaction of full-sized footing	s_a	Allowable settlement
k_{sp}	Modulus of subgrade reaction from <i>PLT</i>	s_f	Settlement of the foundation
K_ϕ	Coefficient for ultimate bearing capacity calculation	$s_{f,all}$	Allowable settlement of the foundation
MAD	Mean absolute deviation	s_i	Settlement of an arbitrary point
q	Load	s_p	Settlement of the plate
q_a	Allowable bearing capacity	$s_{p,all}$	Allowable settlement of the plate
q_c	Cone tip resistance	u_2	Pore water pressure
$q_{c,ave}, q_{c,mean}$	Averaged <i>CPT</i> cone resistance	α, β, γ	Model parameters
$q_{capacity}$	Foundation bearing capacity of the ground	σ_{vo}'	Effective overburden stress at bearing elevation

1. INTRODUCTION

Load-settlement (q - s) behavior of soils is commonly investigated by the plate load test (PLT) through which the ultimate bearing capacity (q_{ult}) and allowable bearing capacity (q_a) of shallow foundations are determined. As a result of PLT , the settlement (s) value is measured against the specified applied pressure (q), which consequently provides the basic geotechnical properties required for the design of shallow foundations. Based on the PLT results, different criteria have been suggested to compute q_{ult} from the q - s curves. In the study performed by **Kulhawy (2004)**, the loading corresponding to the settlement/width ratio of 0.1 ($\frac{s}{B} = 0.1$) was proposed to be q_{ult} , for all soil types except the sensitive clays, where the loading associated with $\frac{s}{B} = 0.04$ introduces q_{ult} . The mentioned criterion is well-known and distinguished in European standard (**Amar et al. 1998**).

One of the consequential benefits from q - s curves is the determination of the modulus of subgrade reaction (k_s), which is simply acquired from dividing the applied pressure by the corresponding settlement ($k_s = \frac{q}{s}$). k_s can be suggested based on the allowable settlement associated with different types of foundations, including shallow footings and mat foundations, and according to various standards in different countries. It can also be suggested as the slope of the initial tangent line to the load-settlement curve at zero settlement; yet, this definition is not widely used in geotechnical engineering practice. Generally, the calculation of $k_s = \frac{q}{s}$ yields more conservative designs in the former method, where it is dependent on the settlement level and is effectively estimated for each specific allowable settlement value. In many previously proposed correlations, like the one presented by **Bowles (1996)**, k_s is calculated for the settlement of 1 inch which is simplified as the following relation:

$$k_s = \frac{q_{ult}}{s = 1 \text{ inch (25mm)}} = 40q_{ult} = 40 \times FS \times q_a \quad (1)$$

where FS is the safety factor and q_a is the allowable bearing capacity.

It is worth noting that k_s depends on some parameters like the shape and width of foundation as well as the spatial variability of the stiffness/strength parameters of the soil underneath (**Mohseni et al. 2018**). **Vesic (1975)** showed different values of k_s for foundations having the same sizes and applied pressures. Also, **Farouk and Farouk (2014)** indicated that the rigidity of the soil-footing system should not be neglected for the determination of k_s . In terms of linear elastic models, soil plasticity is ignored, which is the reason why the distribution of k_s is anomalous at the edges of the foundation. To allow for such an anomaly, non-linear models should be employed. **Terzaghi (1996)** proposed *Eq. (2)* in order to evaluate the modulus of subgrade reaction of full-sized footings resting on sandy subgrades.

$$k_{sf} = k_{sp} \left(\frac{B_p + B_f}{2B_f} \right)^2 \quad (2)$$

where k_{sp} is the modulus of subgrade reaction from *PLT*, k_{sf} is the corresponding value for the actual foundation, B_p is the plate diameter and B_f is the foundation width.

Given the very fact that *PLTs* are costly and time-consuming, researchers have been recently more inclined to invoke empirical relationships to yield k_s , the majority of which are endorsed by in-situ tests (**Naeini et al. 2018**). A variety of field tests, amongst which the *SPT* and cone penetration test (*CPT*) are the most recent common ones, have garnered the attention of researchers to provide experimental correlations for *PLT* parameters. So far, less attention has been paid to the correlation between the results of *PLT* and *CPT*.

CPT is one of the most useful common in-situ tests, which can lend itself to the prediction of non-linear soil constitutive parameters, time-dependent stress-strain characteristics and profiling

the soil elasto-plastic behavior (Holtz *et al.* 2011; Fellenius 2015). On the other hand, given the very fact that repeatability is easily achieved in *CPT* soundings, and also that the accurate stratification and soil layering interpretations are viable with *CPT*, even in small thicknesses, it is therefore preferred amongst other common in-situ tests (Eslami *et al.* 2017, 2019).

Of late, the link between the *PLT* parameters and those of *CPTs* has been investigated in two different categories, the first of which is to directly obtain the bearing capacity based on *CPT* results and the second one is to predict the *q-s* curves through which q_{ult} can be estimated. In this article, the second category is adopted. The proposed methods and relationships for the determination of the ultimate bearing capacity from *CPT* results are enlisted in **Table 1** in chronological order (Saftner and Dagger 2018).

Table 1. Recent direct *CPT* methods to calculate the bearing capacity of footings on clean sands (Saftner and Dagger 2018).

Method	Surface footing	Remarks and embedment
Eslami & Gholami (2006)	$q_{ult} = R_{k1} \times q_c$	where R_{k1} is a function of D_f/B and q_c/σ_{vo}'
		Note: Measured q_c and q_c/σ_{vo}' are geometric means
		Influence zone: Depth of $2B$ beneath footing
Briaud (2007)	$q_{ult} = K_\phi \times q_c$ ($K_\phi = 0.23$)	Based on full-scale tests at Texas A&M University
		Influence zone: Depth of $2B$ beneath footing
Robertson & Cabal (2014)	$q_{ult} = K_\phi \times q_c$ ($K_\phi = 0.16$)	Where K_ϕ is a function of B/D_e , shape, and density
		Influence zone: Depth of $2B$ beneath footing
Mayne & Illingworth (2010)	$q_{ult} = 0.18q_{c,mean}$	Based on 30 footing load tests on 12 sands
		Note: $q_{c,mean}$ is averaged <i>CPT</i> cone resistance
		Influence zone: Depth of $1.5B$ beneath footing
Lehane (2012)	$q_{ult} = 0.16q_{c,ave}$	Based on 47 load tests
		Note: $q_{c,ave}$ is averaged <i>CPT</i> cone resistance
		Influence zone: $[B (m)]^{0.7}$

89 Deploying *CPT* results, many researchers have tried to correlate q to the dimensionless
 90 parameter, $\frac{s}{B}$, which consequently has resulted the following general formula (**Fellenius and**
 91 **Altaee 1994; Decourt 1999; Briaud 2007**).

$$92 \quad q = a_f \left(\frac{s}{B} \right)^{b_f} \quad (3)$$

93 Where q is the footing bearing pressure, s/B is the footing settlement normalized against the
 94 footing width B , and a_f and b_f are the model parameters. Based on **Mayne *et al.* (2012)**, the
 95 value of b_f was suggested to be 0.5, and the value of a_f for sands was reported to be dependent on
 96 the particle size distribution, relative density, geological condition and the percentage of fine
 97 grains. Regarding the ultimate bearing capacity criterion for sandy soils, when $\frac{s}{B} = 0.1$, q_{ult}
 98 equates to $0.316a_f$. Based on the theoretical studies conducted by **Briaud (2007)** and **Mayne *et***
 99 ***al.* (2012)**, **Eq. (4)** was proposed using 32 q - s data sets on 13 different soil types (note that q_c is
 100 the cone tip resistance).

$$101 \quad q = 0.585q_c \sqrt{\frac{s}{B}} \quad (4)$$

102 **Stuedlein and Holtz (2010)** assigned 1.77 MPa for a_f of the soil known as delta soil, yet it
 103 should be noted that the number of the studied data was quite limited. **Uzielli and Mayne (2011)**
 104 used q_{net} instead of q_c in **Eq. (4)** and rewrote it as **Eq. (5)**.

$$105 \quad q = h_s q_{net} \left(\frac{s}{B} \right)^{0.5} < q_{capacity} \quad (5)$$

106 where q_{net} is the net cone resistance, $q_{capacity}$ is the foundation bearing capacity of the ground and
 107 h_s is the empirical fitting term which was considered to be 0.58, 1.12, 1.47 and 2.7, for sands,
 108 silts, crushed (fissured) soils and clays, respectively. It is worth noting that the value of $q_{capacity}$ is

approximately close to the maximum value of q in the load-displacement profile (q_{max}). **Mayne (2014)** incorporated the soil material index, I_c , as an indicative of the type of soil behavior, into the other empirical relationships and proposed a correlation which could predict the q - s trend (**Eq. (6)**).

$$q = q_{net} \sqrt{\frac{s}{B}} \left[2.8 - \frac{2.3}{1 + \left(\frac{I_c}{2.4}\right)^{15}} \right] \quad (6)$$

Most researchers, who have previously studied the relationship between q - s profiles and *CPT* results, have confirmed that q is an *a priori* function of $\left(\frac{s}{B}\right)^{0.5}$ based on the correlations they have presented whose differences lay solely on the magnification factor. However, the mentioned relationships are open to question as q grows excessively in higher settlements. Their proposed correlations were therefore more acceptable for the values of $\frac{s}{B}$ up to 0.1, beyond which they would render unrealistic q values. In this study, an attempt has been made to reconcile this by establishing a novel and more appealing model, which could intrinsically capture the limiting nature of the bearing pressure.

Generally, it should be noted that the q - s curves in this study were obtained from reliable sources including 46 *PLTs* and their corresponding *CPT* logs. In the following sections, first, the collected database and the input and output variables are explained and then, the results of the modeling are provided in terms of equations and predicted versus measured trends of q - s . Also, the validation of the proposed hyperbolic function, and the comparison with previous models are discussed and the variations of q_{ult} , q_a and k_s with *CPT* parameters are thoroughly elaborated. Finally, sensitivity analysis of the input variables is presented.

2. METHOD OF ANALYSIS

Naturally, in q - s curves, values of the imposed pressure tend to be bounded to two extremes. In the suggested models, two different boundary conditions are expected for the lower extreme ($s \rightarrow 0$) and the higher extreme ($s \rightarrow +\infty$), where q tends to 0 and q_{max} , respectively.

There are some limitations associated with the previous models, including failure to incorporate the asymptotic behavior at limit settlements ($s \rightarrow +\infty$); hence, suggesting the need for simpler models with far superior applicability. It should be noted that the proposed function $q = f(s)$ to fit a PLT load-displacement profile should meet the following conditions: $f(0) = 0$, $f'(0)$ should be the global maximum, and $f'(\infty) \approx 0$ should be satisfied. Therefore, it is deemed that if a function meets the aforementioned criteria and is capable of precise prediction of the q - s curve, it can accurately serve to estimate the q_{max} , q_{ult} , q_a and k_s parameters, as schematically illustrated in **Figure 1**.

Many functions have been proposed to predict the load-settlement behavior of geo-materials amongst which the hyperbolic function has been admittedly used effectively in analyzing geotechnical properties, such as predicting the settlement, assessing the compressibility behavior and describing the relationship between the void ratio and effective stress (**Al-Shamrani 2005; Sridharan 2006; Zhang et al. 2014; Ahmed and Siddiqua 2016; Soltani et al. 2017; Liu and Zheng 2019**). Upon reviewing the literature, to the best of the authors' knowledge, very limited efforts have been devoted to the prediction of the q - s behavior of shallow footings on the basis of *CPT* records using the hyperbolic function. The hyperbolic function considered in the present paper is given in **Eq. (7)**, which has three constant coefficients.

$$q(s) = \frac{\alpha s}{\beta s + \gamma} \quad (7)$$

$$\text{boundary conditions} \left\{ \begin{array}{l} q(0) = 0 \\ \lim_{s \rightarrow +\infty} q(s) \approx \frac{\alpha}{\beta} \end{array} \right.$$

where α, β and γ are the model parameters, which can be obtained from *PLT* results using regression analysis. Schematic illustration of the proposed hyperbolic model is depicted in **Figure 1** along with the index parameters.

Figure 1. Schematic illustration of the hyperbolic function.

As shown in **Figure 1**, q_{max} is defined as the horizontal asymptotic of the bearing pressure function, q_{ult} is the value of bearing capacity corresponding to $\frac{s}{B} = 0.1$, q_a is the allowable bearing capacity equivalent to the allowable settlement (s_a) and k_s is the slope of the line starting at the origin and ending at the arbitrary point with the settlement of s_i and the bearing pressure of q_i .

CPT strength measurement is based on the soil failure with respect to the cone penetration, which is driven consistently and at a slow pace. Such properties presumably make *CPT* one of the most viable options among the in-situ tests to determine the above-mentioned hyperbolic model parameters. Herein, by adopting some *CPT* records, α, β and γ can be estimated as the

main contribution of the current paper that can be suggested from the load-displacement profiles of *PLT*. In other words, these parameters are linked to q_{max} , q_{ult} , q_a and k_s (**Eqs. (8a) to (8d)**).

$$q_{max} = \frac{\alpha}{\beta} \quad (8a)$$

$$q_{ult} = \frac{0.1\alpha B}{0.1\beta B + \gamma} \quad (8b)$$

$$q_a = \frac{\alpha s_a}{\beta s_a + \gamma} \quad (8c)$$

$$k_s = \frac{\alpha}{\beta s + \gamma} \quad (8d)$$

where α , β and γ can be presented as functions of the cone tip and shaft resistances, q_c and f_s . Therefore, with the *CPT* records at hand, model parameters α , β and γ can be predicted accordingly. By and large, a general model can be established to estimate the q - s profile on the basis of a database containing *CPT* and *PLT* results.

It is important to note that the foundation width (B) is also considered in the modeling. To this end, $\frac{s}{B}$ has been used to consider the effect of the plate dimension. This makes the settlement dimensionless consistent with previous studies like **Mayne and Dasenbrock (2018)**. Ergo, **Eq. (7)** could be rewritten as follows:

$$q(s) = \frac{\alpha \frac{s}{B}}{\beta \frac{s}{B} + \gamma} \quad (9)$$

Although α , β and γ are primarily functions of q_c and f_s , they are assumed to be functions of q_t and R_f herein to take the influence of pore water pressure into account. Hence, q_t (corrected cone resistance) could be defined as:

$$q_t = q_c + u_2(1 - a) \quad (10)$$

where u_2 is the pore water pressure and a is the net area ratio of cone tip.

Hence, in terms of the dimensional analysis for the hyperbolic model parameters, shown in *Eq. (9)*, the unit of α is kPa , and β and γ are both dimensionless. It is worth noting that the effect of embedment depth, D_f is reflected in q_t in such a way that the more the depth of the foundation, the more effectively it will impact q_t . In general, the current study seeks to validate the hyperbolic model and derive a relationship between the model and *CPT* parameters.

3. REVIEW OF THE DATABASE

The experimental data employed for the validation of *Eq. (9)* were gathered from credible sources, including 46 *CPT* logs and 46 q - s results from *PLTs*. Furthermore, other parameters like the footing width (B) and embedment depth (D_f) of the *PLTs* were documented. For *CPT* data, the depth of $2B$ has been regarded as the effective zone of load influence, according to the majority of the common methods for the estimation of the settlement beneath the foundation under symmetric loading (**Valikhah and Eslami 2019**). The parameters acquired from *CPT* and used in the analyses are the tip resistance q_t (q_c corrected for pore pressure) and skin friction ($R_f = \frac{f_s}{q_c}$). The mentioned *CPT* parameters were introduced in an arithmetic average sense through a depth of $2B$ so as to reflect the mean soil shear strength (**Eslami and Mohammadi 2016**). Based on the soil and loading conditions and according to **Schmertmann (1978)**, the effective depth under the foundation is equal to approximately $2B$. **Table 2** lists the experimental data related to a series of tests performed on a wide range of soil types, from silty clays to sands. The parameter q_{ult} is reported corresponding to $s/B \cong 0.1$. On the other hand, for any of the q - s curves in different cases, several data points with respect to various settlements were considered as the values for the input parameter, and the amount of pressure was considered as the output. Bar charts of the data are depicted in **Figure 2**, where the

vertical axis is the relative frequency. As shown in **Figure 2**, the data covers a wide range of *CPT* values, which belong to silty clays and sands.

Figure 2. Bar charts of the input variables.

Table 2. A summary of the data employed in this research.

Soil Type	Case No.	Footing Shape	from CPT		from PLT					Reference
			q_t (kPa)	R_f	D_f (m)	B (m)*	L/B	q_{ult} (kPa)	s (mm)	
Silt	N1	Square	2500	0.5	0	1	1	300	98	Eslami and Gholami (2006)
	N2		2800	0.5	0	1	1	325	97	
Silty Sand	N3	Square	7000	0.5	0	0.6	1	1260	55	
	N4		10000	0.5	0	0.6	1	1280	55	
Silty Clay	N5	Circular	1400	0.6	0	0.45	1	170	40	
	N6		1700	0.6	0	0.6	1	170	55	
	N7		2000	0.6	0	0.6	1	170	55	
Silty Clay	N8	Circular	3100	0.6	1.5	0.6	1	520	60	
	N9		4600	0.6	1.5	0.6	1	310	55	

	N10		5400	0.6	1.5	0.6	1	310	60	
	N11		6000	0.6	1.5	0.6	1	690	60	
Glaciofluvial Sand	N12	Rectangular	10720	0.51	0.4	0.6	1.18	1740	59	Mayne and Illingworth (2010)
	N13		10720	0.51	0.6	1.2	1.1	1740	119	
	N14		10720	0.51	0.8	1.7	1.12	1740	170	
	N15		10720	0.51	1.1	2.4	1.08	1740	245.8	
Siliceous Sand	N16	Square	3440	0.44	0.5	0.5	1	480	51	
Sand, Silty Sand	N17	Square	7520	0.65	0.76	1	1	1540	100	Briaud and Gibbens (1999)
	N18		7520	0.65	0.76	1.5	1	1540	154	
Silt	N19	Square	1700	0.5	0	1	1	375	115	Eslami and Gholami (2006)
	N20		2000	0.5	0	1	1	370	100	
Silty Sand	N21	Square	3000	0.5	0	0.6	1	1260	60	
Silty Clay	N22	Circular	500	0.6	0	0.3	1	170	33	
	N23		900	0.6	0	0.3	1	170	25	
Silty Clay	N24	Circular	1000	0.6	1.5	0.6	1	600	72	
	N25		1700	0.6	1.5	0.6	1	600	72	
	N26		2500	0.6	1.5	0.6	1	600	60	
White Fine Sand	N27	Square	3660	0.54	0	0.69	1	620	65	Mayne and Illingworth (2010)
Glaciofluvial Sand	N28	Rectangular	4010	0.63	0	1	1.02	840	102.4	
	N29		4010	0.63	0	1	1.02	840	102.4	
	N30		3200	0.63	1.1	2.4	1.08	640	260	
Compacted Fill	N31	Square	880	0.53	0	0.46	1	150	47	
	N32		3860	0.48	0	0.63	1	580	64	
	N33		2870	0.58	0	0.8	1	520	82	
Alluvial Sand	N34	Circular	6720	0.6	2.2	2.2	1	1280	250	
	N35		6720	0.6	2.2	2.2	1	1280	250	
	N36		10460	0.52	2.35	2.35	1	1730	245	
	N37		10460	0.52	2.35	2.35	1	1730	245	
Dune Sand	N38	Square	4010	0.66	0	0.7	1	840	71.7	
	N39		4010	0.66	0	0.7	1	840	71.7	
	N40		4010	0.66	0	1	1	840	102.4	
	N41		4010	0.66	0	1	1	840	102.4	
	N42		4010	0.66	0	1	1	840	102.4	
Silty Sand	N43	Circular	1710	0.55	0.6	1.82	1	1710	186	
Siliceous Dune Sand	N44	Square	480	0.44	0.5	0.5	1	480	51	
	N45		480	0.44	1	1	1	480	102	
	N46		480	0.44	1	1	1	480	102	

The main scope of this paper is the examination of the relationships between *CPT* and load-settlement parameters. It is worth noting that several geotechnical parameters could be estimated from *CPT* data, as highlighted in a number of previous studies (Eslami et al. 2019).

4. RESULTS

4.1. Hyperbolic model for load-displacement profiles

Based on the presented database, 46 *PLTs* were selected from the literature whose results were then fitted by the well-established hyperbolic model. The selected data set was compiled from all over the globe and was not restricted to a specific location so as to introduce sufficient diversity. The fitting parameters, including α, β and γ , were computed based on the least squares error optimization scheme. **Table 3** enlists the parameters for all the 46 cases. Furthermore, absolute fraction of variance (R^2), root mean square error (*RMSE*) and mean absolute deviation (*MAD*) are defined in *Eqs. (11), (12)* and *(13)*, respectively, and were exploited herein to assess the fitting accuracy of the relevant correlations.

$$R^2 = 1 - \left[\frac{\sum_1^M (q_{mi} - q_{ci})^2}{\sum_1^M (q_{mi})^2} \right] \quad (11)$$

$$RMSE = \sqrt{\frac{1}{M} \sum_1^M (q_{mi} - q_{ci})^2} \quad (12)$$

$$MAD = \frac{\sum_1^M |q_{mi} - q_{ci}|}{M} \quad (13)$$

where q_{mi} and q_{ci} are the measured and calculated pressures, respectively. Lower values of *RMSE* and *MAD* (close to zero) and higher values of R^2 (close to one) are indicators of superior model performance. **Table 3** corroborates the accuracy of *Eq. (9)* in replicating the load-displacement trends acquired from *PLTs*, substantiated in forms of high R^2 and low *RMSE* and *MAD* values. To be more specific, the R^2 values have remained higher than 99% and the *RMSE* and *MAD* values are lower than 34 and 17 kPa, respectively; hence, bearing witness to the efficacy of *Eq.*

(9). It should be noted that k_{s0} is the maximum modulus of subgrade reaction, values of q_a and k_s are corresponding to $\frac{s}{B} = 0.05$, and q_{max} is the asymptotic load.

Table 3. Summary of the regression analyses for the hyperbolic model, encapsulating all the studied data.

Case No.	α (MPa)	β	γ	R^2	RMSE (kPa)	MAD (kPa)	q_{max} (kPa)	q_a (kPa) (s/B=0.05)	k_{s0} (MN/m ³)	k_s (MN/m ³) (s/B=0.05)
N1	59	168.0	2.65	0.99	4	9	348	265	22	5
N2	62	162.4	2.62	0.99	5	9	379	286	23	6
N3	247	167.0	2.67	0.99	17	9	1480	1121	154	22
N4	277	170.3	2.70	0.98	34	15	1628	1236	171	25
N5	34	168.9	2.69	0.99	2	9	200	152	28	3
N6	32	162.1	2.62	0.99	2	9	200	151	21	3
N7	33	170.2	2.70	0.99	2	9	197	149	21	3
N8	101	166.1	2.66	0.99	8	10	609	461	63	9
N9	62	169.4	2.69	0.99	4	9	364	276	38	6
N10	60	165.5	2.66	0.99	4	9	360	272	37	5
N11	135	169.3	2.69	0.99	10	10	800	607	84	12
N12	307	163.7	2.64	0.99	17	8	1877	1419	194	28
N13	307	168.9	2.69	0.99	20	9	1819	1380	95	28
N14	307	165.1	2.65	0.99	17	8	1861	1409	68	28
N15	307	161.3	2.61	0.997	17	8	1905	1439	49	29
N16	87	166.3	2.66	0.997	5	8	521	394	65	8
N17	267	163.7	2.64	0.996	16	8	1633	1235	101	25
N18	267	169.8	2.70	0.994	20	9	1574	1194	66	24
N19	73	170.8	2.71	0.989	7	12	427	324	27	6
N20	58	163.5	2.63	0.994	8	17	357	270	22	5
N21	236	161.2	2.61	0.993	18	9	1464	1106	151	22
N22	32	165.6	2.66	0.991	3	10	195	147	40	3
N23	33	163.4	2.63	0.995	2	11	203	153	42	3
N24	116	171.0	2.71	0.988	11	13	678	515	71	10
N25	115	168.6	2.69	0.988	11	13	680	515	71	10
N26	115	166.3	2.66	0.994	8	9	692	524	72	10
N27	101	165.5	2.65	0.985	13	17	612	464	55	9
N28	138	164.7	2.65	0.990	14	12	837	633	52	13
N29	138	168.5	2.68	0.987	16	14	818	620	51	12
N30	114	167.0	2.67	0.997	6	7	680	515	18	10
N31	29	170.7	2.71	0.995	2	9	170	129	23	3
N32	97	170.9	2.71	0.988	11	13	570	432	57	9

N33	90	162.6	2.63	0.996	5	8	552	417	43	8
N34	212	167.4	2.67	0.993	18	8	1266	960	36	19
N35	212	161.3	2.61	0.996	14	7	1314	992	37	20
N36	303	166.9	2.67	0.996	18	7	1815	1375	48	28
N37	303	162.4	2.62	0.997	16	8	1865	1410	49	28
N38	150	170.9	2.71	0.996	9	8	880	668	79	13
N39	150	167.7	2.68	0.997	8	8	897	680	80	14
N40	150	162.8	2.63	0.997	8	8	924	698	57	14
N41	150	161.3	2.61	0.996	9	8	932	704	58	14
N42	150	169.2	2.69	0.997	8	8	889	674	56	13
N43	327	165.5	2.66	0.993	25	9	1976	1495	68	30
N44	90	162.5	2.63	0.993	7	9	554	418	68	8
N45	89	161.2	2.61	0.994	7	9	552	417	34	8
N46	91	164.5	2.64	0.993	7	9	553	419	34	8

239

240 Maximum soil strength means that the soil has reached the failure state or is on the verge of
241 failure. *CPT* has also the same mechanism with its resistance parameters (R_f and q_t) being
242 equivalent to the soil failure state. Based on the experimental and numerical studies, a
243 logarithmic spiral failure mode has been considered for the *CPT* results of homogenous soils as
244 shown in **Figure 3**. According to **Eslami and Mohammadi (2016)**, the failure mechanism of
245 *CPT* tests is approximately similar to that of shallow foundations. Therefore, it can be observed
246 that the pressure corresponding to the ultimate bearing capacity state or the same failure
247 threshold can be correlated to various *CPT* parameters.

Figure 3. Failure mechanism around the base of penetrometer (After **Eslami and Mohammadi 2016**)

4.2. Prediction of model parameters from CPT data

With regard to **Table 3**, it is clear that β and γ are roughly constant and equal to approximately 166.4 and 2.66, respectively. However, α possesses different values. Hence, α in **Eq. (9)** can be rewritten as **Eq. (14)** with the objective of reaching a general correlation for the hyperbolic model parameter(s).

$$\alpha = h(q_t, R_f) \quad (14)$$

To date, various approaches have been adopted to derive a general correlation for α . The aim in this study is to find a viable formulation, which correlates the model parameters in hyperbolic load-displacement model to the *CPT* data available in the proximity of the *PLT* location. To this end, the Volterra series is employed, the implication of which is on the basis of *GMDH*-type neural network (**MolaAbasi et al. 2013; MolaAbasi and Shooshpasha 2017**). Instead, the core concept of this regression scheme is to invoke genetic algorithm in combination with the multi-

layer perceptron neural networks to find an optimized configuration of hidden layers and neurons to form the polynomial correlation. Herein, the Volterra series is rewritten for the two input variables, including q_t and R_f , and a single output, α , as **Eq. (15)**:

$$\alpha = h(q_t, R_f) = a_1 + a_2 R_f + a_3 q_t + a_4 R_f^2 + a_5 q_t^2 + a_6 q_t R_f \quad (15)$$

where the parameters a_i are constant variables which are obtained from the regression analysis.

To fairly evaluate the efficacy of the proposed model and to compare it with the previous relationships, data were randomly categorized in two groups of training and validation, 70% of which were used for training and the rest were kept for validation. Therefore, 14 out of the total 46 data sets, obtained from the q - s curves, were randomly selected for validation data and the rest were utilized for the sake of training. In order to equate the ranges of training and validation in the modeling, their statistical parameters, including minimum, maximum and average, were monitored to remain comparable (MolaAbasi *et al.* 2015; MolaAbasi and Eslami 2018), as enlisted in **Table 4**. It is evident that, the statistical characteristics are in a similar level and are quite close to each other.

Table 4. Statistical parameters of the training and validation series.

Series	Parameter	q_t (kPa)	R_f	B (m)	q (kPa)	s (mm)
Training	average	4276	0.7	1	787	98
	min	480	0.44	0.4	170	25
	max	10720	0.66	2.35	1740	260
Validation	average	4599	0.73	1	897	115
	min	880	0.48	0.3	150	47
	max	10720	0.65	2.4	1740	250

Aforementioned regression analysis converts *Eq. (9)* to *Eqs. (16a)* and *(16b)*. It should be noted that these correlations are based only on the training data and the validation data has not been introduced to the regression process.

$$q = \frac{\alpha \frac{s}{B}}{2.68 + 161 \frac{s}{B}} \quad (16a)$$

$$\alpha(MPa) = 292.65 - 1026.95R_f - 0.008q_t + 964.37R_f^2 + 8.45 \times 10^{-7} q_t^2 + 0.05q_tR_f \quad (16b)$$

where q_t is the corrected q_c and R_f is the skin friction. With regard to the proposed roughly simple equation, predicted and measured values can be compared. Cases related to the predicted and measured q - s curves are presented in **Figure 4**, which clearly proves that *Eq. (16)* is a powerful modelling tool, according to the statistical parameters provided in **Table 5**.

Figure 4. Predicted and measured pressure values for (a) training data set; and (b) validation data set.

Table 5. Statistical results of the model.

Model stage	R ²	RMSE (kPa)	MAD (kPa)
Training	0.992	54	38
Validation	0.989	64	44
Total	0.990	57	39

4.3. Comparison with previous models

Given the very fact that the validation data were not incorporated in the model training process, they are used hereinafter for the purpose of comparison with previous methods to elaborate on the aptitude of different models to imitate the load-displacement trends.

To compare the current method with the previous ones, two specific model sets were considered. In the first set, relationships, which predicted q - s curves, including those proposed by **Mayne and Dasenbrock (2018)**, **Uzielli and Mayne (2011)** and **Stuedlein and Holtz (2010)**, were considered and in the second set, correlations proposed by **Briaud (2007)**, **Lehane et al. (2013)**, as well as **Robertson (2010)** are employed, considering $\frac{s}{B} = 0.1$ to assess q_{ult} . In the former set, scaled cumulative frequency (SCF) is presented against the relative error defined in **Eq. (17)** for comparison purpose.

$$E_r(\%) = \frac{q_{ci} - q_{mi}}{q_{mi}} \times 100 \quad (17)$$

Figure 5 shows the results of the first set where the relationships suggested by **Uzielli and Mayne (2011)** and **Stuedlein and Holtz (2010)** could be observed to render lower values for q (E_r is in the negative range). However, **Mayne and Dasenbrock (2018)** have proposed a more accurate prediction on the basis of the soil type, I_c . As it is plainly visible, the proposed formula in the current study is way more accurate than the rest as it is much closer to the vertical axis ($E_r = 0\%$) in all ranges of the $SCFs$ and consequently provides a better prediction. On the other hand, positive values of E_r indicate that the calculated q is more than its measured value (overestimation); whereas the negative values exhibit an opposite status (underestimation). Previous methods could, at large, be included in the latter group; hence, being more conservative and designs based on these models could be conceived more cost prohibitive.

313 In the latter set, however, the calculated vs. measured ultimate bearing capacity values have been
 314 employed to indicate the accuracy of the proposed relationships. Likewise, statistical parameters,
 315 such as R^2 , $RMSE$, and MAD , have been superimposed on the curves to make a quantitative
 316 comparison, as depicted in **Figure 6**. It is evident that, the method presented in the current study
 317 poses more aptitude to estimate q_{ult} in comparison to the other approaches.

318 **Figure 5.** Graphical representation of the accuracy of empirical correlations.
 319

Figure 6. Comparison of the accuracy of the current study in estimation of the ultimate bearing capacity of shallow footings with other relationships proposed in the literature.

4.4. Sensitivity analysis

In order to examine the effect of every single input variable on the output parameter, sensitivity analyses were performed by changing each of the input parameters at a constant pace while the rest were unwavering (Liong *et al.* 2000). The considered rate of changes ranges from -10% to 10%. As a result of the changes in every input variable, *RMSE* in the estimation of output (q) was determined and presented in **Figure 7**. In other words, the sensitivity analysis with respect to the changes of the parameter under study is drawn, while other parameters were adopted in the average sense; that is, changes of *RMSE* with respect to the input variables. As it is plainly demonstrated, the changes in parameters B and s barely affect q ; whereas the variations of R_f and q_t , particularly R_f , have substantial influences on the output parameters. Variations of the left sides of **Figure 7** in terms of R_f and q_t are almost similar whereas changes in the right hand side of R_f curve are more pronounced. Such a result corroborates that R_f is the most influential parameter on *RMSE*.

Another observation from **Figure 7** is that any perturbation in the measured soil parameters q_t and R_f , which can be considered as epistemic uncertainty and could be presumably due to measurement error, will have a reflection on the accuracy of the load/pressure estimations for shallow foundations. In other words, one could easily deduce that the soil parameters measurements, substantiated in form of in-situ tests logging, have paramount impacts on the accuracy of the relevant predictions as appears from **Figure 7**. This would imply that the type of in-situ test equipment and its measurement accuracy play a crucially important part in the appropriate estimation of other parameters, let's say the ultimate bearing capacity of shallow footings for example.

Figure 7. Results of the sensitivity analysis of the input parameters.

4.5. Application of the proposed model for future cases

The efficiency of the current approach for the new data set related to sands and silty sands and the calculation of the corresponding settlement are presented schematically in **Figure 8**. First, a *CPT* log is considered and then, parameters q_t and R_f are drawn against the depth (**Figure 8a**). With regard to the defined D_f and B , *CPT* data series are derived from D_f to D_f+2B and their average values are taken into account (**Figure 8b**). The arithmetic mean values of the parameters q_t and q_c , obtained from *CPT* data are considered in the current study. Using this arithmetic mean, resistance peaks are filtered using the method presented by **Eslami and Fellenius (1997)**.

358 Finally, by introducing the mean values of q_t and R_f , acquired from the *CPT* log, α presented in
359 *Eq. (16b)* is computed. Thereafter, the values of the applied pressures corresponding to various
360 settlement levels could be obtained from *Eq. (16a)* and the graph presented in **Figure 8c** could
361 be drawn accordingly. To this end, six values for the settlement (s_1 to s_6) are considered
362 schematically and the respective values of the applied pressure (q_1 to q_6) are acquired so as to
363 draw a complete load-settlement profile.

Figure 8. Schematic illustration of the load-settlement curves based on *CPT* results.

5. DISCUSSION

The main purpose of the current study was to find a robust relationship for the load-settlement behavior of soils based on *CPT* results. Such end was obtained in accordance with the gathered in-situ test results. The proposed formula is *Eq. (16)*, which correlates q to s , B and other properties obtained from *CPT* data components, such as R_f and q_t . The results show the superiority of the proposed relationship over previous ones.

5.1. Ultimate bearing capacity (q_{ult})

Based on different criteria for q_{ult} obtained from *PLTs*, loading up to $0.1B$ settlement is valid particularly for coarse-grained soils and sands. Hence, applying this criterion and putting it into *Eq. (16)*, *Eq. (18)* can be proposed for the evaluation of the ultimate bearing capacity based on *CPT* results.

379 $q_{ult} = 5.32(292.65 - 1026.95R_f - 0.008q_t + 964.37R_f^2 + 8.45 \times 10^{-7}q_t^2 + 0.05q_tR_f) \quad (18)$

380 where q_t is the corrected q_c in kPa and R_f is the skin friction in percent. A 3D illustration of the
 381 variation of q_{ult} with respect to q_t and R_f is given in **Figure 9**. As depicted, the increase in either
 382 CPT parameters leads to an increase in the ultimate bearing capacity. However, the rate of
 383 increase in the q_{ult} value with the increase of q_t is more than that of R_f . Moreover, for higher
 384 values of tip resistance, R_f is observed to be more influential. This phenomenon shows that the
 385 cohesive property will be enhanced in soils due to the increase of R_f , which consequently gives
 386 rise to the augmentation in the ultimate bearing capacity.

387
 388 **Figure 9.** Ultimate bearing capacity curve based on CPT data.

389 Based on the results of a *PLT*, the settlement corresponding to the failure of the plate can be
 390 obtained. In order to link the settlement values of a *PLT* to a true scale foundation, *Eq. (19)* can

391 be adopted from **Terzaghi et al. (1996)**, which relates the settlement of the foundation (s_f) to the
 392 settlement of the plate (s_p).

$$393 \quad \begin{cases} s_f = s_p \frac{B_f}{B_p} & \text{clayey soil} \\ s_f = s_p \left\{ \frac{[B_f(B_p+0.3)]}{[B_p(B_f+0.3)]} \right\}^2 & \text{sandy soil} \end{cases} \quad (19)$$

394 where B_f and B_p are the width (diameter) of the foundation and plate, respectively.

395 Accordingly, the ultimate bearing capacity of the foundation ($q_{ult,f}$) and plate ($q_{ult,p}$) can be
 396 related as follows:

$$397 \quad \begin{cases} q_{ult,f} = q_{ult,p} & \text{clayey soil} \\ q_{ult,f} = q_{ult,p} \left(\frac{B_f}{B_p} \right) & \text{sandy soil} \end{cases} \quad (20)$$

398 Based on the above-mentioned discussion, the factor of safety can be reached as follows:

- 399 1. Calculating the allowable settlement of the plate ($s_{p,all}$) based on the values of B_f , B_p and
 400 $s_{f,all}$, using the relations provided in foundation manuals for the relevant soil type.
- 401 2. Based on the value of q_t from the *CPT* data (i.e., the average q_t values corresponding to the
 402 depths of D_f to $D_f + 2B$) and the value of $s_{p,all}$, the value of q_a for the plate can be obtained.
- 403 3. Obtaining q_{ult} based on the criterion of $\frac{s}{B} = 0.1$ (**Eq. 18**) and calculating the factor of safety
 404 ($FS_p = q_{ult}/q_a$).

405 **5.2. Load-settlement curve (q - s)**

406 One of the applications of **Eq. (16)** is to delineate the q - s profile, while representing the load-
 407 displacement behavior of the footing, as depicted in a three-dimensional fashion in **Figure 10** for
 408 $B=1$ m. From the graphs, it could be observed that q - s surfaces grow with R_f , implying higher q
 409 values in similar settlement levels. On the other hand, for the predetermined settlements of 50

410 and 100 mm, q_a can be drawn in the q - q_t plane, as also shown in **Figure 10**. As it can be seen,
 411 the values of q_a corresponding to 100 mm settlement are detectably higher than those
 412 corresponding to 50 mm settlement with both increasing with R_f value.

413 **Figure 10.** Variations of q against settlement and CPT parameters for $B = 1m$.

414 5.3. Modulus of subgrade reaction (k_s)

415 Another application of **Eq. (16)** is to predict the modulus of subgrade reaction (k_s). As stated
 416 before (**Figure 1**), k_s can be predicted from the q - s curve acquired from PLT data and can be

computed for foundations employing *Eq. (9)*. **Figure 11** shows the three-dimensional representation of k_s as a function of q_t and s for the case of $B=1$ m. It should be noted that the considered value of R_f for this graph is the average of all data; i.e. $R_f=0.6$. As it is clear from the figure, settlement is inversely related to the modulus of subgrade reaction, whereas q_t , as an indicative of soil strength properties, has an augmenting influence on k_s . Generally, settlement is more of consequence than q_t .

Figure 11. Variation of the modulus of subgrade reaction against q_t with respect to different settlement levels ($R_f=0.6$).

6. CONCLUSIONS

In the current paper, a general framework was developed to predict and model the load-settlement response of shallow foundations based on *CPT* results. To this end, 46 q - s curves were carefully assessed and a sensitivity analysis was also conducted. Moreover, the proposed

model was compared to previous relationships readily available from literature. Prominent results obtained in the course of this study include:

- The proposed hyperbolic function was proven to have a high accuracy to predict the load-settlement behavior of shallow foundations.
- Constant parameters of the current hyperbolic model, including γ and β , stem from the general form of the q - s curves and the variable coefficient, α , is dependent on the soil strength properties obtained from *CPT* results. α was related to the corrected cone tip resistance (q_t) and skin friction (R_f) via regression analysis and the Volterra series.
- Dimensionless parameter $\frac{s}{B}$ was used and simple equations with high accuracy were proposed to estimate the allowable and ultimate bearing capacities of shallow foundations.
- To have a more accurate investigation, data were categorized into two groups of training and validation and the model parameters were estimated. Validation data were employed to make a comparison between the proposed model and previous ones, the results of which showed considerably high accuracy of the developed model ($R^2 > 99\%$).
- Sensitivity analysis was performed to assess the individual impacts of the input variables, the results of which demonstrated the higher sensitivity of the model output to R_f .
- All the results of q_{max} , q_{ult} , q_a and k_s were given in the forms of example 3D graphs to be readily used by potential readers.

Compliance with ethical standards

Funding: No funding was received for conducting this study.

Conflicts of Interest: The authors declare no conflict of interest.

Ethical approval: This article does not contain any studies with human participants performed by any of the authors.

Informed consent: Participants of the study were the authors and informed consent is not valid.

REFERENCE

- Ahmed, S.I., and Siddiqua, S. 2016. Compressibility behavior of soils: a statistical approach. *Geotechnical and Geological Engineering*, 34(6): 2063–2070. Springer.
- Al-Shamrani, M.A. 2005. Applying the hyperbolic method and C/C_c concept for settlement prediction of complex organic-rich soil formations. *Engineering geology*, 77(1–2): 17–34. Elsevier.
- Amar, S., Baguelin, F., Canepa, Y., and Frank, R. 1998. New design rules for the bearing capacity of shallow foundations based on Ménard pressuremeter tests. In *Geotechnical site characterization*. pp. 727–733.
- Bowles, L.E. 1996. *Foundation analysis and design*. McGraw-hill.
- Briaud, J.-L. 2007. Spread footings in sand: load settlement curve approach. *Journal of Geotechnical and Geoenvironmental Engineering*, 133(8): 905–920. American Society of Civil Engineers.
- Briaud, J.-L., and Gibbens, R. 1999. Behavior of five large spread footings in sand. *Journal of Geotechnical and Geoenvironmental Engineering*, 125(9): 787–796. American Society of Civil Engineers.
- Decourt, L. 1999. Behavior of foundations under working load conditions. 11th Pan-American Conference on Soil Mechanics and Geotechnical Engineering, Foz do Iguaçu, 4: 453–488.
- Eslami, A., Alimirzaei, M., Aflaki, E., and Molaabasi, H. 2017. Deltaic soil behavior classification using CPTu records—Proposed approach and applied to fifty-four case histories. *Marine Georesources & Geotechnology*, 35(1): 62–79. Taylor & Francis.
- Eslami, A., and Fellenius, B.H. 1997. Pile capacity by direct CPT and CPTu methods applied to 102 case histories. *Canadian Geotechnical Journal*, 34(6): 886–904. NRC Research Press Ottawa, Canada.
- Eslami, A., and Mohammadi, A. 2016. Drained soil shear strength parameters from CPTu data for marine deposits by analytical model. *Ships and Offshore Structures*, 11(8): 913–925. Taylor & Francis.
- Eslami, A., Moshfeghi, S., MolaAbasi, H., and Eslami, M.M. 2019. Piezocone and Cone Penetration Test (CPTu and CPT) Applications in Foundation Engineering. Butterworth-Heinemann.

483 Eslami, A. and Gholami, M. 2006. Analytical Model for the Ultimate Bearing Capacity of Foundations
484 from Cone Resistance. *Scientia Iranica*, 13(3), pp.223-233.

485 Farouk, H., and Farouk, M. 2014. Calculation of subgrade reaction modulus considering the footing-soil
486 system rigidity. In *Vulnerability, Uncertainty, and Risk: Quantification, Mitigation, and*
487 *Management*. pp. 2498–2507.

488 Fellenius, B.H. 2015. Static tests on instrumented piles affected by residual load. *DFI Journal-The Journal*
489 *of the Deep Foundations Institute*, 9(1): 11–20. Taylor & Francis.

490 Fellenius, B.M., and Altaee, A. 1994. Stress and settlement of footings in sand. *GEOTECHNICAL*
491 *SPECIAL PUBLICATION*,: 1760. Citeseer.

492 Holtz, R.D., Kovacs, W.D., and Sheahan, T.C. 2011. *An introduction to geotechnical engineering*.
493 Pearson Upper Saddle River, NJ.

494 Kulhawy, F.H. 2004. On the axial behavior of drilled foundations. In *GeoSupport 2004: drilled shafts,*
495 *micropiling, deep mixing, remedial methods, and specialty foundation systems*. pp. 34–51.

496 Lehane, B.M. 2012. Relating foundation capacity in sands to CPT qc. *Geotechnical and Geophysical Site*
497 *Characterization 4*,: 63. CRC Press.

498 Lehane, B.M., Li, Y., and Williams, R. 2013. Shaft capacity of displacement piles in clay using the cone
499 penetration test. *Journal of Geotechnical and Geoenvironmental Engineering*, 139(2): 253–266.
500 American Society of Civil Engineers.

501 Liong, S.-Y., Lim, W.-H., and Paudyal, G.N. 2000. River stage forecasting in Bangladesh: neural network
502 approach. *Journal of computing in civil engineering*, 14(1): 1–8. American Society of Civil
503 Engineers.

504 Liu, Y., and Zheng, Y. 2019. *Plastic Mechanics of Geomaterial*. Springer.

505 Mayne, P.W. 2014. Interpretation of geotechnical parameters from seismic piezocone tests. In
506 *Proceedings, 3rd International Symposium on Cone Penetration Testing*. pp. 47–73.

507 Mayne, P.W., and Dasenbrock, D. 2018. Direct CPT Method for 130 Footings on Sands. In *Innovations*
508 *in Geotechnical Engineering*. pp. 135–146.

509 Mayne, P.W., and Illingworth, F. 2010. Direct CPT method for footing response in sands using a database
510 approach. In *Proceedings of the 2nd International Symposium on Cone Penetration Testing*,
511 *Huntington Beach, Calif*.

512 Mayne, P.W., Uzielli, M., and Illingworth, F. 2012. Shallow footing response on sands using a direct
513 method based on cone penetration tests. In *Full-Scale Testing and Foundation Design: Honoring*
514 *Bengt H. Fellenius*. pp. 664–679.

515 Mohseni, S., Payan, M., and Jamshidi Chenari, R. 2018. Soil-structure interaction analysis in natural
516 heterogeneous deposits using random field theory. *Innovative Infrastructure Solutions*, 3(1): 62.
517 Springer.

518 MolaAbasi, H., Dikmen, U., and Shooshpasha, I. 2015. Prediction of shear-wave velocity from CPT data
519 at Eskisehir (Turkey), using a polynomial model. *Near Surface Geophysics*, 13(2): 155–167.

520 MolaAbasi, H., and Eslami, A. 2018. Prediction of drained soil shear strength parameters of marine
521 deposit from CPTu data using GMDH-type neural network. *Marine Georesources &*
522 *Geotechnology*,: 1–10. Taylor & Francis. doi:10.1080/1064119X.2017.1415400.

523 MolaAbasi, H., Eslami, A., and Shourijeh, P.T. 2013. Shear wave velocity by polynomial neural networks
524 and genetic algorithms based on geotechnical soil properties. *Arabian Journal for Science and*
525 *Engineering*, 38(4): 829–838. Springer.

526 MolaAbasi, H., and Shooshpasha, I. 2017. Polynomial Models Controlling Strength of Zeolite-Cement
527 Sand Mixtures. *Scientia Iranica*, 24(2): 526.

528 Naeini, S.A., Moayed, R.Z., Kordnaeij, A., and Mola-Abasi, H. 2018. Prediction of subgrade reaction
529 modulus of clayey soils using group method of data handling. *Scientia Iranica*,. Sharif University of
530 Technology.

531 Robertson, P.K. 2010. Soil behaviour type from the CPT: an update. In 2nd International symposium on
532 cone penetration testing. pp. 575–583.

533 Robertson, P.K. and Cabal, K.L. 2014. Guide to cone penetration testing. Sixth edition. Published by
534 Gregg In-situ, Signal Hill, California: 126 pages.

535 Saftner, D., and Dagger, R. 2018. Cone Penetration Testing Manual for Highway Geotechnical Engineers.

536 Schmertmann, J.H. 1978. Guidelines for cone penetration test: performance and design. United States.
537 Federal Highway Administration.

538 Soltani, A., Deng, A., Taheri, A., Sridharan, A., and Estabragh, A.R. 2017. A framework for
539 interpretation of the compressibility behavior of soils. *Geotechnical Testing Journal*, 41(1): 1–16.
540 ASTM International.

541 Sridharan, S. 2006. Non-vanishing derivatives of Lyapunov exponents and the pressure function.
542 *Dynamical Systems*, 21(4): 491–500. Taylor & Francis.

543 Stuedlein, A.W., and Holtz, R.D. 2010. Undrained displacement behavior of spread footings in clay. In
544 *Art of Foundation Engineering Practice*. pp. 653–669.

545 Terzaghi, K. 1955. Evaluation of cone coefficients of subgrade reaction. *Geotechnique*, 5(4): 297–326. Thomas
546 Telford Ltd.

- 547 Terzaghi, K., Peck, R.B., and Mesri, G. 1996. Soil mechanics in engineering practice. John Wiley &
548 Sons.
- 549 Uzielli, M., and Mayne, P.W. 2011. Serviceability limit state CPT-based design for vertically loaded
550 shallow footings on sand. *Geomechanics and Geoengineering: An international journal*, 6(2): 91–
551 107. Taylor & Francis.
- 552 Valikhah, F., and Eslami, A. 2019. CPT-Based Nonlinear Stress-Strain Approach for Evaluating
553 Foundation Settlement: Analytical and Numerical Analysis. *Arabian Journal for Science and*
554 *Engineering*, 44(10): 8819–8834. Springer.
- 555 Vesic, A.B. 1961. Beams on elastic subgrade and the Winkler's hypothesis. In *Proc. 5th Int. Conf. on*
556 *SMFE*. pp. 845–851.
- 557 Vesic, A.S. 1975. Bearing Capacity of Shallow Foundations, *Foundation Engineering Handbook*, ed.
558 Winterkorn, FS and Fand, HY. Van Nostrand Reinhold, New York.
- 559 Zhang, Q.Q., Li, S.C., Liang, F.Y., Yang, M., and Zhang, Q. 2014. Simplified method for settlement
560 prediction of single pile and pile group using a hyperbolic model. *International Journal of Civil*
561 *Engineering*, 12(2): 146–159. *International Journal of Civil Engineering*.