Strength Deterioration Mechanism of Bentonite Modified Loess After Wetting-Drying Cycles

Zelin Niu

Xi'an University of Architecture and Technology

Jian Xu (✉ xujian@xauat.edu.cn)

Xi'an University of Architecture and Technology

Yanfeng Li

Xi'an University of Architecture and Technology

Zefeng Wang

Xi'an University of Architecture and Technology

Bao Wang

Xi'an University of Architecture and Technology

Research Article

Keywords: Wetting-drying cycles, Bentonite, Loess, SEM, Direct shear test

Posted Date: September 3rd, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-746249/v1>

License: © ⓘ This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Title page

Strength deterioration mechanism of bentonite modified loess after wetting-drying cycles

Zelin Niu^{1,2}, Jian Xu^{1,2*}, Yanfeng Li¹, Zefeng Wang¹, Bao Wang^{2,3}

¹School of Civil Engineering, Xi'an University of Architecture and Technology, Xi'an 710055, Shaanxi, China

²Shaanxi Key Laboratory of Geotechnical and Underground Space Engineering, Xi'an University of Architecture and Technology, Xi'an 710055, Shaanxi, China

³School of Environment and Municipal Engineering, Xi'an University of Architecture and Technology, Xi'an 710055, Shaanxi, China

Corresponding author: **Jian Xu** E-mail: xujian@xauat.edu.cn Telephone number: +86 29 82202947

Information about all authors:

Zelin Niu: E-mail: niuzldq@xauat.edu.cn ORCID: <https://orcid.org/0000-0002-4435-8333>

Jian Xu: E-mail: xujian@xauat.edu.cn ORCID: <https://orcid.org/0000-0003-1728-9536>

Yanfeng Li: E-mail: liyanfeng@xauat.edu.cn ORCID: <https://orcid.org/0000-0002-4176-4520>

Zefeng Wang: E-mail: wzf15735103791@xauat.edu.cn ORCID: <https://orcid.org/0000-0003-0768-3994>

Bao Wang: E-mail: wangbao@xauat.edu.cn ORCID: <https://orcid.org/0000-0001-8980-8767>

Abstract: The employment of bentonite modified loess (BML) is a common method of constructing the anti-seepage lining of landfills in the loess region of China, and its long-term secure performance is threatened by wetting-drying (W-D) cycles. Taking the remolded loess (RL) and BML with 15% in mass of bentonite as research objects, the W-D cycles test, scanning electron microscope (SEM) test and direct shear test were carried out to analyze the effects of W-D cycles on the microstructure and shear strength of samples. The regression equations between strength and micro-pore structure parameters were established by multivariate linear stepwise regression method. The damage mechanism of BML after W-D cycles was studied by establishing damage degree models based on porosity and cohesion. Results indicate that clay minerals such as montmorillonite in BML absorb water and expand to fill the macropores, resulting in more medium and small pores and more pronounced surface contact of particles. After W-D cycles, the particle arrangement of samples before and after bentonite modification tends to be loose. Both the porosity and fractal dimension increase and tend to stabilize after five cycles. The BML exhibits lower porosity and greater fractal dimension while its cohesion and internal friction angle show more significant decrease after W-D cycles than those of RL. The damage variables based on porosity and cohesion well describe the W-D induced damage of loess before and after modification from macro- and micro-scale perspectives. The damage degree of samples increases with W-D cycles, but the increment decreases.

Keywords: Wetting-drying cycles; Bentonite; Loess; SEM; Direct shear test

Declarations

Funding: The research described in this paper was financially supported by the National Natural Science Foundation of China (Grant Nos. 51878551, 51478385).

Conflicts of interest/Competing interests: The authors have no conflicts of interest to declare that are relevant to the content of this article.

Availability of data and material: Some or all data, figures, or code that support the findings of this study are available from the corresponding author upon reasonable request.

Code availability: Not applicable

Authors' contributions: Conceptualization: [Zelin Niu]; Methodology: [Jian Xu], [Bao Wang]; Formal analysis and investigation: [Zelin Niu], [Yanfeng Li], [Zefeng Wang]; Writing - original draft preparation: [Yanfeng Li], [Zefeng Wang]; Writing - review and editing: [Zelin Niu], [Yanfeng Li]; Data Curation: [Zelin Niu], [Zefeng Wang], [Yanfeng Li]; Funding acquisition: [Jian Xu]; Resources: [Jian Xu]; Supervision: [Jian Xu], [Bao Wang].

1 Introduction

There are abundant loess resources in the Northwest of China, which refers to silt deposits formed by wind transport in the Quaternary period. The weak cementation between loess particles results in large pores and high porosity. Sanitary landfill is the primary disposal method of municipal solid waste (MSW) in China, and the compacted clay liner is a good choice for the anti-seepage system at the bottom of the landfill. With the lack of adequate suitable clay resources in Northwest China, the transfer of appropriate clay resources from the outside areas needs a large amount of financial support, which will increase the cost of the anti-seepage project of the landfill. So, the local loess resources will undoubtedly become the best choice of anti-seepage materials for the landfill. However, the loess is an impervious layer at the bottom of a landfill, which does not meet the permeability and strength requirements. Therefore, how to modify the loess to suit compacted clay liner requirements has become one of the research hotspots.

Scholars have carried out macroscopic and microscopic tests on the bentonite-modified soils. In terms of macroscopic tests, Mei et al. (2020) conducted tests on the engineering properties of the sand improved by bentonite mud, and found that the bentonite mud well improves the permeability, shear strength, and slump of the water-rich sand soil. Cheng et al. (2020) studied the stabilizing effect of nano-bentonite on the consolidation of clay. Nano-bentonite can promote the internal cementation of soil particles and effectively reduce the compressibility of clay. Qasaimeh et al. (2020) investigated the feasibility of hydrophilic nano-bentonite modified clay for landfill cover. Qie et al. (2017) noticed that soil compaction and bentonite content had a considerable effect on the cohesion of BML, but insignificant on the internal friction angle. Rahmani et al. (2020) studied the influence of bentonite and lime on the physicochemical and rheological properties of loess and found that the hydration, agglomeration and interparticle flocculation caused by additives promoted the intergranular cementation. In terms of microscopic tests, Wang et al. (2016) analyzed the adsorption characteristics of loess modified soil-bentonite (LSB) for lead by SEM and X-ray diffraction (XRD), and the adsorption capacity of LSB increases linearly with the loess content. Yan et al. (2011) observed a significant decrease in the number of macropores in fine-grained soil mixed with bentonite based on the mercury intrusion porosimetry (MIP). Zhang et al. (2011) conducted permeability tests and SEM tests on BML and revealed the mechanism of the decrease of permeability of modified loess from the microscopic perspective. Yang et al. (2011) analyzed the pore structure of loess samples with different bentonite contents by SEM tests and found that with the increase of bentonite content, the number of pores in loess increased sharply, but the pore area and pore diameter decreased.

The Loess Plateau of China is a typical arid and semi-arid region, where the loess is subject to frequent W-D cycles due to rainfall and evaporation (Wang et al. 2015). Therefore, it is necessary to study the influence of W-D cycles on the strength and microstructure of loess. Muñoz-Castelblanco et al. (2012) studied the correlation between the water retention properties and the microstructure of unsaturated loess in northern France and noticed that the change of microstructure accompanied the change of hydraulic state in the process of W-D. Zuo et al. (2020) analyzed the mechanical properties and microstructure deterioration mechanism of silty loess under long-term seepage conditions through compression tests and microscopic tests. The formation of cracks in loess is closely related to the matric suction change and the decrease of loess strength (Mu et al. 2020; Mady and Shein 2020; Ye et al. 2020). Many scholars have studied the hydraulic behavior and microstructure of loess under W-D cycles through multiscale methods. Zhou et al. (2019) studied W-D cycles and loess layer thickness on the release and transport of soil colloidal particles (SCPs) of loess columns. Ye et al. (2019) used SEM and

nuclear magnetic resonance (NMR) technology to study the microscopic characteristics of paleosols, found that the proportion of micropores decreases after W-D cycles while those of the macropores and mesopores increase. Xu et al. (2020a, b) studied the failure mechanism of sodium sulfate saline intact loess under the coupled action of W-D cycles and salt weathering. The modified loess under W-D cycles has also attracted wide attention. The addition of lime, fly ash are mainly used to improve the strength and collapsibility of loess (Zhang et al. 2017; Yan et al. 2017). Yan et al. (2017) studied the unconfined compressive strength and pore size distribution of lime-fly ash loess (LFL) under W-D and freeze-thaw conditions. Zhang et al. (2017) studied the influence of W-D cycles on the strength of cement stabilized loess (CSL). However, there are few studies on the relationship between the mechanical properties and microstructure of BML under W-D cycles. The degradation mechanism of strength and microstructure of BML under W-D cycles needs to be further studied.

In this study, laboratory tests were carried out on the RL and BML with 15% in mass of bentonite to investigate the shear strength and microstructure characteristics after W-D cycles and to explore the macro-and micro-scale damage mechanism under W-D cycles and put forward damage models of BML after W-D cycles. The results will have a particular reference value for improving local loess resources in Northwest China and the construction of anti-seepage linings in landfills.

2 Materials and methods

2.1 Soil property

The test loess was taken from the sidewall of a foundation pit in Xi'an, Shaanxi Province, with a depth of 2-3 m from the surface. It belongs to the late Pleistocene Q_3 loess with yellowish-brown color and obvious vertical joints. The loess samples were pre-treated sufficiently by air-drying, grinding, and sieving. According to the Standard for Geotechnical Test Methods GB/T50123-2019 (Ministry of Housing and Urban-Rural Development of the People's Republic of China 2019), the basic physical properties of the loess samples were analyzed, as listed in Table 1. The particle size distribution curve of test loess is shown in Fig. 1. The uniformity coefficient C_u is 8.33, and the curvature coefficient C_c is 1.33. The distribution of grain composition of the loess is: sand (12.88%), silt (80.42%), and clay (6.7%). The bentonite used in the tests is natural sodium-based bentonite, which is grey-white and powdery. The basic properties such as expansion index, liquid-plastic limit and specific gravity were determined, and the mineral components were determined by XRD. The basic properties of bentonite are shown in Table 1. The particle size distribution curve is shown in Fig. 1. The C_u is 5.65, and C_c is 2.19.

Table 1 Physical properties of the tested soil

Loess physical index	Value	Sodium bentonite physical index	Test methods	Value	Main minerals of bentonite	XRD results (%)
Liquid limit, w_L (%)	30.2	Specific gravity		2.65	Montmorillonite	70.56
Plastic limit, w_P (%)	17.8	Liquid limit, w_L /%	ASTM D 4318-05	314	Quartz	18.30
Plasticity index, I_p	12.4	Plastic limit, w_P /%		40	Plagioclase	5.8
Initial water	22.32	Swelling index	ASTM	39	Kaolin	2.94

content, w (%)	mL/2g	D 5890-06			
Optimum moisture content, w_{op} (%)	18	Anion exchange capacity (meq / 100g)	ASTM D 7503-10	91	Potassium feldspar
Maximum dry density ρ_{dmax} (g/cm ³)	1.54			Else	2

Fig. 1 Particle-size distribution curve of loess

2.2 Preparation of soil samples

BML samples were prepared according to the percentage of the dry weight of bentonite to that of loess. The calculated loess and bentonite were poured into a small agitator to mix and homogenize sufficiently. Through the light compaction test, the optimal water content of BML is 20%, and the maximum dry density is 1.61 g/cm³. The water content and dry density of the improved loess samples are set accordingly. The direct shear test samples of RL and BML are made of ring knife samples with a diameter of 61.8 mm and a height of 20 mm. The SEM samples are cut from the ring knife samples with a size of 10 mm × 10 mm × 20 mm, and the preparation process of BML is shown in Fig. 2.

Fig. 2 Preparation process of bentonite modified loess

2.3 Tests procedures

2.3.1 Wetting-drying cycles

The drying process of samples adopts an electro-thermostatic blast oven. The temperature control range is $+10 - 250$ °C, and the temperature fluctuation is ± 1 °C. During the test, to increase the drying rate and reduce the influence of temperature on the structure of soil samples, the drying temperature was set to 45°C. The time required for the water content of the samples to reach a stable state was verified by trial tests. The test procedure is shown as follows. Two sets of standard ring knife samples ($d=61.8$ mm, $h=20$ mm) of RL and 15% BML were weighed and placed in a drying oven for drying at 45 °C, taken out at regular intervals and weighed to calculate the water content. Fig. 3 shows the relationship between water content and the drying time. The water content of the samples decreases over drying time. The water content of the samples decreases significantly in the first 6 h and tends to be stable after 24 h. Besides, the water content of RL decreases over drying time, which is higher than that of the BML. The water content of RL is more diminutive than BML after reaching a stable state, but the water content is less than 1%. Therefore, it can be seen from the above verification test that the samples drying at 45 °C for 24 h can achieve a better drying effect, and the drying time is set to 24 h.

The water film transfer method is used in the sample wetting process. The filter paper is more prominent than the sample diameter and is placed on the surface of the sample. A certain amount of water is added to the filter paper through the dropper. The water evenly penetrated the soil through the filter paper. When the water content reaches the preset value, the samples are fully wrapped with a plastic film and kept in a close chamber for 24 h. The water is evenly diffused in the soil to complete a W-D cycle. The number of W-D cycles is 0, 1, 2, 3, 4, 5, and 10.

Fig. 3 Relationship between water content and drying time

2.3.2 Direct shear test

After different W-D cycles, the samples were mounted on the strain-controlled direct shear test apparatus. Considering the actual landfill load, the normal pressure is set to 30, 50, 100, 150 kPa, respectively, which represents the change of normal pressure at the top of the impervious layer during the whole landfill process. The shear rate of the test is 0.08mm/min. If the shear stress has a peak, continue to

shear until the shear displacement reaches 4 mm or stop the test when the shear displacement reaches 6 mm.

2.3.3 SEM test

The test process for the SEM tests is shown in Fig. 4. The SEM samples after different W-D cycles were broken from the middle, and the flat section without obvious cracks was selected as the observation surface. The sidewall of the selected sample was wrapped tightly with tin foil to expose the observation section, which was then fixed on the metal base with conductive glue. Then gold plating was performed to make the surface of the sample conductive after vacuuming, and then used in SEM scanning. The Quanta 600FEG SEM was used in the SEM tests. Three points are selected on each sample surface to ensure that representative structural units can be thoroughly selected. The 1000 and 2000 magnification are selected to scan the sample, respectively.

Fig. 4 SEM test procedure

3 Results

3.1 Microstructure of loess after W-D cycles

3.1.1 Qualitative analysis of SEM images of samples

Fig. 5 presents the SEM images (×2000) of the RL after different W-D cycles. From the Figure, the soil particles of the RL without W-D cycles are mainly silt grains and silt-clay aggregates. The contact area between the particles is small, and the contact mode is mainly point contact. The aerial pores distribution has an obvious difference with the intergranular large pores, the aerial pores are inter-connective between soil particles. The skeletal structure of the loess presents a clot mosaic colloidal structure. With the increase of W-D cycles, the clay films are generated on the surface of silt grains with a diameter of about 30 μm. The partially cemented silt-clay aggregates gradually separate during the water migration process, the number of intergranular pores increases and some intergranular pores are gradually connected to form new water migration channels. The cementation between the particles is weakened to

produce the loosened soil structure, resulting in the reduction of soil strength. After four W-D cycles, the original pores continue to serve as the main water migration channel, and the weakly cemented particles lose their linkage, leading to an increase in the number of intergranular pores, and the soil structure is further reduced. However, after five W-D cycles, the changes in the number of pores and soil particles are insignificant, and a new relatively stable structure was formed inside the soil, and the soil strength stabilized with the increase of W-D cycles.

Fig. 5 SEM images of RL under W-D cycles (×2000)

Fig. 6 shows the SEM images (×2000) of BML with different W-D cycles. From the figure, the particles of BML without the W-D cycle are mainly composed of cemented clay aggregates, the surface of the particles is wrapped by clay film, the contact between particles is mainly surface cementation, and the pores are uniformly distributed and are mainly small and medium-sized intergranular pores. The skeleton of the modified loess particles presents an inlaid cemented structure, so the structure of the modified loess is more stable than unmodified loess. After the fourth W-D cycle, the clay minerals between the soil particles are gradually reduced, the cementation between the soil particles decreases, and the partially cemented clay aggregates are gradually separated into small particles. The contact between particles is still dominated by surface cementation, the soil structure becomes looser, and intergranular pores with larger diameters are generated. After five W-D cycles, part of the clay film on the surface of aggregates particles is further dissolved into small pieces, which are attached to the surface of monomer particles or filled in the intergranular pores. The contact mode between particles gradually transitions from surface cementation to point contact. The small and medium-sized pores continue to decrease, while the large intergranular pores gradually increase and tend to be connected. The pore wall develops smoothly as a water migration channel during W-D cycles. After the tenth W-D cycle, the monomer silt particles with a diameter of about 25μm in the skeleton particles increases, the cemented clay minerals are significantly reduced, the cementation between the particles is weak, and the contact mode is mainly point contact. The pores are mainly aerial pores, which leads to the weakening of the soil structure and strength.

Fig. 6 SEM images of BML under W-D cycles ($\times 2000$)

3.1.2 Quantitative analysis of loess SEM images

Based on the particles (pores) and cracks analysis system (PCAS) (Liu et al. 2011), SEM images with the magnification of 1000 times were selected for microscopic quantitative analysis. Fig. 7 shows the identification and analysis process of pores and particles. Binarized images are obtained through threshold segmentation and denoising steps, and the pores and particles are automatically segmented and identified. The white and black areas represent the pores and particles, respectively. Various geometric parameters and statistical parameters of pores and particles are obtained by a built-in algorithm. The quantitative indicators of microstructure such as surface porosity and fractal dimension were selected to describe the changes of particles and pores of the samples after the W-D cycles. The pore area ratio n is the ratio of the pore area to the total area in the statistical area; the fractal dimension of the pore reflects the development and complexity of the soil. Generally, the larger the fractal dimension, the more complex the pore structure distribution, the scattered distribution of soil particles and the weak degree of agglomeration.

Fig. 7 Pores and particles identification and analysis process by PCAS system

Fig. 8 (a) illustrates the porosity of RL and BML after W-D cycles. It can be seen that the porosity of RL and BML increases with the number of W-D cycles and tends to be stable after five cycles. After five W-D cycles, due to the continuous migration of water in the pore channel, some small particles are washed away from the pore wall, the original small and medium-sized pores are enlarged to form larger pores, resulting in higher porosity. After more W-D cycles, the pores are gradually dominated by aerial

pores. The pore channels for the migration of water are redistributed and soil particles are rearranged. The original structure becomes a relatively uniform loose structure, and the porosity no longer changes. Furthermore, the porosity of RL is always greater than that of BML after W-D cycles. The pore structure of RL is mainly composed of large intergranular pores between particles. The addition of bentonite makes montmorillonite and other mineral components swell and fill into the macropores in the loess skeleton, strengthening the cementation between particles and reducing its porosity. The porosity of the BML is lower than that of the RL during the whole W-D cycles process.

The variation of pore fractal dimension of RL and BML with W-D cycles are shown in Fig. 8 (b). The results show that the pore fractal dimension of RL and BML increases firstly, and the fractal dimension of RL reaches the peak after three W-D cycles. they all tends to be stable after five W-D cycles. The fractal dimension of pores of BML is smaller than that of RL before W-D cycles because of the coexistence of aerial pores and intergranular pores in the pore structure of RL and the uneven distribution of pores among particles. While the filling of bentonite makes the number of large pores in BML decreases sharply, the pores are mainly medium and small, and the pore structure of BML is more complex than that of RL. Therefore, the fractal dimension of RL in the initial state is more significant than that of the improved loess. After W-D cycles, the main primary water migration channel in RL is the well-connected pores, while the primary interconnected pore channel is less in BML. Influenced by water migration, more small and complex pores are formed in the soil. The number and shape of pores in the soil gradually develop. The pore structure is more complex than that of RL, so the pore fractal dimension is larger than that of RL. After more W-D cycles, due to the rearrangement of soil particles and pores, the soil structure of RL and BML changes from the original mosaic cementation structure to a uniform loose structure, the pore structure is relatively stable, and the fractal dimension of pores tends to be stable after a decreasing trend.

Fig. 8 Variation of porosity and fractal dimension of loess under W-D cycles

3.1.3 Analysis of porosity-based damage degree

To further analyze the change of porosity of RL and BML after W-D cycles, a continuous variable D is introduced as the porosity damage degree, as shown in Eq. (1):

$$\begin{cases} D_1 = \frac{|n_1 - n_{01}|}{1 - n_{01}} \\ D_2 = \frac{|n_2 - n_{02}|}{1 - n_{02}} \end{cases} \quad (1)$$

where D_1 and D_2 represent the porosity damage of RL and BML after W-D cycles, respectively; n_1 and n_2 are the porosity of RL and BML samples after W-D cycles, respectively; n_{01} and n_{02} are the initial porosity of RL and BML samples. $D=0$ corresponds to the initial undamaged state of the sample, and $D=1$ indicates that the sample is in a fully damaged state, and $0 < D < 1$ indicates that the sample is in a damaged state.

According to the change curve of porosity in the micro-quantitative index of RL and BML after the W-D cycles in Fig. 8 (a), it can be found that the relationship between W-D cycle number N and porosity n of RL and BML after different W-D cycles as follows:

$$\begin{cases} n_1(N) = a_1N + b_1N^2 + n_{01} \\ n_2(N) = a_2N + b_2N^2 + n_{02} \end{cases} \quad (2)$$

where N is the number of W-D cycles; a_1 , a_2 , b_1 , and b_2 are all fitted parameters. Transform the form of Eq. (2) into the following equation:

$$\begin{cases} |n_1 - n_{01}| = |N(a_1 + b_1N)| \\ |n_2 - n_{02}| = |N(a_2 + b_2N)| \end{cases} \quad (3)$$

Substituting Eq. (3) into Eq. (1) can obtain the univariate prediction model for the number of W-D cycles and porosity damage as follows:

$$\begin{cases} D_1 = \frac{|N(a_1 + b_1N)|}{1 - n_{01}} \\ D_2 = \frac{|N(a_2 + b_2N)|}{1 - n_{02}} \end{cases} \quad (4)$$

where D_1 and D_2 respectively represent the porosity damage of RL and BML after W-D cycles; N is the number of W-D cycles; n_{01} and n_{02} are the initial porosity of RL and BML samples, the values are 0.2960 and 0.1657; a_1 , a_2 , b_1 , and b_2 are all fitted parameters, with values of 0.0377, 0.0651, -0.0023, and -0.0042 respectively.

In Eq. (4), D_1/D_2 obtains Eq. (5), and Eq. (5) can reflect the relationship between the porosity damage of RL and 15% BML during the W-D cycles:

$$\frac{D_1}{D_2} = \left| \frac{a_1 + b_1N}{a_2 + b_2N} \right| * \frac{1 - n_{02}}{1 - n_{01}} \quad (5)$$

Fig. 9 (a) presents the variation of the damage degree of porosity of RL and BML with the number of W-D cycles. The result shows that the porosity damage of RL and BML increases during the previous five W-D cycles, but it keeps stable of both samples from fifth W-D cycles.

The porosity damage of the BML samples is greater than that of RL during the development of W-D cycles. Although the porosity of RL is always higher than that of BML during the whole W-D cycles, the porosity of BML varies within a large range after the impact of W-D cycle. Because the fine bentonite particles swell and fill in the large pores of the loess grains skeleton before the W-D cycle. During the reciprocating W-D cycle, the montmorillonite continuously undergoes the processes of water swellable and shrinkage. After several W-D cycles, the damage of the expanded montmorillonite in the process of water shrinkage is irreversible, resulting in a more significant change in the pore structure of the BML than before. Therefore, the porosity damage also shows a larger trend than that of the RL. Fig. 9 (b) compares the calculated value and the tested value of the univariate damage prediction model based on porosity. From the figure that most of the data points are distributed on both sides of the straight-line $y=x$,

indicating that the predicted value of the damage model is similar to the experimental value, the model can better predict the RL and BML porosity damage rules under the action of W-D cycles.

Fig. 9 Comparison of porosity damage degree and model results

3.2 Analysis of shear strength of loess under W-D cycles

3.2.1 The curves between shear stress and shear displacement

Fig. 10 and Fig. 11 show the relationship between shear stress and shear displacement of RL and BML under different vertical pressures during W-D cycles. The relationship between shear stress and shear displacement of RL shows strain softening under the action of low vertical pressure ($p = 30\text{kPa}$), the curves of RL gradually transits to strain hardening with the vertical pressure increase. The shear stress of samples increases with the growth of shear displacement after different W-D cycles. However, the relationship between shear stress and shear displacement of BML is strain-softening without the influence of W-D cycles, while the relationship between shear stress and shear displacement is strain hardening when it experiences the W-D cycles, and the shear stress increases with the growth of shear displacement.

Fig. 10 shear stress vs. shear displacement curves of RL under vertical pressure

Fig. 11 shear stress vs. shear displacement curves of BML under vertical pressure

3.2.2 Strength parameters

Fig. 12(a) shows the variation of the cohesion of RL and BML with the number of W-D cycles, the cohesion of both loess decreased gradually with the increase of the W-D cycles, and tended to be stable after five W-D cycles. The cohesion of BML was higher than that of RL in initial state, it was consistently lower than that of RL in the first to fourth W-D cycles, and when it is stable after five cycles, it is higher than that of RL. Because the cohesion is related to the cementation between soil particles, double-layer water and the attraction between molecules. Without the effect of the W-D cycle, due to montmorillonite and other minerals in bentonite, water swelling fills the pores between loess particles, and ion exchange forms a diffuse double layer, which enhances the bonding force and electrostatic attraction between soil particles. The interaction force between modified loess particles is more substantial than RL particles, so the modified loess cohesion is greater than RL. During the W-D cycles, the cement structure and diffusion electric double layer are destroyed due to water migration, and the cohesion decreases sharply. Finally, when the cohesion tends to be stable, the existence of some clay aggregates makes the cohesion of modified still higher than that of RL after multiple W-D cycles.

Fig. 12(b) presents the variation curve of the internal friction angle of RL and BML with the number of W-D cycles. As shown in the figure, the internal friction angle of RL samples fluctuates with the increase of the W-D cycles, while the internal friction angle of BML shows a trend of continuous attenuation with the increase of the W-D cycles and the attenuation amplitude gradually decreases. The internal friction angle of the sample depends on the friction and occlusion between the particles. The addition of bentonite in the loess acts as the clay aggregates between the soil particles, and more small particles adsorb on the particles surface, causing the friction between the soil particles increases. With the development of W-D cycles, the friction between particles weakens, and the internal friction angle between particles decreases due to the lubrication of water film.

Fig. 12 Strength parameters of loess under W-D cycles

3.2.3 Analysis of shear strength

Fig. 13 illustrates the variation of shear strength of RL and BML under different W-D cycles. Under different vertical pressures, the shear strength of RL and BML first decreases and then tends to be stable with the increase of the number of W-D cycles, which is consistent with the variation law of cohesion under W-D cycles. Before the W-D cycles, the clay minerals in the BML fill in the aerial pores and large intergranular voids, the soil particles are mainly surface cementation, the BML particles structural stability is higher than that of the RL, so the shear strength of the BML is higher than that of the RL. The

shear strength of BML is lower than that of RL after the W-D cycles, but the shear strength of BML and RL tends to be stable after five W-D cycles, and the shear strength of BML is higher than that of RL. In the previous W-D cycles, as the scouring effect of water migration on soil particles, the clay film on the surface of modified loess particles is continuously dissolved, the large agglomerated particles are separated. The cementation between particles is weakened, the contact area is continuously reduced, the soil structure changes significantly, and the strength change of BML is more extensive than RL. With the increasing of W-D cycles, the influence of water migration on soil structure is weakened, and the soil particles and pores are rearranged, the particles are mainly point-to-point contact. However, due to the clay minerals in bentonite, the bond strength between the modified loess particles is greater than that of RL, so the shear strength of BML is higher than that of RL.

Fig. 13 Shear strength curves of loess under W-D cycles

3.2.4 Analysis of cohesion damage degree

The influence of W-D cycles on the internal friction angle of RL and BML is smaller than that on the cohesion. Therefore, based on the cohesion to further analyze the deterioration rule during the W-D cycles. A continuous variable λ was introduced, named cohesion damage degree:

$$\left\{ \begin{array}{l} \lambda_1 = \frac{|c_1 - c_{01}|}{c_{01}} \\ \lambda_2 = \frac{|c_2 - c_{02}|}{c_{02}} \end{array} \right. \quad (6)$$

where: $\lambda=0$ corresponds to the non-damaged state, $\lambda=1$ corresponds to the completely damaged state, $0 <$

$\lambda < 1$ corresponds to the different degree of cohesive damage state; c_{01} and c_{02} represent the cohesion of RL and BML samples in the initial state, respectively; c_1 and c_2 respectively represent the cohesion of RL and BML after W-D cycles.

According to the curve of cohesion of RL and BML under W-D cycles in Fig. 12(a), it can be found that there are quadratic polynomial relationships and the exponential relationship between the cohesion c of RL and BML after experiencing different W-D cycles N :

$$\begin{cases} c_1 = c_{01} + a_1 N + b_1 N^2 \\ c_2 = a_2 * N^{b_2} \end{cases} \quad (7)$$

Substituting Eq. (7) into Eq. (6), the relationship between the cohesion of RL and BML and the number of W-D cycles are obtained, respectively:

$$\begin{cases} \lambda_1 = \frac{|N(a_1 + b_1 N)|}{c_{01}} \\ \lambda_2 = \left| 1 - \frac{a_2 * N^{b_2}}{c_{02}} \right| \end{cases} \quad (8)$$

where λ_1 and λ_2 are the cohesion damage degree of RL and BML after W-D cycles, respectively; N is the number of W-D cycles; c_{01} and c_{02} are the initial cohesion of RL and BML samples, respectively, with values of 58.68 and 87.33; a_1 , a_2 , b_1 and b_2 are the fitted parameters, with values of -10.3979, 0.6000, 46.0906 and -0.3422, respectively.

In Eq. (8), λ_1/λ_2 can be obtained as Eq. (9), which reflects the quantitative relationship between the cohesion damage degree of RL and that of BML in the process of W-D cycles:

$$\frac{\lambda_1}{\lambda_2} = \frac{|N(a_1 + b_1 N)|}{|c_{02} - a_2 * N^{b_2}|} * \frac{c_{02}}{c_{01}} \quad (9)$$

Fig. 14 (a) presents the curves of cohesion-based damage degree of RL and BML after different W-D cycles. The cohesion-based damage degree of RL and BML increases with the increase of W-D cycles and tends to be stable after five cycles. In the process of W-D cycles, the damage degree of BML is greater than that of RL. The reason is that the water migration in the process of W-D cycles constantly destroys the surface electric double layer of clay minerals attached to the surface of soil particles, the intermolecular force decreases continuously, and the cementation between particles continued to decrease, the cohesion after the W-D cycles decreases more significant than the initial state, so the BML cohesion damage degree under the W-D cycles is more significant than that of RL.

The cohesion damage degree of RL and BML after W-D cycles was calculated by equation (8), and compared with the experimental values of cohesion damage degree. The comparison results are shown in Fig. 14 (b). It can be seen from the figure that the data points are distributed on both sides of the straight-line $y=x$, which indicates that the predicted value of the cohesive damage model is similar to the experimental value and that the model can better predict the damage regularity of the cohesion of RL and BML under the action of W-D cycles.

Fig. 14 Comparison of cohesion damage degree and model results

3.3 Correlation analysis of shear strength and microstructure of loess

3.3.1 Multivariate linear stepwise regression method

The mechanical properties of loess and modified loess are not only related to their own mineral composition, but also to the degree of association of pores and particles. The expansion and development of surface cracks of loess under W-D cycles are closely related to the connection of internal particle pore structure. Therefore, to investigate the correlation between the strength characteristics of loess and microscopic particle pores, the regression equation between the shear strength parameters of loess and microscopic pore structure parameters was established by the multivariate linear stepwise regression analysis. The stepwise method involves introducing the independent variables into the model individually, conducting an F-test after each new independent variable is introduced, and performing a t-test on the selected independent variables singly, and removing the variables with insignificant changes from the equation individually. The expression of the model is as follows (Wang et al. 2007; He et al. 2009):

$$Y = \beta_0 + \beta_1 X_1 + \beta_2 X_2 + \cdots + \beta_i X_i \quad (10)$$

where: β_0 is the regression constant; β_1 is the partial regression coefficient of the independent variable X_1 ; β_2 is the partial regression coefficient of the independent variable X_2 ; β_i is the partial regression coefficient of the independent variable X_i ; i is the number of independent variables. The results of partial regression coefficients and regression constants were obtained by data analysis.

In the multivariate linear stepwise regression analysis, the shear strength parameters were selected as the cohesion (c) and the internal friction angle (φ). The parameters of micro-pore structure of loess were selected as equivalent diameter (D_e), oblate degree (O_d), pore area ratio (λ), average form factor (F), probability entropy (H), fractal dimension (D_{fp}) (Cox and Budhu 2008; Liu et al. 2011). The D_e is the average diameter of an equivalent circle equal to the pore area of the soil. The O_d is the ratio of the short axis and long axis of the pore, the value is less than 1. The smaller the value, the pore tends to be elongated, otherwise, the closer to the round shape. The λ indicates the ratio of the pore area to the total area within the same cross section. The F characterizes the pore boundary roundness, and the value is in the range of (0,1), the pore shape is closer to round with the increase of F . The H is used to describe the directionality of the pore arrangement. The value of H varies between (0,1) and the smaller the H , the more pronounced the directionality of the pores. The D_{fp} reflects the variation law of pore complexity

with its area, and the larger the D_{fp} reflects the more complex pore structure and the more dispersed pore distribution of the soil. The experimental results and the obtained parameters are shown in Table 2.

Table 2 Summary of strength and micro-pore structure parameters of loess

Loess	Wetting-dryin g cycles	Strength parameters		Micro-pore structure parameters					
		$c /$ kPa	$\varphi / ^\circ$	D_e / μm	O_d	λ	F	H	D_{fp}
Remolde d loess	0	58.6	21.4	4.573	0.585	29.60	0.372	0.983	1.197
		8	2	4	0	%	8	6	1
	1	47.8	22.0	4.310	0.614	29.13	0.333	0.991	1.200
		6	0	2	2	%	7	7	7
	2	42.0	20.8	4.759	0.607	36.65	0.352	0.989	1.237
		0	6	8	4	%	9	3	7
	3	37.6	20.9	4.464	0.618	38.07	0.347	0.992	1.242
		9	8	9	5	%	9	0	7
	4	29.1	24.4	4.593	0.610	40.48	0.341	0.989	1.232
		7	5	2	2	%	2	2	8
	5	17.0	20.6	4.099	0.616	40.43	0.334	0.994	1.225
		7	6	5	7	%	9	7	6
	10	16.0	20.7	4.772	0.623	42.53	0.329	0.993	1.219
		0	5	2	6	%	8	5	5
	0	87.3	31.5	3.782	0.590	16.57	0.384	0.987	1.162
		3	0	5	9	%	2	6	6
Bentonite modified loess	1	46.8	28.8	4.131	0.584	20.08	0.391	0.990	1.2211
		2	0	9		%	6	7	
	2	36.4	25.9	4.275	0.575	26.28	0.301	0.991	1.244
		3	0	1	0	%	9	3	8
	3	30.8	20.2	4.375	0.586	30.86	0.298	0.989	1.255
		3	0	2	5	%	2	5	7
	4	27.3	19.2	4.808	0.587	35.13	0.310	0.983	1.281
		0	3	8	1	%	0	8	3
	5	25.8	18.0	4.503	0.591	38.07	0.288	0.991	1.272
		1	0	6	9	%	0	5	7
	10	23.3	17.2	4.937	0.610	38.56	0.374	0.989	1.247
		3	2	5	5	%	1	4	7

3.3.2 Results of regression analysis

The regression models of shear strength and micro-pore structure parameters were calculated by multivariate linear stepwise regression analysis through SPSS software and obtained as shown in Table 3. The cohesion of loess is negatively linearly correlated with the λ , i.e., the cohesion decreases gradually with the increase of λ . The λ , H , and D_{fp} can jointly explain 84% of the loess cohesion, indicating that the λ , H , and D_{fp} have a strong influence on the loess cohesion. The c is negatively correlated with λ . The

larger the pore area is, the easier for the particles to slide, and the bonding effect between the soil particles is weakened, leading to the reduction of the loess cohesion. The c is negatively correlated with H . With the increase of H , the pore orientation weakened, the pore direction distribution tended to be random, and the loess cohesion gradually decreased. The c is negatively correlated with D_{fp} . With the increase of D_{fp} , the complexity of pore distribution of different pore sizes and shapes in the plane increases, the more complex the pore structure of the soil, the more dispersed the pore distribution is, the easier the skeleton of soil particles will be destroyed, and the loess cohesion will be smaller.

The φ is linearly correlated with the λ , and the correlation coefficient of the regression equation is 0.6. The φ is negatively correlated with the λ , i.e., the φ decreases with the increase of the λ . The larger λ is, the more pores in the unit area, the bonding between soil particles is weakened, the easier the sliding between particles, and the internal friction angle decreases. It can be seen that the λ is one of the factors affecting the φ of loess.

Table 3 Regression analysis of strength and micro-pore structure parameters of loess

	Regression model	R^2	F	P
	Model 1 $c = 102.061 - 195.169 \lambda$	0.65	25.238	<0.001
c	Model 2 $c = 394.346 - 142.838 \lambda - 251.362 D_{fp}$	0.77	22.257	<0.001
	Model 3 $c = 2087.196 - 115.357 \lambda - 285.656 D_{fp} - 1676.723 H$	0.84	22.976	<0.001
φ	$\varphi = 35.657 - 40.486 \lambda$	0.60	20.368	<0.001

Figures 15 (a)-(c) show the comparison between the fitted results of the stepwise regression equations and the measured values of the cohesion of the remold loess and modified loess. From the figures, as the independent variables in the regression equation increase, the range of error bands gradually decreases and the correlation coefficients of the regression models increases subsequently. When the regression model contains λ , H , and D_{fp} , the fitted correlation coefficient R^2 is 0.84, and the fitted value of cohesion has a high linear correlation with the measured value, indicating that the fitted regression model 3 can be used to predict the cohesion of loess. Figure 15 (d) shows the comparison between the measured and fitted values of the internal friction angle. The fitted values of the internal friction angle fit well with the measured, and both have similar decay laws with the increase of wetting-drying cycles. It is indicated that the regression equation between macro-mechanical parameters and microstructural parameters established by multivariate linear stepwise regression method can well reflect the influence law of loess microstructure on macro-mechanical strength.

Fig. 15 Comparison of measured and fitted values of shear strength parameters

4 Discussions

4.1 Microstructure evolution of BML under W-D cycles

In the process of W-D cycles, the soil mechanical properties are very complex, which are affected by many factors, such as soil water retention characteristics, mineral composition, W-D cycle stage, microstructural characteristics, and cracking intensity (Tang et al. 2020). Ni et al. (2020) considered that the reasons for the changes of loess particle microstructure under W-D cycles were that the dissolution and recrystallization of soluble salts at different water contents affected the size and shape of the particle's skeleton, and the clay cementation was affected by swelling and suction, and caused the arrangement of loess particles. The W-D cycle is essentially the process of water migration inside the soil. In this process, the pores in the soil are used as migration channels. The water continuously washes the primary pores, causing the dissolution of some fine particles and part of clay minerals on the surface, making the primary small and medium pores transition to large pores, weakening the soil structure and reducing the soil strength. The essence of the microstructure change of BML under the action of the W-D cycles is that the cementation strength and double electron layer destruction of the clay minerals such as montmorillonite on the surface of the modified loess particles make some cementation aggregates separate into small particles, the particles are rearranged, and the microstructure of the soil gradually be destroyed and forms a new stable structure. As the W-D cycles continue, the pore structure almost does not change, and the soil strength reaches stability.

4.2 Multiscale comparison of damage regulation of loess under W-D cycles

The deformation of soil can be divided into macroscopic deformation and microscopic deformation, and the macro characteristics such as strength are the reflections of its microscopic structure of the soil. The combination of macro strength test and micropore structure observation can better observe and explain the deformation failure regularity of loess.

Fig. 16 illustrates the curve of damage degree of RL and BML under different W-D cycles. The variation of damage degree of soil micro porosity and macro cohesion is consistent under the action of W-D cycles. The damage degree of samples increases with the increase of W-D cycles; after five W-D cycles, the damage degree of the sample tends to be stable. It is revealed that the W-D cycles have a decelerating degradation effect on the loess before and after bentonite modification. The damage of soil is reflected by the cohesion and micro-porosity, which have macro and micro consistency.

Fig. 16 Comparison of damage degree of loess under W-D cycles

5 Conclusions

This paper took RL and BML as study objects, through SEM tests and direct shear tests to research the damaged relationship between microstructure and macroscopic strength of samples under different W-D cycles. The main conclusions are as follows:

(1) The essence of bentonite that could modify loess is that montmorillonite minerals in the bentonite absorb water and swell to fill the macropores in the framework of loess particles, and the macropores decrease while the mesopores and micropores increases. The particle contact of RL is mainly pointing content, while the BML is surface content. The microstructure of BML is more stable than RL under W-D

cycles.

(2) With the increase of W-D cycles, the cement structure and diffusion electric double layers of the loess are destroyed, resulting in the loss of the particle arrangement of RL and BML, and the porosity and pore fractal dimension increase gradually. After 5 W-D cycles, the particles are rearranged until the soils reach a new stable structure, the porosity and fractal dimension are increasingly stable, but the porosity of BML is smaller than RL, the microstructure is more complex, and the pore fractal dimension is more significant.

(3) The cohesion of RL and BML all decreases under the W-D cycles, but the decay rates of BML are larger than RL. The internal friction angle of RL has no noticeable change under W-D cycles, but it decreases with the increase of W-D cycles.

(4) The regression equation between macro-mechanical parameters and microstructural parameters established by multivariate linear stepwise regression method can well reflect the influence law of loess microstructure on macro-mechanical strength.

(5) Based on the changes of porosity and cohesion of samples during the W-D cycles, the continuous damage variables about porosity and cohesion are introduced respectively, establishing damage degree models of porosity and cohesion, which can better predict the damage regulation of porosity and cohesion of RL and BML during the W-D cycles.

Acknowledgments

The research presented in this paper was supported by the National Natural Science Foundation of China (Grant Nos. 51878551, 51478385). These financial supports are gratefully acknowledged.

References

- Cheng G, Zhu H-H, Wen Y-N, et al (2020) Experimental Investigation of Consolidation Properties of Nano-Bentonite Mixed Clayey Soil. *Sustainability* 12:459. <https://doi.org/10.3390/su12020459>
- Cox MR, Budhu M (2008) A practical approach to grain shape quantification. *Eng Geol* 96:1–16. <https://doi.org/10.1016/j.enggeo.2007.05.005>
- He F-G, Chen W-W, Han W-F, Zhang J-K (2009) Correlation of microstructure indices and performance of sand solidified with polymer material SH (In Chinese). *Rock Soil Mech* 30:3803–3807+3880. <https://doi.org/10.16285/j.rsm.2009.12.016>
- Liu C, Shi B, Zhou J, Tang C (2011) Quantification and characterization of microporosity by image processing, geometric measurement and statistical methods: Application on SEM images of clay materials. *Appl Clay Sci* 54:97–106. <https://doi.org/10.1016/j.clay.2011.07.022>
- Mady AY, Shein EV (2020) Assessment of pore space changes during drying and wetting cycles in hysteresis of soil water retention curve in Russia using X-ray computed tomography. *Geoderma Reg* 21:e00259. <https://doi.org/10.1016/j.geodrs.2020.e00259>
- Mei Y, Tian X, Hu C, et al (2020) Engineering Properties of Bentonite Modified Sand and Its Application in Shield Construction (In Chinese). *Mater Rep* 34:14087–14092. <https://doi.org/10.11896/cldb.19070200>

- 552 Ministry of Housing and Urban-Rural Development of the People's Republic of China (2019) GB/T
553 50123-2019 Standard for geotechnical testing method
- 554 Mu QY, Dong H, Liao HJ, et al (2020) Water-retention curves of loess under wetting–drying cycles.
555 *Géotechnique Lett* 10:135–140. <https://doi.org/10.1680/jgele.19.00025>
- 556 Muñoz-Castelblanco JA, Pereira JM, Delage P, Cui YJ (2012) The water retention properties of a natural
557 unsaturated loess from northern France. *Géotechnique* 62:95–106.
558 <https://doi.org/10.1680/geot.9.P.084>
- 559 Ni W, Yuan K, Lü X, Yuan Z (2020) Comparison and quantitative analysis of microstructure parameters
560 between original loess and remoulded loess under different wetting-drying cycles. *Sci Rep* 10:5547.
561 <https://doi.org/10.1038/s41598-020-62571-1>
- 562 Qasaimeh A, Sharo AA, Bani-Melhem K (2020) Clayey soil amendment by hydrophilic nano bentonite for
563 landfill cover barrier: a case study. *J Environ Eng Landsc Manag* 9.
564 <https://doi.org/10.3846/jeelm.2020.12715>
- 565 Qie Y, Zhang P, Cui Z, et al (2017) The strength characteristics of loess modified with bentonite (In
566 Chinese). *J Agric Univ Hebei* 40:125–128. <https://doi.org/10.13320/j.cnki.jauh.2017.0138>
- 567 Rahmani A, Hazzab A, Aimer H, et al (2020) Improvement of physical-chemical and rheological properties
568 of Ghardaïa loess (southern Algeria) using bentonite clay and lime. *Clays Clay Miner* 68:499–512.
569 <https://doi.org/10.1007/s42860-020-00092-8>
- 570 Tang C-S, Cheng Q, Leng T, et al (2020) Effects of wetting-drying cycles and desiccation cracks on
571 mechanical behavior of an unsaturated soil. *Catena* 194:104721.
572 <https://doi.org/10.1016/j.catena.2020.104721>
- 573 Wang LN, Zhu QK, Zhao WJ, Zhao XK (2015) The drought trend and its relationship with rainfall intensity
574 in the Loess Plateau of China. *Nat Hazards* 77:479–495. <https://doi.org/10.1007/s11069-015-1594-0>
- 575 Wang Y, Chen Y, Xie H, et al (2016) Lead adsorption and transport in loess-amended soil-bentonite cut-off
576 wall. *Eng Geol* 215:69–80. <https://doi.org/10.1016/j.enggeo.2016.11.002>
- 577 Wang Z-Q, Chai S-X, Zhong X-M, et al (2007) Multivariate stepwise regression method use in correlation
578 analysis of microstructure indices and strength of solidified soil (In Chinese). *Rock Soil Mech*
579 28:1650–1654. <https://doi.org/10.16285/j.rsm.2007.08.031>
- 580 Xu J, Li YF, Ren C, Lan W (2020a) Damage of saline intact loess after dry-wet and its interpretation based
581 on SEM and NMR. *Soils Found* 60:911–928. <https://doi.org/10.1016/j.sandf.2020.06.006>
- 582 Xu J, Li YF, Wang SH, et al (2020b) Shear strength and mesoscopic character of undisturbed loess with
583 sodium sulfate after dry-wet cycling. *Bull Eng Geol Environ* 79:1523–1541.
584 <https://doi.org/10.1007/s10064-019-01646-4>

- 585 Yan C, Zhang Z, Jing Y (2017) Characteristics of strength and pore distribution of lime-flyash loess under
586 freeze-thaw cycles and dry-wet cycles. *Arab J Geosci* 10:544.
587 <https://doi.org/10.1007/s12517-017-3313-5>
- 588 Yan X, Fang Y, Zhang P (2011) Experiment study on the effects of bentonite on the micropore structure
589 characteristics of soil (In Chinese). *Chin J Geotech Eng* 33:1302–1307
- 590 Yang B, Zhang H, Zhao T, et al (2011) Responsibility of permeability of modified loess soil on
591 microstructure (In Chinese). *Hydrogeol Eng Geol* 38:96–101.
592 <https://doi.org/10.16030/j.cnki.issn.1000-3665.2011.06.024>
- 593 Ye W, Bai Y, Cui C, Duan X (2020) Deterioration of the Internal Structure of Loess under Dry-Wet Cycles.
594 *Adv Civ Eng* 2020:1–17. <https://doi.org/10.1155/2020/8881423>
- 595 Ye W, Wu Y, Yang G, et al (2019) Study on microstructure and macro-mechanical properties of paleosol
596 under dry-wet cycles (In Chinese). *Chin J Rock Mech Eng* 38:2126–2137.
597 <https://doi.org/10.13722/j.cnki.jrme.2019.0291>
- 598 Zhang C, Jiang G, Su L, Zhou G (2017) Effect of cement on the stabilization of loess. *J Mt Sci* 14:2325–
599 2336. <https://doi.org/10.1007/s11629-017-4365-4>
- 600 Zhang H, Zhao T, Wu J, et al (2011) Laboratory measurement and prediction to the permeability of
601 bentonite-modified loess as a landfill liner (In Chinese). *Rock Soil Mech* 32:1963-1969,1974.
602 <https://doi.org/10.16285/j.rsm.2011.07.007>
- 603 Zhou B, Wu Y, Zhang Z, et al (2019) Laboratory tests on effects of wetting–drying cycles and loess layer
604 thickness on release and transport of loess colloidal particles in artificial loess columns. *Environ Earth*
605 *Sci* 78:478. <https://doi.org/10.1007/s12665-019-8492-9>
- 606 Zuo L, Xu L, Baudet BA, et al (2020) The structure degradation of a silty loess induced by long-term water
607 seepage. *Eng Geol* 272:105634. <https://doi.org/10.1016/j.enggeo.2020.105634>
- 608