Long-term Metal Fume Exposure Assessment of Workers in a Shipbuilding Factory

Ying-Fang Wang

Chung Shan Medical University

Yu-Chieh Kuo

National Cheng Kung University

Lin-Chi Wang (✉ lcwang@cycu.edu.tw)

Chung Yuan Christian University

Research Article

Keywords: Welding fume, exposure assessment, near field and far field model, Bayesian decision analysis, Shipbuilding industry

Posted Date: September 15th, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-880266/v1>

License: © ⓘ This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Version of Record: A version of this preprint was published at Scientific Reports on January 17th, 2022. See the published version at <https://doi.org/10.1038/s41598-021-04761-z>.

Long-term metal fume exposure assessment of workers in a shipbuilding factory

Ying-Fang Wang^{1,2}, Yu-Chieh Kuo³, Lin-Chi Wang^{4,5*}

¹ Department of Occupational Safety and Health, Chung Shan Medical University, 110 Sec. 1
Jianguo Road, Taichung City 40201, Taiwan.

² Department of Occupational Medicine, Chung Shan Medical University Hospital, 110 Sec. 1
Jianguo Road, Taichung City 40201, Taiwan.

³ Department of Environmental and Occupational Health, College of Medicine, National Cheng
Kung University, 138 Sheng-Li Rd, Tainan City 70403, Taiwan.

⁴ Department of Environmental Engineering, Chung Yuan Christian University, 200 Chung Pei
Road, Chung Li District, Taoyuan City, 32023, Taiwan

⁵ Center for Environmental Risk Management, Chung Yuan Christian University, 200 Chung Pei
Road, Chung Li District, Taoyuan City, 32023, Taiwan

---

*Corresponding author: Tel: +886-3-265-4913; E-mail: lcwang@cycu.edu.tw

20   **Abstract**

21   This study aims to assess the metal fume exposure of welders and to determine exposure rates
22   for similar exposure groups in a shipyard through the use of Near-field/Far-field (NF/FF)
23   mathematical models and Bayesian decision analysis (BDA) technique. Emission rates of various
24   metal fumes (i.e., total chromium (Cr), iron (Fe), lead (Pb), manganese (Mn), and nickel (Ni)) were
25   experimentally determined for the gas metal arc welding and flux cored arc welding processes, which
26   are commonly used in shipyards. Then the NF/FF field model which used the emission rates were
27   further validated by welding simulation experiment, and together with long-term operation condition
28   data obtained from the investigated shipyard, the predicted long-term exposure concentrations of
29   workers was established and used as the prior distribution in the BDA. Along with the field
30   monitoring metal fume concentrations which served as the likelihood distribution, the posterior
31   decision distributions in the BDA were determined and used to assess workers' long-term metal
32   exposures. Results show that welders' Fe, Mn and Pb exposures were found to exceed their
33   corresponding action levels with a high probability, indicating preventive measures should be taken
34   immediately. The proposed approach provides a universal solution for conducting exposure
35   assessment with usual limited number of personal exposure data.

36

37   **Keywords:** Welding fume, exposure assessment, near field and far field model, Bayesian decision
38   analysis, Shipbuilding industry

39

40

41   **1. Introduction**

42   The welding process is one which is frequently encountered in the shipbuilding industry.
43   Welding operations produce gaseous and aerosol by-products containing a complex array of metals
44   (e.g., iron, manganese, chromium, and nickel, etc.), metal oxides, and other chemical species
45   volatilized from the welding rod and the flux material incorporated within it, [1]. Recent studies have
46   shown that inhalation of welding fumes can excessively cause respiratory damage, such as bronchitis,
47   asthma [2], lung function change [3], increased lung cancer risk [4, 5], neurotoxicity [6] and many
48   other diseases. In particular, exposures to specific metals contained in welding fume is of concern in
49   the industrial hygiene field. For example, iron exposures can lead to siderosis; zinc, copper, and
50   magnesium exposures can cause metal fume fever; and chromium VI can not only cause severe
51   irritation to the upper respiratory tract, but also could be carcinogenic to human beings [7].

52   The contents of metal and pollutants in the emitted particles and their concentrations in welding
53   fume during the welding process are affected by the involved welding procedures, the filler and the
54   base material of the welding rods, and the presence of coatings [8, 9]. Therefore, investigating the
55   emission rates of the abovementioned pollutants under specific welding conditions is important to
56   assess workers' exposures. Considering that chronic health effects were known to be associated with
57   welding fume exposures, conducting long-term exposure assessments has become an important issue
58   to ensure that shipyard welders can work in a healthy environment.

59   However, it should be noted that obtaining complete long-term exposure data directly from field
60   sampling is quite difficult in the real world because of constraints such as the cost, workers'
61   unwillingness, and interference to work practices, etc. Some researchers have suggested the use of
62   models for predicting exposure concentrations to solve the above problems [10]. Based on laboratory
63   tests, researchers have found that the exposure concentrations predicted by the near field (NF) and
64   far field (FF) model correlate well with the corresponding measured values [11]. However, the
65   suitability of the aforementioned model has not been validated in occupational environment.

66   To date the Bayesian decision analysis (BDA) technique has been adopted by many researchers

67 in determining exposure profiles based on a small amount of sampling data [12] to conduct the long-
68 term exposure. BDA provides a transparent method for incorporating the relative certainty of the
69 information or data used to produce a judgment probability chart [13, 14]. The use of BDA requires
70 knowledge of both prior and likelihood exposure distributions for the targeted similar exposure group
71 (SEG). Subsequently, the posterior exposure distribution can be obtained to describe the exposure
72 profile of the target SEG [13]. In theory, the limited measured concentrations can be used to describe
73 the likelihood exposure distribution in BDA. Many methodologies have been used by industrial
74 hygienists to create exposure data for determining the prior exposure distribution, such as the expert
75 system [12, 15-17], numerical model [17-19], and surrogate exposure method [13, 17, 20]. It should
76 be noted that the use of the expert system might lead to inaccurate estimations of the posterior
77 distribution due to inherent large variations among experts [12, 15-17]. If the numerical model is
78 adopted, it is applicable only when environmental and workforce conditions are comparable to the
79 boundary conditions of the involved numerical method [21]. As for the surrogate method, it requires
80 the validation of the effectiveness of the surrogate in predicting exposures of interest.

81 The aim of the present study was to develop an effective and practical approach for conducting
82 long-term exposure assessment for workers who exposed to welding fumes. First, the emission rates
83 of various emitted metals in welding fumes under various welding operating conditions were
84 determined. Secondly, the resultant emission rates were applied to the NF/FF field model for
85 predicting exposure concentrations of various metals. The model results were further validated by
86 comparing the predicted values with metal fume sampled and measured under the same welding
87 operating conditions with NF/FF field model. After validation, workers' long-term predicted exposure
88 concentrations were established using the NF/FF model and the recorded long-term operation
89 condition data in the shipbuilding factory. Finally, the predicted long-term exposure concentrations
90 and field monitoring metal fume concentrations of the shipbuilding factory served as the prior and
91 likelihood distribution in the BDA, respectively. The resultant posterior distributions were used to
92 characterize workers' long-term exposures to offer the basis for initiating control strategies for the

shipbuilding factory to reduce metal fume exposures of welders. To better understand the research structure, a graphic abstract of this study is depicted in Fig. 1.

2. Materials and Methods

2.1 Chamber experiment for determining metal fume emission rates

(1) Chamber

The construction of the fume generation and collection apparatus used in the present study was according to the Japanese Industrial Standards Z 3930 (Method of measuring total amount of weld fumes generated by covered electrode). The fume collection chamber (Fig. S1) was 70 cm length × 70cm wide× 60cm height in magnitude, which consists of a ground steel workbench and a stainless-steel enclosure. Inside the chamber, arc welding is done with a welding robot which consists of a manipulator, a controller, and a power supply (ARCMAN-RON, KOBE STEEL, LTD., Japan). A base metal, 27cm length × 27cm wide × 1.2cm height in magnitude, was placed at the center of the workbench rotating at a constant speed for each welding condition by a motor located outside of the chamber. Simultaneously, a wire alloy is fed at a constant speed to serve as the filler material for the arc welding process.

(2) Selected welding operation conditions and sampling methods

Two welding processes which are most often used in the shipbuilding factory were selected, including (1) gas metal arc welding (GMAW) with KM56 (AWS ER 70S-6) and KM58 (AWS ER70S-G), and (2) flux cored arc welding (FCAW) with KFX71T (AWS E71T-1) and KFX70T (AWS E70T-1), respectively. According to the field observation, the arcing time, welding speed, and shield gas flow rate were set at 30 s, 28 cm/min, and 20 L/min, respectively. The wire (1.2 mm in diameter) extension and the torch angle were kept at 15 mm and 0°, respectively. Current intensities (Amperes) were set at 120, 220, and 300 Amperes, respectively. The location for collecting the emitted metal fume was at the breathing zone of the welder, which was set at a point 70 cm above the base metal. The sampling time for each testing condition was set at 300 s, including 30 s for arcing time, and the

subsequent 240 s for the arc off period. Three repeated samplings were conducted for each selected welding processes.

(3) Estimated metal fume emission rate

In order to estimate the emission rate from welding processes, a mass balance equation has been proposed as the following [22]:

$$\frac{dC_{in}}{dt} = p \cdot AER \cdot C_{out} + \frac{Q_s}{V} + (AER + k) \cdot C_{in} \quad (1)$$

Where C_{in} , C_{out} : the indoor and outdoor particle concentration; p : the penetration efficiency; AER : air exchange rate; k : the deposition rate; Q_s : the indoor particle generation rate; t : time; V : the efficient volume of the plenum. However, a simplified equation was adopted for estimating the emission rate as followings [23]:

$$ER = V \left[\frac{C_{in} - C_{in,0}}{\Delta t} + (\overline{AER + k}) \cdot \overline{C_{in}} - AER \cdot C_{in,0} \right] \quad (2)$$

Where ER : the average emission rate; C_{in} , $C_{in,0}$: the peak and initial indoor particle concentrations; $\overline{AER + k}$: the average removal rate; Δt : time difference between initial and peak concentration.

Because $C_{in,0}$ is negligible with respect to C_{in} , Eq. (2) was simplified to Eq. (3):

$$ER = V \left[\frac{C_{in}}{\Delta t} + (\overline{AER + k}) \cdot \overline{C_{in}} \right] \quad (3)$$

2.2 Predicting and validating concentrations of metal fume during welding process

(1) The Near-field and Far-field model

In this study, the obtained ER was applied to the NF and FF model for predicting metal fume exposure concentrations (C_{NF-p} and C_{FF-p}) according to Eq. (4) to Eq. (7) (Nicas et al., 2006):

$$C_{N,t} = \frac{ER}{Q} + \frac{ER}{\beta} + ER \left(\frac{\beta Q + \lambda_2 V_N (\beta + Q)}{\beta Q V_N (\lambda_1 - \lambda_2)} \right) e^{\lambda_1 t} - ER \left(\frac{\beta Q + \lambda_1 V_N (\beta + Q)}{\beta Q V_N (\lambda_1 - \lambda_2)} \right) e^{\lambda_2 t} \quad (4)$$

$$C_{F,t} = \frac{ER}{Q} + ER \left(\frac{\lambda_1 V_N + \beta}{\beta} \right) \left(\frac{\beta Q + \lambda_2 V_N (\beta + Q)}{\beta Q V_N (\lambda_1 - \lambda_2)} \right) e^{\lambda_1 t} - ER \left(\frac{\lambda_2 V_N + \beta}{\beta} \right) \left(\frac{\beta Q + \lambda_1 V_N (\beta + Q)}{\beta Q V_N (\lambda_1 - \lambda_2)} \right) e^{\lambda_2 t}$$

(5)

$$\lambda_1 = 0.5 \left[- \left(\frac{\beta V_F + V_N (\beta + Q)}{V_N V_F} \right) + \sqrt{\left(\frac{\beta V_F + V_N (\beta + Q)}{V_N V_F} \right)^2 - 4 \left(\frac{\beta Q}{V_N V_F} \right)} \right] \quad (6)$$

$$\lambda_2 = 0.5 \left[- \left(\frac{\beta V_F + V_N (\beta + Q)}{V_N V_F} \right) - \sqrt{\left(\frac{\beta V_F + V_N (\beta + Q)}{V_N V_F} \right)^2 - 4 \left(\frac{\beta Q}{V_N V_F} \right)} \right] \quad (7)$$

143 where $C_{N,t}$ and $C_{F,t}$: the time-varying concentrations in the near field and in the far field,
144 respectively; ER: emission rate; Q: room supply air rate; β : air flow rate between the near and far
145 fields; V_N and V_F : the near-field and far-field volumes; λ_1 and λ_2 : the model parameter
146 corresponding to air turnover rates.

147 **(2) Determining metal fume concentrations in welding simulation experiment**

148 The schematic of the air samplings at NF and FF regions during welding processes is shown in
149 Fig. S2, which was intended to simulate metal fume exposure concentrations of workers. To validate
150 the predicted concentration by NF and FF model, the concentrations (C_m) at NF (the hemisphere space
151 with a radius 0.6 m away from the emission source) and FF regions (the space between the two
152 hemispheres with a radius 0.6 m and 1.5 m away from the emission source) were measured for each
153 selected welding processes for three repeated times.

154 Three IOM personal inhalable aerosol samplers (SKC Inc., Eighty-four, PA, USA) were used to
155 sample simultaneously at A1, B1 and C1 for NF region concentrations, while another three IOM
156 personal inhalable aerosol samplers were deployed at A2, B2 and C2 for FF region concentrations.
157 The welding time was 30 min. The sampling flow rate was specified at 2.0 L/min and the sampling
158 time was for 30 min. All collected samples were analyzed for selected metals by Inductively Coupled
159 Plasma Atomic Emission Spectroscopy (ICP-AES) analysis following NIOSH Method 7300. The
160 metals selected for analysis, including total chromium (Cr), iron (Fe), manganese (Mn), nickel (Ni),
161 and lead (Pb), were based on the pre-tested samples obtained from the selected shipyard factory.

162 **2.3 Field monitoring on metal fume exposure concentrations of workers in a shipyard factory**

163 Personal samples collected from 18 randomly selected welders were assumed to be representative
164 to field NF region exposure concentrations. In addition, static samples (~1.5 m above the ground level
165 at the location nearest to the 18 randomly selected worker) were assumed to be representative of field
166 FF region exposure concentrations. The IOM personal inhalable aerosol sampler (SKC Inc., Eighty-
167 four, PA, USA) was used to measure the exposure concentration of metal fume with a sampling flow
168 rate specified at 2.0 L/min and the sampling time for ~8 h. Airflow rates between the NF and FF were

determined by an anemometer (TSI Inc., Model 9535, St. Paul, MN, USA). Five metal elements, including Cr, Fe, Mn, Ni and Pb, were analyzed for these field samples from the shipyard factory.

This study was approved by the Human Ethics Committee of the Chung Shan Medical University Hospital with respect to scientific content. We had adherence to relevant ethical guidelines/regulations. A written consent document containing the required information was provided to each subject and the informed consent was obtained from each subject involved in the study.

175

2.4 Using BDA for long-term exposure assessment

In the present study, the predicted long-term metal fume exposure concentrations (C_p) and the field workers' exposure concentrations (C_m) were used for establishing the prior and likelihood exposure distributions in BDA, respectively and the resulting posterior exposure distributions were used to assess the long term exposures of workers. The software of the IH Data Analyst V1.27 (Exposure Assessment Solutions, Inc., Morgantown, West Virginia, USA) was used for conducting BDA. The exposure ratings were classified into five categories: $ER_0 \leq 0.005$ occupational exposure limit (OEL), $0.005OEL < ER_1 \leq 0.05OEL$, $0.05OEL < ER_2 \leq 0.25OEL$, $0.25OEL < ER_3 \leq 0.5OEL$, and $ER_4 > 0.5OEL$, respectively.

185

3. Results and Discussion

3.1 Emission rates of metal fume for the selected welding processes

The emission rates (ER) of the welding metal fume obtained from the chamber experiment are listed in Table 1. Fe and Mn exhibited the highest ERs (=20.5–72.9 mg/min and 1.91–9.35 mg/min, respectively), and were much larger than those of Cr, Ni, and Pb (range= 0.02–0.11 mg/min). The above results can be explained by the relative compositions of the electrodes and were consistent with the findings reported in other study [24]. We also found that the ERs increased as the current intensity increased, which reflected the fact that a higher arc temperature results in a higher fume emission rate. However, the increase in ER is not linear with time due to the variations in time spent in different

metal transfer modes. Some studies have reported the same results for various welding types, for instance, gas metal arc [25-27]. It is also known that metal transfer modes are intrinsically related to both the current intensity and voltage at the tip of the electrode. A previous study indicated that fume rates rise with voltage as one moves from short circuit (low voltage) to globular transfer (the ridge), then drops into the valley during a shift toward spray mode and finally rises again with the onset of streaming (high voltage) transfer [27].

3.2 Predicted exposure concentrations by the NF and FF model

In this study, the obtained ERs (Table 1) were applied to the NF and FF models for predicting metal fume exposure concentrations. The ER values were treated as the generation rate G in the adopted NF and FF models. The interflow term β between the NF and FF region is shown in Table S1, and the average β fell to 6.78–11.1 m^3/min for the FCAW welding processes, and 5.11–9.08 m^3/min for GMAW welding processes, respectively. As for other parameters used in NF and FF models, they were obtained according to the field measured data, and are listed in Table S2.

The predicted concentrations (C_p) of the five metal fume elements (Cr, Fe, Mn, Ni, and Pb) obtained by NF and FF models for the selected welding processes are listed in Table S3. It showed that the predicted concentrations all increased as the applied current increased. Fe and Mn were the two elements with highest concentrations. The above results are consistent with the measured emission rates (Table 1). The mean predicted concentration of each metal in the NF was consistently higher than the corresponding value in FF. Spearman's correlation analyses ($r=0.97$, $p<0.001$) show significant correlations between the NF and FF predicted concentrations.

3.3 Validation of the exposure concentrations obtained from NF and FF models

The measured NF and FF metal concentrations (C_m) obtained from the welding simulations for two welding processes are shown in Table 2. Fe and Mn have their measured NF concentrations above the exposure limit adopted by ACGIH (Threshold Limited Values (TLV) = 10 mg/m^3 and 0.2 mg/m^3 , respectively). As for the measured FF concentrations, Fe was generally above the TLV. These results

revealed that exposure to metal fume concentrations for welding workers could be severe. Similarly, the measured metal concentrations all increased as the applied current increased, and Fe and Mn were the two elements with the highest concentrations. The above results are consistent with Table 1 and Table S3. Moreover, Spearman's correlation ($r=0.98$, $p<0.001$) also showed that there is a significant correlation between the NF and FF measured concentrations. By comparing the C_p with C_m , it is apparent that most of the C_p are underestimated, with the exception of Mn. The underestimation maybe mainly comes from the two factors used in the models, the airflow rates, Q and β (Table S2), which were determined by anemometers. That is because the shipyard factories are usually naturally ventilated, resulting in a large range of wind speed variation on site. Therefore, using field-measured data to validate predicted concentrations by model is important.

Simple liner regression analyses were used to examine the relationship between the predicted concentration (C_p) and measured concentration (C_m) following Eq. (8) and Eq. (9):

$$C_{NF-m} = \alpha_1 C_{NF-p} + \beta_1 \quad (8)$$

$$C_{FF-m} = \alpha_2 C_{FF-p} + \beta_2 \quad (9)$$

All these predicted metal fume exposure concentrations served as a basis for establishing the long-term exposure data bank. Table S4 shows that simple linear regression analyses can reliably relate C_p and their corresponding C_m . All resultant regression coefficients were positive and were statistically significant ($p<0.05$). The high R^2 ($=0.81$ — 0.94) indicates that the proposed surrogate predicting method was adequate for predicting metal fume concentrations.

3.4 Establishing long-term exposure concentrations of workers

After the relation of C_p and C_m was established and C_p was validated, the predicted long-term exposure concentrations of workers can be established using the recorded long-term operation condition data. Therefore, the field observation (30 day records from the investigated shipyard factory) and the developed NF and FF models were used to establish the predicted long-term exposure concentrations of workers in the shipyard factory. The geometric mean (GMs) and geometric standard

247 deviations (GSDs) of the predicted long-term exposure concentrations of shipyard workers in NF and
248 FF regions are listed in Table 3. Results show that the predicted Mn concentrations (0.236 mg/m^3) for
249 NF was higher than the OEL ($=0.2 \text{ mg/m}^3$) promulgated by both the US and Taiwan OSHA.

250

251 **3.5 Assessing the long-term metal fume exposure profile for welding workers**

252 The GMs and GSDs (mg/m^3) of the field metal fume concentrations in the NF and FF regions of
253 the welders in the investigated shipbuilding factory are shown in Table 4. As shown in Table 4, the
254 GMs of Mn in NF and FF regions (1.38 and 0.196 mg/m^3) were above the OEL, and the results were
255 similar to those found in other studies conducted for shipyard welding workers ($=0.004\text{--}2.67 \text{ mg/m}^3$)
256 [28]. Then the predicted long-term exposure concentrations and this field monitoring metal fume
257 concentrations can serve as the prior and likelihood distribution in the BDA, respectively, to obtain
258 the posterior distributions for the long-term metal fume exposure of the welding workers.

259 Figures 2 and 3 show the prior, likelihood, and posterior distributions for Cr, Fe, Mn, Ni, and Pb
260 concentrations in the NF and FF regions, respectively. As shown in Figs. 2 and 3, for prior and
261 likelihood distributions, the dominant probabilities of Fe and Mn mainly fell to ER3 and ER4 in NF
262 and FF regions, while those of Cr were at ER2 and ER3, and those of Ni were mostly at ER0, ER1
263 and ER2 in NF and FF regions. As for Pb, its dominant probabilities of prior distribution were
264 distributed at ER1 and ER2 in NF region but ER2 and ER3 in FF region, while its likelihood
265 distribution were evenly distributed. The above results shows that these metals have different prior
266 distributions in the NF and FF regions. Therefore, using total metal concentration in the fume to
267 directly assess welding workers' exposure profiles, which was commonly seen, could be inappropriate
268 and might underestimate welding workers' exposures. Based on the results of this study, we suggested
269 that it is more appropriate to use the fume concentration of each metal to assess welder's exposure.
270 Furthermore, it should be noted that the dominant probabilities between the prior and likelihood
271 distributions for some metals may be inconsistent, maybe because only limited field samples were
272 measured in the shipbuilding factory. The consistency in both prior and likelihood distributions

suggests the resultant posterior would be more feasible to assess workers' long-term exposures [21]. Because the prior and likelihood distributions of Fe and Mn in the NF region shared the same trend, it is suggested that Fe and Mn concentrations be the primary indicator to assess welders' exposures.

For the posterior distributions which were used to assess welding workers' long-term metal fume exposure profiles, the probabilities of Fe, Mn, and Pb in the NF region were at ER4 with values of 54%, 25%, 0.1%, while Fe and Pb in the FF region were at ER4 with values of 1.6%, and 0.1% respectively, indicating that the above metals should not be ignored since the exposure concentrations could be greater than the action level (0.5 OEL). The dominant probabilities of the posterior distribution in the NF region (Fig. 2) were at ER3 (=82%) for Cr, ER4 (=54%) for Fe, ER3 (=75%) for Mn, ER2 (=92%) for Ni and ER1 (=70%) for Pb, while those in the FF region (Fig. 3) were all at ER3, except for Ni (ER1=80%). These results revealed that the welding workers were indeed exposed to excessive metal fume in both NF and FF regions. Therefore, appropriate control measures should be taken by the shipyard manufacturing industry, such as installing a mobile local exhaust ventilation system, and providing suitable personal respiratory protective equipment for welders.

4. Conclusions

In this study, we found that the NF and FF models were suitable for predicting metal concentrations in welding fume. Using the month-round daily predicted concentrations and field monitoring concentrations in a shipyard manufacturing factory as the prior and likelihood distributions in the BDA, the resultant posterior distributions could be effectively applied to assess the long-term exposures of welders. We found that welders' long-term Fe, Mn and Pb exposures were, probability, to exceed the action level. It is concluded that preventive measures should be taken for reducing welders' exposures immediately. In addition, it is also found that Fe and Mn have the same trends of prior and likelihood distributions in different exposure regions. Therefore, it is suggested that both Fe and Mn concentrations could be used to replace the total fume concentrations to assess welders' exposure. Finally, it should be noted that the obtained posterior distribution can only be

299 regarded as the best solution based on the currently available predicting and monitoring data.

300

301 **SUPPLEMENTARY INFORMATION**

302 Additional information, as noted in the text, is available in the supplementary materials.

303

304 **ACKNOWLEDGMENT**

305 The authors wish to thank the Institute of Labor, Occupational Safety and Health, Ministry of
306 Labor in Taiwan for funding this research project (IOSH-1092018).

307

308 **References**

309

310 [1] A.T. Zimmer, P. Biswas, Characterization of the aerosols resulting from arc welding processes,
311 Journal of Aerosol Science, 32 (2001) 993-1008.

312 [2] L. Lillienberg, J.P. Zock, H. Kromhout, E. Plana, D. Jarvis, K. Torén, M. Kogevinas, A Population-
313 Based Study on Welding Exposures at Work and Respiratory Symptoms, Ann Occup Hyg, 52 (2008)
314 107-115.

315 [3] Z. Loukzadeh, S.A. Sharifian, O. Aminian, A. Shojaoddiny-Ardekani, Pulmonary effects of spot
316 welding in automobile assembly, Occupational Medicine, 59 (2009) 267-269.

317 [4] J. Antonini, Health Effects of Welding, Critical reviews in toxicology, 33 (2003) 61-103.

318 [5] S.S. Siew, T. Kauppinen, P. Kyrrönen, P. Heikkilä, E. Pukkala, Exposure to iron and welding fumes
319 and the risk of lung cancer, Scandinavian Journal of Work, Environment & Health, (2008) 444-450.

320 [6] J.M. Antonini, J.P. O’Callaghan, D.B. Miller, Development of an animal model to study the
321 potential neurotoxic effects associated with welding fume inhalation, NeuroToxicology, 27 (2006)
322 745-751.

323 [7] IARC, IARC MONOGRAPHS ON THE EVALUATION OF CARCINOGENIC RISKS TO HUMANS,
324 International Agency for Research on Cancer., Lyon, France, 1990.

325 [8] B. Knoll, Preliminary research to improved control of welding fume by automated local exhaust,
326 in, TNO Building and Construction Research, Delft, Dutch, 2003a.

327 [9] B. Knoll, Preliminary research to improved control of welding fume by adjusted torch
328 extraction, in, TNO Building and Construction Research, Delft, Dutch, 2003b.

329 [10] C.B.S. Keil, Catherine E; Anthony, T Renee, Mathematical Models for Estimating Occupational
330 Exposure to Chemicals, 2nd Edition, 2nd ed., American Industrial Hygiene Association America,
331 2000.

332 [11] M. Nicas, M.J. Plisko, J.W. Spencer, Estimating Benzene Exposure at a Solvent Parts Washer,
333 Journal of Occupational and Environmental Hygiene, 3 (2006) 284-291.

334 [12] G. Ramachandran, S. Banerjee, J.H. Vincent, Expert Judgment and Occupational Hygiene:
 335 Application to Aerosol Speciation in the Nickel Primary Production Industry, *The Annals of*
 336 *Occupational Hygiene*, 47 (2003) 461-475.

337 [13] P. Hewett, P. Logan, J. Mulhausen, G. Ramachandran, S. Banerjee, Rating exposure control
 338 using Bayesian decision analysis, *J Occup Environ Hyg*, 3 (2006) 568-581.

339 [14] P. Logan, G. Ramachandran, J. Mulhausen, P. Hewett, Occupational exposure decisions: can
 340 limited data interpretation training help improve accuracy?, *Annals of occupational hygiene*, 53
 341 (2009) 311-324.

342 [15] G. Ramachandran, Retrospective Exposure Assessment using Bayesian Methods, *Annals of*
 343 *Occupational Hygiene*, 45 (2001) 651-667.

344 [16] P. Wild, E.A. Sauleau, E. Bourgkard, J.J. Moulin, Combining expert ratings and exposure
 345 measurements: a random effect paradigm, *Ann Occup Hyg*, 46 (2002) 479-487.

346 [17] Y.C. Chen, G. Ramachandran, B.H. Alexander, J.H. Mandel, Retrospective exposure assessment
 347 in a chemical research and development facility, *Environment international*, 39 (2012) 111-121.

348 [18] M. Vadali, G. Ramachandran, J. Mulhausen, Exposure modeling in occupational hygiene
 349 decision making, *J Occup Environ Hyg*, 6 (2009) 353-362.

350 [19] Y. He, Y. Liang, H. Fu, Application of bayesian methods to exposure assessment of area
 351 concentrations at a rubber factory, *International journal of environmental research and public*
 352 *health*, 6 (2009) 622-634.

353 [20] J.C. Soo, P.J. Tsai, S.C. Lee, S.Y. Lu, C.P. Chang, Y.W. Liou, T.S. Shih, Establishing aerosol exposure
 354 predictive models based on vibration measurements, *Journal of hazardous materials*, 178 (2010)
 355 306-311.

356 [21] P.E. Sottas, J. Lavoue, R. Bruzzi, D. Vernez, N. Charriere, P.O. Droz, An empirical hierarchical
 357 Bayesian unification of occupational exposure assessment methods, *Stat Med*, 28 (2009) 75-93.

358 [22] T.L. Thatcher, D.W. Layton, Deposition, resuspension, and penetration of particles within a
 359 residence, *Atmospheric Environment*, 29 (1995) 1487-1497.

360 [23] C. He, L. Morawska, J. Hitchins, D. Gilbert, Contribution from Indoor Sources to Particle
 361 Number and Mass Concentrations in Residential Houses, 38 (2004) 3405-3415.

362 [24] M.J. Keane, A. Siert, B.T. Chen, S.G. Stone, Profiling mild steel welding processes to reduce
 363 fume emissions and costs in the workplace, *Ann Occup Hyg*, 58 (2014) 403-412.

364 [25] M. Keane, A. Siert, S. Stone, B. Chen, J. Slaven, A. Cumpston, J. Antonini, Selecting Processes to
 365 Minimize Hexavalent Chromium from Stainless Steel Welding: Eight welding processes/shielding
 366 gas combinations were assessed for generation of hexavalent chromium in stainless steel welding
 367 fumes, *Weld J*, 91 (2012) 241s-246s.

368 [26] M. Keane, S. Stone, B. Chen, J. Slaven, D. Schwegler-Berry, J. Antonini, Hexavalent chromium
 369 content in stainless steel welding fumes is dependent on the welding process and shield gas type,
 370 *Journal of Environmental Monitoring*, 11 (2009) 418-424.

371 [27] B.J.U. Quimby, G. D., Fume Formation Rates in Gas Metal Arc Welding. new fume chamber
 372 design improves the accuracy of fume generation data, *Welding Research Supplement*, (1999) 142-

373 149.
374 [28] A. Hobson, N. Seixas, D. Sterling, B.A. Racette, Estimation of Particulate Mass and Manganese
375 Exposure Levels among Welders, Ann Occup Hyg, 55 (2011) 113-125.
376

377 Table 1 The emission rates (ER) (mg/min) (CV) of welding metal fume for the selected welding
 378 processes.

Fume type	Current (A)	FCAW		GMAW	
		KFX71T	KFX70T	KM56	KM58
Cr	120	0.02(0.87)	0.03(0.88)	0.02(2.16)	0.03(1.11)
	220	0.04(1.96)	0.04(1.62)	0.03(1.24)	0.03(1.92)
	300	0.07(1.23)	0.09(3.01)	0.06(2.16)	0.09(1.34)
Fe	120	25.2(1.26)	27.9(0.92)	20.5(1.88)	24.7(2.46)
	220	31.8(1.85)	36.2(1.14)	29.4(2.85)	35.1(1.92)
	300	69.8(1.02)	72.9(1.26)	64.7(2.16)	67.8(1.92)
Mn	120	1.91(1.03)	3.91(1.25)	1.93(2.25)	3.06(1.48)
	220	3.39(2.62)	6.23(1.93)	2.65(2.81)	3.45(2.07)
	300	8.01(1.44)	9.35(1.94)	7.94(1.24)	8.78(1.05)
Ni	120	0.02(2.04)	0.03(0.82)	0.03(2.14)	0.03(3.41)
	220	0.05(3.98)	0.08(1.62)	0.04(2.15)	0.05(1.81)
	300	0.11(2.83)	0.11(2.01)	0.06(3.66)	0.09(1.86)
Pb	120	0.02(1.45)	0.03(0.99)	0.02(2.49)	0.02(2.58)
	220	0.04(2.48)	0.03(1.40)	0.03(2.46)	0.03(2.01)
	300	0.09(2.07)	0.10(1.49)	0.06(1.64)	0.08(1.02)

379
 380
 381

382 Table 2 The measured NF and FF metal concentrations (C_m) obtained from the welding simulations
 383 for two welding processes (mg/m³)

Fume type	Current (A)	FCAW				GMAW			
		KFX71T		KFX70T		KM56		KM58	
		NF	FF	NF	FF	NF	FF	NF	FF
Cr	120	0.007	0.002	0.011	0.004	0.003	0.001	0.004	0.002
	220	0.008	0.004	0.016	0.007	0.004	0.002	0.005	0.002
	300	0.011	0.005	0.018	0.009	0.006	0.003	0.006	0.003
Fe	120	22.9	7.15	20.6	8.21	16.1	5.95	20.5	7.69
	220	26.9	13.6	30.7	13.2	20.0	9.17	23.4	11.4
	300	37.9	17.8	34.5	17.1	29.1	15.6	28.7	15.8
Mn	120	0.184	0.057	0.261	0.104	0.241	0.089	0.308	0.116
	220	0.215	0.108	0.389	0.168	0.301	0.138	0.351	0.172
	300	0.303	0.142	0.438	0.217	0.438	0.234	0.431	0.238
Ni	120	0.005	0.001	0.011	0.004	0.003	0.001	0.004	0.002
	220	0.005	0.003	0.016	0.007	0.004	0.002	0.005	0.002
	300	0.008	0.004	0.018	0.009	0.006	0.003	0.006	0.003
Pb	120	0.005	0.001	0.008	0.003	0.003	0.001	0.004	0.002
	220	0.005	0.003	0.012	0.005	0.004	0.002	0.005	0.002
	300	0.008	0.004	0.014	0.007	0.006	0.003	0.006	0.003

384

385 Table 3 The GMs and GSDs (mg/m³) of the predicted long-term exposure concentrations of
 386 shipyard workers in NF and FF regions
 387

	NF (n=25)		FF (n=25)	
	GM	GSD	GM	GSD
Cr	0.008	1.32	0.005	1.09
Fe	6.13	1.35	1.22	1.08
Mn	0.236	1.16	0.098	1.06
Ni	0.009	1.92	0.003	1.11
Pb	0.003	1.41	0.002	1.08

388
 389
 390
 391

392 Table 4 The GMs and GSDs (mg/m³) of the field metal fume concentrations in the NF and FF
 393 regions of the welders

	NF (n=18)		FF (n=18)	
	GM	GSD	GM	GSD
Cr	0.064	2.68	0.013	2.44
Fe	5.31	1.93	1.06	2.58
Mn	1.38	1.97	0.196	2.16
Ni	0.011	2.34	0.001	2.17
Pb	0.008	2.28	0.005	2.56

394
 395

Cp (predicted metal fume concentration)

Cm (measured metal fume concentration)

Long-term exposure condition

Figure 1 Graphic abstract of the research structure of this study

(a) Cr

(b) Fe

(c) Mn

(d) Ni

(e) Pb

Figure 2 The resultant prior, likelihood, and posterior distributions for (a) Cr, (b) Fe, (c) Mn, (d) Ni, and (e) Pb fume concentrations in NF region, respectively.

(a) Cr

(b) Fe

(c) Mn

(d) Ni

(e) Pb

Figure 3 The resultant prior, likelihood, and posterior distributions for (a) Cr, (b) Fe, (c) Mn, (d) Ni, and (e)

Pb fume concentrations in FF region, respectively.

Supplementary Files

This is a list of supplementary files associated with this preprint. Click to download.

- [LongtermmetalfumeexposureassessmentSI0906.docx](#)
- [GraphicalAbstract.pptx](#)