Liquid Droplet Impact on a Sonically Excited Thin Membrane

Abba Abubakar

King Fahd University of Petroleum and Minerals

Bekir Yilbas (✉ bsyilbas@kfupm.edu.sa)

King Fahd University of Petroleum and Minerals

Hussain Al-Qahtani

King Fahd University of Petroleum and Minerals

Ammar Alzaydi

King Fahd University of Petroleum and Minerals

Research Article

Keywords: Droplet impact, hydrophobic surface, sonic oscillation, droplet rebound, contact time

Posted Date: September 20th, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-899203/v1>

License: © ⓘ This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Version of Record: A version of this preprint was published at Soft Matter on January 1st, 2022. See the published version at <https://doi.org/10.1039/D1SM01603B>.

Liquid Droplet Impact on a Sonically Excited Thin Membrane

Abba Abdulhamid Abubakar¹

Bekir Sami Yilbas^{1,2,3*}

Hussain Al-Qahtani¹

Ammar Alzaydi¹

¹*Mechanical Engineering Department, King Fahd University of Petroleum and Minerals, Dhahran, 31261, Saudi Arabia*

²*Interdisciplinary Research Center for Renewable Energy & Power Systems, KFUPM, Dhahran, 31261, Saudi Arabia*

³*Senior Researcher at K.A. CARE Energy Research & Innovation Center at Dhahran, Saudi Arabia*

Correspondence and requests for materials should be addressed to B.S.Y. (Email: bsyilbas@kfupm.edu.sa; Phone: +966 3 860 4481)

ABSTRACT

Impacting droplet characteristics on hydrophobic surfaces can be altered by introducing surface oscillations. Impacting water droplet contact duration, spreading, retraction, and rebounding behaviors are examined at various sonic excitation frequencies of the hydrophobic membrane. Membrane oscillation and droplet behavior are analyzed by utilizing a high-speed camera. The restitution coefficient and membrane dynamics are formulated and the findings are compared with those of the experiments. It is found that the mode of membrane oscillation changes as the sonic excitation frequency is changed. The droplet spreading and retraction rates reduce while rebound height and restitution coefficient increase at a sonic excitation frequency of 75 Hz. However, further increase of the excitation frequency results in reduced rebound height because of increased energy dissipation on the impacted surface. The droplet contact (transition time) duration reduces as the excitation frequency increases. Increasing droplet Weber number enhances the droplet contact period on the membrane, which becomes more apparent at low frequencies of sonic excitation.

Keywords: Droplet impact, hydrophobic surface, sonic oscillation, droplet rebound, contact time

INTRODUCTION

A liquid droplet behavior on hydrophobic surfaces remains important in various applications including self-cleaning,^{1,2,3} drug delivery,⁴ painting,⁵ combustions,⁶ and similar. Depending on the surface wetting state, liquid droplets can slide, roll, and roll/slide over the surface. Droplet sliding mainly occurs on hydrophilic surfaces and droplet wets the surface over a large area. The liquid droplet rolling and rolling/sliding motions are governed by the texture properties and free energy of the hydrophobic surfaces.⁷ The texture topology with hierarchically distributed micro/nano size pillars and cavities is favorable because of achieving a uniform hydrophobic wetting state on the surface. To mobile the liquid droplet on the surface such as rolling, the Lotus effect needs to be created to lower the contact angle hysteresis over the textured surface. Hence, forming the nano-size whiskers over the textured surface enables the creation of the Lotus effect. However, creating the surface texture topology with the Lotus effect is challenging in terms of cost-effective and one-step processing. External excitation of the surface such as sonic pulses can improve droplet mobility; in this case, sonic excitation oscillates the textured surface and the size of the interfacial contact between the droplet fluid and surface changes with time during the oscillation. Since the pinning force of the droplet over the textured surface is governed by the contact angle hysteresis (differences in the advancing and receding contact angles) and the length of the three-phase contact line, surface oscillation alters both the size of the contact line and the contact angle hysteresis. As the amplitude of the surface oscillation increases, the spring back effect can be created and the droplet jumping from the surface can be resulted. However, the jumping behavior depends on the amplitude and frequency of the surface oscillation, droplet size, and droplet fluid properties. As the droplet fluid is excited by the oscillatory motion of the surface, pressure in the droplet fluid changes locally, which in turn causes an imbalance between the pressure and surface tension forces. This gives rise to droplet shape change and the creation of surface tension waves within the droplet fluid. Hence, droplet sphericity modifies, and droplet roundness replaces with an irregular droplet shape. In addition, as the amplitude of surface oscillation increases, droplet expels from the surface, and cyclic rebounding can be initiated. The droplet shape changes and rebound characteristics depend on the oscillation frequency and amplitude, and topology of the textured surface, i.e. evolving of droplet shape and rebound height depend on the excitation wave

characteristics, and surface topology. Consequently, investigation of liquid droplet behavior over the textured surface subjected to external sonic excitation becomes necessary.

Oscillating hydrophobic surfaces creates the spring-back effect and, depending on the oscillation characteristics, droplet shape changes and jumping from the oscillating surface can be resulted. Droplet lifted from the surface behaves like the rebound of impacting droplet and, later, impinges on the oscillating surface. The impacting droplet before rebounding undergoes stretching over the impacted surface.⁸ This gives rise to non-uniform pressure distribution inside the droplet fluid while modifying droplet shape from round to about vertical-elliptic-like before rebounding.⁹ Consequently, droplet behaviour during lifting becomes different than that of the rebounding droplet after impact. In addition, the texture geometry such as micro/nano size pillars and grooves have considerable influence on the retraction dynamics of the droplet. An anisotropic texture topology results in the irregular round shape of the retracting droplet rebounding from the surface.¹⁰ As the retracted droplet shape is modified towards an irregular round shape, droplet rebound height and the shape of the falling droplet change after rebounding.¹¹ In some cases, the directional rebounding of droplet results as the surface has a roughness gradient. As the texture composes of hydrophobic and hydrophilic wetting states, droplet fluid can be captured in the hydrophilic texture space, which alters the rebound dynamics of the droplet.⁹ Hence, the unbalanced pressure and surface tension forces alter droplet retraction behavior before rebounding. In the presence of temperature difference across the fluid interface, the local heating of fluid occurs at the interface. This can create the Marangoni and buoyancy currents while increasing droplet mobility on surfaces.¹² As the temperature difference fluctuates, contact line pinning of the droplet weakens and droplet mobility on the hydrophobic surface further improves.¹³

Impacting droplet on hydrophobic surfaces undergoes spreading and rebounding and depending on the surface wetting state droplet rebound height changes. Although several considerable research studies have been conducted to explore impacting droplet characteristics on hydrophobic surfaces, the main focus was to correlate the influence of Weber number, texture characteristics with the spreading and restitution coefficients.^{14,15,16} The contribution of the oscillating hydrophobic surfaces to the droplet impacting characteristics has received less attention. The interaction between the droplet fluid and the oscillating hydrophobic surface involves the

complicated dynamic process during droplet spreading/retraction and rebounding phases. Moreover, oscillation of hydrophobic surface under sonic excitation also causes droplet liquid to oscillate. However, the surface tension waves created during the oscillation give rise to pressure variation within the droplet fluid. This creates a transient effect on droplet oscillation and the frequency of the droplet fluid differs from the frequency of the external sonic excitation. Hence, the droplet residency (contact duration) on the surface depends on the frequency and amplitude of the sonic excitation. Although research studies carried out previously on droplet oscillation on hydrophobic surfaces,^{17,18} the consideration is given for small size sessile droplets¹⁷ or impacting ellipsoidal droplets.¹⁸ The influence of droplet size and impact height on the oscillation characteristics and transient effects created on the droplet behaviour by the external sonic excitation are left for future study. In the present study, impacting droplet behaviour on the hydrophobic membrane, which is subjected to sonic excitation, is investigated. The mode of oscillations and geometric features of the droplet are assessed using high-speed camera data during membrane oscillation. The effect of membrane oscillation frequency on the droplet rebound height, the spreading rate, and restitution coefficient is assessed for various size water droplets and impact heights. The oscillating hydrophobic membrane surface characteristics are formulated analytically and simulated numerically using the COMSOL Multiphysics code. The transient behaviour of droplet rebounding, spreading, and restitution characteristics are evaluated for different excitation frequencies of the membrane.

EXPERIMENTAL

The membrane is constructed by a circular polyvinyl chloride, which is 0.14 mm thick and 120 mm in diameter. The membrane surface was hydrophobized by deposition of the functionalized nanosize silica specks. The silica particles were synthesized following the procedure reported in the previous work.¹⁹ In the functionalizing cycle of silica particles, the mixture of 14.4 mL of ethanol, 1 mL of de-ionized water, and 25 mL of ammonium hydroxide was prepared. Later, 1.5 mL TEOS and 4 mL of ethanol, and a 3:4 molar ratio of silane were added to the mixture. The dip-coating procedure accommodating the dip-coating unit (Biolin Scientific) was utilized to coat the membrane surface by the functionalized silica particles while using the mixture solution. A goniometer (Kyowa, model DM 501) was used to determine coating wetting state, and JEOL 6460

SEM (scanning electron microscope) and AFM (atomic force microscope, Flex-Axiom, Nano surf) were incorporated for coating texture evaluation. The fixture was designed and manufactured. The design accommodated a membrane and a loudspeaker. A schematic view of the experimental setup is shown in Fig. 1. The computer-controlled loudspeaker (Edifier Inc.) was operated at 9 V (DC) and 0.44 A towards generating sound waves. To reduce the mechanistic vibration of the fixture in the excitation period, the loudspeaker and its surroundings were insulated by foams. The frequency of the oscillation was monitored by an accelerometer. Several initial tests were carried out to secure the repeatability of the accelerometer readings and stability of the fixture during sonic excitations at various frequencies.

A high-speed recording facility (Speed Sense 9040) was used to monitor the impacting droplet behavior on the oscillating membrane. The high-speed camera was set at 5000 frames-per-second with 1280×800 pixels resolutions, which resulted in the pixel size of $14 \mu\text{m} \times 14 \mu\text{m}$. The recorded data were extracted and analyzed by the tracker program. The data repeatability was evaluated, and the standard error was obtained about 3%. The experimental uncertainty ($\pm u$) was determined by adopting the data extracted for droplet spreading, retraction, and rebound heights. Moreover, a confidence level of 96% was achieved from the repeats. The uncertainty (σ_u) is evaluated by [20]: $\sigma_u = \sqrt{\int_{x_o}^{x_n} (x - x_e)^2 f(x) dx}$, where, x is the data variable, x_e is the mean value of the corresponding data variable, n is the number of data points, and $f(x)$ is the function for the probability distribution. $f(x)$ was in the form of a Gaussian function, from which the function diameter was estimated. The pixels influencing the cross-correlation peak were normalized to satisfy the data consistency. The bias error was evaluated as 0.5 pixels due to the difficulties encountered to incorporate the small size peaks in the distribution function. The standard uncertainty was determined at about 3%.

ANALYTICAL FORMULATION

During the droplet impact on the hydrophobic surfaces, the work done overcoming the friction and droplet deformation gives rise to energy dissipation during the droplet transition over the impacting surface.²¹ The restitution coefficient can be expressed as:

$$e = \frac{v_2}{v_1} \quad (1)$$

where v_1 is the velocity at impact, v_2 is the velocity onset of rebound.

Using the energy balance for the impacting droplet over the hydrophobic surface can provide the formulation of the restitution coefficient. The detailed formulation of the restitution coefficient is given in Supplement (S1). The resulting restitution coefficient is:

$$e = \frac{v_2}{v_1} = \sqrt{\frac{h_2}{h_1}} = \sqrt{\frac{P_2 + \psi_2}{P_1 + \psi_1}} = \sqrt{1 - \frac{W}{\rho \frac{4}{3} \pi r_1^3 v_1^2 + \frac{\pi}{4} d_s^2 \sigma (1 - \cos \theta_a)}} \quad (2)$$

where: $P_1 = \frac{1}{2} \rho V_1 v_1^2$ is the initial droplet potential energy (i.e. before impact), $P_2 = \frac{1}{2} \rho V_2 v_2^2$ is the final droplet potential energy (i.e. after rebound), $V_1 = \frac{4}{3} \pi r_1^3$ is the initial droplet volume, $V_2 = \frac{4}{3} \pi r_2^3$ is the final droplet volume (after the rebound), ψ_1 is the initial droplet surface energy, ψ_2 is the final droplet surface energy, ρ is the fluid density and W is the droplet energy loss/gain during the sonic excitation.

On the other hand, the oscillating membrane, which is made from PVC, is very thin (i.e., about 14 μm thick) and has omittable flexural stiffness. Since it is circular and it is under almost the uniform radial force (T_0) at the edges, the membrane deflection can be expressed as:

$$\frac{\partial^2 \vartheta(r, \theta, t)}{\partial t^2} = c^2 \left(\frac{\partial^2 \vartheta(r, \theta, t)}{\partial r^2} + \frac{1}{r} \cdot \frac{\partial \vartheta(r, \theta, t)}{\partial r} + \frac{1}{r^2} \cdot \frac{\partial^2 \vartheta(r, \theta, t)}{\partial \theta^2} \right) \quad (3)$$

where: $c = \sqrt{\frac{F}{\rho h_f}}$ corresponds to the transverse oscillating wave speed on the membrane, ρ_f is the membrane density, t being the time, h_f is membrane thickness, ϑ is transverse deflection, and F is the in-plane tensile force per unit length acting at the edges of the membrane.

At the fixed edges of the membrane (zero displacements at the edges), the following boundary conditions need to be satisfied:

$$\vartheta(r, \theta, t) = 0 \text{ at } r = R \quad (4)$$

It was shown in the previous work that,²² the closed-form solution of Eq. (3) can be obtained with the separable of variable technique and the solution can be expressed as:

$$\begin{aligned} \vartheta(r, \theta, t) = & (A_1 \cdot \cos(c\lambda t) + B_1 \cdot \sin(c\lambda t)) \cdot J_m(\lambda_{mn}r) \\ & \cdot (A_2 \cos(m\theta) + B_2 \sin(m\theta)) \end{aligned} \quad (5)$$

where A_1 and A_2 are the constants, λ is the oscillation wavelength, $J_m(\lambda_{mn}r)$ is the Jacobian matrix, and m is an integer that corresponds to the number of circumferential lines having no-deflection. Hence, the natural frequencies of the oscillating membrane can be obtained from:

$$f_{mn} = \frac{c \cdot k_{mn}}{2\pi R} = \frac{k_{mn}}{2\pi R^2} \sqrt{\frac{F}{\rho_f h_f}} \quad (6)$$

where: k_{mn} could be evaluated from the Bessel function of the first kind and n corresponds to the number of diametral lines with no-deflection, R is the membrane radius, F is $\frac{E h_f^3}{12(1-\nu^2)}$, E is the elastic modulus of the membrane material, ν is Poisson's ratio, h_f is the membrane thickness, and ρ_f is the membrane material density. m and n can be utilized characterizing the mode shape.

The modes shape of the oscillating membrane can be predicted from Eq (6). The oscillating membrane is a two-dimensional elastic body and the properties are provided in Table 1. The uniform radial tensile force per unit length of applied force is considered at the edges of the membrane, which is 1.52 N. The mode shape can also be predicted numerically in COMSOL Multiphysics code using the membrane interface. The membrane has meshed having the 5418 triangular elements. The grid independent study showed that the elements selected lead to the converged solution of the Eigenvalues.

The dimensionless quantities used in the analysis are:

$$Re = \frac{\rho v_1 d_1}{\mu}, We = \frac{\rho v_1^2 d_1}{\gamma}, \beta = \frac{d}{d_1}, \bar{t} = \frac{t}{\tau_c}, \bar{t}_{max} = \frac{t_s}{d_1}, \bar{h} = \frac{h}{h_1}, \bar{v} = \frac{v}{v_1}$$

Where Re is the Reynolds number, We is the Weber number, β is the spreading coefficient, d_i is the diameter of the drop before impact, γ is surface tension, d is the instantaneous droplet velocity on the membrane, τ_c is the capillary time, t being the time, h is the droplet vertical height, h_1 is the droplet impact height, v is the velocity.

RESULTS AND DISCUSSION

An impacting droplet behavior on a hydrophobic membrane subjected to a sonic excitation is examined. Functionalized silicon nanoparticles are deposited on the membrane surface towards achieving a hydrophobic state. The influence of excitation frequency and intensity on the dynamic response of the droplet is assessed using the high-speed recording facility. The spreading, restitution, and rebound characteristics of the droplet are evaluated for various Weber numbers, droplet sizes, and impact heights.

Membrane Surface Topology and Wetting State:

Fig. 2a depicts the SEM micrograph of the deposited surface while Fig. 2b shows the AFM line scan of the deposited surface. The deposited nanoparticles form a film, which covers the entire coated glass surface. The size of the silica particle is about 30 nm and the deposition of nano size particles results in the texture of web structures with the local agglomeration of particles (Fig. 2a). The agglomeration of the particles mainly occurs due to the growth rate of silica particles on the surface, which grows at a higher rate than the nucleation rate of the particles.¹⁹ The web-like structure formed on the deposited surface demonstrates nano size crests and basins as observed from the AFM line scan (Fig. 2b). The maximum crest height is about 170 nm while the average roughness of the surface is 110 nm. The surface roughness parameter (r), which is defined as the

ratio of crest area over the projection area of the surface, is about 0.52. It is worth noting that $r = 1$ represents the smooth surface. The surface wetting state is determined using a Goniometer while incorporating a precision measurement technique.²³ In this case, the droplet image is obtained in 2D on the Goniometer screen and care is taken to resemble the optical image with the minimum shades. A mathematical function is used to fit the circumference of the droplet image. This provides the digital data for the image, and later the horizontal line is added over the image, which passes through the three-phase-contact line of the droplet. Since a small deviation occurs between the horizontal line and the line passing through the interfacial contact line, an angular correction (α_{BL}) is introduced between these lines. The contact angle is, then, determined from:²³

$$\theta = 90^\circ + \arcsin\left(\frac{\Delta y}{R}\right) \mp \alpha_{BL} \quad (3)$$

here, α_{BL} correction angle of the three-phase contact line from the horizontal line, Δy is the difference in the vertical coordinate between the horizontal line and the centre of the fitted function for the droplet circumference, and R is the curvature of the function. The droplet contact angle is measured as $150^\circ \pm 3^\circ$ and hysteresis is about $2^\circ \pm 1^\circ$. The tests are repeated at ten different locations on the deposited surface to obtain the average contact angle of the surface. The standard deviation of the contact angle measurement is found to be about 3° . Hence, the surface demonstrates the Cassie and Baxter state with a low pinning effect under the low hysteresis.

Droplet Dynamics on Membrane Under Sonic Excitations:

The membrane was excited by the sonic excitation with the range of 40 Hz to 150 Hz and 80 dB to 100 dB from the membrane bottom (Fig. 1). The membrane is a circular shape, and the edges are fixed around a circular solid ring. It has a considerably small flexural stiffness, and the deflection of the membrane can be evaluated from Eq. 5. Fig. 3 shows the mode of membrane oscillation obtained from the predictions for the excitation frequencies of 40 Hz and 150 Hz. The mode of oscillation changes as the sonic excitation frequency increases. Fig. 4a depicts the vertical displacement of the hydrophobic surface at the membrane center with the excitation sonic frequencies. The displacement is nondimensionalized by the diameter of the droplet of 10 μL volume and the time is nondimensionalized by the capillary time of 10 μL droplet (0.01173s). It is

worth mentioning that since various droplet sizes are incorporated in the analysis, impact parameters are normalized by 10 μL droplet, which is considered as the reference. The membrane displacement becomes the maximum for the sonic excitation frequency of 75 Hz. Moreover, variation of sound power level with excitation frequency is shown in Fig. 5b. The spacing between the sonic exciter (loudspeaker) and the membrane is selected in such a way that the sound power level remains almost constant with the excitation frequencies, which can be observed from Fig. 4b. The sound power level does not change notably for the spacing selected within the range of the excitation frequency; however, the local maxima of power sound level occur at 75 Hz sonic excitation frequency. Moreover, the natural frequencies and mode shapes predicted from the experiment, simulations, and analytical formulation (Eq. 6) are given in Table 2. The predictions and analytical findings for the natural frequencies of the membrane agree well with the experimental results. Figs. 5a to 5c show membrane vertical displacement after the droplet impact for different Weber numbers and various excitation frequencies. The droplet impact height is kept the same for all Weber numbers and droplet volume is changed from 10 to 40 μL . The red arrow in the figure points to the time of impact and droplet impact period. It is worth mentioning that the experiments are carried out to synchronize the droplet impact with the membrane oscillation; in which case, the droplet impact period is in phase with the oscillation period, i.e., the droplet impacts onto the membrane when the membrane displacement is the minimum. Hence, the membrane undergoes natural oscillation before the time of impact. The amplitude of membrane oscillation before the droplet impact is small for the excitation frequency of 45 Hz (Fig. 5a). Increasing Weber number corresponds to the increased droplet volume, the amplitude of membrane oscillation increases, and the frequency of the membrane oscillation change slightly for the excitation frequency of 45 Hz (Fig. 5a). The droplet spreads/retract and rebounds after the impact, which causes cyclic droplet impacting after the initial impact. The amplitude of the cyclic impact reduces with the increasing number of impacts. Hence, this creates a damping effect on the membrane oscillations, i.e. the frequency and amplitude of membrane oscillation changes as the Weber number increases (Fig. 5a). In this case, the amplitude increases after the first impact, and it dies as the progress of the cyclic impact. The oscillation frequency of the membrane reduces during the droplet cyclic impacts due to rebounding (Fig. 5a). As the excitation frequency of the membrane increases to 75 Hz, the amplitude of the membrane oscillation increases (Fig. 5b). When the droplet impacts onto the oscillating membrane, the amplitude of oscillation changes slightly

while the frequency of the oscillation is not notably affected by the impacting droplet (Fig. 5b). This is true for all the Weber numbers incorporated in the experiments. Hence, as the membrane oscillation increases in terms of frequency and displacement so the influence of impacting droplets on the membrane oscillation becomes negligibly small. Moreover, as the sonic excitation frequency increases, the displacement of the membrane oscillation reduces while the frequency increases (Fig. 5c). As the droplet impacts onto the oscillating membrane, the frequency and the displacement of the membrane change notably (Fig. 5c). In this case, the displacement increases while frequency reduces with increasing Weber number. Hence, the frequency shift in the membrane becomes more apparent for the sonic frequency of 105 Hz.

The optical images of the droplet impacting the sonically excited membrane are shown in Fig. 6. The droplet rebound height becomes the maximum and the body deformation of the droplet in the rebounding cycle becomes large at 75 Hz excitation frequency. The upward force created on the droplet by the spring-back effect and the gravitational force causes the droplet to break into vertically moving small droplets. Nevertheless, this small droplet re-joins upon the second cycle of rebound. Moreover, the droplet spreads/retracts and rebounds on the impacted surface. After the retraction period, the droplet vertically extends and, later, detaches from the surface (rebounds from the surface). Figs. 7a to 7c show the droplet vertical rebound height with time for different sonic excitation frequencies and droplet impact height of 20 μ L droplet. The droplet undergoes several rebounding after the impact onto the membrane surface. With the sonic excitation at a high frequency (105 Hz), the maximum droplet rebounding height reduces while indicating the reducing droplet overall kinetic energy after each impact. Moreover, by reducing sonic excitation frequency, the maximum rebound height increases, which is particularly true for the excitation frequency of 75 Hz. However, further reduction in the oscillation frequency (< 75 Hz), causes the reduced maximum rebound height. Hence, at a certain frequency range, the membrane oscillation under the sonic excitation creates a spring-back effect while increasing droplet kinetic energy and rebound height (Fig. 7a to 7c). The spring-back effect also exists for the large droplet impact heights. However, the ratio of the droplet's first maximum rebound height over the droplet impact height remains small as the impact height increases. This can be explained in terms of the energy dissipation of the droplet during the first impact, i.e., impacting droplet losses some of its kinetic energy because of the interfacial resistance (friction and adhesion) during the spreading on the

surface impacted. This energy dissipation increases as the droplet impact height increase.²⁴ However, for large impact height (30 mm), the spring-back effect on the droplet rebound height becomes less significant. It should be noted that the droplet spreading diameter increases as the droplet impact height increases. This in turn increases the duration of resistance of the droplet on the impacted surface because of the long spreading period. In addition, the droplet kinetic energy dissipation on the surface increases during the long spreading period. Hence a combination of high droplet kinetic energy dissipation and extended resistance time of the droplet over the surface suppresses the spring-back effect created by the oscillation of the membrane. Moreover, the droplet vertical displacement increases with the Weber number. It should be noted that the Weber number represents the droplet inertia force over the surface tension force. The droplet size and impact height attain large values at high Weber numbers. The occurrence of the maximum rebound height changes with the Weber number; hence, increasing the Weber number delays the time occurrence of the maximum rebound height. The time shift of the occurrence of the maximum rebound height changes considerably with the Weber number for low sonic excitation frequency (45 Hz). However, the time occurrence of the maximum rebound height for different Weber numbers becomes close for the excitation frequency at which the maximum spring-back effect is created (75 Hz). This indicates that as the spring-back influence on the droplet impact increases, the shift in time of the maximum rebound height occurring becomes small. As the excitation frequency further increases (105 Hz), the time shift for the occurrence of the maximum rebound height due to different Weber numbers becomes large. Hence, the influence of the excitation frequency on the droplet rebound characteristics remains significantly important.

Figs. 8a to 8c show the spreading coefficient (D/D_o , where D is the droplet diameter over the impacting surface and D_o is the droplet diameter prior to the impact) with time for different values of the Weber number and sonic excitation frequencies. The time is normalized by the capillary time of 10 μ L droplet (0.01173s). It should be noted that the end of spreading and retraction periods are indicated with the error in the figure (the red arrow shows the end of the spreading while the green arrow corresponds to the end of the retraction). The time for the droplet to reach the maximum value of the spreading coefficient increases as the Weber increases. Moreover, the retraction period (between the red and green arrows) remains longer than that of the spreading period. Hence, the droplet kinetic energy dissipated during the droplet spreading lowers the energy

available during the retraction cycle while slowing down the retraction of the droplet after spreading. In addition, the force balance between the Laplace pressure and the surface tension force contributes to a slow rate of retraction. The maximum spreading coefficient becomes slightly larger for 75 Hz excitation frequency than that of 45 Hz and 105 Hz excitations. The short spreading and retraction periods at 75 Hz excitation frequency are related to the energy exchange across the membrane surface and the droplet fluid, which enables an increase of droplet kinetic energy during the spreading and retraction periods via the spring-back effect. Moreover, as the sonic excitation frequency increases to 105 Hz, the mode of oscillation changes to two modes (Fig. 3). It is worth mentioning that the excitation frequencies at 45 Hz and 75 Hz result in a single mode of oscillation (Fig. 3). Hence, the second mode of oscillation causes lateral and vertical motion of the membrane surface. The lateral motion of the membrane can suppress the droplet spreading and retraction motions on the surface. This gives rise to the shortening of the spreading and retraction periods with creating no spring-back effect on the droplet motion (Fig. 8c). Hence, the droplet energy is dissipated via frictional and deformation work of the droplet during the lateral motion of the membrane at 105 Hz frequency. This gives rise to short spreading and retraction periods.

Fig. 9a shows the restitution coefficient with sonic excitation frequency for different Weber numbers. The restitution coefficient increases with sonic excitation frequency up to the frequency of 75 Hz at which the maximum restitution coefficient results. However, a further increase of the excitation frequency causes a reduction in the restitution coefficient. This indicates that the droplet kinetic energy dissipation during the transition period of spreading and retraction becomes large for frequencies greater than 75 Hz. Fig. 9b shows the droplet contact duration with sonic excitation frequency for different Weber numbers while Fig. 9c depicts the normalized maximum droplet height, during the spreading and retractions periods, with sonic excitation frequency for different Weber numbers. The time is normalized by the capillary time of 10 μ L droplet (0.01173s) while the average droplet height is normalized by the diameter of 10 μ L droplet. The droplet contact time increases with the Weber number for all excitation frequencies and the rise of the contact time is almost linear with the Weber number. As the excitation frequency increases the droplet contact time reduces, i.e., the normalized droplet contact time becomes about 3.1 for the Weber number of 24 at 45 Hz excitation frequency while it is about 1.7 for the same Weber number at 75 Hz frequency; hence it is almost half of the duration of the low-frequency excitation. Consequently,

the droplet contact time reduces as the excitation frequency increases beyond 75 Hz. In the case of Fig. 9c, the average droplet height reduces as the Weber number increases, which is true for all excitation frequencies. Increasing the frequency beyond 75 Hz, the average droplet diameter also further increases. At the frequency of 105 Hz, the average droplet height becomes 0.29 while it is 0.2 at 45 Hz for the Weber number of 24. The droplet contact time (Fig. 9b) and the rebound height (Figs. 7a to 7c) reduce, but droplet average height on the impacted surface (Fig. 9c) increases at high excitation frequency (105 Hz, Fig. 9c). This behavior is attributed to the mode of oscillation of the membrane at high frequency, i.e., it changes one mode to two modes of oscillation at high frequency. The droplet kinetic energy dissipation during the spreading and retraction periods suppresses the large size spreading of the droplet while reducing the droplet contact duration.

CONCLUSION

Liquid droplet impacting on the sonically excited circular hydrophobic membrane is considered and droplet impact characteristics are examined. The influence of sonic excitation frequency, droplet volume, and impact height on the spreading, retraction, and rebounding behavior of the droplet is investigated. Depending on the sonic excitation frequency, one and two modes of membrane oscillation have resulted. The membrane vertical displacement reaches the maximum in the first mode of oscillation while the location of the maximum vertical displacement moves to the mid-point of the radius of the membrane in the second mode of the oscillation. The droplet spreading, retraction, and rebound height change as the frequency of the sonic excitation changes. In this case, rebound height attains the maximum while spreading and retraction reduce at 75 Hz excitation frequency. As the excitation frequency increases furthermore by 105 Hz, rebound height reduces while spreading and retraction behavior of the droplet remains almost the same as that occurring at 75 Hz frequency. The attainment of low rebound height is related to the lateral motion of membrane oscillation at 105 Hz frequency; in which case, the mode of oscillation changes to the second mode, and the droplet kinetic energy dissipation during spreading and retraction becomes large. The average droplet height during the transition period on the surface increases as the sonic excitation frequency and the Weber number increase. The droplet contact time (transition time) over the membrane surface increases with the Weber number, which is more pronounced at a low frequency of sonic excitation. The spreading coefficient increases with the Weber number;

however, increasing excitation frequency suppresses the droplet spreading rate. The retraction period of the droplet remains longer than the spreading period over the impacting surface, which becomes more apparent as the excitation frequency reduces.

REFERENCES

1. Hassan, G., Yilbas, B. S., Al-Sharafi, A. & Al-Qahtani, H. Self-cleaning of a hydrophobic surface by a rolling water droplet. *Sci. Rep.* **9**, 5744 (2019).
2. Yilbas, B. S., Al-Sharafi, A. & Sahin, A. Z. Solar energy harvesting and a water droplet cleaning of micropost arrays surfaces. *Int. J. Energy Res.* **44**, 2072–2083 (2020).
3. Wisdom, K. M. *et al.* Self-cleaning of superhydrophobic surfaces by self-propelled jumping condensate. *Proc. Natl. Acad. Sci.* **110**, 7992–7997 (2013).
4. Chou, W.-L., Lee, P.-Y., Yang, C.-L., Huang, W.-Y. & Lin, Y.-S. Recent advances in applications of droplet microfluidics. *Micromachines* **6**, 1249–1271 (2015).
5. Guettler, N., Knee, P., Ye, Q. & Tiedje, O. Initial droplet conditions in numerical spray painting by electrostatic rotary bell sprayers. *J. Coatings Technol. Res.* **17**, 1091–1104 (2020).
6. Qiao, Y.-Y., Ma, Y.-L., Zhang, Z.-G. & Liu, C.-C. Experimental study on sodium droplet combustion and spatial temperature distribution characteristics. *J. Nucl. Sci. Technol.* **55**, 1079–1086 (2018).
7. Backholm, M. *et al.* Water droplet friction and rolling dynamics on superhydrophobic surfaces. *Commun. Mater.* **1**, 1–8 (2020).
8. Li, X., Ma, X. & Lan, Z. Dynamic behavior of the water droplet impact on a textured hydrophobic/superhydrophobic surface: the effect of the remaining liquid film arising on the pillars' tops on the contact time. *Langmuir* **26**, 4831–4838 (2010).
9. Yuan, Z., Matsumoto, M. & Kurose, R. Directional rebounding of a droplet impinging hydrophobic surfaces with roughness gradients. *Int. J. Multiph. Flow* **138**, 103611 (2021).
10. Fan, Y. L., Zhan, Z., Guo, C., Kim, J.-H. & Lee, J. Retraction dynamics of a water droplet impacting onto a microgrooved hydrophobic surface at different velocities and surface temperatures. *Int. J. Heat Mass Transf.* **168**, 120851 (2021).
11. Fink, V. *et al.* Drop bouncing by micro-grooves. *Int. J. Heat Fluid Flow* **70**, 271–278 (2018).

12. Al-Sharafi, A., Yilbas, B. S. & Ali, H. Water droplet mobility on a hydrophobic surface under a thermal radiative heating. *Appl. Therm. Eng.* **128**, 92–106 (2018).
13. Tsao, Y.-H., Wang, T.-Y., Tsao, H.-K. & Sheng, Y.-J. Thermally assisted mobility of nanodroplets on surfaces with weak defects. *J. Colloid Interface Sci.* **604**, 150–156 (2021).
14. Abubakar, A. A. *et al.* Experimental and model studies of various size water droplet impacting on a hydrophobic surface. *J. Fluids Eng.* **143**, 61402 (2021).
15. Tan, J. *et al.* Regulating droplet impact on a solid hydrophobic surface through alternating current electrowetting-on-dielectric. *Phys. Fluids* **33**, 42101 (2021).
16. Abubakar, A. A., Yilbas, B. S. & Al-Qahtani, H. A Water Droplet Impact on a Hydrophobic Soft Surface. *J. Fluids Eng.* **143**, (2021).
17. Singha, P., Nguyen, N.-K., Zhang, J., Nguyen, N.-T. & Ooi, C. H. Oscillating sessile liquid marble-A tool to assess effective surface tension. *Colloids Surfaces A Physicochem. Eng. Asp.* **627**, 127176 (2021).
18. Yun, S. The role of oscillation in ellipsoidal drop impact on a solid surface. *J. Colloid Interface Sci.* (2021).
19. Yong, W. Y. D., Zhang, Z., Cristobal, G. & Chin, W. S. One-pot synthesis of surface functionalized spherical silica particles. *Colloids Surfaces A Physicochem. Eng. Asp.* **460**, 151–157 (2014).
20. Bhattacharya, S., Charonko, J. J. & Vlachos, P. P. Particle image velocimetry (PIV) uncertainty quantification using moment of correlation (MC) plane. *Meas. Sci. Technol.* **29**, 115301 (2018).
21. Hassan, G., Yilbas, B. S., Al-Sharafi, A., Sahin, A. Z. & Al-Qahtani, H. Solar energy harvesting and self-cleaning of surfaces by an impacting water droplet. *Int. J. Energy Res.* **44**, 388–401 (2020).
22. Asmar, N. H. *Partial differential equations with Fourier series and boundary value problems.* (Courier Dover Publications, 2016).
23. Heib, F. & Schmitt, M. Statistical Contact Angle Analyses with the High-Precision Drop Shape Analysis (HPDSA) Approach: Basic Principles and Applications. *Coatings* vol. 6 (2016).
24. Abubakar, A. A. *et al.* Droplet Impacting on a Hydrophobic Surface: Influence of Surface

Wetting State on Droplet Behavior. *J. Fluids Eng.* **142**, (2020).

Acknowledgment

The authors acknowledge the financial support of Deanship of Scientific Research at King Fahd University of Petroleum and Minerals (KFUPM) through Projects# DF201016 and King Abdullah City for Atomic and Renewable Energy (K.A. CARE) to accomplish this work.

Author contributions

A.A. Abubakar did the experimental and analytical works, and contributed to the writing of the manuscript.

B. S. Yilbas did the research work with the collaboration of other co-authors and wrote the manuscript.

H. Al-Qahtani did some part of the experimental and analytical work, and contributed to the writing of the manuscript.

A. Alzaydi did some part of the experimental work and contributed to the writing of the manuscript.

Declaration of interest

We declare that the work carried out and presented in this manuscript does not involve in any Financial Interest.

Supplementary Information

S1: Analytical Formulation of Restitution Coefficient.

List of Tables

Table 1. Parameters used in the analysis to obtain mode shapes.

Table 2. Mode of membrane oscillation and natural frequencies.

List of Figures

Figure 1. Schematic view of the experimental setup.

Figure 2. a) SEM image of the hydrophobized surface, and b) AFM line scan of hydrophobized surface.

Figure 3. Mode shapes predicted from numerical code (COMSOL) at various frequencies.

Figure 4. Variation of: a) membrane displacement amplitude and b) sonic power with excitation frequency.

Figure 5. Variation of vertical displacement at membrane center with time for different Weber numbers at sonic excitation frequencies of: a) 45 Hz, b) 75 Hz, and c) 105 Hz. The droplet impacting period is in phase with the sonic waves.

Figure 6. Optical images of impacting droplets (20 μL) at different sonic excitation frequencies.

Figure 7. Droplet vertical rebound heights at the membrane center with time for different Weber numbers at different sonic excitation frequencies: a) 45 Hz, b) 75 Hz, c) 105 Hz. The droplet impacting period is in phase with the sonic excitation.

Figure 8. Spreading coefficient with time for different Weber numbers at sonic excitation frequencies of: a) 45 Hz, b) 75 Hz, c) 105 Hz. The droplet impacting period is in phase with the sonic waves. Red arrow shows end of spreading and green arrow points end of retraction.

Figure 9. Variation of droplet behavior with sonic excitation frequency for various Weber numbers: a) restitution coefficient, b) droplet contact time, and c) maximum droplet height over the impacted surface.

Table 1. Parameters used in the analysis to obtain mode shapes.

Parameter	Value
$R(mm)$	60
$\rho(kg/m^3)$	930
$h(mm)$	14×10^{-3}
$T_0(N/m)$	1.52
$E(MPa)$	880
ν	0.38

Table 2. Mode of membrane oscillation and natural frequencies.

Oscillation modes	Natural frequencies (Hz)		
	Experimental	Analytical	Numerical
	70.0 + 5	68.9	70.79
(1,0)			
(1,1)	105.0 + 5	110.64	106.64
(1,2)	135.0 + 5	137.23	136.24

Figure 1. Schematic view of the experimental setup.

Figure 2. a) SEM image of the hydrophobized surface, and b) AFM line scan of hydrophobized surface.

Figure 3. Mode shapes predicted from numerical code (COMSOL) at various frequencies.

Figure 4. Variation of: a) membrane displacement amplitude and b) sonic power with excitation frequency.

Figure 5. Variation of vertical displacement at membrane center with time for different Weber numbers at sonic excitation frequencies of: a) 45 Hz, b) 75 Hz, and c) 105 Hz. The droplet impacting period is in phase with the sonic waves.

Figure 6. Optical images of impacting droplets (20 μL) at different sonic excitation frequencies.

Figure 7. Droplet vertical rebound heights at the membrane center with time for different Weber numbers at different sonic excitation frequencies: a) 45 Hz, b) 75 Hz, c) 105 Hz. The droplet impacting period is in phase with the sonic excitation.

Figure 8. Spreading coefficient with time for different Weber numbers at sonic excitation frequencies of: a) 45 Hz, b) 75 Hz, c) 105 Hz. The droplet impacting period is in phase with the sonic waves. Red arrow shows end of spreading and green arrow points end of retraction.

Figure 9. Variation of droplet behavior with sonic excitation frequency for various Weber numbers: a) restitution coefficient, b) droplet contact time, and c) maximum droplet height over the impacted surface.

Supplementary Files

This is a list of supplementary files associated with this preprint. Click to download.

- [SupplementaryinformationS1.docx](#)