Soot Distribution and Thermal Regeneration of Marine Diesel Particulate Filter

Xiangli Wang

Nantong University

Peiyong Ni (✉ np614@126.com)

Nantong University

Research Article

Keywords: marine diesel engine, diesel particulate filter, soot distribution, regeneration.

Posted Date: November 15th, 2021

DOI: <https://doi.org/10.21203/rs.3.rs-963513/v1>

License: © ⓘ This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Soot Distribution and Thermal Regeneration of Marine Diesel Particulate Filter

Xiangli Wang ¹, Peiyong Ni ^{2,*}

¹ School of Electrical Engineering, Nantong University, Nantong 226019, China

² School of Mechanical Engineering, Nantong University, Nantong 226019, China

Abstract:

Particles from marine diesel engine exhaust gas have caused serious air pollution and human health. Diesel particulate filter (DPF) can effectively reduce particle emissions from marine diesel engines. The distribution and regeneration of soot in DPF are two important issues. In this paper, a mathematical model of a marine DPF was built up and the particle trap process and the regeneration dynamics were simulated. The results show that the cake soot mass concentrations during trap process increase linearly with the increase of the exhaust gas flows while the depth soot mass concentrations firstly increase linearly and then keep constant. Soot is mainly concentrated in the front and rear portion of the filter and less soot is in the middle. The soot distribution in the cake and depth layer shows the unevenness during the trap and regeneration process. The initial soot loadings have great effects on pressure drops and soot mass concentrations before regeneration, but little effect after regeneration. The exhaust gas temperature heated to 850 K can achieve 94% efficiency for the DPF regeneration. There is no obvious difference in pressure drops and soot mass concentrations between fast heating and slow

* Corresponding author. School of Mechanical Engineering, Nantong University, Nantong 226019, China
E-mail address: npy614@126.com (P. Ni).

heating. The heating duration of exhaust gas has an important impact on DPF regeneration.

Keywords: marine diesel engine; diesel particulate filter; soot distribution; regeneration

1. Introduction

Particulate matter (PM) emissions from marine diesel engines have a great negative impact on the coastal and marine environment and human health. Especially, the large ship diesel engines fueled with heavy fuel oil (HFO) emit more and more harmful particulate pollutants with more complex composition. At present, there are no unified regulations of particulate matter emissions on the global scale. However, some countries and international organizations have formulated the particle emission regulation for marine diesel engines¹. Consequently, some measures of particulate matter reduction have been adopted, such as use of clean alternative fuels and installation of after-treatment devices. Currently, the wall-flow DPF is considered as one of the most effective after-treatment technologies for reducing diesel engine particles.

DPFs are installed in diesel engine pipes to trap the particles passing through the porous walls. As the porous walls are loaded with particles, filter cake layers on the walls and depth layers inside the porous are formed due to the fact that many particles are unable to pass through the walls. Thus, this can cause a higher pressure drop across the DPF, resulting in engine performance decline. It is required that the DPF is regenerated periodically to remove the collected soot by combustion². The commonly used regeneration methods include passive regeneration³ and active regeneration⁴. Passive regeneration is a method to oxidize the accumulated particles using a catalyst or fuel

additive at typical exhaust temperature⁵. However, passive regeneration efficiency is low under low engine load conditions. Additionally, catalyzed regeneration is not suitable for diesel engines with high sulfur fuels due to the sulfur poisoning. Oppositely, active regeneration is a method to increase the exhaust gas temperature by injecting fuel into exhaust pipe⁶ or post injection in cylinder⁷. Recently, the microwave assisted regeneration is also used to remove the deposited soot at a low temperature^{8,9}. Thermal regeneration is a very effective modes to remove the soot particles trapped by the DPF. However, thermal regeneration method is restrictive due to the fact that the DPF carrier can be damaged when it is overheated. Therefore, it is important to reasonably control the heating temperature.

Many experimental and simulated studies on the temperature characteristics during DPF regeneration have been performed. Chen et al.¹⁰ reported that the maximum soot layer temperature occurred at gas-soot interface. Chong et al.¹¹ measured the heat release of diesel PM to predicting the temporal distributions of thermal energy during DPF regeneration. Yamamoto and Yamauchi¹² concluded that the filter clogging could be avoided at the filter temperature of 800 K. Yu et al.¹³ found that the DPF substrate thickness and volumetric heat capacitance affected the speed of the temperature front. Liu et al.¹⁴ reported that the reasonable content should be from 7% to 12% due to the peak temperature limit. Meng et al.¹⁵ found that the 575 °C regeneration temperature resulted in large total amount of emitted particles in the downstream of the DPF. Yu and Luss¹⁶ concluded that the inlet cone could crack the ceramic support due to higher temperature

gradients. Deng et al.¹⁷ reported that the maximum radial temperature gradient appeared in the front of the filter section and contraction section while the peak of axial temperature gradient appeared in the front of the filter section. They also showed the appropriate regeneration conditions at the particle load of 5 g/L and the flow rate of 30 g/s. Lupše et al.¹⁸ found the heat capacity of the filter has an important effect on the high temperature exposure time of filter support. Zhang et al.¹⁹ improved the DPF temperature gradient using the multidisciplinary design optimization model. Ebrahimmataj et al.²⁰ found that the cake layer and the substrate wall were appropriate for soot burning at low and high temperature respectively. Yu et al.²¹ reported that widening the width of the moving temperature front lowered the peak value of regeneration temperature.

Based on the above literature review, it is noticed that the temperature distribution and the soot cake layer in the DPF for diesel engines under different regeneration conditions are being paid close attention. However, the regeneration characteristics of DPFs for marine diesel engines were rarely reported. Therefore, it was numerically simulated in this study. The effects of exhaust gas flow, initial soot loading and heating mode on the DPF regeneration dynamics were deeply investigated. The purpose of this paper is to provide some useful information for the design of marine diesel engine DPF.

2. Numerical simulation

2.1 Mathematical models

A wall-flow DPF made of Silicon Carbide was studied in this study. According to the characteristics of soot burning inside the carrier during the regeneration process, four

assumptions can be made for the model. First, there is no change in gas state parameters in the radial direction of the outlet and inlet channels inside the carrier. The second assumption is that the gas into the DPF is regarded as ideal gas. The third is that the particles only consist of carbon and is uniformly distributed on the inner wall of the tunnel. The last is that the airflow is treated as laminar flow after it enters each channel.

The steady-state continuity equations of the gas phase in the inlet and outlet channel is

$$\frac{\partial}{\partial z} (d^2 \rho_i v_i) = (-1)^i 4d \rho_w v_w \quad (1)$$

where z is axial direction in channel, d is the length of the channel, $i=1$ represents the inlet, $i=2$ is the outlet channel, v_i is the axial flow velocity of the channel, v_w is the filtration velocity of decent air flow, ρ_i is the gas density in the inlet and outlet channel, and ρ_w is the gas density in wall.

The momentum balance equation of the gas phase in the channels is written as

$$\frac{\partial p_i}{\partial z} + \frac{\partial}{\partial z} (\rho_i v_i^2) = -\frac{\alpha_i \mu v_i}{d^2} \quad (2)$$

where p_i is the pressure of the gas in the inlet and outlet channel, α_i is the friction coefficient in the channel and μ is the dynamic viscosity.

The energy equation of the gas phase in the filter is given by

$$C_{pg}(T_i) \rho_i(T_i) \frac{\partial T_i}{\partial z} = \frac{4}{d - 2w_p} (T_w - T_i) \left[h_i + (-1)^i C_{pg}(T_i) \rho_w(T_w) v_w \right] \quad (3)$$

where $C_{pg}(T_i)$ is the specific heat capacity of the gas in the inlet and outlet channel, T_i is the temperature of in the inlet and outlet, T_w is the gas temperature within the wall,

and h_i is the convective heat transfer coefficient of gas and wall.

The energy equation of the solid phase in the filter is written as¹⁶

$$\frac{\partial}{\partial t}(\rho_p w C_{pp} T_w + \rho_s w_s C_{ps} T_w) = Q_{cond} + Q_{conv} + Q_{wall} + Q_{react} \quad (4)$$

where ρ_p is the density of particulate layer, w is the particulate layer thinness, w_s is the substrate layer thickness, C_{pp} is the specific heat capacity of particulate layer, C_{ps} and ρ_s are the specific heat capacity and density of the substrate layer, respectively, Q_{cond} is the conductive heat transfer along the channel wall, Q_{conv} are the convective heat transfer from the channel flow, Q_{wall} is the convective heat transfer from the flow through the wall, and Q_{react} are the heat generated by the exothermic PM oxidation.

They are expressed as

$$Q_{cond} = \lambda_p \frac{\partial}{\partial z} \left(w \frac{\partial T_w}{\partial z} \right) + \lambda_s w_s \frac{\partial^2 T_w}{\partial z^2} + \lambda_{eff} \frac{1}{r} \frac{\partial}{\partial r} \left[r (w_s + w) \frac{\partial T_w}{\partial r} \right] \quad (5a)$$

$$Q_{conv} = -h_1 (T_w - T_1) - h_2 (T_w - T_2) \quad (5b)$$

$$Q_{wall} = C_{pg} v_w \rho_w (T_1 - T_w) \quad (5c)$$

$$Q_{react} = -\Delta H \rho_p \frac{dw}{dt} / M_p \quad (5d)$$

where λ_p is the particulate thermal conductivity, λ_s is the substrate thermal conductivity, λ_{eff} is the effective radial heat conductivity, r is the radial distance from the axis of the filter, ΔH is the combined reaction enthalpy of soot oxidation, and M_p is the molecular weight of particulate.

The model of the DPF regeneration with oxygen includes the following reaction²²

where α is an oxidation reaction index. The particle combustion reaction enthalpy ΔH is related to α .

$$\Delta H = 2(\alpha - 0.5)\Delta H_{CO_2} + 2(1 - \alpha)\Delta H_{CO} \quad (7)$$

where ΔH_{CO_2} is the formation enthalpy of CO_2 , ΔH_{CO} is the formation enthalpy of CO .

The oxygen reaction rate through PM layer is assumed to be

$$r_{O_2} = k_0 T_w \exp\left(-\frac{E}{RT_w}\right) s_p \frac{\rho_g(T_w)}{M_{O_2}} y \quad (8)$$

where k_0 is a pre-exponential factor, E is the apparent activation energy, R is the universal gas constant, s_p is the specific area of deposit layer, y and M_{O_2} are the mole fraction and molecular weight of oxygen.

2.2 Model setup and parameter setting

The DPF is designed for a six-cylinder marine diesel engine with a rated power of 290 kW and a rated speed of 1500 r/min. The engine exhaust mass flows at E3 operating conditions are 515 kg/h, 843 kg/h, 1205 kg/h and 1590 kg/h, respectively, and the corresponding exhaust temperatures are 588 K, 685 K, 733 K and 789 K. The basic parameters of this DPF are shown in Table 1. The calculated geometry modules include the filter body, carrier inlet and outlet, filter body inlet and outlet, carrier outer wall, and filter outer wall. The filter diameter and length are 260 mm and 300 mm, respectively. The basic structure and mesh of the DPF are shown in Figure 1. The number of mesh cells for each computational case is about 576000.

Table 1 Basic parameters of the DPF

Basic parameters	Parameter value
Filter diameter (mm)	260
Filter length (mm)	300
Wall thickness (mm)	0.254
Width of inlet channel (mm)	1.54
Width of outlet channel (mm)	1.54
Cell density (cpsi)	200
Filter density (kg/m ³)	1500
Thermal conductivity (W/m·K)	1
Oxygen mass fraction (%)	7

Figure 1 Basic structure and mesh of the DPF

The setting of boundary conditions includes the inlet, outlet, wall parameters of the filter body and carrier, the substance transport and post-processing modules. The DPF inlet uses the engine exhaust mass flow rates as the boundary condition, the outlet uses the ambient pressure as the boundary condition, and the wall temperature is set to the ambient temperature of 300 K. The density of the soot layer is 100 kg/m³, the soot migration constant is 1×10^{-15} , the permeability of the filter wall is $5 \times 10^{-13} \text{ m}^2$ and the soot filter layer permeability is $5 \times 10^{-14} \text{ m}^2$. In the soot deep filtration model, the depth filtration threshold is 3 kg/m³ and the depth filtration permeability is $9 \times 10^{-15} \text{ m}^2$. The initial soot mass per unit mass of exhaust gas is 0.0005.

In the soot regeneration mode, the O_2 -thermal mode is chosen. Soot reacts with the oxygen in the exhaust gas to convert carbon into CO and CO_2 . The regeneration reaction rate increases rapidly by increasing the DPF inlet temperature, so that the soot burns rapidly in a short time.

3. Simulation results and analysis

3.1 Effect of exhaust gas flow on particle trap process

In this subsection, the results of simulations run by varying the exhaust flows are presented. Figure 2 shows the variations of the soot concentrations and soot layer thickness with time with the initial soot loading of 0 g/L on the DPF. As can be seen from Figure 2a, the soot mass concentrations in depth layer first increase and then keep unchanged except at the small exhaust air flow (515 kg/h). Due to the limited ability of the wall surface layer to accumulate soot, it will not increase after reaching a certain level. It is also found that the soot concentrations of the depth filter at the larger flows reach the saturation value of 2.58 g/L at different times. The larger the exhaust mass flow is, the earlier the time to reach the saturation value of soot density. It is noted that the cake filtration gradually dominates and the cake soot mass concentrations increase linearly after deep filtration. Moreover, the cake soot mass concentrations increase with the increase of the exhaust flow. Thus, the total soot mass concentrations in depth and cake layers basically increase linearly with time.

Figure 2b shows the average soot thickness at different sections along the axial direction. As can be seen from Figure 2b, the soot distribution in cake layer has a larger

thickness at the front and rear portion of the filter and the position of the lowest point gradually moves to the front as the exhaust flow increases. The soot distribution of the cake layer becomes uneven with the increase of the exhaust flow rate. This is due to the fact that the unevenness of the exhaust inlet flow velocity increases as the exhaust flow rate increases. It is also found that the largest soot cake thickness of $0.07\text{ }\mu\text{m}$ occur at the rear portion of the filter at the exhaust flow of $1590\text{ m}^3/\text{h}$. Compared with the soot thicknesses of the cake layer, those of the depth layer are thinner except at the low exhaust flow of 515 kg/h .

Figure 2b shows a deposition distribution of soot in the DPF filter. It is found that soot mass concentration obviously increases with the increase of the exhaust gas flow. As can be seen from the figure, soot is mainly deposited at the filter inlet position and the rear outlet position in the initial stage, and less soot is in the radial outer side and the axial middle position of the filter. As the capture time becomes longer, soot gradually diffuses to the axially intermediate position of the filter, but the shape of the distribution is not changed. Overall, more soot is distributed in the front and rear portion of the filter and less in the middle, showing a concave-shaped distribution. In addition, in the radial direction, there is more soot distributed in the axial center position and less in the outer side, showing a convex-shaped distribution.

Figure 2 Effects of exhaust gas flow on soot trap process with an initial soot loading of 0 g/L: (a) soot concentration, (b) soot thickness, (c) spatial distributions of soot concentration

3.2 Effect of exhaust gas flow on DPF regeneration process

The DPF regeneration process at different exhaust gas flows with an initial soot loading of 10 g/L is presented in Figure 3. The regeneration mode is the active regeneration mode of oxygen combustion by heating the exhaust gas temperature to 850 K at the time of 100 s.

The peaks of the mean filter temperatures decrease with the increase of the exhaust flow, but appear early due to higher exhaust gas temperature. The peak temperature at the exhaust gas flow of 515 kg/h is about 900 K, which is higher than the heating temperature. Correspondingly, the pressure drops of the filter increase and the maximum pressure drops appear earlier when the DPF inlet mass flow rates increase. It also can be seen in Figure 3b that the DPF filter pressure drops first increase, then decrease and finally keep unchanged.

The decreases in soot concentrations also indicate that the DPF regeneration has begun, show in Figure 3c. The corresponding exhaust temperatures at large exhaust gas flows are high, which accelerates the DPF regeneration. The soot concentrations almost keep unchanged after about 220 s, which indicates the completion of the DPF regeneration, just like the filter pressure drops. There is difference between the soot cake layer thickness and the soot depth layer thickness at different exhaust gas flows. The cake layer thickness is mainly distributed in front and middle portion of the DPF and the layer thickness is mainly distributed in middle and rear portion of the DPF except at the high exhaust flow of 1590 kg/h.

Figure 4 Effects of exhaust gas flow on DPF regeneration process with an initial soot loading of 10 g/L: (a) mean filter temperature, (b) pressure drop, (c) soot concentration, (d) soot thickness

3.3 Effect of initial soot loading on DPF regeneration

Figure 4 shows the effect of initial soot loadings on the DPF regeneration at the exhaust gas flow of 1205 kg/h. For this case, the exhaust gas is heated to the temperature of 850 K when the regeneration is in progress for 100 s.

As can be seen in Fig. 4a, the mean filter temperatures have a slight increase with the increase of the initial soot loading. This reason is that more heat is released with more soot oxidation. It is easily found that the initial soot loading and exhaust gas flow have

similar effects on the pressure drops and soot concentrations. As the initial soot loading increase, the pressure drops and soot concentrations increase in the first 100 s due to soot clogging. However, the initial soot loadings have little effect on the pressure drops and soot concentrations when the DPF regeneration begins after 100 s.

There are some differences between the distributions of deep soot thickness and cake soot thickness with different initial soot loadings. In the front portion of the DPF, the deep soot thickness increases when the initial soot loading is from 2 g/L to 4 g/L, but the cake soot thickness decreases. When the initial soot loading is greater than 4 g/L, it has no effect on the cake soot thickness in the filter front. In the rear portion of the filter, the deep soot thickness with higher initial soot loadings is thicker, but the cake soot thickness is smaller. Similarly, the initial small and middle soot loadings have no effect on soot thickness at the rear portion of the filter. The above non-uniformity of soot distribution along the axial direction is attributed to the non-uniformity of DPF temperature distribution.

(a)

(b)

Figure 4 Effects of initial soot loading on DPF regeneration process at the exhaust gas flow of 1205 kg/h: (a) mean filter temperature, (b) pressure drop, (c) soot concentration, (d) soot thickness

3.4 Effect of heating mode on DPF regeneration

Figures 5-7 show the effect of heating mode on the DPF regeneration at the exhaust 1205 kg/h. Figure 5 presents the results of the DPF regeneration at different heating temperatures. The exhaust gas is heated to constant temperatures from 50 s to 100 s and then the temperatures are kept constant, as shown in Figure 6a. The maximum filter temperatures increase with the increase of the heating temperature and the highest temperatures appear earlier. When the heating temperature is 900 K, the peak filter temperature is 1022 K in 140 s.

Figure 5 Effect of heating temperature on DPF regeneration process with the initial soot loading of 10 g/L at the exhaust 1205 kg/h: (a) temperature, (b) pressure drop, (c) soot concentration, (d) soot thickness

It is easily found that the pressure drops and soot mass concentrations decrease with the increase of the heating temperature. they attenuate sharply from 100 s to 140 s especially at 850 K and 900 K. The increase in the heating temperature is also advantageous to reduce the thickness in the soot cake layer. However, it seems that the heating temperature has no obvious effect on the thickness in the soot depth layer. Overall, the heating temperature of 850 K can achieve the DPF regeneration efficiency of 94%. Therefore, it is the suitable DPF regeneration temperature.

Figure 6 shows the results of on DPF regeneration process at different heating rates. For this case, two heating methods for slow heating and rapid heating are used at the initial exhaust temperature of 733 K, as shown in Figure 6a. The highest filter temperatures for slow heating and rapid heating are 994 K and 960 K, respectively and the corresponding times are 96 s and 140 s.

It can be seen from Figures 6b-c that the moment of the soot concentrations and pressure drops decline is different due to the different time to reach the soot ignition temperature. At rapid heating mode, there is an early significant drop in soot mass concentration in 80 s. As can be seen from Figure 6d, the heating rate has no influence on the distributions of the soot thickness in the DPF front but has some influence in the DPF back. The rapid heating mode is conducive to reduce the soot thickness in the cake layer but is not helpful for the reduction of the soot thickness in the depth layer.

(a)

(b)

Figure 6 Effect of heating rate on DPF regeneration process with the initial soot loading of 10 g/L at the exhaust 1205 kg/h: (a) temperature, (b) pressure drop, (c) soot concentration, (d) soot thickness

Figure 7 shows the results of on DPF regeneration process at different heating times. In this case, two heating modes of continuous heating and short time heating are used at the initial exhaust temperature of 733 K, shown in Figure 7a. For the short time heating, the exhaust gas temperature is heated to 850 K in 100~120 s and decreases to 733 K in 120~170 s. There is no difference in the maximum filter temperatures between the two modes before 150 s, but there is large difference after 150 s. The maximum filter temperature at the short time heating has a greater attenuation than that at the continuous heating.

The duration of heating time has obvious effects on the pressure drop and soot concentration, shown in Figures 7b-d. Shorter heating time is insufficient to oxidate the soot in the cake layer and depth layer. When the heating stops, the soot concentrations increase. Correspondingly, the soot thickness in the depth and cake layers for shorter

heating time presents a lower concentration distribution than that for the continuous heating. As a result, the pressure drop for the short time heating increases due to more soot deposit.

Figure 7 Effect of heating time on DPF regeneration process with the initial soot loading of 10 g/L at the exhaust 1205 kg/h: (a) temperature, (b) pressure drop, (c) soot concentration, (d) soot thickness

4. Conclusions

The pressure drops and soot mass concentrations obviously increase with the growth of the exhaust gas flows and initial soot loadings before regeneration, but increase slightly after regeneration. The mean filter temperatures are affected by the exhaust gas flow, but

is less affected by the initial soot loading. As the initial soot loading is from 2 g/L to 4 g/L, the deep soot thickness in the front of the DPF increases, but the cake soot thickness decreases. The initial soot load over 4 g/L has no effect on the cake of the cake in front of the DPF. The proper temperature of 850 K for heating exhaust gas can achieve 94% DPF regeneration efficiency. The heating rates has little effects on pressure drops and soot mass concentrations. The heating duration of exhaust gas has an important impact on DPF regeneration.

CRedit authorship contribution statement

Xiangli Wang: Investigate, Software, Writing—Original draft preparation, Data curation.

Peiyong Ni: Methodology, Software, Formal analysis, Funding acquisition, Supervision, Writing—Review and editing.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Acknowledgments

This work was supported by the National Key Research and Development Program of China (Grant No. 2017YFE0116100).

References

Chen, K., Martirosyan, K.S., Luss, D., 2011. Temperature gradients within a soot layer during DPF regeneration. *Chem. Eng. Sci.* 66(13), 2968–2973.

Chong, H.S., Aggarwal, S.K., Lee, K.O., Yang, S.Y., 2011. Measurements of heat release of diesel PM for advanced thermal management strategies for DPF regeneration. *Combust. Sci. and Tech.* 183, 1328–1341.

Deng, Y.W., Cui, J.H., Cui, J.Q., Zhang, B., Zhao, X.H., Zhang, Z.Q., et al., 2017. Investigations on the temperature distribution of the diesel particulate filter in the thermal regeneration process and its field synergy analysis. *Appl. Therm. Eng.* 123, 92–102.

E, J.Q., Zhao, M.Y., Zuo, Q.S., Zhang, B., Zhang, Z.Q., Peng, Q.G., et al., 2020. Effects analysis on diesel soot continuous regeneration performance of a rotary microwave-assisted regeneration diesel particulate filter. *Fuel* 260, 116353.

Ebrahimnataj, M.R., Ehteram, M.A., Sahebi, M., Abdolmaleki, S., 2018. Numerical and experimental study on the gaseous emission and back pressure during regeneration of diesel particulate filters. *Transport. Res. D.* 62, 11–26.

Ko, J., Si, W., Jin, D., Myung, C.L., Park, S., 2016. Effect of active regeneration on time-resolved characteristics of gaseous emissions and size-resolved particle emissions from lightduty diesel engine. *J. Aerosol Sci.* 91, 62–77.

Koltsakis G.C., Stamatelos A.M., 1997. Modes of catalytic regeneration in diesel particulate filters. *Ind. Eng. Chem. Res.* 36, 4155–4165.

Kurien, C., Srivastava, A.K., Gandigudi, N., Anand, K., 2020. Soot deposition effects and microwave regeneration modelling of diesel particulate filtration system, *J. Energy Inst.* 93 (2), 463–473.

- Lao, C.T., Akroyd, J., Eaves, N., Smith, A., Morgan, N., Bhawe, A., Kraft, M., 2019. Modelling particle mass and particle number emissions during the active regeneration of diesel particulate filters. *P. Combust. Inst.* 37 (4), 4831–4838.
- Liu, B., Sun, P., Aggarwal, S.K., Zhao, S.B., Huang, B., 2020. An experimental-computational study of DPF soot capture and heat regeneration. *Int. J. Green Energy* 17(4), 301–308.
- Lupše, J., Campolo, M., Soldati, A., 2016. Modelling soot deposition and monolith regeneration for optimal design of automotive DPFs. *Chem. Eng. Sci.* 151, 36–50.
- Meng, Z.W., Chen, C., Li, J.S., Fang, J., Tan, J., Qin, Y., et al, 2020. Particle emission characteristics of DPF regeneration from DPF regeneration bench and diesel engine bench measurements. *Fuel* 262, 116589.
- Ni, P.Y., Wang, X.L., Li H., 2020. A review on regulations, current status, effects and reduction strategies of emissions for marine diesel engines. *Fuel* 279, 118477.
- Smith, J.D., Ruehl, C., Burnitzki, M., Sobieralski, W., Dwyer, H., 2019. Real-time particulate emissions rates from active and passive heavy-duty diesel particulate filter regeneration. *Sci. Total Environ.* 680, 32–139.
- Soltani, S., Andersson, R., Andersson, B., 2018. The effect of exhaust gas composition on the kinetics of soot oxidation and diesel particulate filter regeneration. *Fuel* 220, 453–463.
- Stepień, Z., Ziemiański, L., Żak, G., Wojtasik, M., Jeczminek, L., Burnus, Z., 2015. The evaluation of fuel borne catalyst (FBC's) for DPF regeneration. *Fuel* 161, 278–286.

Yamamoto, K., Yamauchi, K., 2013. Numerical simulation of continuously regenerating diesel particulate filter. *P. Combust. Inst.* 34, 3083–3090.

Yu, M.T., Luss, D., 2012. Inlet cone effect on particulate matter deposition and regeneration temperature in a diesel particulate filter. *Ind. Eng. Chem. Res.* 51, 3791–3800.

Yu, M.T., Luss, D., Balakotaiah, V., 2013a. Analysis of flow distribution and heat transfer in a diesel particulate filter. *Chem. Eng. J.* 226: 68–78.

Yu, M.T., Luss, D., Balakotaiah, V., 2013b. Regeneration modes and peak temperatures in a diesel particulate filter. *Chem. Eng. J.* 232, 541–554.

Zhang, B., E, J.Q., Gong, J.K., Yuan, W.H., Zuo, W., Li, Y., et al., 2016. Multidisciplinary design optimization of the diesel particulate filter in the composite regeneration process. *Appl. Energ.* 181, 14–28.

Zhang, J., Wong, V.W., Shuai, S., Chen, Y., Sappok, A., 2018. Quantitative estimation of the impact of ash accumulation on diesel particulate filter related fuel penalty for a typical modern on-road heavy-duty diesel engine. *Appl. Energy* 229, 1010–1023.

1. Ni, P.Y., Wang, X.L. & Li H. A review on regulations, current status, effects and reduction strategies of emissions for marine diesel engines. *Fuel* 279, 118477 (2020).
2. Lao, C.T. et al. Modelling particle mass and particle number emissions during the active regeneration of diesel particulate filters. *P. Combust. Inst.* 37 (4), 4831–4838 (2019).

3. Zhang, J., Wong, V.W., Shuai, S., Chen, Y. & Sappok, A. Quantitative estimation of the impact of ash accumulation on diesel particulate filter related fuel penalty for a typical modern on-road heavy-duty diesel engine. *Appl. Energy* 229, 1010–1023 (2018).
4. Smith, J.D., Ruehl, C., Burnitzki, M., Sobieralski, W. & Dwyer, H. Real-time particulate emissions rates from active and passive heavy-duty diesel particulate filter regeneration. *Sci. Total Environ.* 680, 32–139 (2019).
5. Stepień, Z. et al. The evaluation of fuel borne catalyst (FBC's) for DPF regeneration. *Fuel* 161, 278–286 (2015).
6. Soltani, S., Andersson, R. & Andersson, B. The effect of exhaust gas composition on the kinetics of soot oxidation and diesel particulate filter regeneration. *Fuel* 220, 453–463 (2018).
7. Ko, J., Si, W., Jin, D., Myung, C.L. & Park, S. Effect of active regeneration on time-resolved characteristics of gaseous emissions and size-resolved particle emissions from light duty diesel engine. *J. Aerosol Sci.* 91, 62–77 (2016).
8. E, J.Q. et al. Effects analysis on diesel soot continuous regeneration performance of a rotary microwave-assisted regeneration diesel particulate filter. *Fuel* 260, 116353 (2020).
9. Kurien, C., Srivastava, A.K., Gandigudi, N. & Anand, K. Soot deposition effects and microwave regeneration modelling of diesel particulate filtration system, *J. Energy Inst.* 93 (2), 463–473 (2020).

10. Chen, K., Martirosyan, K.S. & Luss, D. Temperature gradients within a soot layer during DPF regeneration. *Chem. Eng. Sci.* 66(13), 2968–2973 (2011).
11. Chong, H.S., Aggarwal, S.K., Lee, K.O. & Yang, S.Y. Measurements of heat release of diesel PM for advanced thermal management strategies for DPF regeneration. *Combust. Sci. and Tech.* 183, 1328–1341 (2011).
12. Yamamoto, K. & Yamauchi, K. Numerical simulation of continuously regenerating diesel particulate filter. *P. Combust. Inst.* 34, 3083–3090 (2013).
13. Yu, M.T., Luss, D. & Balakotaiah, V. Analysis of flow distribution and heat transfer in a diesel particulate filter. *Chem. Eng. J.* 226: 68–78 (2013).
14. Liu, B., Sun, P., Aggarwal, S.K., Zhao, S.B. & Huang, B. An experimental-computational study of DPF soot capture and heat regeneration. *Int. J. Green Energy* 17(4), 301–308 (2020).
15. Meng, Z.W. et al. Particle emission characteristics of DPF regeneration from DPF regeneration bench and diesel engine bench measurements. *Fuel* 262, 116589 (2020).
16. Yu, M.T. & Luss, D. Inlet cone effect on particulate matter deposition and regeneration temperature in a diesel particulate filter. *Ind. Eng. Chem. Res.* 51, 3791–3800 (2012).
17. Deng, Y.W. et al. Investigations on the temperature distribution of the diesel particulate filter in the thermal regeneration process and its field synergy analysis. *Appl. Therm. Eng.* 123, 92–102 (2017).

18. Lupše, J., Campolo, M. & Soldati, A. Modelling soot deposition and monolith regeneration for optimal design of automotive DPFs. *Chem. Eng. Sci.* 151, 36–50 (2016).
19. Zhang, B. et al. Multidisciplinary design optimization of the diesel particulate filter in the composite regeneration process. *Appl. Energ.* 181, 14–28 (2016).
20. Ebrahimnataj, M.R., Ehtheram, M.A., Sahebi, M. & Abdolmaleki, S. Numerical and experimental study on the gaseous emission and back pressure during regeneration of diesel particulate filters. *Transport. Res. D.* 62, 11–26 (2018).
21. Yu, M.T., Luss, D. & Balakotaiah, V. Regeneration modes and peak temperatures in a diesel particulate filter. *Chem. Eng. J.* 232, 541–554 (2013).
22. Koltsakis G.C. & Stamatelos A.M. Modes of catalytic regeneration in diesel particulate filters. *Ind. Eng. Chem. Res.* 36, 4155–4165 (1997).