Multimodal Optimization with the Local Optimum Ranking 2 Algorithm

Francisco Daniel Filip Duarte (✉ danielduarte1181@gmail.com)

<https://orcid.org/0000-0003-0523-161X>

Research Article

Keywords: multimodal optimization, genetic algorithm, structural optimization, local ranking

Posted Date: April 5th, 2022

DOI: <https://doi.org/10.21203/rs.3.rs-973713/v5>

License: This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Title: Multimodal Optimization with the Local Optimum Ranking 2 Algorithm

Name: Francisco Daniel Filip Duarte

Email: danielduarte1181@gmail.com

Orcid: <https://orcid.org/0000-0003-0523-161X>

Degree: Master in Applied Science in Mechanical Engineering from Concordia University, Canada (2019)

Location: Mexico

email to be displayed: danielduarte1181@gmail.com

All figures except fig 3 to be displayed in color.

All references mentioned in the Reference List are cited in the text, and vice versa.

The local optimum ranking 2 (LOR2) is a patent pending algorithm. In order to use it for commercial purposes contact danielduarte1181@gmail.com.

Highlights:

1. Innovative Local optimum ranking 2 (LOR2), a new niching algorithm.
2. Provides a local rank, given by the objective value within each local optimum.
3. Identification of local apices, to speeds up design process.
4. A multi-focus, multimodal optimization with equalized exploration effort on each local optimum.
5. Allows to discretize the domain for a thorough function exploration.

Abbreviations:

LOR2 – Local optimum ranking 2
LOR2b – Local optimum ranking 2 with dominance propagation
DE – Differential evolution
GA – Genetic algorithm
PSO – Particle swarm optimization
FS – Fitness sharing method
L2PS – Local optimum ranking 2 population sorting
PV – Polarization vertex
PME - Polarized mesh element
L2bGA-L2bPS - LOR2b genetic algorithm with LOR2b population sorting

Multimodal Optimization with the Local Optimum Ranking 2 Algorithm

F. D. Filip Duarte ¹,
danielduarte1181@gmail.com

¹Independent - www.filipduarte.com

ABSTRACT: In optimization tasks, it is interesting to achieve a set of efficient solutions instead of one single output, in the case the best solution is not suitable. Many niching methods offer a diversified response, yet some important problems are common: (1) The most interesting solutions of each local optimum are not identified. Thus, the output is the overall population of solutions, which increases the work of the designer in verifying which solution is the most interesting. (2) Existing niching algorithms tend to distribute the solutions on the most promising regions, over-populating some local optima and sub-populating others, what can lead to a poor optimization.

To solve these challenges, a novel niching method is presented, named local optimum ranking 2. This sorting methodology favors the exploration of a defined number of local optima and ranks each local population by objective value within each local optimum. Thus, is performed a multi-focus exploration, with an equalized number of solutions on each local optimum, while identifying which solutions are the local apices.

The algorithm is applied in the design optimization of a metallic cantilever beam, showcasing how it offer both efficiency and diversity for design challenges.

Keywords: multimodal optimization, genetic algorithm, structural optimization, local ranking.

1. Introduction

The design of many engineering systems is an example of application of some of the most known global optimization algorithms (GOAs). In single-objective optimization (SOO), at each iteration, the population of solutions is ranked by the single objective value, and the best solutions are selected to be part of the next generation of the optimization process, until the algorithm converges, most often to a single point in the domain. Several niching algorithms offer the alternative of providing a diversified set of distinct and competitive responses, in what is also called a multimodal optimization (MMO).

The local optimum ranking 2 (LOR2) provides a novel approach among niching algorithms, in ranking a population of solutions inside each local optimum and downgrading duplicates, allowing to identify and properly process the most competitive local optima of the design space in a multi-focus approach. By downgrading replicate solutions, it allows also have less local conglomeration, facilitating a broader exploration inside each local optimum. The LOR2 provides several metrics for the population of solutions, such as the local optimum each solution belongs to, the rank of each solution, measured by its objective value inside its local optimum and its level of redundancy, and which are the apices of each local optimum region. Thus, the LOR2 can be combined with GOAs in multiple ways. Besides substituting regular objective value sorting by the local rank sorting, cross-over operations can be applied only to solutions of the same local optimum, the local apices can substitute the global best vector in swarm methods, creating multiple local swarms, and many other combinations can be generated.

In order to exemplify its operation, a mathematical model of a spacecraft component is implemented to work in conjunction with a version of the genetic algorithm (GA) combined with LOR2.

2. Related work

Mathematical or numerical optimization has started at the same time as the advent of Newton's classic mechanics and calculus, with the use of numerical optimization algorithms based on gradient. These methods have been for centuries the core of numerical optimization with application in several fields of engineering. Since the last few decades, several heuristic optimization algorithms have been created. A subgroup of these heuristics is called GOA, which works with a population of solutions. Global optimization is presently applied in many areas of engineering, especially those where a small percentage of efficiency increase can represent the economy of large financial amounts. This is the case of artificial intelligence (AI), logistics, telecommunication, and systems in space, aerospace, automotive, and energy sectors, among others, with many publications available in the public domain.

The genetic algorithm (GA) is a very popular global optimization algorithm (GOA), which is inspired by the theory of evolution of living organisms which reproduce by mating. It states that beneficial mutations tend to accumulate along time, thus generating its evolution. Goldberg [1] describes the functionality of the GA. Kennedy [2] described the method called particle swarm optimization (PSO), which is based on the flocking movement of birds and the schooling of fishes. Other GOAs which are also popular, are differential evolution (DE) [3], simulated annealing [4], and cuckoo search algorithm [5], among many others.

In order to find multiple feasible solutions of a function, multimodal optimization (MMO) algorithms or niching methods were created, which work in conjunction with GOAs. Some well-known niching algorithms are presented:

- **Fitness sharing (FS)** – Created by Holland [6] and improved by Goldberg and Richardson [7], this algorithm mimics how living species compete for resources on nature, which favors its broader distribution on a given geographic region. In this algorithm, the fitness value is divided by a function that integrates the presence of other solutions within a niching radius.
- **Clearing method** – In this MMO algorithm, a number of the best solutions within a niching radius have their fitness preserved. Exceeding solutions have their fitness cleared.
- **Crowding with redistricted tournament selection** – Created by Harik in 1995 [8], in this method, a GOA has a population POP_P which generates POP_Q. A set of N solutions randomly chosen from POP_P is selected. A single solution of POP_Q competes with the closer solution of the set, and the best solution is kept in the next generation. This process is repeated to all solutions of POP_Q.
- **Deterministic Crowding** - In a GOA which performs crossover operations, each offspring of the generated pair competes with the closest parent. The solution with the best fitness is kept for the next generation. This method was created in 1992 by Mahfoud [9]
- **Species Conservation** – This algorithm, created by LI et al. [10] identifies solutions which have the best objective value within a niche radius, denominated seeds, and at each generation equals the position of all non-dominant solutions to its respective the seeds, while generating mutations of the seeds with the GA. Thus, multiple local optima are identified and kept in the optimization process.

De Jong introduced the concept of crowding methods [11] in 1975. Among other niching methods are derating [12], parallelization [13], and

clustering [14].

The Institute of Electrical and Electronics Engineers (IEEE) presents the world congress of computational intelligence (WCCI) [15], providing conferences on neural networks, fuzzy systems, and evolutionary computation. The congress of evolutionary computation (CEC) promotes a niching competition every year [16], where participants evaluate the efficiency of their niching algorithms by benchmarking it with a test work function suite [17].

Li et al. published in 2017 a survey on the latest progress of MMO algorithms [18], listing several of the most popular methods and some recent developments. They describe the operation of several niching methods like FS, crowding variations, DC, derating, among others. Also, they mention that other non-evolutionary algorithms, like PSO and DE, have been applied with a niching approach, and expound the challenges commonly faced in using niching algorithms while testing it on benchmark functions.

Sareni and Krahenbuhl [19] describe the operation of several niching algorithms, including FS, four types of crowding and clearing, and exemplify their application in test problems. Passaro and Starite propose a niching PSO [20], exploring several variations. Wong provides a short survey on MMO algorithms [21].

Yue et al. [22] propose a DE with crowding distance for MMO. Liang et al. [23] describe a clustering-based DE for MMO. Wu et al. [24] applied a multimodal ant colony optimization for imaging sensors. Polakova [25] et al. describes a DE which preserves diversity in optimization.

Truss structures are interesting numerical models to test the performance of optimization algorithms. While it has a simple formulation, it illustrates well the challenges faced in the optimization of structural designs and other domains, like the presence of several local optima. Deb and Surendra applied GA for the weight reduction of 2D and 3D trusses [26], by seeking optimal topology and cross section sizes. Deb also describe the optimization of design parameters of a class of welded structures, using GA and proving it has better performance than other tested methods [27]. Gomes and Beck [28] describe the use of the PSO algorithm in the optimization of a steel-frame transmission tower, with the aid of a neural network as metamodel. Wang et al. [29] describe the optimization of truss structures with nodes position displacement and cross-section variation, considering frequency constraints, describing the challenges faced in not getting trapped in a local optimum response.

Devert et al. [30] describe a study of 2D truss design, comparing the optimization efficiency of the generative and ontogenic approach. Lingyun et al. [31] apply GA to optimize the shape and size of trusses with frequency constraints. Gomes [32], Perez and Behdinan [33] also optimize a truss, applying a particle swarm algorithm. Cheng [34] applied GA in the design of steel truss arch bridges.

In the field of MMO applied to the design of structures, interestingly there are fewer examples. Lin and Chen propose a multistage algorithm for multimodal optimization of structures [35]. Islam proposes a niching evolutionary algorithm to find multiple solutions of a truss structure [36]. Huang et al. propose a niching PSO [37] for the design of composite structures. Other publications also present the MMO applied to structures [38]–[40], in dealing with the challenge of providing a diverse set of efficient designs.

There are many publications in SOO of structures, mainly related to industrial research and development in the field of automotive, civil engineering, space, and aerospace sectors. In order to evaluate the efficiency of more complex structural designs, finite element models (FEM) are one of the most popular choices for structural models. This method segments the structure in several elements, and their interaction is evaluated generating a field of deformation and stress. Cook et al. offer a reference with the fundamentals of FEM [41]. Ugural [42] also offers an introduction of analytical models of structures, and FEM formulation.

Liu and Tovar [43] generated a topology optimization study in MATLAB, to reduce weight of structures. Gauchia et al. [44] performed the torsional stiffness and weight optimization of a bus structure using GA and FEM. Park and Dang [45] applied a CAD-CAE interface integration to automate the design optimization of metallic structural components, using GA and supported with metamodel to reduce computation costs. Zheng et al. [46] designed a lunar lander using FEM, using commercial software called Abaqus and LS-Dyna. These are only a few of many examples of structural design studies applying FEM and optimization algorithms.

3. Methodology

Several niching algorithms provide options to explore both efficiency and diversity of a function. However, as mentioned, these algorithms have some important hindrances: (1) they provide as output the overall population, not identifying which solutions are the local apices, giving a large workload to designers to verify, often manually, which solution is the most suitable for the design task. Also, (2) most niching algorithms distribute the population of solutions on the locations of the domain which presented best fitness, what can overpopulate some local optima and reduce the number of solutions exploring other promising local optima. Since a local optimum can present a poor outcome in the initial phase of the exploration, yet a competitive output if properly processed, these niching algorithms can present low performance for several functions.

The LOR2 keeps in the optimization process all best-evaluated regions of interest of the design space, with an equalized number of solutions on each local optimum to properly process it. Also, it downgrades solutions considered redundant, thus a broader exploration is achieved inside each local region. In addition, it provides several metrics for the population of solutions, which allows it to be combined with GOAs in multiple ways: the rank of each solution inside each local optimum region, its redundancy level, and which solution is the local apex.

The LOR2 evaluates the solutions of a population-based GOA, in order to explore the most feasible regions of the design space. For this, the design space is normalized, where each design variable is defined between zero and one. Once each solution is evaluated by the single objective value, the population of solutions is sorted with the solution with the best objective value at first. With a normalized optimization space, is possible to calculate the distance matrix $\mathbf{D}$ between each solution of the sorted population. Assuming a normalized optimization space with H dimensions can be represented by a hypercube, the size of the greatest diagonal inside this hypercube L is given as the square root of H . To have all distances in the design space between 0 and 1, the normalized distance matrix $\mathbf{Z}$ is defined as the distance matrix $\mathbf{D}$ divided by the size of the greatest diagonal of the design space hyper-cube L .

In the LOR2 the local optimum apex is a solution with the best objective value within the local optimum, and a sub solution is a point belonging to a local optimum which is not a leader. Each local optimum leader receives a local optimum rank equal to zero, and each sub solution receives the local optimum rank equal to the number of solutions non-penalized for redundancy in the same local optimum, which have better objective value. Four operational variables are defined: d_1 which is the local optimum radius, d_2 which is the redundancy radius, the number of allowed replicates N_r , and the number of allowed local apices N_A .

If a solution does not have another solution with a better objective value within a distance smaller than d_1 , it can potentially be an apex. If the number of local apices already identified by the algorithm is lower than the maximum number of allowed apices N_A , then this solution is also considered as an apex. Since there is a limited number of allowed apices, exceeding leader candidates are defined as a sub solution of the closest apex recorded by the algorithm.

Following this, it is necessary to define the redundancy penalty of each solution. If two solutions have their distance smaller than the redundancy radius d_2 , then the solution with a worse objective value has its redundancy penalty increased by one. In order to allow intensive localized exploration, a number of allowed replicates, N_r , are allowed to each solution and are not penalized for redundancy.

Once each point has its redundancy penalty and local optimum rank evaluated, a rank vector with three variables is generated, with the following sequence: redundancy penalty, local rank, and objective value. This will prioritize non-redundant solutions in competitive regions of the design space, with the best objective values, promoting an equal number of solutions on each local optimum. With this, in the LOR2 sorting, the candidate solutions are sorted by the first rank variable, and then for identical values in the first variable, the second variable is the sorting parameter. The same rule is applied for the third rank variable, and thus the sorting process is accomplished.

The LOR2 algorithm presents some similarities to the SC algorithm, yet it differs in some important aspects: (1) the number of allowed apices,

called seeds in the SC, can be adjusted in the LOR2, allowing to adapt the search spectrum of the algorithm according to the size of the population of solutions of the GOA and the landscape of the function. (2) On each generation of the LOR2, evolved sub solutions are preserved, promoting an efficient matured diversification inside each optimum. (3) The LOR2 presents 3 metrics for each solution, differently than SC, which allows the algorithm to be combined with many GOAs in multiple ways. These 3 metrics are:

- Local optima index, which is the niche each solution belongs to.
- Local rank, which allows identifying the apices of each optimum and how competitive each solution is inside each optimum.
- Redundancy penalty, which defines how redundant each solution is inside the local optima.

Figure 1 displays a curve with five local optima in a 2D domain.

Fig. 1 – A curve denominated "5 local optima with noise"

To illustrate the advantages of the LOR2 algorithm, its operation is compared with other methods in figure 1. The genetic algorithm with hill climb (GA+HC), simulated annealing with hill climb (SA+HC), and the genetic algorithm with hill climb and local optimum ranking 2 (LOR2+GA+HC) are applied to optimize the function with 5 local optima (fig.1), where the distribution of the solutions in the domain at iterations 2, 4 and 6 are presented at figure 2. It is possible to note that the LOR2 algorithm favors a multi-focus exploration of the domain while keeping local conglomeration under adjusted levels. In contrast, the other algorithms provide an overall exploration of the domain and then focus on a single region, converging all populations of candidate solutions to one single point.

Fig. 2 - Example of the LOR2 multi-focus approach in the optimization of a function with 5 local optima. Apices are identified in red, sub solutions in blue.

The LOR2 is presented for a minimization task, at algorithms 1 and 2.

Algorithm 1: Local Optimum Ranking 2 – Phase 1 (LOR2-1)

```
1: procedure LOR2-1(Pop, iter, par)
2:   Sort the population of solutions Pop by objective value,
3:   with best objective value at first
4:   Calculate the normalized distance matrix Z of sorted Pop
5:   ApicesCount  $\leftarrow$  0
6:   ApicesList  $\leftarrow$  []
7:   Reset all LOR2 variables
8:   for i = 1 to par.PopSize do
9:     PointDefined  $\leftarrow$  0
10:    (verify if the point is close to a recorded local optimum apex)
11:    for j = ApicesList do
12:      if Z(i,j)  $\leq$  par.d1 do
13:        PointDefined  $\leftarrow$  1
14:        Pop(i).LocalOptimum  $\leftarrow$  Pop(j).LocalOptimum
15:        Pop(i).IsLocalApice  $\leftarrow$  0
16:        break for loop
17:      end if
18:    end for
19:    (if it is not close to a local optimum then it can be a local optimum apex)
20:    if PointDefined = 0 do
21:      if ApicesCount < par.MaxApicesCount do
22:        ApicesCount  $\leftarrow$  ApicesCount + 1
23:        ApicesList  $\leftarrow$  [ApicesList, i]
24:        Pop(i).LocalOptimum = ApicesCount
25:        Pop(i).IsLocalApice  $\leftarrow$  1
26:        (if local optimum apices list is full, select closer leader)
27:      else if ApicesCount  $\geq$  par.MaxApicesCount do
28:        SmallerDistance  $\leftarrow$  inf
29:        for j = ApicesList do
30:          if Z(i,j) < SmallerDistance do
31:            CloserLocalApice  $\leftarrow$  j
32:            SmallerDistance  $\leftarrow$  Z(i,j)
33:          end if
34:        end for
35:        Pop(i).LocalOptimum  $\leftarrow$  Pop(CloserLocalApice).LocalOptimum
36:        Pop(i).IsLocalApice  $\leftarrow$  0
37:      end if
38:    end if
39:  end for
```

As a variation, line 11 of Algorithm 1 can be substituted by:

for j = i-1 **do**

This will generate the local optimum ranking 2 with dominance propagation (LOR2b), where the local dominance is propagated to neighboring solutions with worse objective value, throughout the design space, thus identifying all local optima and the basins of attraction, while not considering noisy fluctuations within d_1 distance. This variation has proven to be more efficient for algorithms which perform permutation such as GA, and a worse for combination for swarm methods such as PSO.

With this, it is necessary to evaluate the redundancy penalty and the local optimum rank of each point and sort the population of solutions, as described at algorithm 2, of LOR2 phase 2:

Algorithm 2: Local Optimum Ranking 2 – Phase 2 (LOR2-2)

```
1: procedure LOR2-2(Pop, iter, par)
2:   (define redundancy Level of each solution)
3:   for i = 1 to par.PopSize do
4:     for j = 1 to i-1 do
5:       if Z(i, j) < par.d2 do
6:         Pop(j).ReplicasQty ← Pop(j).ReplicasQty + 1
7:         DeltaRedundacy ← Pop(j).ReplicasQty - par.AllowedReplicates
8:         Pop(i).RedundacyPenalty ← max(0, DeltaRedundacy)
9:         Break Loop
10:      end if
11:    end for
12:  end for
13:  RegionCount ← 0
14:  (define the Local rank for each solution)
15:  for i = 1 to par.PopSize do
16:    LocalOptimum ← Pop(i).LocalOptimum
17:    Pop(i).LocalRank ← RegionCount(LocalOptimum)
18:    if Pop(i).RedundacyPenalty = 0 do
19:      RegionCount(LocalOptimum) ← RegionCount(LocalOptimum) + 1
20:    end if
21:  end for
22:  for i = 1 to par.PopSize do (write ranks and sort)
23:    Pop(i).Rank(1) ← Pop(i).RedundacyPenalty
24:    Pop(i).Rank(2) ← Pop(i).LocalRank
25:    Pop(i).Rank(3) ← Pop(i).ObjectiveValue
26:  end for
27:  Sort Pop by rank 1 to 3 and select the best solution
```

It is important to note that the algorithm is configured for minimization tasks. For a maximization task, the sorting at line 2 of algorithm 1 should have the greater objective value at first, and the objective value at line 25 of algorithm 2 must be multiplied by -1.

The normalized distance calculation formula is based on the Euclidean distance between two points, divided by the length of the greater diagonal of the normalized design with H dimensions. Thus the Z matrix formulation is defined:

$$Z(i, j) = \frac{Dist(i, j)}{\sqrt{N}} \quad (\text{eq. 1})$$

An option to reduce computation costs is to only calculate distances as required by the algorithm and store the calculated values. In order to define efficient operational parameters for the LOR2, several ways can be applied, like meta optimization or trial and error. Another interesting option is following the general rule of design space ratio of exploration (DSRE), herein described.

It is possible to evaluate the maximum number of possible local optima in the design space and calculate which fraction of the domain is to be considered in the optimization. If we call t any positive integer close to x , where:

$$t < x < t + 1$$

We define the floor function as:

$$floor(x) = t \quad (\text{eq. 2})$$

In a given space with H dimensions, the number of possible local optima is given by the number of possible hyper-cubical subspaces which can fit in the design space, which is an approximation for the hyper-spherical sub-regions. The number of intersecting local optima that can fit in one dimension, N , is given by the normalized length divided by the radius of the hyper-sphere of the local optimum. Since in the algorithm all distances are divided by the length of the greater diagonal, the radius of the hyper-sphere is multiplied by the square root of H . Thus, we have:

$$N = floor\left(\frac{1}{d_1\sqrt{H}}\right) \quad (\text{eq. 3})$$

If we call b the approximate quantity of possible local optima in the overall design space, we have:

$$b = N^H \quad (\text{eq. 4})$$

It is possible to see that for a design space with an increased number of coordinates H , the space volume significantly increases. It is interesting that during the optimization, the exploration effort would concentrate mostly in the regions of greater interest, than in the overall domain. If we consider the volume V_{EXP} occupied by the local optimum regions delimited by d_1 , having a hyper spherical region approximated by a hyper cubical region, we have:

$$V_{EXP} = N_A(d_1\sqrt{H})^H \quad (\text{eq. 5})$$

$$d_1 = \frac{1}{\sqrt{H}} \left(\frac{V_{EXP}}{N_A} \right)^{\frac{1}{H}} \quad (\text{eq. 6})$$

Although the LOR2 operational parameters can vary, we define as default, or initial guess, the values following. It is suggested that the local exploration may be concentrated in 10% of the volume of the design space. Thus, we have:

$$d_1 = \frac{1}{\sqrt{H}} \left(\frac{0.1}{N_A} \right)^{\frac{1}{H}} \quad (\text{eq. 7})$$

While keeping $0.05 \leq d_1 \leq 0.2$. In addition, it is defined,

$$d_2 = 0.05 d_1 \quad (\text{eq. 8})$$

With this, it is possible to properly define d_1 and d_2 according to the number of optimum regions N_A and the number of coordinates of the design space. The number of solutions per local optimum N_{SL} must be enough to allow an appropriate local exploration. It is defined by the size of the population of solutions N_P in the overall design space divided by the number of local optima, which is given by the number of allowed apices N_A :

$$N_{SL} = N_P / N_A \quad (\text{eq. 9})$$

To allow an appropriate localized exploration, we maintain $N_{SL} \geq 20$. The number of allowed replicates N_R can be defined as equal to 8 for an initial guess, providing an average balance of localized and diffused exploration. Thus, the only parameter which should be defined by the user is the number of apices N_A . Yet N_A can also be automatically defined by the number of local optima of the function, given by the number of basins of attraction identified by one generation of the algorithm LOR2b, over a sufficiently populated domain, what can make the LOR2 a parameterless algorithm.

The LOR2 can be applied to sort a population of solutions favoring an equal distribution on each considered local optimum of the design space. For this, the GOA working with the LOR2 sorting must be operating with aggregated population like occurs for example in the GA. In the GA, the operators of mutation and crossover are applied to an existing population POP_P, and thus another population, POP_Q, is generated. After POP_Q has its objective values defined, the two populations are added (aggregated), generating POP_R. This population POP_R, in the original configuration of the GA, is then sorted according to the single objective value, and the best solutions are kept, generating POP_P of the following iteration.

The LOR2 can be applied by substituting the regular objective value sorting with the LOR2 sorting, favoring a local optima distribution, as illustrated in figure 3. This sorting with the LOR2 is called local optimum ranking 2 population sorting process (L2PS).

Fig. 3 – Flow chart exemplifying the application of the L2PS process in an optimization algorithm

Some algorithms do not work with aggregated populations, but rather work with ameliorated populations, which is the case of simulated annealing, for example. In this algorithm, the population POP_P of the following generation is made of some solutions of the existing POP_P population and some solutions of the POP_Q population, by following the selection process of each method. This does not allow the L2PS process to be applied, therefore, to apply a local rank sorting it is necessary to modify these algorithms to work with aggregated populations. Thus, it is generated a larger POP_R population which can then be sorted by the L2PS and generate the population POP_P of the following generation with a local optimum ranking distribution.

By allowing large or an unlimited number of local optima, the LOR2 algorithm also can be applied to generate partitions in the form of a mesh,

for a populated domain with any number of coordinates, with a Cartesian, random or clustered distribution.

Once the population of each local optima is defined by the LOR2, it is possible to calculate the position of the polarization vertex (PV) of each element, which is given by the average position of all inputs of the same local optima. With all PVs defined, each polarized mesh element (PME) is generated by the points of the data set closer to each PV, as in a Dirichlet partition, which is also called Voronoi partition [47].

One challenge arising from generating a mesh over a large data set is the computing cost related to the calculation of distances between each input. A possible alternative is segmenting the data set in regions of similitude, and then identify each local optimum. Another alternative is to define the PVs over a sparser data set and include all the inputs only for the evaluation of each PME function. A domain partitioning can be useful to segment response surfaces, to generate a response surface mesh, and to generate meshes in partitioned domains models such as FEM.

At figure 4 at the left side is noted the related local optimum subspaces of the function displayed at figure 1, and its local optimum apices identified by the LOR2. At the right side at figure 4, its respective PMEs are displayed. These subspaces are defined for a limited number of local apices. The domain is segmented in five main subspaces, related to each local optimum. The local apices at left, and PVs at right, are marked with different colors.

Fig. 4 – Local optimum partitions distribution and respective local apices at the left side. With these local optimum partitions, the PMEs and respective PVs are generated, at right side. LOR2 parameters are local optimum radius $d_1=0.1$ and number of allowed apices $N_l=5$.

At figure 5 is demonstrates the difference of operation of the LOR2 by allowing an unlimited number of local optimum apices. At figure 5 at the left side is possible to see the “fish scale” pattern of local optimum distribution. At right side, the respective PMEs are illustrated. Each local apex and each PV are marked with a point with different color.

Fig. 5 – Local optimum partitions distribution and respective local apices at the left side. PMEs and respective PVs at right side. LOR2 parameters are local optimum radius $d_1=0.05$ and number of allowed apices $N_l=\text{inf}$

4. Experiment: Structural optimization

In order to demonstrate another application of the LOR2 algorithm, a structural design optimization example is presented. Spacecrafts that are required to land without impact on a moon or a planet with gravity, need to have a set of stabilizing legs to maintain the vehicle vertically oriented and facilitate lift-off. These stabilizing legs are structures that consist of a curved cantilever beam, which are required to have low weight, in order to avoid fuel consumption, and are also required to have limited deformation under loading. Achieving a near optimum design configuration for this structure can reduce the elevated costs associated with moon exploration or interplanetary missions and is an interesting optimization problem. This

optimization problem is here used to demonstrate the capacity of the LOR2 algorithm in achieving as an optimization outcome a multiple set of efficient design configurations, providing both efficiency and diversity for SOO.

In order to derive the FEM formulation for the structure, we calculate the energy balance of the system, expressed in terms of displacement functions, according to Ugural [42]. This is given by the variation of elastic energy subtracted by the work performed by field and surface forces.

$$\Delta E = \Delta E_{elastic} - \Delta W_{field} - \Delta W_{surface} = 0 \quad (\text{eq.10})$$

If the entire structure is divided in n elements, the elastic potential energy increased on each element is given by the integration on the volume V on each element of the generated strain deformation $\Delta \epsilon$ multiplied by its corresponding tension σ . The variation of elastic potential energy for the entire system is given,

$$\Delta E_{elastic} = \sum_1^n \int_V (\sigma_x \Delta \epsilon_x + \sigma_y \Delta \epsilon_y + \sigma_z \Delta \epsilon_z) dV \quad (\text{eq.11})$$

Similarly, the amount of work performed by field forces and surface forces on the structure can be defined as:

$$\Delta W_{field} = \sum_1^n \int_V (F_x \Delta u + F_y \Delta v + F_z \Delta w) dV \quad (\text{eq.12})$$

$$\Delta W_{surface} = \sum_1^n \int_s (p_x \Delta u + p_y \Delta v + p_z \Delta w) ds \quad (\text{eq.13})$$

Thus,

$$\Delta E = \sum_1^n \int_V (\sigma_x \Delta \epsilon_x + \sigma_y \Delta \epsilon_y + \sigma_z \Delta \epsilon_z) dV - \sum_1^n \int_V (F_x \Delta u + F_y \Delta v + F_z \Delta w) dV - \sum_1^n \int_s (p_x \Delta u + p_y \Delta v + p_z \Delta w) ds = 0 \quad (\text{eq.14})$$

Using a simplified notation for each element we define:

$$\sum_1^n \int_V ((\Delta \epsilon)_e^T \{\sigma\}_e - \{\Delta f\}_e^T \{F\}_e) dV - \sum_1^n \int_s \{\Delta f\}_e^T \{p\}_e ds = 0 \quad (\text{eq.15})$$

If we call the resultant of external forces applied on the nodes on each element of the FEM model $\{Q\}_e$, and substitute σ for its expression in terms of nodal displacements, it is defined:

$$\sum_1^n \{\Delta \delta\}_e^T ([K]_e \{\delta\}_e - \{Q\}_e) = 0 \quad (\text{eq.16})$$

Considering the equilibrium equation can also be defined for one single element, we have,

$$[K]_e \{\delta\}_e - \{Q\}_e = 0 \quad (\text{eq.17})$$

For the entire system, the assembled form of the previous equation is,

$$(\Delta \delta)^T ([K] \{\delta\} - \{Q\}) = 0 \quad (\text{eq.18})$$

Since this equation must be satisfied for any arbitrary variations of nodal displacements $(\Delta \delta)^T$, it is possible to conclude that,

$$[K] \{\delta\} = \{Q\} \quad (\text{eq.19})$$

Where the global stiffness matrix $[K]$ and the total global nodal force matrix $[Q]$ can be defined as,

$$[K] = \sum_1^n [K]_e \quad (\text{eq.20})$$

$$[Q] = \sum_1^n [Q]_e \quad (\text{eq.21})$$

The stabilizing leg is a beam is composed of three sections made of an "I" profile with a hole in the center, where the design configuration of each section can vary under certain limits. A side view of the cantilever beam with the default design configuration, where all design variables are equal to 0.5, is presented in figure 6. The double line at the top and the bottom of each section of the structure are related to the position of the flange of the "I" beam, and the distance between each parallel double line represents the thickness of the flange, which can also vary. The structure parts related to the connection with the spacecraft and the foot of the stabilizing leg are not considered in the FEM analysis, therefore only the central section of the structure is modeled. The total height of the structure is about 1 meter, and it must have limited deformations over its 3 meters length.

Fig. 6 – The 2D profile of the beam with default configuration (units in m)

In order to calculate the deformations and tensions of the beam, a 2D FEM model with triangular element mesh was generated in MATLAB, as seen in figure 7. The optimization algorithm, the mesh generation code, and the FEM processing core were independently coded in MATLAB, thus no MATLAB built-in applications we applied to any of these design steps. The material coefficients used for the model are from the aluminum alloy 2024-T4 [48].

Fig. 7 – The 2D FEM mesh of the beam with default configuration (units in m)

As boundary conditions, the beam is fixed on left side, and a vertical load is placed on the right side of the structure. Under these conditions, the structure must have all nodal displacements limited to a maximum allowed value of 0.05 m. Along all the structure it is necessary to maintain maximum Von Misses principal tension σ_1 lower than the maximum tension allowed, 300 MPa.

For this optimization task, the LOR2b genetic algorithm with LOR2b population sorting (L2bGA-L2bPS), a combination of GA with LOR2b, is selected, where the crossover operation occurs only within the same local optima identified by dominance propagation. The goal of the optimization is to generate a diverse set of very efficient design configurations which minimizes the overall structural weight, while maintaining deformations and maximum tensions under defined values. At figure 1 and 2, previously presented, it is seen how the LOR2 algorithm can explore in parallel multiple local optima of a given function. Thus, similarly, the LOR2 algorithm is in this experiment applied for structural optimization, to generate a set of multiple local optima design configurations for the beam, providing both efficiency and diversity for a SOO.

The number of generations of the optimization is set to 800. Part of the operational parameters of the algorithms are presented in table 6, and additional details are provided in Appendix A. Using a computer with quad-core processor AMD A8-7410 APU with 2.2GHz, this optimization task took approximately two days to be completed. Since the algorithm is multi-focus, the intensive localized exploration one each local region is reduced when compared to a regular SMO task, thus it requires more computation time.

Number of generations	:	800
Population size.....	:	200
Maximum number of apices.....	:	4
Local optimum region radius (d1).....	:	0.100
Redundancy radius (d2).....	:	0.050
Allowed replicates per point.....	:	2

Table 6– Operational parameters for experiment II

In order to increase the diversity of sub solutions, the LOR2 parameters are not defined according DSRE, but by experimental trial and error. With a population size of 200 solutions, 4 allowed apices and 2 allowed replicates, and a larger d_2 , it is reduced the number of solutions near the apices of each local optimum. This generates less conglomeration and an increased probability of exploring multiple regions inside each local optimum,

with greater diversification of solutions. The downside is that it reduces the intensive localized exploration near each apex, thus requiring more iterations for the optimization to converge.

Fig. 8 – Convergence curve

Figure 8 displays the convergence curve of the 4 apices along the 800 generations. It is possible to see that the primary apex in light blue has a good convergence without fluctuation, while apices 2, 3, and 4 present some fluctuation along the generations. This is because when an apex optimizes, it dislocates its position inside the design space, and when it comes closer to an existing apex with lower objective value, this lower leader becomes a sub solution of the leader with better objective value. Thus, some apices can be suppressed along the optimization, and other further solutions with lower objective value are considered other local apices. Since some apices can be suppressed and not have other solutions to replace them, it is interesting to record the last population of solutions along the generations which presented all the allowed apices, to assure the desired diversity and efficiency output for the optimization task.

Fig. 9 – Optimized design polygons - Apices 1 to 4 (in blue) and sub solutions (in gray)

Figure 9 displays the design polygons of the achieved design configurations. The apices of the 4 local regions achieved represent 4 main design configurations, which are presented in blue, while the sub solutions of each 4 local optima are presented in gray. The best design solution achieved is leader 1 with 48.92 kg as objective value. Very close to this value are leader 2, 3, and 4 with 51.05 kg, 51.66 kg, and 52.76 kg respectively. The outline of the achieved design configurations in this optimization study are displayed in figure 10.

Fig. 10 – Optimized design configurations (m) - Apices 1 to 4 (in blue) and sub solutions (in gray)

These solutions displayed in blue are the best local optima configurations, the apices of each local optima, which are the 4 most competitive solutions in terms of weight efficiency while having significant distance between each other in the design space. This distance between each leader is of at least d_1 in the normalized design space, which translates into different design configurations for the structure. This illustrates that a single optimization study using a GOA combined with LOR2 algorithm, with a combination that has segregated populations, can generate distinct local apices designs with competitive performance, and several sub solutions. This multi-focus approach provides diversified solutions and reduces the probability of the optimization process getting trapped in a poor local optimum, as can happen in the single modal optimization.

Figure 11 displays the field distribution of principal stress σ_1 measured in Pascals (Pa). It is possible to see that all maximum stresses are less than 300 MPa, as a design requirement. As expected, the greater concentration of stress occurs near thin regions of the structure.

Fig. 11 – Optimized design configurations (m), principal stresses σ_1 (Pa) - Apices 1 to 4

Figure 12 displays the field distribution of total displacement under loading in meters. It is possible to note that the maximum displacements for all design configurations are less than 0.05 m, as the second design requirement.

Fig. 12 – Optimized design configurations (m) – Displacement field (m) - Apices 1 to 4

The optimization of a cantilever beam under loading is performed with the L2GA-L2PS algorithm, a combination of the GA and LOR2, having a GA with segregated population - which means the cross-over process occurs only between solutions of the same local optimum region. As expected, the optimization task provided 4 different efficient designs as output, due to its multi-focus approach. With this multi-focus approach, it is generated a set of efficient configurations, which provides options for the design process, and a lower probability of having the optimization process getting trapped in poor local optima. The graphical analysis of structure profiles demonstrates the designs indeed differ, having several sub solutions, and the plots of σ_1 stresses and nodal displacements confirming the designs are under the specified requirements.

This optimization experiment showcases the advantages of the multi-focus approach of the LOR2 algorithm when compared to single-focus methods. As the results demonstrate, it is expected that the LOR2 algorithm can provide important contributions to several design challenges of SOO.

5. Concluding Remarks

GOAs presented a great advantage when compared with gradient-based optimization since these methods allow a better exploration of the overall design space. However, most GOAs converge to a single point in the design space, what can bring large variance values for the output, since many functions present several local optima. Thus, many niching methods were created to achieve a diversified set of solutions and identify the diverse local optima. The LOR2 presents important advantages before existing niching methods, like the identification of the most suitable and interesting solutions among all the population, and an equalized exploration effort on each local optimum region. Also, it has a great versatility in giving many ways to be combined with GOAs, since it provides several metrics of the population of solutions.

It is also important to note that the experiments here described considered only the application of the LOR2 with the parallel exploration of selected local optima. Yet for many functions is possible to use the LOR2 to discretize the domain by listing and locating each local optimum that presented the most competitive responses. This can facilitate the methodical thorough exploration of the function and provide results with increased efficiency than those presented in this study.

The LOR2 demonstrated its capacity of achieving distinct and efficient design configuration in the multimodal design optimization of a metallic cantilever beam. Since the four main solutions are identified, it signifies an important advancement in MMO, by avoiding the need to verify manually a large number of possible solutions as the optimization output while reducing the chances of a poor convergence by exploring multiple optima in parallel.

Given the versatility and efficiency of the LOR2, it is expected that the LOR2 will benefit several advanced design tasks and optimization challenges in general, especially for functions with large domains that present multiple global optima.

References

- [1] D. Goldberg, "Genetic Algorithms in Search, Optimization and Machine Learning," *Addison-Wesley Professional*, 1989.
- [2] J. Kennedy and R. Eberhart, "Particle Swarm Optimization," *Proceedings of the IEEE International Conference on Neural Networks*, pp. 1942–1948, 1995.
- [3] R. Storn and K. Price, "Differential Evolution – A Simple and Efficient Heuristic for global Optimization over Continuous Spaces," *Journal of Global Optimization*, vol. 11, no. 4, pp. 341–359, 1997, doi: 10.1023/A:1008202821328.
- [4] T. H. A. Scollen, "Simulated Annealing, Introduction, Application and Theory," *Nove Science Publishers, Inc. New York*, 2018.
- [5] A. H. Gandomi, X.-S. Yang, and A. H. Alavi, "Cuckoo search algorithm: a metaheuristic approach to solve structural optimization problems," *Engineering with Computers*, vol. 29, no. 1, pp. 17–35, 2013, doi: 10.1007/s00366-011-0241-y.
- [6] J. H. Holland, *Adaptation in Natural and Artificial Systems*. Ann Arbor, MI: Univ. of Michigan Press, 1975.
- [7] D. E. Goldberg and J. Richardson, "Genetic algorithms with sharing for multimodal function optimization," *Proc. of the Second International Conference on Genetic Algorithms*, pp. 41–49, 1987.
- [8] G. R. Harik, "Finding multimodal solutions using restricted tournament selection," *Proc. of the Sixth International Conference on Genetic Algorithms*, 1995.

- [9] S. W. Mahfoud, "Crowding and preselection revisited," *Parallel problem solving from nature 2*, 1992.
- [10] J.-P. Li, M. E. Balazs, and P. J. Clarkson, "A Species Conserving Genetic Algorithm for Multimodal Function Optimization." [Online]. Available: <http://direct.mit.edu/evco/article-pdf/10/3/207/1493290/106365602760234081.pdf>
- [11] K. A. De Jong, "An Analysis of the Behavior of a Class of Genetic Adaptive Systems.," University of Michigan, USA, 1975.
- [12] D. Beasley, D. R. Bull, and R. R. Martin, "A sequential niche technique for multimodal function optimization," *Evolutionary Computation*, 1993.
- [13] M. Bessaou, A. Petrowski, and P. Siarry, "Island Model Cooperating with Speciation for Multimodal Optimization," *Springer Berlin Heidelberg*, 2000.
- [14] X. Yin and N. Gernay, "A fast genetic algorithm with sharing scheme using cluster analysis methods in multi-modal function optimization," *International Conference on Artificial Neural Networks and Genetic Algorithms*, pp. 450–457, 1993.
- [15] "World Congress of Computational Intelligence," 2020. <https://wcci2020.org>
- [16] "Congress of Evolutionary Computation - Niching Competition," 2020. <http://epitropakis.co.uk/cec20-niching/competition>
- [17] Xiaodong Li, A. Engelbrecht, and M. G. Epitropakis, "Benchmark Functions for CEC'2013 Special Session and Competition on Niching Methods for Multimodal Function Optimization," pp. 1–7, 2013.
- [18] X. Li, M. G. Epitropakis, K. Deb, and A. Engelbrecht, "Seeking Multiple Solutions: An Updated Survey on Niching Methods and Their Applications," *IEEE Transactions on Evolutionary Computation*, vol. 21, no. 4, pp. 518–538, 2017, doi: 10.1109/TEVC.2016.2638437.
- [19] B. Sareni and L. Krahenbuhl, "Fitness sharing and niching methods revisited," *IEEE Transactions on Evolutionary Computation*, vol. 2, no. 3, pp. 97–106, 1998, doi: 10.1109/4235.735432.
- [20] A. Passaro and A. Starita, "Niching in Particle Swarm Optimization," *Department of Computer Science*, vol. Doctor of, no. June, p. 133, 2007.
- [21] K.-C. Wong, "Evolutionary Multimodal Optimization: A Short Survey," *ArXiv*, vol. abs/1508.0, 2015.
- [22] C. Yue *et al.*, "Differential evolution using improved crowding distance for multimodal multiobjective optimization," *Swarm and Evolutionary Computation*, vol. 62, p. 100849, 2021, doi: <https://doi.org/10.1016/j.swevo.2021.100849>.
- [23] J. Liang *et al.*, "A clustering-based differential evolution algorithm for solving multimodal multi-objective optimization problems," *Swarm and Evolutionary Computation*, vol. 60, p. 100788, 2021, doi: <https://doi.org/10.1016/j.swevo.2020.100788>.
- [24] Y. Wu, W. Ma, Q. Miao, and S. Wang, "Multimodal continuous ant colony optimization for multisensor remote sensing image registration with local search," *Swarm and Evolutionary Computation*, vol. 47, pp. 89–95, 2019, doi: <https://doi.org/10.1016/j.swevo.2017.07.004>.
- [25] R. Poláková, J. Tvrdík, and P. Bujok, "Differential evolution with adaptive mechanism of population size according to current population diversity," *Swarm and Evolutionary Computation*, vol. 50, p. 100519, 2019, doi: <https://doi.org/10.1016/j.swevo.2019.03.014>.
- [26] K. Deb and S. Gulati, "Design of truss-structures for minimum weight using genetic algorithms," *Finite Elements in Analysis and Design*, vol. 37, no. 5, pp. 447–465, 2001, doi: [https://doi.org/10.1016/S0168-874X\(00\)00057-3](https://doi.org/10.1016/S0168-874X(00)00057-3).
- [27] K. Deb, "Optimal Design of a Class of Welded Structures via Genetic Algorithms," in *31st Structures, Structural Dynamics and Materials Conference*, 1990. doi: 10.2514/6.1990-1179.
- [28] W. J. de S. Gomes and A. T. Beck, "Global structural optimization considering expected consequences of failure and using ANN surrogates," *Computers & Structures*, vol. 126, pp. 56–68, 2013, doi: <https://doi.org/10.1016/j.compstruc.2012.10.013>.
- [29] D. Wang, W. H. Zhang, and J. S. Jiang, "Truss Optimization on Shape and Sizing with Frequency Constraints," *AIAA Journal*, vol. 42, no. 3, pp. 622–630, 2004, doi: 10.2514/1.1711.
- [30] A. Devert, T. Weise, and K. Tang, "A Study on Scalable Representations for Evolutionary Optimization of Ground Structures," *Evolutionary Computation*, vol. 20, no. 3, pp. 453–472, Sep. 2012, doi: 10.1162/EVCO_a_00054.
- [31] W. Lingyun, Z. Mei, W. Guangming, and M. Guang, "Truss optimization on shape and sizing with frequency constraints based on genetic algorithm," *Computational Mechanics*, vol. 35, no. 5, pp. 361–368, 2005, doi: 10.1007/s00466-004-0623-8.
- [32] H. M. Gomes, "Truss optimization with dynamic constraints using a particle swarm algorithm," *Expert Systems with Applications*, vol. 38, no. 1, pp. 957–968, 2011, doi: <https://doi.org/10.1016/j.eswa.2010.07.086>.
- [33] R. E. Perez and K. Behdinan, "Particle swarm approach for structural design optimization," *Computers & Structures*, vol. 85, no. 19, pp.

1579–1588, 2007, doi: <https://doi.org/10.1016/j.compstruc.2006.10.013>.

- [34] J. Cheng, “Optimum design of steel truss arch bridges using a hybrid genetic algorithm,” *Journal of Constructional Steel Research*, vol. 66, no. 8, pp. 1011–1017, 2010, doi: <https://doi.org/10.1016/j.jcsr.2010.03.007>.
- [35] C.-Y. Lin and W.-T. Chen, “Stochastic multistage algorithms for multimodal structural optimization,” *Computers & Structures*, vol. 74, no. 2, pp. 233–241, 2000, doi: [https://doi.org/10.1016/S0045-7949\(99\)00016-4](https://doi.org/10.1016/S0045-7949(99)00016-4).
- [36] Md. J. Islam, X. Li, and K. Deb, “Multimodal Truss Structure Design Using Bilevel and Niching Based Evolutionary Algorithms,” in *Proceedings of the Genetic and Evolutionary Computation Conference*, 2017, pp. 274–281. doi: 10.1145/3071178.3071251.
- [37] L. Huang, C.-T. Ng, A. H. Sheikh, and M. C. Griffith, “Niching particle swarm optimization techniques for multimodal buckling maximization of composite laminates,” *Applied Soft Computing*, vol. 57, pp. 495–503, 2017, doi: <https://doi.org/10.1016/j.asoc.2017.04.006>.
- [38] K. Martini, “Harmony Search Method for Multimodal Size, Shape, and Topology Optimization of Structural Frameworks,” *Journal of Structural Engineering-asce*, 2011.
- [39] J. A. Czyz and S. A. Lukasiewicz, “Multimodal optimization of structures with frequency constraints”, doi: <https://doi.org/10.2514/3.12573>.
- [40] C.-Y. Lin and I.-M. Huang, “A topographical approach for multimodal structural optimal designs,” *Transactions on the Built Environment*, vol. 28, 1997.
- [41] R. D. Cook, D. S. Malkus, and M. E. Plesha, *Concepts and Applications of Finite Element Analysis*, Third Edit. New York: John Wiley & Sons, 1988.
- [42] A. C. Ugural and S. K. Fenster, *Advanced Mechanics of Materials and Applied Elasticity*, Fifth edit. Prentice Hall, 2012.
- [43] K. Liu and A. Tovar, “An efficient 3D topology optimization code written in Matlab,” *Structural and Multidisciplinary Optimization*, vol. 50, no. 6, pp. 1175–1196, 2014, doi: 10.1007/s00158-014-1107-x.
- [44] A. Gauchia, V. Diaz, M. J. L. Boada, and B. L. Boada, “Torsional stiffness and weight optimization of a real bus structure,” *International Journal of Automotive Technology*, vol. 11, no. 1, pp. 41–47, 2010, doi: 10.1007/s12239-010-0006-4.
- [45] H.-S. Park and X.-P. Dang, “Structural optimization based on CAD–CAE integration and metamodeling techniques,” *Computer-Aided Design*, vol. 42, no. 10, pp. 889–902, 2010, doi: <https://doi.org/10.1016/j.cad.2010.06.003>.
- [46] G. Zheng, H. Nie, J. Chen, C. Chen, and H. P. Lee, “Dynamic analysis of lunar lander during soft landing using explicit finite element method,” *Acta Astronautica*, vol. 148, pp. 69–81, 2018, doi: <https://doi.org/10.1016/j.actaastro.2018.04.014>.
- [47] A. Jara, “Theory and computations for the Dirichlet process and related models: An overview,” *International Journal of Approximate Reasoning*, vol. 81, pp. 128–146, 2017, doi: <https://doi.org/10.1016/j.ijar.2016.11.008>.
- [48] “ASM Aerospace Specifications Metals Inc. - Aluminum Alloy 2024-T4,” 2000. <http://asm.matweb.com/search/SpecificMaterial.asp?bassnum=MA2024T4>

Appendix A – Operational parameters of GOAs

The GA algorithm have the following parameters for its operation.

GA Parameters	value	comment
Ratio of mutated pop	0.5	between 0 and 1
Mutation probability	0.02	between 0 and 1
Max mutation range	0.25	between 0 and 1

Table A1– GA parameters

The GA operates with the random pair selection. In the L2bGA-L2bPS variations, the pair selection is still random, yet it occurs only inside the same local optimum. Experiments have demonstrated that generating individuals either mutated or recombined provide increased efficiency than generating individual solutions both mutated and recombined. In this study, the selected ratio of the mutated population size from the overall generated population is 0.5, as described in table A1.