Development of Sustainable Phycoremediation with the help of *Chlorella Pyrenoidosa* for Textile Wastewater Analysis using Response Surface Methodology

Shubhangi Mishra

IIT BHU

Pradeep Srivastava (✉ pkshivastava.bce@itbhu.ac.in)

IIT BHU: Indian Institute of Technology BHU Varanasi

Virendra Singh

IIT BHU

Monika Sharma

Banasthali Vidyapith

Research

Keywords: Bioremediation, Textile wastewater management, Microalgae, River Ganga, Environmental protection, Eco-friendly, Restoration of aesthetic property

Posted Date: November 4th, 2020

DOI: <https://doi.org/10.21203/rs.3.rs-98881/v1>

License: © ⓘ This work is licensed under a Creative Commons Attribution 4.0 International License. [Read Full License](#)

Abstract

The uncontrolled utilization for the textile products is increasing year by year resulting with the elevating wastewater generated from the textile industries, which makes it among the prevalent sources of critical environmental deterioration issue globally. Products obtained from the dyes used are the primary toxic product for aquatic life, they cause aesthetic pollution, eutrophication, perturbation and increase in BOD and COD in aquatic life. Three types of textile wastewaters (Acid Yellow dye, Acid orange dye and Basic pink dye) has been used for wastewater treatment and microalgal (*Chlorella pyrenoidosa*) biomass production. Nitrogen content in textile wastewaters is very less, hence urea is used as nitrogen source in wastewater. Optimal growth condition (Urea-0.4g/L, wastewater- 40%(v/v)) is developed through Response surface methodology (RSM). The biomass productivity for chlorella sp. is 1.2-1.5 g/L/day in textile wastewaters. The reduction efficiency of COD, Nitrate-N Ammonia-N, Phosphate-P, and Dye(color) removal for Chlorella is 90-95%, 75-85%, 90-98%, 65-74% and 40-65%.After harvesting the Biomass by flocculation method it can be further used for biofuel production by in-situ transesterification.

1. Introduction

An important natural resource for any living being on this earth is water, essentially required to be safe to be consumed but unfortunately is getting polluted by various sources, on a fast pace. The point sources as well as dispersed sources are responsible for originating water pollutants. Keeping a check on point source are practically easier as they can be treated on single flow localized site where pollutant can be controlled treatment processes before discharge into the environment. However dispersed source does not favor such control, resulting in water pollution on a large scale. Ensuring plans for significant development standards and proper land use. The algal cells might be producing numerous reactive oxygen species, inducing peroxidation in cells, where chloroplast damage would inhibit chlorophyll synthesis therefore, hampering the process of photosynthesis however being easily grown algae can be remarkably significant in bioremediation[1]. Significance of treatment of wastewater should be marked as a water use as it is interconnected with the other uses of water. With respect to nutrient and water requirement, mass cultivation is the most crucial step. Wastewater from industries like textile is source for water which is easily available, cheap and additionally encompasses obligatory nutrients (nitrates, phosphate, micronutrients etc.) and potential source of carbon for development of algae[2].

There are a number of textile industries which are dumping their wastewater untreated into the environment which are not only toxic but also changing the BOD COD levels and hence the entire physiochemical parametric texture. Many types of chemical dye used in textile industries are very harmful to the aquatic life and fish species. Dyes can be toxic enough to cause skin issues like irritation, allergies, dermatitis resulting in carcinogenic effects[3]. The textile wastewater holds a typical characteristic of strong order high chemical oxygen demand (COD) high salinity variable PH and elevated temperature [4]. Coloured dyes in the wastewater adversely affect aesthetics, gas solubility, transparency of water and can equally prove to be hazardous to both aquatic flora and fauna resulting with critical environmental issues. Also, to be included that most synthetic azodyes and their metabolites are mutagenic and carcinogenic potent enough to be toxic to human health to be toxic to human health. The process of treatment of the textile effluents includes mainly physical and chemical ways, but they cost expensive. It becomes difficult to treat the dye wastewater by physical and chemical due to their complicated molecular structures. Not only this has the disposal of thickened sludge generated a bigger problem using biological methods for textile wastewater remediation is gaining interest now. Majority of the studies are focusing on the application of bacteria, algae and fungi to check coloured wastewater from the textile [5]. The research areas using microalgae in phytoremediation of coloured textile wastewater is gaining attention because of their significant role and fixation of carbon dioxide, in addition it can be sustainably and economically used for production of biofuel[6]. In this research an attempt is to use a microalgae named *Chlorella pyrenoidosa* for treatment of wastewater using a complete in-situ eco-friendly operation on a low cost self - designed tubular photobioreactor. Although, many studies have been done earlier by different researchers earlier, an innovative approach of cost

effectiveness to pilot technology is referred, yet an attempt is made for people, so that it becomes accessible and affordable not only for the large scale industrialists on a large scale and the small scale textile manufacturers, to check before discharging the untreated wastewater which is extremely toxic not only for the environment but also for the Ganga inhabitants and people using the gangawater by any means.

The study deals with designing and evaluating a sustainable approach for bioremediation using *Chlorella pyrenoidosa* and analysis of pollutant removal from textile wastewater, making the technology accessible on a larger scale.

2. Materials And Methods

2.1. Culture Preparation

The microalgae strain *Chlorella pyrenoidosa* (NCIM Accession number 2738), was collected from National Chemical Laboratory, Council of Scientific Research, Pune, India. 10% (v/v) of inoculums of exponentially growing algae culture is used for the biomass growth and optimization. Along with the parametric studies which are designed for the characterization and defining optimal operating requirements for *Chlorella pyrenoidosa* as mass culture [7], also monometric studies were implemented to study if the pollutants could significantly reduce the O₂-CO₂ efficiency for gas-exchange of the *Chlorella*.

A reformed Trypticase-glucose-yeast extract (TGYE) medium comprising 5.0 g of Tryptone-phytone,, yeast extract 1 gram, glucose (2.5) and 15 grams of agar per liter of distilled water were used as the plating medium. Followed by which the samples were withdrawn from the photosynthetic gas-exchange unit when the steady state of growth were observed by the algal culture. All plates were counted after 24 hr of incubation at 39 C.

2.2. Sample Collection (textile wastewater) and characterization

The effluents as wastewater were taken from textile industries and their outlets into the river Ganga in Varanasi using the Grab Sampling method. Textile wastewater contains many dyes which affects the aquatic system. Three types textile dyes are collected named as Acid yellow 17 dye, Acid orange 7 dye and Basic pink dye containing textile wastewater. The Characterization of physical and chemical parameters and biological parameters like Titerimetric method for COD, Winkler method for BOD, Nessler's method for Nitrogen estimation of each batch sample collected was determined using standard protocols (APHA).

2.3. Experimental Studies

Three textile azo dyes were used in the research investigation, named as Acid yellow, Acid orange, Basic pink. To determine the wavelength giving a maximum absorption, the absorbance of these three dyes were examined from 300 to 700 nanometers using a spectrophotometer (Shimadzu UV/Vis 160). Acid yellow (AY) is an acidic dye with absorption maximum at 650 nm while acid orange (AO) is another acidic dye with maximum absorption at 670 nm whereas basic pink (BP) is a basic dye with absorption maximum at 580 nm.

2.4. Physiochemical Parameters

Titrimetric method is used for COD studies. Before performing the COD test, preparation of number of standards using potassium hydrogen phthalate is done.

Already prepared different range of vials are chosen for testing the Chemical oxygen demand. However if the expected results are not indicated more ranged vials can be used. Given the known standard limits one vial, blank and others marked with known levels of standards. Among those as the wastewater sampling vials were compared. Note: Around 10% of samples are at least duplicated in case of multiple samples of wastewater are being simultaneously run. Winkler

method for BOD and DO studies, the method involves absolutely filled to the top, bottle of sample avoiding any air sac to avoid errors in the test. A set of reagents forming an acid compound is titrated for fixing the DO. A change in colour of solution is indicated when exposure of drops of reagent neutralizes the acid as titration. A level of oxygen dissolved in the sample is achieved at the end point noticed by change in colour. Nessler method is used for Nitrogen estimation studies, where the ammonia present in the sample (under strongly alkaline conditions) reacts with the nessler reagent (K_2HgI_4) producing species of yellow color. The ammonia concentration is in direct proportion to the intensity of the color.

2.5 Microalgae strain and growth optimization

Shake flask study has been performed in inoculum in wastewater sample, samples were taken daily in 2 ml volumes from each shaker flask and analyzed for soluble N for 10 to 20 days and was used to determine the algal growth rate (k).

(Fig. 1) Methodology of Bioremediation of textile wastewater using designed Bubble column tubular Photo-bioreactor.

Experimental Setup – A Photobioreactor (made of perspex) of volume of 10.5 L, which was in continuous illumination by tubular fluorescent lamps (40W PHILIPS tube lights). The light intensity kept 5400lux at the surface of culturing vessels so that the growth of microalgae can be maximum. The culture medium of textile effluent is diluted and divided in to runs according to the factorial design to calculate the optimum growth condition. The microalgal cells were inoculated with a concentration of 20% (V of inoculation/ V of solvent) in a 10.8 L reactor incubated at room temperature with a 16/8-hour dark/light period for 8 days and optical density was recorded per day.

2.6 Cell Mass Extraction

After the treatment of wastewater in the PBR biomass is harvested with the flocculation technique. The characterization of chemical, physical and biological parameter of every batch sample collected was analyzed performing the standard protocols (APHA). The major nitrogen and carbon elimination processing in the algal photobioreactor were assimilation into biomass (algal) and stripping ahead.

As soon as growth in algae was observed and it started multiplying, both phosphorus and nitrogen substance in wastewater started dropping significantly. During the first week of growth, a major portion of the nitrogen and phosphorus was reduced reporting a rapid removal rate. However, the removal rate slowed down followed by the initial period. By the closing stages of this study, around 80% of total inorganic nitrogen and phosphorus removal was observed. On a broader spectrum, compared to the smaller inoculum size, more phosphorus and nitrogen removal was analyzed for higher inoculum size. The findings suggest that decrease the amount of phosphorus and nitrogen was reported where *Chlorella* cultivation can be one of the viable approaches checking the eutrophication problem. Furthermore to be mentioned, that higher inoculum sized algal ponds might be favourable to be installed as a secondary process comparative to a tertiary treatment.

3. Results And Discussion

3.1 Textile wastewater characterization

The Physico-chemical characterization of textile wastewaters was done by the standard protocol given in APHA manual. Sample was collected with method of discrete sampling at different location from Textile industry in or near Varanasi, India. The result of textile wastewater characterization conferred in Table 1 indicates that values of pH, colour, temperature, total dissolved solid (TDS), total suspended solid (TSS), alkalinity (Carbonate), total nitrogen (ammonia), total nitrogen (Nitrate), total Phosphorus, Biological oxygen demand (BOD), Dissolved oxygen (DO) and Chemical oxygen

demand (COD). BOD content is high (67.2 mg/L) in the case of acid orange textile wastewater and in all the textile dyes the nitrogen content (ammonia + nitrate) is low. Table 3 shows that the values of pH, TSS, TDS, Nitrogen (ammonia) and Phosphorus (phosphate) found for acid yellow wastewater used in this study were 8.1, 63 mg/L, 120 mg/L, 0.32 mg/L and 1.4 mg/L. However, COD and BOD are 296 mg/L and 28.8 mg/L respectively. The values of pH, TSS, TDS, Nitrogen (ammonia) and Phosphorus (phosphate) obtained for acid yellow wastewater used in this study were 8.2, 74 mg/L, 132 mg/L, 0.18 mg/L and 3.8 mg/L. However, COD and BOD are 288 mg/L and 33.6 mg/L respectively. The values of pH, TSS, TDS, Nitrogen (ammonia) and Phosphorus (phosphate) obtained for acid orange wastewater used in this study were 8.1, 43 mg/L, 135 mg/L, 0.38 mg/L and 2.3 mg/L. However, COD and BOD are 272 mg/L and 67.2 mg/L respectively.

3.2. Microalgae growth optimization and Kinetics Study

The microalgae culture was inoculated in the shake flask (250 ml) under light control for 10 days and allowed for the growth in Batch Mode operation, after that the growth and Biomass content is calculated. The graph of 2(a) shows the growth kinetics curve for the *Chlorella pyrenoidosa*, the results obtained by cultivating the *Chlorella pyrenoidosa* in the Bolds basal media (BBM). Lag phase occurred for 3 days and log phase occurred for 7 days for the *Chlorella pyrenoidosa*. The growth constant (μ) is 0.21 g/L/day and maximum growth rate constant (μ_{max}) is 0.29 g/L/day.

Growth curve (Fig. 2(b)) of *Chlorella pyrenoidosa* in Acid yellow 17 dye, Acid orange 7 dye and Basic pink dye textile wastewater in composition of 10% of wastewater and BBM 90%, the biomass productivity is 0.98 ± 0.3 g/L/day, 0.96 ± 0.2 g/L/day, 1.2 ± 0.3 g/L/day respectively. As the nitrogen content in textile wastewaters is very low and for the microalgae growth nitrogen content is very important, hence different types of nitrogen source are used like sodium Nitrate (NaNO_3), ammonium nitrate (NH_4NO_3), ammonium chloride (NH_4Cl) and urea (NH_2CONH_2) in the concentration 0.2 g/Ltr, 0.4 g/Ltr, 0.4 g/L and 0.2 g/Ltr respectively. The biomass productivity is 0.75 ± 0.2 g/L/day in all the sources showed in Fig. 2(c). Hence nitrogen content is enriched by urea. Urea is a low cost source having the high biomass productivity. The physicochemical characteristics of textile wastewater are highly fluctuating but they are comparable and within range as reported [8]. However, the components of textile wastewaters vary as per the raw materials and ingredients used in textile manufacturing. Nitrogen (Ammonia) and Nitrogen (Nitrate) in textile wastewaters are generally low, hence an external nitrogen source is required. Low Nitrogen content has an added advantage as it enhances the lipid productivity in the Microalga biomass but low nitrogen content also affects the growth of microalgae. The urea is the best nitrogen source for the textile wastewater as it is cheap and easily available. The maximum biomass density 0.79 g/L/day was found in the case of Ammonium nitrate (NH_4NO_3). Similarly, the carbon source is also optimized using different carbon sources like Sodium carbonate (Na_2CO_3), Sodium bi-carbonate (NaHCO_3), and Potassium Bi-carbonate (KHCO_3), the biomass productivity is 0.4 ± 0.1 , 0.2 ± 0.05 , 0.2 ± 0.05 g/L/day respectively. The maximum biomass productivity was found in the case of sodium carbonate (Fig. 2(d)).

The biomass concentration of algae reaches to approximately 6 g/L by around 8th day after having a lag phase of 2 days from the day of inoculation in BBM while in the textile wastewaters (Acid yellow, Acid orange and Basic pink) when inoculated by the acclimatized algal species operated for 10 days monitoring the algal growth, in 20% dyes mixed with 10% BBM, the graph elevated to a maximum of around 1 g/L biomass concentration on 8th day for pink dye treatment and around 10 g/L biomass concentration on around 8th day of yellow and orange dye which shows a significant increase in growth compared to BBM only. Biomass concentrations were optimized by various nitrogen sources where a number of nitrogen sources were exposed with algae for comparative analysis. The biomass concentrations were found increasing with NH_4NO_3 in comparison to NaNO_3 , NH_4Cl and Urea but it was interesting to find out that Urea which did not show rise in graph initially (lag phase is long) but showed significant growth during log phase, not only this Urea is found to be the most cheapest Nitrogen source to be used (around 10 Rs/ kg) and very easily available. Amongst the various Carbon sources used for optimization, Sodium bicarbonate was found showing maximum biomass concentration 3.5 g/L on 5th

day which was considerably higher with respect to Sodium Carbonate and Potassium bicarbonate with biomass concentration of 2 g/l on 5th and 6th day respectively.

3.3. Statistical Optimization Study

ANOVA model is calculated for biomass productivity, The **F-value(model)** of 9.68 indicates the significance of the model. **P-values estimated 0.0001 which is** not as much as 0.0500 designate significance of model terms. Comparative to the pure error, the **F-value (Lack of Fit)** as 0.50 designate that it is not significant. Predicted R^2 of 0.6404 is in realistic agreement with the adjusted R^2 0.8073; i.e. alteration as a reduced amount from 0.2. The signal to noise ratio is measured by precision. It is desirable to get a ratio greater than 4. The obtained proportion 9.623 specifies a signal which is adequate. ANOVA model is calculated for colour removal, the **Model F-value** of 20.64 indicates the model is significant. **P-values found 0.0001 which is** a lesser amount of 0.0500 point towards the significance of model terms. Relative to the pure error the **Lack of Fit F-value** of 1.98 indicates that there is no significance of Lack of Fit. The Predicted R^2 of 0.7561 is in concurrence to adjusted R^2 of 0.9035; i.e. the variation is not as much of 0.2. Adeq Precision measures the signal to noise ratio. A ratio greater than 4 is considerable. The obtained proportion of 14.205 implies an adequate signal. ANOVA is calculated for Nitrogen removal, The **F-value (Model)** of 17.25 suggests significance of the model. **P-values calculated 0.0001 which is** a smaller amount than 0.0500 determines its significance. Relative to the pure error the **F-value (Lack of Fit)** of 3.02 indicates that it is not significant. The Predicted R^2 of 0.6991 is in rational agreement with the Adjusted R^2 of 0.9035; i.e. the variance is less than 0.2. Adeq Precision processes the signal to noise ratio. A ratio more than 4 is considerable. The obtained proportion of 13.65 designates signal which is adequate. ANOVA is calculated for Phosphorus removal, The **Model F-value** of 16.87 infers the model is significant. The significance of the model terms is indicated by **P-values found 0.0001 which is** less than 0.0500. Relative to the pure error the **Lack of Fit F-value** of 3.67 implies the Lack of Fit is not significant. The Predicted R^2 of 0.7561 is in judicious agreement with the Adjusted R^2 of 0.69; i.e. the variance is less than 0.2. Adeq Precision processes the signal to noise ratio. A ratio heigher than 4 is considerable. The obtained proportion of 13.02 indicates an adequate signal.

Then optimized value for various parameter like pH, carbon source, Nitrogen source and wastewater % used for the biomass productivity, colour removal, Nitrogen removal, and Phosphorus removal are 8.431 ± 0.6 , 0.29 ± 0.1 g/L, 0.2 ± 0.05 g/L and $38.90 \pm 5\%$ respectively. Obtained optimized results for biomass productivity, colour removal, Nitrogen removal, Phosphorus removal are 1.13 ± 0.2 g/L/Day, $65 \pm 2\%$, $91 \pm 3\%$, $65 \pm 1\%$ respectively as given the figure(3).

Figure 4: Surface plot of Biomass productivity includes interaction effect between (a) Carbon source and pH, (b) Nitrogen Source and pH, (c) wastewater% and pH, (d) Carbon Source and Nitrogen Source, (e) wastewater% and Carbon source and (f) Wastewater% and Nitrogen source.

Surface plots obtained from the RSM optimization for biomass productivity with correlation effect of Carbon source and pH, Nitrogen Source and pH, wastewater% and pH, Carbon Source and Nitrogen Source, wastewater% and Carbon source and Wastewater% and Nitrogen source are represented in the figure (4). The optimized value of pH, carbon source, Nitrogen source and wastewater % are 8.431 ± 0.6 , 0.29 ± 0.1 g/L, 0.2 ± 0.05 g/L and $38.90 \pm 5\%$ respectively.

Surface plots obtained from the RSM optimization for Colour removal efficiency% with correlation effect of Carbon source and pH, Nitrogen Source and pH, wastewater% and pH, Carbon Source and Nitrogen Source, wastewater% and Carbon source and Wastewater% and Nitrogen source are represented in the figure (5). The optimized value of pH, carbon source, Nitrogen source and wastewater % are 8.431 ± 0.6 , 0.29 ± 0.1 g/L, 0.2 ± 0.05 g/L and $38.90 \pm 5\%$ respectively.

Surface plots obtained from the RSM optimization for Nitrogen removal efficiency % with correlation effect of Carbon source and pH, Nitrogen Source and pH, wastewater% and pH, Carbon Source and Nitrogen Source, wastewater% and

Carbon source and Wastewater% and Nitrogen source are represented in the figure (6). The optimized value of pH, carbon source, Nitrogen source and wastewater % are 8.431 ± 0.6 , 0.29 ± 0.1 g/L, 0.2 ± 0.05 g/L and $38.90 \pm 5\%$

Surface plots obtained from the RSM optimization for Phosphorus removal efficiency % with correlation effect of Carbon source and pH, Nitrogen Source and pH, wastewater% and pH, Carbon Source and Nitrogen Source, wastewater% and Carbon source and Wastewater% and Nitrogen source are represented in the figure (7).

The optimized value of pH, carbon source, Nitrogen source and wastewater % are 8.431 ± 0.6 , 0.29 ± 0.1 g/L, 0.2 ± 0.05 g/L and $38.90 \pm 5\%$ respectively.

3.4. Analysis of pollutant removal

Potential of microalgae in degrading specific pollutants are being studied. Microalgae has been reported for degradation of large number of micropollutants, p-chlorophenol collected from a site where water contaminated with a number of aromatic pollutants can be removed at a rate of 10.00 mg/ Ltr in one day by *Chlorella vulgaris* and *Coenochloris pyrenoidosa*[9].

The analysis of parameters including COD, ammonia, colour and phosphorus were examined with respect to the methodology described in APHA (2000) at the beginning as well as at the end of the run. The composition contained by textile wastewater are found to be complicated containing heavy metals [10], dyes, salts [11] and reagents [12]. Many procedures have been employed absorption with activated carbon, exchange of ions and filtration by membrane, ozonation and irradiation [13]. Cultivation of algae in textile effluents uses carbon, nitrogen and phosphorous and other nutrients for its growth. During the process of bioconversion, the microalgae uses dyes and CO₂ as their carbon sources and finally transform them into metabolites moreover these algae can equally be employed as bio sorbent as the dyes hold the potential to absorb onto their surface.

As can be found in the graph shown in Fig. 8 (a) COD concentration was ranging from 250–300 mg/L for all the three dyes i.e. acid yellow, acid orange and basic pink on day 0 but as the growth continues a steady fall in the graph can be seen, as soon as it reaches the 8th day the COD level drops down to 50 mg/L which shows that *Chlorella pyrenoidosa* is efficient enough to remove COD. On the contrary when the same study was performed with phosphorus, the level of phosphorus in acid yellow and acid orange was around 2.5 mg/L while in basic pink it was around 4.0 mg/L way higher than the other two but as the growth reaches between 4 to 6 days the graph falls down to 1.0 mg/L which confirms the efficiency of the alga in removing phosphorus as can be seen in Fig. 8 (b). Figure 8 (c) shows removal of ammonia where the level for the three dyes having ammonia were as high as 14–16 mg/L which experiences a steep fall in the graph and falls down to 2 mg/L at around 8th day of inoculation. The removal of colour was studied for the three dyes which were ranging from 0.09 to 0.10 on the day 0 but the intensity of colour was significantly decreased to the level of 0.05 on the fifth day and fell down to 0.04 on the 9th day of inoculation confirming the ability of *Chlorella pyrenoidosa* in removing colour of the dyes successfully.

The efficiency of nitrogen (ammonia) removal, Nitrogen (nitrate) removal, COD removal, colour removal, and phosphorus removal in three types textile wastewaters (acid yellow dye containing textile wastewater, acid orange dye containing textile wastewater, basic pink dye containing textile wastewater) is explained in the form of bar chart given in figure (9).

A very little variation in nitrogen (ammonia) removal efficiency in acid yellow dye containing textile wastewater ($91 \pm 3\%$), acid orange dye containing textile wastewater ($90 \pm 3\%$), and basic pink dye containing textile wastewater ($91 \pm 1\%$). A small variation found in nitrogen (Nitrate) removal efficiency in acid yellow dye containing textile wastewater ($79 \pm 2\%$), acid orange dye containing textile wastewater ($68 \pm 3\%$), and basic pink dye containing textile wastewater ($70 \pm 4\%$).

A very little or negligible variation in Phosphate removal reported, efficiency in acid yellow dye containing textile wastewater ($65 \pm 2\%$), acid orange dye containing textile wastewater ($60 \pm 1\%$), and basic pink dye containing textile wastewater ($63 \pm 1\%$). However a minor variation in COD removal efficiency in acid yellow dye containing textile wastewater ($91 \pm 1\%$), acid orange dye containing textile wastewater ($94 \pm 2\%$), and basic pink dye containing textile wastewater ($90 \pm 2\%$). A small decrease observed in color removal efficiency in acid yellow dye containing textile wastewater ($65 \pm 2\%$), acid orange dye containing textile wastewater ($59 \pm 5\%$), and basic pink dye containing textile wastewater ($55 \pm 5\%$) respectively.

The efficiency of nitrogen (ammonia) removal, Nitrogen (nitrate) removal, COD removal, colour removal, and phosphorus removal in three types textile wastewaters (acid yellow dye containing textile wastewater, acid orange dye containing textile wastewater, basic pink dye containing textile wastewater) is explained in the form of bar chart given in Table (3).

Conclusions

Three types of textile wastewater were used for the study containing the Acid yellow, Acid orange and Basic Pink dye. The growth of microalgae species *Chlorella pyrenoidosa* was low initially $0.3\text{--}0.4$ g/L/day but after acclimatization biomass productivity increased up to $1.2\text{--}1.5$ g/L/Day in textile dyes. Nitrogen content in all type textile wastewaters was very less, hence urea is used as nitrogen source in wastewater. Then optimized value for various parameter like pH, carbon source, Nitrogen source and wastewater % used for the biomass productivity, colour removal, Nitrogen removal, and Phosphorus removal are 8.431 ± 0.6 , 0.29 ± 0.1 g/L, 0.2 ± 0.05 g/L and $38.90 \pm 5\%$ respectively. Obtained optimized results for biomass productivity, colour removal, Nitrogen removal, Phosphorus removal are 1.13 ± 0.2 g/L/Day, $65 \pm 2\%$, $91 \pm 3\%$, $65 \pm 1\%$ respectively. The COD removal efficiency obtained $92 \pm 1\%$ in nearly all three types of textile wastewater. Harvesting (flocculation method) is optimized using RSM in which chitosan was used as flocculant. The optimum condition achieved for flocculation is 0.5 g/l at pH 10.0 having the mixing time and settling time 30 min and 120 min respectively. Low amount of Nitrogen enhances the lipid productivity in the algal biomass. Therefore, *Chlorella pyrenoidosa* can be an alternative for textile wastewater bioremediation and high biomass can be achieved using urea. The algal biomass produced may be advantageous as fertilizers, feedstock, and production of biofuel. This technology can be used for techno economic wastewater treatment and enhanced biomass production process.

Declarations

Acknowledgements

We gratefully acknowledge Head and Mentor, School of Biochemical Engineering, IIT BHU, DST (WOS-B), MHRD and BHU for providing funds and research facilities, bringing this research work into fruition.

Availability of data and materials

All the data generated during the study have been submitted in the main manuscript so no supportive materials attached separately.

Funding

This work was supported by Ministry of Science and Technology, Department of Science and Technology, Women Scientist Scheme – B (Ref no. DST/WOS-B/2017/287-AAS)

Author Information

Affiliations-

Contributions-

Conceptualization, P.S. and S.M.; Methodology, V.S. and S.M.; Software, V.S.; Validation, M.S. and P.S.; Formal analysis, P.S. and S.M.; Investigation, P.S. and M.S.; Data Curation, M.S.; Resources, P.S. and S.M.; Writing original draft preparation, V.S. and S.M.; Editing and Improvisation, M.S. and P.S. All authors have read and agreed to the published version of the manuscript. The authors read and approved the final manuscript.

Corresponding Author

Correspondence to Prof. Pradeep Srivastava

Competing Interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Ethics declarations

All authors of this research paper have directly participated in the planning and execution of this study. Manuscript has not been published elsewhere and that it has not been submitted simultaneously for publication somewhere else.

On behalf of all the authors, I look forward to your positive response.

References

1. Cai H, Liang J, Ning XA, Lai X, Li Y. Algal toxicity induced by effluents from textile-dyeing wastewater treatment plants. *Int. J. Environ. Sci.* 2020;91: 199–208.
2. Fazal T, Mushtaq A, Rehman F, Khan AU, Rashid N, Farooq W, Rehman MS, Xu J. Bioremediation of textile wastewater and successive biodiesel production using microalgae. *Renew. Sust. Energ. Rev.* 2018; 82:3107–26.
3. Mahajan P, Kaushal J, Upmanyu A, Bhatti J. Assessment of phytoremediation potential of *Chara vulgaris* to treat toxic pollutants of textile effluent. *J. Toxicol.* 2019 3;2019.
4. Mantzavinos D, Psillakis E. Enhancement of biodegradability of industrial wastewaters by chemical oxidation pre-treatment. *Journal of Chemical Technology & Biotechnology: Clean Technol Envir.* 2004; 79(5):431–54.
5. Taştan BE, Ertuğrul S, Dönmez G. Effective bioremoval of reactive dye and heavy metals by *Aspergillus versicolor*. *Bioresour. Technol.* 2010;101(3):870–6.
6. Huang G, Chen F, Wei D, Zhang X, Chen G. Biodiesel production by microalgal biotechnology. *Appl. Energy.* 2010;87(1):38–46
7. Sorokin C, and J. Myers. A high temperature strain of *Chlorella*. *Science.* 1951; 117:330–331.
8. Ramanan R, Kim BH, Cho DH, Oh HM, Kim HS. Algae–bacteria interactions: evolution, ecology and emerging applications. *Biotechnol Adv.* 2016;34(1):14–29.
9. Subashchandrabose SR, Ramakrishnan B, Megharaj M, Venkateswarlu K, Naidu R. Mixotrophic cyanobacteria and microalgae as distinctive biological agents for organic pollutant degradation. *Environ. Int.* 2013;51:59–72.
10. Dellamatrice PM, Silva-Stenico ME, Moraes LA, Fiore MF, Monteiro RT. Degradation of textile dyes by cyanobacteria. *Braz J Microbiol.* 2017; 48(1):25–31.

11. Srinivasan A, Viraraghavan T. Decolorization of dye wastewaters by biosorbents: a review. J. Environ. Manage. 2010; 91(10):1915–29.
12. Logroño W, Pérez M, Urquizo G, Kadier A, Echeverría M, Recalde C, Rákhely G. Single chamber microbial fuel cell (SCMFC) with a cathodic microalgal biofilm: a preliminary assessment of the generation of bioelectricity and biodegradation of real dye textile wastewater. Chemosphere. 2017;176:378–88.
13. Bhuiyan MR, Rahman MM, Shaid A, Bashar MM, Khan MA. Scope of reusing and recycling the textile wastewater after treatment with gamma radiation. J Clean Prod. 2016; 112:3063–71.

Tables

Table 1: Physicochemical characterization of textile wastewater (Acid Yellow, Acid Orange and Basic pink dye).

S.N.	Parameter	Acid Yellow 17 dye	Acid Orange 7 Dye	Basic Pink Dye
1.	Colour(660nm)	Yellow (0.024)	Orange (0.032)	Dark Pink (0.045)
2.	pH	8.1	8.1	8.2
3.	Temperature	35 ⁰ C	35 ⁰ C	38 ⁰ C
4.	Total suspended solids	63mg/L	43mg/L	74mg/L
5.	Total dissolved solids	120mg/L	135mg/L	132mg/L
6.	Alkalinity(carbonate)	69.6mg/L	52.8mg/L	76.8 mg/L
7.	Nitrogen (ammonia)	0.32mg/L	0.38mg/L	0.18mg/L
8.	Nitrogen (Nitrate)	0.85mg/L	0.12mg/L	0.225mg/L
9.	Phosphate	1.4mg/L	2.3mg/l	3.8mg/L
10.	Dissolved oxygen	10.8mg/L	16mg/L	12.8mg/L
11.	BOD	28.8mg/L	67.2mg/L	33.6mg/L
12.	COD	296mg/L	272mg/L	288mg/L

Table 2: RSM table of Raw Material optimization for *Chlorella Pyrenoidosa*

	Factor 1	Factor 2	Factor 3	Factor 4	Response 1	Response 2	Response 3	Response 4
Run	A:pH	B:Carbon Source	C:Nitrogen Source	D:Wastewater%	Biomass Productivity	Colour Removal	Nitrogen Removal	Phosphorus removal
		g/L	g/L		g/L/day	%	%	%
1	5	0.4	0.2	20	0.58	41	71	42
2	11	0.4	0.2	20	0.61	42	72	44
3	8	0.3	0.65	40	0.89	60	88	59
4	5	0.2	0.2	20	0.66	48	75	48
5	5	0.4	0.5	60	0.78	58	85	59
6	5	0.4	0.5	20	0.98	62	89	63
7	2	0.3	0.35	40	0.41	42	70	45
8	5	0.2	0.2	60	0.64	51	79	53
9	8	0.3	0.05	40	0.86	54	80	52
10	14	0.3	0.35	40	0.38	35	60	36
11	8	0.3	0.35	40	1.2	72	98	70
12	8	0.3	0.35	0	0.19	30	60	29
13	11	0.2	0.5	20	0.52	46	73	47
14	8	0.3	0.35	40	1.34	69	95	70
15	5	0.2	0.5	60	0.59	45	71	44
16	11	0.4	0.2	60	0.66	48	70	47
17	11	0.2	0.2	20	0.71	51	80	54
18	5	0.2	0.5	20	0.65	48	73	48
19	11	0.2	0.5	60	0.59	44	71	44
20	11	0.4	0.5	60	0.56	43	69	43
21	8	0.5	0.35	40	0.99	65	91	66
22	8	0.3	0.35	40	1.1	69	94	70
23	8	0.1	0.35	40	0.7	64	92	62
24	8	0.3	0.35	40	1.26	68	95	69
25	5	0.4	0.2	60	0.66	49	76	50
26	11	0.2	0.2	60	0.65	48	74	51
27	8	0.3	0.35	80	0.59	43	71	45
28	11	0.4	0.5	20	0.56	41	69	40
29	8	0.3	0.35	40	0.98	64	91	65

Table 3: Removal efficiency of pollutant in three types of textile wastewater

Parameter	Removal Efficiency in Acid Yellow dye (%)	Removal Efficiency in Acid Orange Dye (%)	Removal Efficiency in Basic Pink Dye (%)
Nitrogen (ammonia)	91±3%	90±3%	91±1%
Phosphate	65±2%	60±1%	63±1%
COD	91±1%	94±2%	90 ±2%
Color removal	65±2%	59±5%	55±5%

Figures

Figure 1

Methodology of Bioremediation ox textile wastewater using designed Bubble column tubular Photobioreactor.

Figure 2(a)

Figure 2(b)

Figure 2(c)

Figure 2(d)

Figure 2

owth kinetics of *Chlorella pyrenoidosa* (a) Time course of *C. Pyrenoidosa* biomass concentration using the Bolds basal media. Growth rate constant is 0.21g/Day. (b) Growth curve of *Chlorella pyrenoidosa* in textile wastewater (Acid yellow 17 dye, Acid orange 7 dye and Basic pink dye) 10% and BBM 90% (c) Biomass density in various nitrogen source. (d) Carbon source optimization using three carbon sources.

Figure 3

Optimized result from RSM

Figure 4

Surface plot of Biomass productivity includes interaction effect between (a) Carbon source and pH, (b) Nitrogen Source and pH, (c) wastewater% and pH, (d) Carbon Source and Nitrogen Source, (e) wastewater% and Carbon source and (f) Wastewater% and Nitrogen source.

Figure 5

Surface plot of Colour removal efficiency% includes interaction effect between (a) Carbon source and pH, (b) Nitrogen Source and pH, (c) wastewater% and pH, (d) Carbon Source and Nitrogen Source, (e) wastewater% and Carbon source and (f) Wastewater% and Nitrogen source.

Figure 6

Surface plot of Nitrogen removal efficiency% includes interaction effect between (a) Carbon source and pH, (b) Nitrogen Source and pH, (c) wastewater% and pH, (d) Carbon Source and Nitrogen Source, (e) wastewater% and Carbon source and (f) Wastewater% and Nitrogen source

Figure 7

Surface plot of Phosphorus removal efficiency% includes interaction effect between (a) Carbon source and pH, (b) Nitrogen Source and pH, (c) wastewater% and pH, (d) Carbon Source and Nitrogen Source, (e) wastewater% and Carbon source and (f) Wastewater% and Nitrogen source.

Figure 8

Analysis of Pollutant removal in Acid yellow, Acid Orange and Acid Pink dye wastewaters (a) COD removal (b) Phosphorus removal (c) Ammonia removal (d) Color removal.

Figure 9

Comparative Analysis of Efficiency of Pollutant removal in Acid yellow, Acid Orange and Acid Pink dye wastewaters for nitrogen (ammonia) removal, Nitrogen (nitrate) removal, COD removal, colour removal, and phosphorus removal.